

R news and tutorials contributed by (552) R bloggers

- Home
- About
- add your blog!
- Contact us
- RSS
- R jobs ���

#### Welcome!

Here you will find daily **news and tutorials about R**, contributed by over 555 bloggers.
There are many ways to **follow us -**

#### By e-mail:



#### On Facebook:



If you are an R blogger yourself you are invited to add your own R content feed to this site (Non-English R bloggers should add

themselves- <u>here</u>)
Search & Hit Enter

### **■** Jobs for R-

#### users

- Applied Researcher in Algorithmic Research
- Sr. Data Scientist in the Financial

- <u>Industry</u>
- R programmer /
  - research analyst
- Sr. Java Software
- Engineer (m/f) -Data Mining - IT
- Startup
- Executive
- Director of
- **Institutional**
- Research

#### **Popular Searches**

- <u>heatmap</u>
- hadoop
- web scraping
- maps
- pca
- twitter
- ggplot
- finance
- shiny
- excel
- ggplot2
- LaTex
- googlevis
- **boxplot**
- trading
- animation
- <u>eclipse</u>
- **RStudio**
- <u>knitr</u>
- quantmod time series
- **tutorial**
- how to import image file to R
- alt=
- market research
- gis
- <u>rattle</u>
- <u>ecdf</u>
- remdr
- sweave

#### **Recent Posts**

- 8 new R jobs (for Augest 25th 2014)
- New in OpenCPU
  - 1.4.4: session
  - namespaces
- Forecasting with
- R in WA
- R: Stem (Pre-
- Processed) Text
- **Blocks**
- JAGS and Stan
- Computational
- Actuarial Science, with R
- VCI The Value
- Charts Indicator
- R OOP a little

- privacy please?
   An adverse
   consequence of fitting "maximal" linear mixed models
- More ESA 2014
   Program Text Mining: Topics as
   Communities
- Entering the field as a data scientist with certification
- Pro Grammar and Devel Hoper
- stringdist 0.8: now with soundex
- RcppEigen 0.3.2.2.0

#### Other sites

- SAS blogs
- Jobs for R-users
- Statistics of Israel

# Connecting to a MongoDB database from R using Java

September 24, 2010 By <u>nsaunders</u>



It would be nice if there were an R package, along the lines of RMySQL, for MongoDB. For now there is not – so, how best to get data from a MongoDB database into R?

One option is to retrieve JSON via the MongoDB <u>REST interface</u> and parse it using the *rjson* package. Assuming, for example, that you have retrieved your CiteULike collection in JSON format from this URL:

#### 1 http://www.citeulike.org/json/user/neils

- and saved it to a database named *citeulike* in a collection named *articles*, you can fetch the first 5 articles into R like so:

That works, but you may not want to use the MongoDB REST interface: for example, it may be slow for large queries or there might

be security concerns.

Not to be deterred, I took the approach that has served me well my whole professional life: wing it, using what I could glean from Google searches and the Web. In the end, using Java in R to connect with MongoDB was surprisingly easy. Here's a basic how-to.

I'll assume that MongoDB is installed and running on your machine. Packages for Ubuntu/Debian can be obtained here.

#### 1. Install R packages

You'll need rJava and rjson. The latter was a simple install.packages("rjson") from the R console. The former gave me some problems so as I use Ubuntu, I went with sudo apt-get install r-cran-rjava. That should also install the necessary dependencies, including a JDK if you don't already have one.

#### 2. Install the MongoDB Java driver

Create a directory, e.g. ~/mongodb/java, change into it and grab the latest driver from GitHub. I renamed the file to mongo.jar. Having no idea what to do with it, I searched and discovered this guide. I ran:

The Java class files are located in com/mongodb.

#### 3. Experiment with rJava

Still in ~/mongodb/java, I started an R console and loaded the libraries:

```
1 library(rJava)
2 library(rjson)
```

Next, I added the MongoDB classes to the classpath:

```
1    .jinit()
2    .jaddClassPath("~/mongodb/java/mongo.jar")
```

The next step was to consult the MongoDB Java tutorial and try to figure out how to convert "normal" Java syntax to rJava. First, rJava has no *import*, so you create a new Mongo object like this:

```
1  m <- .jnew("com/mongodb/Mongo", "localhost")
2  print(m)
3  # [1] "Java-Object{com.mongodb.Mongo@c2ea3f}"</pre>
```

OK – that seems to have worked; we have a Java object of class *Mongo*, connected to the server on *localhost*.

You can see the available methods like this:

```
.jmethods(m)
 1
 2
 3
       [1] "public com.mongodb.DB com.mongodb.Mongo
       [2] "public java.util.List com.mongodb.Mongo
 5
       [3] "public void com.mongodb.Mongo.dropDatab
           "public java.lang.String com.mongodb.Mon
"public java.lang.String com.mongodb.Mon
"public java.util.List com.mongodb.Mongo
 6
 7
       Ī5Ī
 8
       [6]
            "public void com.mongodb.Mongo.setWriteC
       [7]
10
           "public com.mongodb.WriteConcern com.mon
       [8]
            "public com.mongodb.ServerAddress com.mo
11
       Ī9Ī
           "public void com.mongodb.Mongo.close()'
12
      [10]
           "public static com.mongodb.DB com.mongod
13
      [11]
      [12] "public java.lang.String com.mongodb.Mon
```

```
[13] "public final native void java.lang.Obje
15
      [14] "public final void java.lang.Object.wait
16
      [15] "public final void java.lang.Object.wait
17
      [16] "public boolean java.lang.Object.equals([17] "public java.lang.String java.lang.Object[18] "public native int java.lang.Object.hash
18
19
20
      [19] "public final native java.lang.Class jav
21
      [20] "public final native void java.lang.Obje
22
      [21] "public final native void java.lang.Obje
23
```

As a non-Java programmer, that means very little to me. Instead, I typed m\$, hit the tab key a couple of times and saw this:

```
1    m$MAJOR_VERSION    m$dropDatabase(    m$
2    m$MINOR_VERSION    m$debugString()    m$
3    m$getDB(    m$getConnectPoint()    m$
4    m$getDatabaseNames()   m$getAllAddress()    m$
```

That's much more useful – I recognise those methods. Let's try connecting with the *citeulike* database:

```
db <- m$getDB("citeulike")
print(db)
# [1] "Java-Object{citeulike}"</pre>
```

Progress, no errors, it's all good. Using the same approach – type db\$ and hit tab, I saw this:

```
db$requestStart()
                                   db$getCollection
2
    db$requestDone()
                                   db$doEval(
3
    db$requestEnsureConnection()
                                   db$eval(
4
    db$dropDatabase()
                                   db$getStats()
5
    db$setWriteConcern(
                                   db$getCollection
6
    db$getWriteConcern()
                                   db$collectionExi
7
    db$getCollection(
                                   db$resetIndexCac
    db$createCollection(
                                   db$getLastError(
```

Which led me to believe that I could access the *articles* collection like this:

```
1  col <- db$getCollection("articles")
2  print(col)
3  # [1] "Java-Object{articles}"</pre>
```

You get the idea. The Java methods follow the names of the MongoDB shell commands. Let's fetch the first article:

```
1 | article <- col$findOne()
2 | article <- article$toString</pre>
```

Success! The *toString()* method converts the article to a JSON string. Now all that's left is to get that into an R data structure:

```
article <- fromJSON(article)</pre>
 1
     article$title
 3
     # [1] "A computational genomics pipeline for
 4
     article$authors
     # [1] "Andrey O. Kislyuk"
[4] "Matthew S. Hagen"
 5
                                        "Lee S. Katz"
 6
                                      "Andrew B. Conley
      [7] "Viswateja Nelakuditi"
                                     "Jay C. Humphrey
 7
      [10] "Dhwani Ğovil"
                                     "Raydel D. Mair"
 8
      [13] "Maria L. Tondella"
                                      "Brian H. Harcour
     [16] "I. King Jordan"
10
```

Let the statistical analysis of your CiteULike library (or any other data from MongoDB) begin.

Filed under: computing, programming, R, research diary, statistics Tagged: java, mongodb, rjava, rjson Comments: 3 Tweet it!



Tags: computing, java, mongodb, programming, R, research diary, rjava, rjson, statistics

Comments are closed.

### Top 3 Posts from the past 2 days

- Using apply, sapply, lapply in R
- dplyr: A gamechanger for data manipulation in R
- Installing R packages


Search & Hit Enter

#### Top 9 articles of the week

- dplyr: A gamechanger for data manipulation in R
- 2. Using apply, sapply, lapply in R
- 3. R Passes SPSS in Scholarly Use, Stata Growing Rapidly
- 4. Installing R packages
- 5. Do your "data janitor work" like a boss with dplyr
- 6. <u>Data Cleaning is a critical part of the Data Science process</u>
- 7. googleVis 0.5.5 released
- 8. 21 R navigation tools
- 9. Box-plot with R Tutorial

#### **Sponsors**







Quantide: statistical consulting and training











<u>Plotly: collaborative, publication-quality graphing.</u>









## An **R** based reporting and data analysis platform in the cloud





NYC, Feb-Aug, 2014 5 weekends/round







Search & Hit Enter

Full list of contributing R-bloggers

R-bloggers was founded by Tal Galili, with gratitude to the R community.

Is powered by WordPress using a bavotasan.com design.
Copyright © 2014 **R-bloggers**. All Rights Reserved. Terms and Conditions for this website