

## User table

```
create table CAN_BASIC_DET(CAN_BASIC_ID int NOT NULL AUTO_INCREMENT,CAN_FIRST_NAME
char(20),CAN_MIDDLE_NAME varchar(20),CAN_LAST_NAME varchar(20),CAN_DOB
date,CAN_GENDER char,CAN_MOBILE char(20),CAN_EMAIL char(20),CAN_CURRENT_LOCATION
char(20),CAN_PREFERRED_LOCATION char(20),CAN_COUNTRY char(10),CAN_BASIC_DATE_TIME
timestamp,PRIMARY KEY(CAN_BASIC_ID));
```

```
create table CAN_PACKAGE_DET (CAN_PACKAGE_ID int NOT NULL AUTO_INCREMENT,CAN_BASIC_ID
int,CAN_CTC char(20),CAN_ECTC char(20),CAN_NOTICE_PERIOD
char(20),CAN_PACKAGE_DATE_TIME timestamp,PRIMARY KEY(CAN_PACKAGE_ID),FOREIGN
KEY(CAN_BASIC_ID)REFERENCES CAN_BASIC_DET(CAN_BASIC_ID));
```

```
create table CAN_INTERVIEW_STATUS(CAN_INTERVIEW_ID int NOT NULL
AUTO_INCREMENT,CAN_BASIC_ID int,CAN_LEVEL_STATUS char,CAN_INTERVIEW_DATE_TIME
timestamp,CAN_HACKER_RANK_STATUS char(20),PRIMARY KEY(CAN_INTERVIEW_ID),FOREIGN
KEY(CAN_BASIC_ID)REFERENCES CAN_BASIC_DET(CAN_BASIC_ID));
```

```
create table CAN_OFFER(CAN_OFFER_ID int NOT NULL AUTO_INCREMENT,CAN_OFFER_DATE
timestamp,CAN_BASIC_ID int,CAN_OFFER_STATUS char,CAN_OFFER_ACCEPT
char,CAN_OFFER_JOINING_DATE timestamp,CAN_HACKER_RANK_STATUS char(20),PRIMARY
KEY(CAN_OFFER_ID),FOREIGN KEY(CAN_BASIC_ID)REFERENCES CAN_BASIC_DET(CAN_BASIC_ID));
```

```
create table CAN_REPORTS(CAN_REPORTS_ID int NOT NULL
AUTO_INCREMENT,CAN_REPORTS_GENERATED_BY char(20),CAN_REPORTS_NAME
char(20),CAN_REPORTS_DATE_TIME timestamp,PRIMARY KEY(CAN_REPORTS_ID));
```

```
create table CAN_FILE_UPLOAD(CAN_FILE_UPLOAD_ID int NOT NULL
AUTO_INCREMENT,CAN_FILE_NAME char(20),CAN_FILE_DATE_TIME timestamp,CAN_FILE_STATUS
ENUM('fail', 'success'),PRIMARY KEY(CAN_FILE_UPLOAD_ID));
```