

EAE 298 Aeroacoustics
Fall Quarter 2016
Homework #1

John Karasinski

October 11, 2016

Problem 1. [50 pts]

The values in the wav file are in volts. B&K measurement microphones invert the pressure a negative voltage from the microphone corresponds to a positive pressure. When you apply the calibration constant, account for this sign reversal. For this problem, the pre-calculated constant calibration factor is 116 pascals/volt. Convert the time series in voltage to pascals. (Assume that all of the power in the boom waveform is within the range of flat response of the microphone).

Part (a)

[10 pts] Plot the waveform in pascals as a function of time. What is the peak pressure in the time domain? Notice the shape of the first arrival it has the classic N wave shape of a sonic boom. Notice the duration in time from the positive-pressure peak to the negative-pressure peak.



Solution


Figure 1: The waveform in pascals as a function of time. Peak pressure is noted at 75.25 Pa, and the duration in time from the positive-pressure peak to the negative-pressure peak is noted at 0.13 sec.

Part (b)

[30 pts] Calculate and plot the single-sided power spectral density function (G_{xx}).

Solution**Part (c)**

[10 pts] Convert and plot the standard narrowband sound pressure level with the reference pressure of 20 micro-Pascal.

Solution

Problem 2. [50 Pts]

Write a computer program to convert the narrow band spectra to one-third octave and octave band spectra.

Part (a)

[20 pts] Convert the narrowband spectrum to one-third octave band spectrum and make a plot

Solution

You only get to YOLOSWAG once.

Part (b)

[20 pts] Convert the one-third octave band spectrum to octave band spectrum and make a plot

Solution

You only get to YOLOSWAG once.

Part (c)

[10 pts] Convert the octave band spectrum to the overall sound pressure level

Solution

You only get to YOLOSWAG once.