REPORT FOR EN 60950-1

SMARTfit, Inc
3977 Camino Ranchero
Camarillo, CA 93012
USA

This report is for the SMARTfit product Movable adjustable Mini and 5 PODS, SMARTfit part number 1-30101-X, X is just a color reference. This is the most complex version of the product line, all other products are a sub-set of this product.

Test item particulars.....:	
Equipment mobility.....:	[x] movable [] hand-held [] transportable [] stationary [] for building-in [] direct plug-in
Connection to the mains .....:	[] pluggable equipment [] type A [] type B [] permanent connection [] detachable power supply cord [] non-detachable power supply cord [X] not directly connected to the mains
Operating condition.....:	[X] continuous [] rated operating / resting time:
Access location .....:	[] operator accessible [] restricted access location
Over voltage category (OVC) .....:	[] OVC I [] OVC II [] OVC III [] OVC IV [X] other: not directly connected to the mains
Mains supply tolerance (%) or absolute mains supply values .....:	N/A
Tested for IT power systems .....:	[] Yes [X] No
IT testing, phase-phase voltage (V) .....:	N/A
Class of equipment .....:	[] Class I [] Class II [X] Class III [] Not classified
Considered current rating of protective device as part of the building installation (A) .....:	N/A
Pollution degree (PD) .....:	[] PD 1 [X] PD 2 [] PD 3
IP protection class .....:	IPX0
Altitude during operation (m) .....:	Up to 2000m
Altitude of test laboratory (m) .....:	Less than 2000m
Mass of equipment (kg) .....:	About than 374Kg

Possible test case verdicts:

- test case does not apply to the test object .....: N/A
- test object does meet the requirement..... : P (Pass)
- test object does not meet the requirement..... : F (Fail)

Manufacturer's Declaration per sub-clause 6.2.5 of IECEE 02:

The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided.....: ☐ Yes

Not applicable

When differences exist; they shall be identified in the General product information section.

Name and address of factory (ies) ..... : SMARTfit, Inc
3977 Camino Ranchero
Camarillo, CA 93012 USA

General product information:

Product Description

Exercise equipment

Abbreviations used in the report:

- normal conditions	N.C.	- single fault conditions	S.F.C
- functional insulation	OP	- basic insulation	BI
- double insulation	DI	- supplementary insulation	SI
- between parts of opposite polarity	BOP	- reinforced insulation	RI

Indicate used abbreviations (if any)

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

1	**GENERAL**	P

1.5	**Components**		P
1.5.1	General	See below.	P
	Comply with IEC 60950-1 or relevant component standard	See appended table 1.5.1.	P
1.5.2	Evaluation and testing of components		P
1.5.3	Thermal controls		N/A
1.5.4	Transformers		N/A
1.5.5	Interconnecting cables		N/A
1.5.6	Capacitors bridging insulation		N/A
1.5.7	Resistors bridging insulation		N/A
1.5.7.1	Resistors bridging functional, basic or supplementary insulation		N/A
1.5.7.2	Resistors bridging double or reinforced insulation between a.c. mains and other circuits		N/A
1.5.7.3	Resistors bridging double or reinforced insulation between a.c. mains and antenna or coaxial cable		N/A
1.5.8	Components in equipment for IT power systems		N/A
1.5.9	Surge suppressors		N/A
1.5.9.1	General	UL listed power supply	N/A
1.5.9.2	Protection of VDRs		N/A
1.5.9.3	Bridging of functional insulation by a VDR		N/A
1.5.9.4	Bridging of basic insulation by a VDR		N/A
1.5.9.5	Bridging of supplementary, double or reinforced insulation by a VDR		N/A

1.6	**Power interface**		N/A
1.6.1	AC power distribution systems		N/A
1.6.2	Input current		N/A
1.6.3	Voltage limit of hand-held equipment		N/A
1.6.4	Neutral conductor		N/A

1.7	**Marking and instructions**		P
1.7.1	Power rating and identification markings		P
1.7.1.1	Power rating marking		N/A
	Multiple mains supply connections.....:		N/A

	Rated voltage(s) or voltage range(s) (V) ..... :		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	Symbol for nature of supply, for d.c. only ..... :		N/A
	Rated frequency or rated frequency range (Hz) .... :		N/A
	Rated current (mA or A) ..... :		N/A
1.7.1.2	Identification markings	See below	P
	Manufacturer's name or trade-mark or identification mark ..... :	See labels.	P
	Model identification or type reference ..... :	See labels.	P
	Symbol for Class II equipment only ..... :		N/A
	Other markings and symbols ..... :	Other symbols do not give rise to misunderstanding.	P
1.7.2	Safety instructions and marking	See below.	P
1.7.2.1	General	Specification is available.	P
1.7.2.2	Disconnect devices		N/A
1.7.2.3	Overcurrent protective device	7.5A fuse	P
1.7.2.4	IT power distribution systems		N/A
1.7.2.5	Operator access with a tool		N/A
1.7.2.6	Ozone		N/A
1.7.3	Short duty cycles		N/A
1.7.4	Supply voltage adjustment ..... :		N/A
	Methods and means of adjustment; reference to installation instructions ..... :		N/A
1.7.5	Power outlets on the equipment ..... :		N/A
1.7.6	Fuse identification (marking, special fusing characteristics, cross-reference) ..... :	7.5DCA automotive fuse	P
1.7.7	Wiring terminals		N/A
1.7.7.1	Protective earthing and bonding terminals ..... :		N/A
1.7.7.2	Terminals for a.c. mains supply conductors		N/A
1.7.7.3	Terminals for d.c. mains supply conductors		N/A
1.7.8	Controls and indicators		N/A
1.7.8.1	Identification, location and marking ..... :		N/A
1.7.8.2	Colors ..... :		N/A
1.7.8.3	Symbols according to IEC 60417 ..... :		N/A
1.7.8.4	Markings using figures ..... :		N/A
1.7.9	Isolation of multiple power sources ..... :		N/A
1.7.10	Thermostats and other regulating devices ..... :		N/A
1.7.11	Durability		P

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7.12	Removable parts		N/A
1.7.13	Replaceable batteries ..... :	Li battery	P
	Language(s) ..... :		—
1.7.14	Equipment for restricted access locations..... :		N/A

2	**PROTECTION FROM HAZARDS**		P
2.1	Protection from electric shock and energy hazards		P
2.1.1	Protection in operator access areas	Labels for pinch points. Labels for the need for weights on the back side of the unit.	P
2.1.1.1	Access to energized parts	No access	P
	Test by inspection ..... :		P
	Test with test finger (Figure 2A) ..... :		N/A
	Test with test pin (Figure 2B) ..... :		N/A
	Test with test probe (Figure 2C) ..... :		N/A
2.1.1.2	Battery compartments		P
2.1.1.3	Access to ELV wiring		N/A
	Working voltage (Vpeak or Vrms); minimum distance through insulation (mm)		—
2.1.1.4	Access to hazardous voltage circuit wiring		N/A
2.1.1.5	Energy hazards ..... :		N/A
2.1.1.6	Manual controls		N/A
2.1.1.7	Discharge of capacitors in equipment		N/A
	Measured voltage (V); time-constant (s)..... :		—
2.1.1.8	Energy hazards – d.c. mains supply		N/A
	a) Capacitor connected to the d.c. mains supply .. :		N/A
	b) Internal battery connected to the d.c. mains supply ..... :		N/A
2.1.1.9	Audio amplifiers ..... :		N/A
2.1.2	Protection in service access areas		N/A
2.1.3	Protection in restricted access locations		N/A

2.2	**SELV circuits**		P
2.2.1	General requirements		P
2.2.2	Voltages under normal conditions (V) ..... :	12VDC	P
2.2.3	Voltages under fault conditions (V) ..... :	0 to 12VDC	P
2.2.4	Connection of SELV circuits to other circuits ..... :	4 conductor cable to connect	P

		CPU to Panels.	

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

2.3	**TNV circuits**		N/A
2.3.1	Limits		N/A
	Type of TNV circuits..... :		—
2.3.2	Separation from other circuits and from accessible parts		N/A
2.3.2.1	General requirements		N/A
2.3.2.2	Protection by basic insulation		N/A
2.3.2.3	Protection by earthing		N/A
2.3.2.4	Protection by other constructions ..... :		N/A
2.3.3	Separation from hazardous voltages		N/A
	Insulation employed ..... :		—
2.3.4	Connection of TNV circuits to other circuits		N/A
	Insulation employed ..... :		—
2.3.5	Test for operating voltages generated externally		N/A

2.4	**Limited current circuits**		N/A
2.4.1	General requirements		N/A
2.4.2	Limit values		N/A
	Frequency (Hz) ..... :		—
	Measured current (mA)..... :		—
	Measured voltage (V)..... :		—
	Measured circuit capacitance (nF or µF) ..... :		—
2.4.3	Connection of limited current circuits to other circuits		N/A

2.5	**Limited power sources**		N/A
	a) Inherently limited output		N/A
	b) Impedance limited output		N/A
	c) Regulating network limited output under normal operating and single fault condition		N/A
	d) Overcurrent protective device limited output		N/A
	Max. output voltage (V), max. output current (A), max. apparent power (VA)..... :		—
	Current rating of overcurrent protective device (A) .:		—
	Use of integrated circuit (IC) current limiters		

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

2.6	**Provisions for earthing and bonding**		N/A
2.6.1	Protective earthing		N/A
2.6.2	Functional earthing		N/A
2.6.3	Protective earthing and protective bonding conductors		N/A
2.6.3.1	General		N/A
2.6.3.2	Size of protective earthing conductors		N/A
	Rated current (A), cross-sectional area (mm^2), AWG ..... :		—
2.6.3.3	Size of protective bonding conductors		N/A
	Rated current (A), cross-sectional area (mm^2), AWG ..... :		—
	Protective current rating (A), cross-sectional area (mm^2), AWG ..... :		
2.6.3.4	Resistance of earthing conductors and their terminations; resistance (Ω), voltage drop (V), test current (A), duration (min)..... :		N/A
2.6.3.5	Colour of insulation ..... :		N/A
2.6.4	Terminals		N/A
2.6.4.1	General		N/A
2.6.4.2	Protective earthing and bonding terminals		N/A
	Rated current (A), type, nominal thread diameter (mm)..... :		—
2.6.4.3	Separation of the protective earthing conductor from protective bonding conductors		N/A
2.6.5	Integrity of protective earthing		N/A
2.6.5.1	Interconnection of equipment		N/A
2.6.5.2	Components in protective earthing conductors and protective bonding conductors		N/A
2.6.5.3	Disconnection of protective earth		N/A
2.6.5.4	Parts that can be removed by an operator		N/A
2.6.5.5	Parts removed during servicing		N/A
2.6.5.6	Corrosion resistance		N/A
2.6.5.7	Screws for protective bonding		N/A
2.6.5.8	Reliance on telecommunication network or cable distribution system		N/A

2.7	**Overcurrent and earth fault protection in primary circuits**	N/A

2.7.1	Basic requirements		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	Instructions when protection relies on building installation		N/A
2.7.2	Faults not simulated in 5.3.7		N/A
2.7.3	Short-circuit backup protection		N/A
2.7.4	Number and location of protective devices ..... :		N/A
2.7.5	Protection by several devices		N/A
2.7.6	Warning to service personnel ..... :		N/A

2.8	**Safety interlocks**		N/A
2.8.1	General principles		N/A
2.8.2	Protection requirements		N/A
2.8.3	Inadvertent reactivation		N/A
2.8.4	Fail-safe operation		N/A
	Protection against extreme hazard		N/A
2.8.5	Moving parts		N/A
2.8.6	Overriding		N/A
2.8.7	Switches, relays and their related circuits		N/A
2.8.7.1	Separation distances for contact gaps and their related circuits (mm) ..... :		N/A
2.8.7.2	Overload test		N/A
2.8.7.3	Endurance test		N/A
2.8.7.4	Electric strength test		N/A
2.8.8	Mechanical actuators		N/A

2.9	**Electrical insulation**		P
2.9.1	Properties of insulating materials		P
2.9.2	Humidity conditioning		N/A
	Relative humidity (%), temperature (°C) ..... :		—
2.9.3	Grade of insulation		P
2.9.4	Separation from hazardous voltages		N/A
	Method(s) used ..... :		—

2.10	**Clearances, creepage distances and distances through insulation**		P
2.10.1	General	Functional insulation only.	P
2.10.1.1	Frequency ..... :		N/A
2.10.1.2	Pollution degrees ..... :	2	P

2.10.1.3	Reduced values for functional insulation	See 5.3.4.	P

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.10.1.4	Intervening unconnected conductive parts		N/A
2.10.1.5	Insulation with varying dimensions		N/A
2.10.1.6	Special separation requirements		N/A
2.10.1.7	Insulation in circuits generating starting pulses		N/A
2.10.2	Determination of working voltage		N/A
2.10.2.1	General		N/A
2.10.2.2	RMS working voltage		N/A
2.10.2.3	Peak working voltage		N/A
2.10.3	Clearances		N/A
2.10.3.1	General		N/A
2.10.3.2	Mains transient voltages		N/A
	a) AC mains supply ..... :		N/A
	b) Earthed d.c. mains supplies ..... :		N/A
	c) Unearthed d.c. mains supplies ..... :		N/A
	d) Battery operation ..... :		N/A
2.10.3.3	Clearances in primary circuits		N/A
2.10.3.4	Clearances in secondary circuits		N/A
2.10.3.5	Clearances in circuits having starting pulses		N/A
2.10.3.6	Transients from a.c. mains supply ..... :		N/A
2.10.3.7	Transients from d.c. mains supply ..... :		N/A
2.10.3.8	Transients from telecommunication networks and cable distribution systems ..... :		N/A
2.10.3.9	Measurement of transient voltage levels		N/A
	a) Transients from a mains supply		N/A
	For an a.c. mains supply ..... :		N/A
	For a d.c. mains supply ..... :		N/A
	b) Transients from a telecommunication network :		N/A
2.10.4	Creepage distances		N/A
2.10.4.1	General		N/A
2.10.4.2	Material group and comparative tracking index		N/A
	CTI tests..... :		—
2.10.4.3	Minimum creepage distances		N/A
2.10.5	Solid insulation		N/A
2.10.5.1	General		N/A
2.10.5.2	Distances through insulation		N/A
2.10.5.3	Insulating compound as solid insulation		N/A

2.10.5.4	Semiconductor devices		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.10.5.5.	Cemented joints		N/A
2.10.5.6	Thin sheet material – General		N/A
2.10.5.7	Separable thin sheet material		N/A
	Number of layers (pcs)..... :		—
2.10.5.8	Non-separable thin sheet material		N/A
2.10.5.9	Thin sheet material – standard test procedure		N/A
	Electric strength test		—
2.10.5.10	Thin sheet material – alternative test procedure		N/A
	Electric strength test		—
2.10.5.11	Insulation in wound components		N/A
2.10.5.12	Wire in wound components		N/A
	Working voltage ..... :		N/A
	a) Basic insulation not under stress ..... :		N/A
	b) Basic, supplementary, reinforced insulation ..... :		N/A
	c) Compliance with Annex U ..... :		N/A
	Two wires in contact inside wound component; angle between 45° and 90° ..... :		N/A
2.10.5.13	Wire with solvent-based enamel in wound components		N/A
	Electric strength test		—
	Routine test		N/A
2.10.5.14	Additional insulation in wound components		N/A
	Working voltage ..... :		N/A
	- Basic insulation not under stress ..... :		N/A
	- Supplementary, reinforced insulation ..... :		N/A
2.10.6	Construction of printed boards		N/A
2.10.6.1	Uncoated printed boards		N/A
2.10.6.2	Coated printed boards		N/A
2.10.6.3	Insulation between conductors on the same inner surface of a printed board		N/A
2.10.6.4	Insulation between conductors on different layers of a printed board		N/A
	Distance through insulation		N/A
	Number of insulation layers (pcs)..... :		N/A
2.10.7	Component external terminations		N/A
2.10.8	Tests on coated printed boards and coated components		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

2.10.8.1	Sample preparation and preliminary inspection		N/A
2.10.8.2	Thermal conditioning		N/A
2.10.8.3	Electric strength test		N/A
2.10.8.4	Abrasion resistance test		N/A
2.10.9	Thermal cycling		N/A
2.10.10	Test for Pollution Degree 1 environment and insulating compound		N/A
2.10.11	Tests for semiconductor devices and cemented joints		N/A
2.10.12	Enclosed and sealed parts		N/A

3	**WIRING, CONNECTIONS AND SUPPLY**		P
3.1	General		P
3.1.1	Current rating and overcurrent protection	Power supply is an 8ADC supply with our system having a 7.5A fuse.	P
3.1.2	Protection against mechanical damage	Wires chosen with thick insulation and installation instructions about layout.	P
3.1.3	Securing of internal wiring		N/A
3.1.4	Insulation of conductors		N/A
3.1.5	Beads and ceramic insulators		N/A
3.1.6	Screws for electrical contact pressure		N/A
3.1.7	Insulating materials in electrical connections		N/A
3.1.8	Self-tapping and spaced thread screws		N/A
3.1.9	Termination of conductors		N/A
	10 N pull test		N/A
3.1.10	Sleeving on wiring		N/A

3.2	**Connection to a mains supply**		N/A
3.2.1	Means of connection		N/A
3.2.1.1	Connection to an a.c. mains supply		N/A
3.2.1.2	Connection to a d.c. mains supply		N/A
3.2.2	Multiple supply connections		N/A
3.2.3	Permanently connected equipment		N/A
	Number of conductors, diameter of cable and conduits (mm) ..... :		—
3.2.4	Appliance inlets		N/A
3.2.5	Power supply cords		N/A

3.2.5.1	AC power supply cords		N/A
	Type ..... :		—

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Rated current (A), cross-sectional area (mm^2), AWG ..... :	7.5ADC	—
3.2.5.2	DC power supply cords	Rated 10 amp	P
3.2.6	Cord anchorages and strain relief	Sufficient	P
	Mass of equipment (kg), pull (N) ..... :		—
	Longitudinal displacement (mm) ..... :		—
3.2.7	Protection against mechanical damage		N/A
3.2.8	Cord guards		N/A
	Diameter or minor dimension D (mm); test mass (g) ..... :		—
	Radius of curvature of cord (mm) ..... :		—
3.2.9	Supply wiring space		N/A
3.3	**Wiring terminals for connection of external conductors**		N/A
3.3.1	Wiring terminals		N/A
3.3.2	Connection of non-detachable power supply cords		N/A
3.3.3	Screw terminals		N/A
3.3.4	Conductor sizes to be connected		N/A
	Rated current (A), cord/cable type, cross-sectional area (mm^2)..... :		—
3.3.5	Wiring terminal sizes		N/A
	Rated current (A), type, nominal thread diameter (mm) ..... :		—
3.3.6	Wiring terminal design		N/A
3.3.7	Grouping of wiring terminals		N/A
3.3.8	Stranded wire		N/A
3.4	**Disconnection from the mains supply**		N/A
3.4.1	General requirement		N/A
3.4.2	Disconnect devices		N/A
3.4.3	Permanently connected equipment		N/A
3.4.4	Parts which remain energized		N/A
3.4.5	Switches in flexible cords		N/A
3.4.6	Number of poles - single-phase and d.c. equipment		N/A
3.4.7	Number of poles - three-phase equipment		N/A
3.4.8	Switches as disconnect devices		N/A
3.4.9	Plugs as disconnect devices		N/A

3.4.10	Interconnected equipment		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
3.4.11	Multiple power sources		N/A
3.5	**Interconnection of equipment**		P
3.5.1	General requirements		P
3.5.2	Types of interconnection circuits ..... :	Interconnection circuits of SELV through the connectors.	P
3.5.3	ELV circuits as interconnection circuits		N/A
3.5.4	Data ports for additional equipment		N/A
4	**PHYSICAL REQUIREMENTS**		P
4.1	Stability		N/A
	Angle of 10°		N/A
	Test force (N) ..... :		N/A
4.2	**Mechanical strength**		N/A
4.2.1	General		N/A
	Rack-mounted equipment.		N/A
4.2.2	Steady force test, 10 N		N/A
4.2.3	Steady force test, 30 N		N/A
4.2.4	Steady force test, 250 N		N/A
4.2.5	Impact test		N/A
	Fall test		N/A
	Swing test		N/A
4.2.6	Drop test; height (mm) ..... :		N/A
4.2.7	Stress relief test		N/A
4.2.8	Cathode ray tubes		N/A
	Picture tube separately certified ..... :		N/A
4.2.9	High pressure lamps		N/A
4.2.10	Wall or ceiling mounted equipment; force (N) ..... :		N/A
4.3	**Design and construction**		N/A
4.3.1	Edges and corners	rounded	P
4.3.2	Handles and manual controls; force (N) .....:		N/A
4.3.3	Adjustable controls		N/A
4.3.4	Securing of parts	Tie downs	P
4.3.5	Connection by plugs and sockets		N/A

4.3.6	Direct plug-in equipment		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Torque ..... :		—
	Compliance with the relevant mains plug standard ..... :		N/A
4.3.7	Heating elements in earthed equipment		N/A
4.3.8	Batteries		N/A
	- Overcharging of a rechargeable battery		N/A
	- Unintentional charging of a non-rechargeable battery		N/A
	- Reverse charging of a rechargeable battery		N/A
	- Excessive discharging rate for any battery		N/A
4.3.9	Oil and grease		N/A
4.3.10	Dust, powders, liquids and gases		N/A
4.3.11	Containers for liquids or gases		N/A
4.3.12	Flammable liquids ..... :		N/A
	Quantity of liquid (l) ..... :		N/A
	Flash point (°C) ..... :		N/A
4.3.13	Radiation		N/A
4.3.13.1	General		N/A
4.3.13.2	Ionizing radiation		N/A
	Measured radiation (pA/kg) ..... :		—
	Measured high-voltage (kV) ..... :		—
	Measured focus voltage (kV) ..... :		—
	CRT markings ..... :		—
4.3.13.3	Effect of ultraviolet (UV) radiation on materials		N/A
	Part, property, retention after test, flammability classification ..... :		N/A
4.3.13.4	Human exposure to ultraviolet (UV) radiation ..... :		N/A
4.3.13.5	Lasers (including laser diodes) and LEDs		N/A
4.3.13.5.1	Lasers (including laser diodes)		N/A
	Laser class ..... :		—
4.3.13.5.2	Light emitting diodes (LEDs)		N/A
4.3.13.6	Other types ..... :		N/A

4.4	**Protection against hazardous moving parts**		N/A
4.4.1	General		N/A
4.4.2	Protection in operator access areas ..... :		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	Household and home/office document/media shredders		N/A
4.4.3	Protection in restricted access locations ..... :		N/A
4.4.4	Protection in service access areas		N/A
4.4.5	Protection against moving fan blades		N/A
4.4.5.1	General		N/A
	Not considered to cause pain or injury. a)……:		N/A
	Is considered to cause pain, not injury. b) ……:	Pinch points, label indicators	P
	Considered to cause injury. c) ……:	Topple over, weights provided for stability, labeled.	P
4.4.5.2	Protection for users		N/A
	Use of symbol or warning ……:	Labels for pinch points, weights required for stability	P
4.4.5.3	Protection for service persons		N/A
	Use of symbol or warning ……:		N/A

4.5	**Thermal requirements**		N/A
4.5.1	General		N/A
4.5.2	Temperature tests		N/A
	Normal load condition per Annex L ..... :		—
4.5.3	Temperature limits for materials		N/A
4.5.4	Touch temperature limits		N/A
4.5.5	Resistance to abnormal heat ..... :		N/A

4.6	**Openings in enclosures**		N/A
4.6.1	Top and side openings		N/A
	Dimensions (mm) ..... :		—
4.6.2	Bottoms of fire enclosures		N/A
	Construction of the bottom, dimensions (mm) .. :		—
4.6.3	Doors or covers in fire enclosures		N/A
4.6.4	Openings in transportable equipment		N/A
4.6.4.1	Constructional design measures		N/A
	Dimensions (mm) ..... :		—
4.6.4.2	Evaluation measures for larger openings		N/A
4.6.4.3	Use of metallized parts		N/A
4.6.5	Adhesives for constructional purposes		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Conditioning temperature (°C), time (weeks)..... :		—
4.7	**Resistance to fire**		P
4.7.1	Reducing the risk of ignition and spread of flame		P
	Method 1, selection and application of components wiring and materials	Use of materials with the required flammability classes.	P
	Method 2, application of all of simulated fault condition tests		N/A
4.7.2	Conditions for a fire enclosure		N/A
4.7.2.1	Parts requiring a fire enclosure		N/A
4.7.2.2	Parts not requiring a fire enclosure		N/A
4.7.3	Materials		P
4.7.3.1	General		P
4.7.3.2	Materials for fire enclosures		N/A
4.7.3.3	Materials for components and other parts outside fire enclosures		N/A
4.7.3.4	Materials for components and other parts inside fire enclosures		N/A
4.7.3.5	Materials for air filter assemblies		N/A
4.7.3.6	Materials used in high-voltage components		N/A
5	**ELECTRICAL REQUIREMENTS AND SIMULATED ABNORMAL CONDITIONS**		P
5.1	**Touch current and protective conductor current**		N/A
5.1.1	General		N/A
5.1.2	Configuration of equipment under test (EUT)		N/A
5.1.2.1	Single connection to an a.c. mains supply		N/A
5.1.2.2	Redundant multiple connections to an a.c. mains supply		N/A
5.1.2.3	Simultaneous multiple connections to an a.c. mains supply		N/A
5.1.3	Test circuit		N/A
5.1.4	Application of measuring instrument		N/A
5.1.5	Test procedure		N/A
5.1.6	Test measurements		N/A
	Supply voltage (V) ..... :		—
	Measured touch current (mA) ..... :		—

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Max. allowed touch current (mA) ..... :		—
	Measured protective conductor current (mA) ..... :		—
	Max. allowed protective conductor current (mA)... :		—
5.1.7	Equipment with touch current exceeding 3,5 mA		N/A
5.1.7.1	General ..... :		N/A
5.1.7.2	Simultaneous multiple connections to the supply		N/A
5.1.8	Touch currents to telecommunication networks and cable distribution systems and from telecommunication networks		N/A
5.1.8.1	Limitation of the touch current to a telecommunication network or to a cable distribution system		N/A
	Supply voltage (V) ..... :		—
	Measured touch current (mA) ..... :		—
	Max. allowed touch current (mA) ..... :		—
5.1.8.2	Summation of touch currents from telecommunication networks		N/A
	a) EUT with earthed telecommunication ports ..... :		N/A
	b) EUT whose telecommunication ports have no reference to protective earth		N/A

5.2	**Electric strength**		N/A
5.2.1	General		N/A
5.2.2	Test procedure		N/A

5.3	**Abnormal operating and fault conditions**		P
5.3.1	Protection against overload and abnormal operation	Fuse protected.	P
5.3.2	Motors	Pump, fused and thermal fuse	P
5.3.3	Transformers		N/A
5.3.4	Functional insulation..... :	Functional insulation complied with the requirements c).	P
5.3.5	Electromechanical components	5.3.2	N/A
5.3.6	Audio amplifiers in ITE ..... :		N/A
5.3.7	Simulation of faults		N/A
5.3.8	Unattended equipment		N/A
5.3.9	Compliance criteria for abnormal operating and fault conditions		N/A
5.3.9.1	During the tests		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.3.9.2	After the tests		N/A
6	**CONNECTION TO TELECOMMUNICATION NETWORKS**		N/A
6.1	Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment		N/A
6.1.1	Protection from hazardous voltages		N/A
6.1.2	Separation of the telecommunication network from earth		N/A
6.1.2.1	Requirements		N/A
	Supply voltage (V) ..... :		—
	Current in the test circuit (mA) ..... :		—
6.1.2.2	Exclusions ..... :		N/A
6.2	**Protection of equipment users from overvoltages on telecommunication networks**		N/A
6.2.1	Separation requirements		N/A
6.2.2	Electric strength test procedure		N/A
6.2.2.1	Impulse test		N/A
6.2.2.2	Steady-state test		N/A
6.2.2.3	Compliance criteria		N/A
6.3	**Protection of the telecommunication wiring system from overheating**		N/A
	Max. output current (A) ..... :		—
	Current limiting method ..... :		—
7	**CONNECTION TO CABLE DISTRIBUTION SYSTEMS**		N/A
7.1	General		N/A
7.2	Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous voltages in the equipment		N/A
7.3	Protection of equipment users from overvoltages on the cable distribution system		N/A
7.4	Insulation between primary circuits and cable distribution systems		N/A
7.4.1	General		N/A
7.4.2	Voltage surge test		N/A
7.4.3	Impulse test		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

A	**ANNEX A, TESTS FOR RESISTANCE TO HEAT AND FIRE**		N/A
A.1	Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2)		N/A
A.1.1	Samples ..... :		—
	Wall thickness (mm) ..... :		—
A.1.2	Conditioning of samples; temperature (°C) ..... :		N/A
A.1.3	Mounting of samples ..... :		N/A
A.1.4	Test flame (see IEC 60695-11-3)		N/A
	Flame A, B, C or D ..... :		—
A.1.5	Test procedure		N/A
A.1.6	Compliance criteria		N/A
	Sample 1 burning time (s)..... :		—
	Sample 2 burning time (s)..... :		—
	Sample 3 burning time (s)..... :		—
A.2	Flammability test for fire enclosures of movable equipment having a total mass not exceeding 18 kg, and for material and components located inside fire enclosures (see 4.7.3.2 and 4.7.3.4)		N/A
A.2.1	Samples, material ..... :		—
	Wall thickness (mm) ..... :		—
A.2.2	Conditioning of samples; temperature (°C) ..... :		N/A
A.2.3	Mounting of samples ..... :		N/A
A.2.4	Test flame (see IEC 60695-11-4)		N/A
	Flame A, B or C ..... :		—
A.2.5	Test procedure		N/A
A.2.6	Compliance criteria		N/A
	Sample 1 burning time (s)..... :		—
	Sample 2 burning time (s)..... :		—
	Sample 3 burning time (s)..... :		—
A.2.7	Alternative test acc. to IEC 60695-11-5, cl. 5 and 9		N/A
	Sample 1 burning time (s)..... :		—
	Sample 2 burning time (s)..... :		—
	Sample 3 burning time (s)..... :		—
A.3	Hot flaming oil test (see 4.6.2)		N/A
A.3.1	Mounting of samples		N/A
A.3.2	Test procedure		N/A
A.3.3	Compliance criterion		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

B	**ANNEX B, MOTOR TESTS UNDER ABNORMAL CONDITIONS (see 4.7.2.2 and 5.3.2)**		N/A
B.1	General requirements		N/A
	Position ..... :		—
	Manufacturer ..... :		—
	Type ..... :		—
	Rated values ..... :		—
B.2	Test conditions		N/A
B.3	Maximum temperatures		N/A
B.4	Running overload test		N/A
B.5	Locked-rotor overload test		N/A
	Test duration (days) ..... :		—
	Electric strength test: test voltage (V) ..... :		—
B.6	Running overload test for d.c. motors in secondary circuits		N/A
B.6.1	General		N/A
B.6.2	Test procedure		N/A
B.6.3	Alternative test procedure		N/A
B.6.4	Electric strength test; test voltage (V) ..... :		N/A
B.7	Locked-rotor overload test for d.c. motors in secondary circuits		N/A
B.7.1	General		N/A
B.7.2	Test procedure		N/A
B.7.3	Alternative test procedure		N/A
B.7.4	Electric strength test; test voltage (V) ..... :		N/A
B.8	Test for motors with capacitors		N/A
B.9	Test for three-phase motors		N/A
B.10	Test for series motors		N/A
	Operating voltage (V) ..... :		—

C	**ANNEX C, TRANSFORMERS (see 1.5.4 and 5.3.3)**		N/A
	Position ..... :		—
	Manufacturer ..... :		—
	Type ..... :		—
	Rated values ..... :		—

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Method of protection ..... :		—
C.1	Overload test		N/A
C.2	Insulation		N/A
	Protection from displacement of windings ..... :		N/A
D	**ANNEX D, MEASURING INSTRUMENTS FOR TOUCH-CURRENT TESTS (see 5.1.4)**		N/A
D.1	Measuring instrument		N/A
D.2	Alternative measuring instrument		N/A
E	**ANNEX E, TEMPERATURE RISE OF A WINDING (see 1.4.13)**		N/A
F	**ANNEX F, MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES (see 2.10 and Annex G)**		N/A
G	**ANNEX G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES**		N/A
G.1	Clearances		N/A
G.1.1	General		N/A
G.1.2	Summary of the procedure for determining minimum clearances		N/A
G.2	Determination of mains transient voltage (V)		N/A
G.2.1	AC mains supply ..... :		N/A
G.2.2	Earthed d.c. mains supplies ..... :		N/A
G.2.3	Unearthed d.c. mains supplies ..... :		N/A
G.2.4	Battery operation ..... :		N/A
G.3	Determination of telecommunication network transient voltage (V) ..... :		N/A
G.4	Determination of required withstand voltage (V)		N/A
G.4.1	Mains transients and internal repetitive peaks ..... :		N/A
G.4.2	Transients from telecommunication networks ..... :		N/A
G.4.3	Combination of transients		N/A
G.4.4	Transients from cable distribution systems		N/A
G.5	Measurement of transient voltages (V)		N/A
	a) Transients from a mains supply		N/A
	For an a.c. mains supply		N/A
	For a d.c. mains supply		N/A

	b) Transients from a telecommunication network		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.6	Determination of minimum clearances ..... :		N/A
H	**ANNEX H, IONIZING RADIATION (see 4.3.13)**		N/A
J	**ANNEX J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6)**		N/A
	Metal(s) used ..... :		—
K	**ANNEX K, THERMAL CONTROLS (see 1.5.3 and 5.3.8)**		N/A
K.1	Making and breaking capacity		N/A
K.2	Thermostat reliability; operating voltage (V) ..... :		N/A
K.3	Thermostat endurance test; operating voltage (V) ..... :		N/A
K.4	Temperature limiter endurance; operating voltage (V) ..... :		N/A
K.5	Thermal cut-out reliability		N/A
K.6	Stability of operation		N/A
L	**ANNEX L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.2)**		P
L.1	Typewriters		N/A
L.2	Adding machines and cash registers		N/A
L.3	Erasers		N/A
L.4	Pencil sharpeners		N/A
L.5	Duplicators and copy machines		N/A
L.6	Motor-operated files		N/A
L.7	Other business equipment	See summary of testing.	P
M	**ANNEX M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)**		N/A
M.1	Introduction		N/A
M.2	Method A		N/A
M.3	Method B		N/A
M.3.1	Ringing signal		N/A
M.3.1.1	Frequency (Hz) ..... :		—
M.3.1.2	Voltage (V) ..... :		—
M.3.1.3	Cadence; time (s), voltage (V) ..... :		—
M.3.1.4	Single fault current (mA) ..... :		—
M.3.2	Tripping device and monitoring voltage ..... :		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
M.3.2.1	Conditions for use of a tripping device or a monitoring voltage		N/A
M.3.2.2	Tripping device		N/A
M.3.2.3	Monitoring voltage (V) ..... :		N/A
N	**ANNEX N, IMPULSE TEST GENERATORS (see 1.5.7.2, 1.5.7.3, 2.10.3.9, 6.2.2.1, 7.3.2, 7.4.3 and Clause G.5)**		N/A
N.1	ITU-T impulse test generators		N/A
N.2	IEC 60065 impulse test generator		N/A
P	**ANNEX P, NORMATIVE REFERENCES**		—
Q	**ANNEX Q, Voltage dependent resistors (VDRs) (see 1.5.9.1)**		N/A
	a) Preferred climatic categories ..... :		N/A
	b) Maximum continuous voltage ..... :		N/A
	c) Pulse current ..... :		N/A
R	**ANNEX R, EXAMPLES OF REQUIREMENTS FOR QUALITY CONTROL PROGRAMMES**		N/A
R.1	Minimum separation distances for unpopulated coated printed boards (see 2.10.6.2)		N/A
R.2	Reduced clearances (see 2.10.3)		N/A
S	**ANNEX S, PROCEDURE FOR IMPULSE TESTING (see 6.2.2.3)**		N/A
S.1	Test equipment		N/A
S.2	Test procedure		N/A
S.3	Examples of waveforms during impulse testing		N/A
T	**ANNEX T, GUIDANCE ON PROTECTION AGAINST INGRESS OF WATER (see 1.1.2)**		N/A
			—
U	**ANNEX U, INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION (see 2.10.5.4)**		N/A
			—
V	**ANNEX V, AC POWER DISTRIBUTION SYSTEMS (see 1.6.1)**		N/A

V.1	Introduction		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
V.2	TN power distribution systems		N/A
W	**ANNEX W, SUMMATION OF TOUCH CURRENTS**		N/A
W.1	Touch current from electronic circuits		N/A
W.1.1	Floating circuits		N/A
W.1.2	Earthed circuits		N/A
W.2	Interconnection of several equipments		N/A
W.2.1	Isolation		N/A
W.2.2	Common return, isolated from earth		N/A
W.2.3	Common return, connected to protective earth		N/A
X	**ANNEX X, MAXIMUM HEATING EFFECT IN TRANSFORMER TESTS (see clause C.1)**		N/A
X.1	Determination of maximum input current		N/A
X.2	Overload test procedure		N/A
Y	**ANNEX Y, ULTRAVIOLET LIGHT CONDITIONING TEST (see 4.3.13.3)**		N/A
Y.1	Test apparatus ..... :		N/A
Y.2	Mounting of test samples ..... :		N/A
Y.3	Carbon-arc light-exposure apparatus ..... :		N/A
Y.4	Xenon-arc light exposure apparatus ..... :		N/A
Z	**ANNEX Z, OVERVOLTAGE CATEGORIES (see 2.10.3.2 and Clause G.2)**		N/A
AA	**ANNEX AA, MANDREL TEST (see 2.10.5.8)**		N/A
BB	**ANNEX BB, CHANGES IN THE SECOND EDITION**		—
CC	**ANNEX CC, Evaluation of integrated circuit (IC) current limiters**		N/A
CC.1	General		N/A
CC.2	Test program 1……..:		N/A
CC.3	Test program 2……..:		N/A
DD	**ANNEX DD, Requirements for the mounting means of rack-mounted equipment**		N/A
DD.1	General		N/A
DD.2	Mechanical strength test, variable N……..:		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
DD.3	Mechanical strength test, 250N, including end stops……:		N/A
DD.4	Compliance……:		N/A
EE	**ANNEX EE, Household and home/office document/media shredders**		N/A
EE.1	General		N/A
EE.2	Markings and instructions		N/A
	Use of markings or symbols……:		N/A
	Information of user instructions, maintenance and/or servicing instructions……:		N/A
EE.3	Inadvertent reactivation test……:		N/A
EE.4	Disconnection of power to hazardous moving parts:		N/A
	Use of markings or symbols……:		N/A
EE.5	Protection against hazardous moving parts		N/A
	Test with test finger (Figure 2A) ……:		N/A
	Test with wedge probe (Figure EE1 and EE2) ……:		N/A

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

1.5.1	TABLE: List of critical components				P
Object/part No.	Manufacturer/ trademark	Type/model	Technical data	Standard (Edition / year)	Mark(s) of conformity
PCB	Interchangeable	Interchangeable	V-1 or better, 105°C	UL 796	UL
Supplementary information:					

4.7	TABLE: Resistance to fire				P
Part	Manufacturer of material	Type of material	Thickness (mm)	Flammability class	Evidence
PCB	--	--	--	1	1 .