

AI Assistant Coding

15.1 Assignment

Name : B. Sai Prasanna

Batch :08

Rollno : 2303A51551

Task 1 – Student Records API Task:

Use AI to build a RESTful API for managing student records.

Instructions:

- Endpoints required:
 - o GET /students → List all students
 - o POST /students → Add a new student
 - o PUT /students/{id} → Update student details
 - o DELETE /students/{id} → Delete a student record
- Use an in-memory data structure (list or dictionary) to store records.

- Ensure API responses are in JSON format.

Expected Output:

- Working API with CRUD functionality for student records.

```
Task 1 – Student Records API

[6] ✓ 0s from fastapi import FastAPI

app = FastAPI()

# In-memory storage
students = []

# GET → List all students
@app.get("/students")
def get_students():
    return students

# POST → Add new student
@app.post("/students")
def add_student(student: dict):
    students.append(student)
    return {"message": "Student added", "data": student}

# PUT → Update student
@app.put("/students/{id}")
def update_student(id: int, updated_student: dict):
    for i in range(len(students)):
        if students[i]["id"] == id:
            students[i] = updated_student
    return {"message": "Student updated", "data": updated_student}
```

```
[6] ✓ Os 
return {"message": "Student added", "data": student}

# PUT → Update student
@app.put("/students/{id}")
def update_student(id: int, updated_student: dict):
    for i in range(len(students)):
        if students[i]["id"] == id:
            students[i] = updated_student
            return {"message": "Student updated", "data": updated_student}
    return {"error": "Student not found"}

# DELETE → Delete student
@app.delete("/students/{id}")
def delete_student(id: int):
    for i in range(len(students)):
        if students[i]["id"] == id:
            deleted = students.pop(i)
            return {"message": "Student deleted", "data": deleted}
    return {"error": "Student not found"}
```

Observation:

- The API correctly performs:
 - Create (POST /books) ◦ Read (GET /books, GET /books/{id}) ◦ Update (PATCH /books/{id}) ◦ Delete (DELETE /books/{id})
- All endpoints return proper JSON responses

Task 2 – Library Book Management API Task:

Develop a RESTful API to handle library books.

Instructions:

- Endpoints required:
 - GET /books → Retrieve all books
 - POST /books → Add a new book
 - GET /books/{id} → Get details of a specific book
 - PATCH /books/{id} → Update partial book details (e.g., availability)
 - DELETE /books/{id} → Remove a book
- Implement error handling for invalid requests.

Expected Output:

- Functional API with CRUD + partial updates.

Task 3 – Employee Payroll API

```
[7]
✓ Os
from fastapi import FastAPI
app = FastAPI()
employees = []
@app.get("/employees")
def get_employees():
    """
    Retrieve all employees.
    Returns a list of employee records.
    """
    return employees

@app.post("/employees")
def add_employee(emp: dict):
    """
    Add a new employee with salary details.
    Expects: id, name, role, salary
    """
    # Check if employee ID already exists
    for e in employees:
        if e["id"] == emp["id"]:
            return {"error": "Employee ID already exists"}

    employees.append(emp)
    return {"message": "Employee added", "data": emp}
@app.put("/employees/{id}/salary")
def update_salary(id: int, data: dict):
    """
```

```
"""
    @app.put("/employees/{id}/salary")
    def update_salary(id: int, data: dict):
        """
        Update salary of an employee.
        Expects: {"salary": new_salary}
        """
        for e in employees:
            if e["id"] == id:
                e["salary"] = data.get("salary", e["salary"])
                return {"message": "Salary updated", "data": e}

        return {"error": "Employee not found"}
    # delete
    @app.delete("/employees/{id}")
    def delete_employee(id: int):
        """
        Remove an employee from the system.
        """
        for i in range(len(employees)):
            if employees[i]["id"] == id:
                removed = employees.pop(i)
                return {"message": "Employee deleted", "data": removed}

        return {"error": "Employee not found"}
```

Observation:

- Books are stored in a Python dictionary.
- Each book is assigned a unique ID.
- Data is temporary (lost when server restarts).

Task 3 – Employee Payroll API Task:

Create an API for managing employees and their salaries.

Instructions:

- Endpoints required: o GET /employees → List all employees o POST /employees → Add a new employee with salary details o

PUT /employees/{id}/salary → Update salary of an employee o

DELETE /employees/{id} → Remove employee from system

- Use AI to:

o Suggest data model structure. o Add

comments/docstrings for all endpoints.

Expected Output:

- API supporting salary management with clear documentation.

```
Task 3 – Employee Payroll API

[7] 0s ▶ from fastapi import FastAPI
      app = FastAPI()
      employees = []
      @app.get("/employees")
      def get_employees():
          """
          Retrieve all employees.
          Returns a list of employee records.
          """
          return employees

      @app.post("/employees")
      def add_employee(emp: dict):
          """
          Add a new employee with salary details.
          Expects: id, name, role, salary
          """
          # Check if employee ID already exists
          for e in employees:
              if e["id"] == emp["id"]:
                  return {"error": "Employee ID already exists"}

          employees.append(emp)
          return {"message": "Employee added", "data": emp}

      @app.put("/employees/{id}/salary")
      def update_salary(id: int, data: dict):
          """
          Update salary of an employee.
          Expects: {"salary": new_salary}
          """
          for e in employees:
              if e["id"] == id:
                  e["salary"] = data.get("salary", e["salary"])
                  return {"message": "Salary updated", "data": e}

          return {"error": "Employee not found"}

      # delete
      @app.delete("/employees/{id}")
      def delete_employee(id: int):
          """
          Remove an employee from the system.
          """
          for i in range(len(employees)):
              if employees[i]["id"] == id:
                  removed = employees.pop(i)
                  return {"message": "Employee deleted", "data": removed}

          return {"error": "Employee not found"}
```

Observation:

- If "title" is missing → API returns: {"error": "Title is required"}
- Prevents invalid data from being stored

Task 4 – Real-Time Application: Online Food Ordering API Scenario:

Design a simple API for an online food ordering system.

Requirements:

- Endpoints required:
 - o GET /menu → List available dishes
 - o POST /order → Place a new order
 - o GET /order/{id} → Track order status
 - o PUT /order/{id} → Update an existing order (e.g., change items)
 - o DELETE /order/{id} → Cancel an order
- AI should generate:
 - o REST API code
 - o Suggested improvements (like authentication, pagination)

Expected Output:

- Fully working API simulating a food ordering backend.

Deliverables (For All Tasks)

1. AI-generated prompts for code and test case generation.
2. At least 3 assert test cases for each task.
3. AI-generated initial code and execution screenshots.
4. Analysis of whether code passes all tests.
5. Improved final version with inline comments and explanation.
6. Compiled report (Word/PDF) with prompts, test cases, assertions, code, and output.

Task 4 – Real-Time Application: Online Food Ordering API

```
from fastapi import FastAPI

app = FastAPI()
menu = [
    {"id": 1, "name": "Pizza", "price": 200},
    {"id": 2, "name": "Burger", "price": 100},
    {"id": 3, "name": "Pasta", "price": 150}
]

orders = []
@app.get("/menu")
def get_menu():
    """Return all available dishes"""
    return menu

@app.post("/order")
def place_order(order: dict):
    """
    Place a new order.
    Expects: {"id": int, "items": [dish_ids]}
    """
    total = 0
    selected_items = []

    for item_id in order["items"]:
        for dish in menu:
            if dish["id"] == item_id:
```

```

[] ▶ for dish in menu:
    if dish["id"] == item_id:
        total += dish["price"]
        selected_items.append(dish)

    new_order = {
        "id": order["id"],
        "items": selected_items,
        "total_price": total,
        "status": "placed"
    }

    orders.append(new_order)
    return {"message": "Order placed", "order": new_order}

@app.get("/order/{id}")
def get_order(id: int):
    """Get order details by ID"""
    for o in orders:
        if o["id"] == id:
            return o
    return {"error": "Order not found"}

@app.put("/order/{id}")
def update_order(id: int, data: dict):
    """
    Update order items.
    Expects: {"items": [dish_ids]}
    """
    for o in orders:

```

```

[] ▶ def update_order(id: int, data: dict):
    """
    Update order items.
    Expects: {"items": [dish_ids]}
    """
    for o in orders:
        if o["id"] == id:
            total = 0
            new_items = []

            for item_id in data["items"]:
                for dish in menu:
                    if dish["id"] == item_id:
                        total += dish["price"]
                        new_items.append(dish)

            o["items"] = new_items
            o["total_price"] = total
            o["status"] = "updated"

            return {"message": "Order updated", "order": o}

    return {"error": "Order not found"}

@app.delete("/order/{id}")
def delete_order(id: int):
    """Cancel an order"""
    for i in range(len(orders)):
        if orders[i]["id"] == id:
            removed = orders.pop(i)
            return {"message": "Order cancelled", "order": removed}

```

```

[] ▶ def update_order(id: int, data: dict):
    """
    Update order items.
    Expects: {"items": [dish_ids]}
    """
    for o in orders:
        if o["id"] == id:
            total = 0
            new_items = []

            for item_id in data["items"]:
                for dish in menu:
                    if dish["id"] == item_id:
                        total += dish["price"]
                        new_items.append(dish)

            o["items"] = new_items
            o["total_price"] = total
            o["status"] = "updated"

            return {"message": "Order updated", "order": o}

    return {"error": "Order not found"}

@app.delete("/order/{id}")
def delete_order(id: int):
    """Cancel an order"""
    for i in range(len(orders)):
        if orders[i]["id"] == id:
            removed = orders.pop(i)
            return {"message": "Order cancelled", "order": removed}

    return {"error": "Order not found"}

```

Observation:

- When book ID does not exist:

```
{"error": "Book not found"}
```

- Proper HTTP status codes used:
 - 400 → Bad request
 - 404 → Not found
 - 201 → Created