University of Hertfordshire UH

School of Physics, Engineering and Computer Science

MSc Data Science Project
7PAM2002

Department of Physics, Astronomy and Mathematics

Data Science FINAL PROJECT REPORT

Project Title:

Predicting Bike Sharing Demand Using Machine Learning and Temporal Features.

Student Name and SRN:

Thammishetti Venkat Sai Prathap

24089794

Supervisor: Pushp Raj Tiwari

Date Submitted: 21/04/2026

Word Count: 4874

GitHub Repository: https://github.com/Saiprathap22/Predicting-Bike-Sharing-Demand-Using-Machine-Learning-and-Temporal-Features

DECLARATION STATEMENT

This report is submitted in partial fulfilment of the requirement for the degree of Master of Science **in Data Science** at the University of Hertfordshire.

I have read the detailed guidance to students on academic integrity, misconduct and plagiarism information at Assessment Offences and Academic Misconduct and understand the University process of dealing with suspected cases of academic misconduct and the possible penalties, which could include failing the project or course.

I certify that the work submitted is my own and that any material derived or quoted from published or unpublished work of other persons has been duly acknowledged. (Ref. UPR AS/C/6.1, section 7 and UPR AS/C/5, section 3.6)

I did not use human participants in my MSc Project.

I hereby give permission for the report to be made available on module websites provided the source is acknowledged.

Student Name printed: Thammishetti Venkat Sai Prathap

Student Name signature : Thammishetti venkat Sai Prathap

Student SRN number: 24089794

UNIVERSITY OF HERTFORDSHIRE

SCHOOL OF PHYSICS, ENGINEERING AND COMPUTER SCIENCE

1. Abstract:

This project looks at how machine learning and time-series methods can predict hourly bike rentals. It uses the UCI Bike Sharing Dataset from the Capital Bikeshare system in Washington, D.C. The study compares three modeling approaches: Random Forest, XGBoost with time lag features, and SARIMAX. Cyclical sin/cos encoding for hour and month variables to keep circular periodicity, lag features at one-hour, daily, and weekly intervals to capture autocorrelation, and time-aware cross-validation using TimeSeriesSplit to stop data leakage are all important feature engineering techniques. I used RMSE, MAE, R^2, and MAPE to test the models on a 20% chronological test set that i don't use for training. The tuned XGBoost model did the best job, with R^2=0.955, RMSE=46.13, and MAE=29.84. This is a big improvement over SARIMAX (R^2=0.486). This shows that gradient-boosted ensemble methods with temporal lag features can effectively capture the nonlinear, cyclical demand patterns that are common in urban bike sharing systems. The results are better than those found in similar studies and show that using lag features and cyclical encoding are the best ways to model this problem.

Table of contents:

	Title	Page No
1	Abstract	3
2	Introduction	6
2.1	Research Question	6
2.2	Aims	6
2.3	Objectives	7
3	Literature Review	7
3.1	Operational Context and Motivation	7
3.2	Machine Learning Approaches	7
3.3	Statistical Time-Series Methods	8
4	Dataset Description	8
5	Ethical Considerations	8
6	Exploratory Data Analysis (EDA)	9
6.1	Target Variable Distribution	9
6.2	Categorical Feature Distributions	9
6.3	Feature Correlations	10
6.4	Temporal Patterns	12
6.5	Feature Spread and Outlier Check	14
7	Methodology	15
7.1	Feature Engineering and Preprocessing	15
7.2	Random Forest Model	15
7.3	XGBoost Model	15
7.4	SARIMAX Model	16
7.5	Mathematical Formulation	16
7.6	Evaluation Metrics	17
8	Hyperparameter Tuning	17
8.1	Random Forest — Tuned	17
8.2	XGBoost — Tuned	17

8.3	SARIMAX — Tuned (auto_arima)	17
9	Results	18
9.1	Random Forest Results	19
9.2	XGBoost Results	19
9.3	SARIMAX Results	20
9.4	Tuned Model Results	20
9.5	Tuned SARIMAX Results	21
10	Analysis and Discussion	22
10.1	Why XGBoost Outperformed Random Forest	22
10.2	Random Forest Feature Importance	23
10.3	Why SARIMAX Underperformed	23
10.4	Comparison to Published Literature	24
10.5	Practical Implications and Limitations	24
11	Conclusion	25
12	Future Work	25
13	References	26
14	Appendix	27

2. Introduction

Bike-sharing systems are now an important part of sustainable urban transportation systems all over the world. These systems have grown to include over 500 programs and more than 500,000 bicycles around the world since they became popular in the early 2000s (Shaheen et al., 2010). Each rental transaction creates a digital record with a timestamp of the start, end, and length of the trip. This turns docking station networks into dense sensors of how people move around cities, which is different from traditional public transportation.

It is very important for business to be able to accurately predict demand. When bikes aren't available where they're needed or docking bays are full at return points, users stop using the system and operators have to deal with expensive rebalancing logistics. Good forecasting helps to put bikes in the right places before peak demand, plan maintenance better, and run the fleet more smoothly. Better forecasting at the city level makes bike sharing a more environmentally friendly way to get around in the last mile.

A lot of different things affect how many people use bike-sharing systems, including time and place. The time of day is the main factor that affects demand, with sharp peaks in commuter traffic at 08:00 and 17:00–18:00. Temperature, humidity, wind speed, and seasonal changes also affect demand in ways that are not always clear. These complicated interactions on many levels make it necessary to use machine learning methods that can learn how features relate to each other directly from data. This project uses Random Forest, XGBoost with temporal lag features, and SARIMAX on the UCI Bike Sharing Dataset to see if gradient-boosted ensemble methods with autocorrelation features do much better than classical statistical time-series models.

2.1. Research Question

How well can machine learning and time-series models use environmental and temporal features to predict hourly bike rental demand? Do adding autocorrelation lag features and cyclical encoding make predictions more accurate than baseline methods?

2.2. Aims

To create and test machine learning and statistical models that can predict hourly bike rental demand using the Capital Bikeshare dataset.

To use the same held-out test set to compare Random Forest, XGBoost, and SARIMAX using the same evaluation metrics.

To evaluate the effect of temporal feature engineering—cyclical encoding and lag features—on model precision.

To compare the results to what has already been written about predicting the demand for bike sharing.

2.3. Objectives

Preparing the UCI Bike Sharing Dataset (hour.csv) for time-series analysis by loading it and doing some work on it. Use exploratory data analysis to learn about patterns in demand, how the seasons affect it, and how features are related to each other.

Creating temporal features like cyclical sin/cos encoding and lag variables that happen every hour, every day, and every week. using consistent 80/20 chronological train-test splits to set up baseline and tuned versions of Random Forest, XGBoost, and SARIMAX.

Using RandomizedSearchCV with TimeSeriesSplit cross-validation to find the right hyperparameters.use RMSE, MAE, R^2, and MAPE to test all models and see how they compare to published benchmarks.

3. Literature Review

As bike-sharing systems have grown in popularity in big cities, demand forecasting for these systems has become a hot topic in academia. This part looks at the most important work in a critical way and points out the gaps that this project fills.

3.1. Operational Context and Motivation

Shaheen, Guzman, and Zhang (2010) conducted one of the initial extensive global assessments of bike-sharing systems, analysing more than 100 programs that included around 139,300 bicycles throughout Europe, the Americas, and Asia. Their taxonomy put systems into three groups, with IT-Based Systems being the last one. In these systems, all transactions are recorded digitally. Shaheen et al. (2010) identified accurate demand forecasting and the physical redistribution of bikes as the main operational problems. They also said that weather, time of day, and user demographics are all important factors that affect demand. But their study was only a review of the context; they didn't suggest a predictive model. This is what led to the data-driven approach used in this project.

3.2. Machine Learning Approaches

Sathishkumar, Park, and Cho (2020a) utilised five regression models—GBM, XGBoost, SVM, Bagged Trees, and Linear Model—on the Seoul Bike Sharing dataset, comprising 8,760 hourly records from 2017 to 2018. Their GBM had a R^2 of 0.92 and an RMSE of 172.73. Hour and Temperature were always the two most important predictors. This study is the most methodologically comparable and serves as a key standard. Sathishkumar et al. (2020a), on the other hand, used a static 75/25 split without temporal ordering, didn't use lag features to take advantage of autocorrelation, and used raw integer encoding for hour and month instead of cyclical transformations. The current project is focused on filling in these gaps. Sathishkumar and Cho (2020b) expanded upon this research by employing a rule-based CUBIST model, which was compared against Random Forest, CART, KNN, and Conditional Inference Trees utilising both the Seoul dataset and the Capital Bikeshare dataset—identical datasets to those utilised herein. CUBIST got a R^2 value of 0.89 on the Capital Bikeshare data,

which is the most directly comparable published benchmark for this dataset. The authors observed interpretative benefits of rule-based methodologies. Nonetheless, neither lag features nor time-sensitive cross-validation were utilised.

3.3. Statistical Time-Series Methods

Smith, Williams, and Oswald (2002) showed that parametric time-series models like ARIMA work well for short-term predictions of unimodal traffic patterns, but they don't work as well when demand is driven by more than one interacting covariate. The demand for bike sharing, which is affected by a number of factors, including time, weather, and behaviour, is a perfect example of this multi-driver scenario. This is why SARIMAX is used as a statistical baseline to measure the performance gap between machine learning and other methods.

4. Dataset Description

Source: UCI Machine Learning Repository — Bike Sharing Dataset

(https://archive.ics.uci.edu/dataset/275/bike+sharing+dataset)

I used the UCI Bike Sharing Dataset from Fanaee-T and Gama in 2014. It came from Washington D.C.'s Capital Bikeshare system.There are 17,379 hourly records from 2011 to 2012, and each record has 16 attributes that show the time (hour, day, month, year), the weather (temperature, humidity, wind speed, and weather status), and seasonal indications.

The target variable, cnt, shows how many rentals there are each hour. The dataset has no missing values or duplicate records, and it covers two years, which means it includes both seasonal cycles and year-on-year growth. This makes the year variable (yr) useful for making predictions.

5. Ethical Considerations

This project only uses public data that has been anonymised and combined. There is no personally identifiable information in the UCI Bike Sharing Dataset. Rental records are reported as hourly aggregate counts without any user identifiers. The data is not subject to GDPR rules for processing personal data because of this.

At no point in this study were there any surveys, interviews, or people involved. The dataset is accessible for academic purposes, and its utilisation in publications necessitates citation of the original work by Fanaee-T and Gama (2014). This project follows the University of Hertfordshire's rules for citations, ethics, and best research practices. Approval from the university's ethics committee was not necessary.

6. Exploratory data analysis (EDA)

I did some exploratory data analysis to see how the target variable was distributed, find patterns in demand over time, spot any unusual data points, and check how different features relate to rental demand.the analysis helped me make decisions about feature engineering and modelling that came after it.

6.1. Target Variable Distribution



Figure 1: How many bike rentals there are every hour (cnt). The distribution is right-skewed, with a median of about 142 and a mean of about 189 rentals per hour.

- Shows that the target variable cnt is right-skewed, with a median of about 142 and a mean of 189 rentals per hour.
- The distribution has a long right tail that shows that there are sometimes high-demand commuter peaks, but most hours have low to moderate demand.

6.2. Categorical Feature Distributions



Figure 2: Frequency distributions of categorical features: season (left), weather situation (center), and weekday (right).

- The frequency distributions for season, weather, and day of the week are shown in Figure 2.

- There are about the same number of records for each of the four seasons (about 4,200 to 4,500), which shows that the differences in demand between seasons are real and not due to sampling bias. Most of the observations (about 11,400) were made when the weather was clear.
- Misty or cloudy conditions were second (about 4,600). There are about 2,400 to 2,500 records for each of the seven days of the week, which shows that weekday is a useful feature.

6.3. Feature Correlations



Figure 3: A heatmap showing how all the numbers are related. The temperature features have the strongest positive correlation with cnt ($r \approx 0.40$), while the humidity features have a moderate negative correlation ($r \approx -0.32$).

- The correlation heatmap (Figure 3) shows that temperature (temp, atemp) has the strongest positive correlation with cnt ($r \approx 0.40$), humidity has a moderate negative correlation ($r \approx -0.32$), and wind speed has a weak negative correlation ($r \approx -0.12$).
- It was noted that temp and atemp are very similar ($r \approx 0.99$), but both are kept because tree-based models don't care about multicollinearity.
- The registered user count ($r \approx 0.97$ with cnt) shows that most of the demand comes from people who ride the bus to work.



Figure 4: Scatter plot of temperature and rental count, showing a nonlinear relationship with demand peaking at a normalised temperature of 0.4–0.7.



Figure 5: A scatter plot showing the relationship between wind speed and rental count. Weak negative correlation with significant variability across all wind speeds.

- The scatter plot of temperature and demand (Figure 4) shows that there is a nonlinear relationship between the two.
- Demand peaks at normalised temperatures of 0.4–0.7 and then drops off at very high values.
- This confirms that nonlinear tree-based models are better than linear regression. Figure 5 shows that demand and wind speed have a weak and noisy negative relationship.

6.4. Temporal Patterns



Figure 6: Average rentals by hour of the day (with a 95% confidence interval) . There is a clear bimodal commuter pattern, with a morning peak at 08:00 (about 350) and an evening peak at 17:00–18:00 (about 460).

- Figure 6 shows the average demand by hour of the day. It shows the main bimodal commuter pattern: a sharp peak in the morning at 08:00 (about 350 rentals/hour).
- A larger peak in the evening at 17:00–18:00 (about 460 rentals/hour). Between midnight and 5:00 AM, demand is almost nonexistent.
- This dual-peak structure shows that hour is the best predictor and encourages cyclical sin/cos encoding to keep the circular continuity between 23:00 and 00:00.



Figure 7: Average monthly rentals (with a 95% confidence interval). In the summer, demand is at its highest (about 240/hour), but it drops to about 90–100/hour in January and February.

- Figure 7 It shows that monthly demand has a seasonal pattern, with the most demand in the summer(June to September, about 235 to 240 rentals per hour).
- The lowest in the winter (January to February, about 90 to 115 rentals per hour).



Figure 8: Average hourly rental count by year: 2011 (about 145) and 2012 (about 234). This shows that demand has gone up by 61%



Figure 9: Total rentals by year: 2011 (around 1.25 million) and 2012 (around 2.05 million). Year-on-year growth shows that yr variable carries a significant signal.

- Figures 8 and 9 show that average hourly rentals went up from about 145 in 2011 to 234 in 2012, and total annual rentals went up from about 1.25 million to 2.05 million. This shows that year (yr) is a useful predictive feature.

6.5. Feature Spread and Outlier Check



Figure 10: Boxplot of predictor features spread. Hour (hr) and month (mnth) have the widest natural range. No extreme outliers in predictor variables.

- Figure 10's boxplot shows how all of the predictor features are spread out and how big they are.

- The hour variable (hr) has the biggest range (0–23), and the month variable (1–12) comes next.
- There isn't much difference between the Boolean features (holiday, working day) and the normalised meteorological features. There were no extreme outliers in the predictor variables.

7. Methodology

I used a comparative machine learning method to guess how many bikes will be rented each hour. I look at three model families: Random Forest, XGBoost, and SARIMAX. Each one captures demand dynamics in a different way. All models go through the same preprocessing and evaluation pipeline every time. First, baseline models are tested, and then hyperparameter optimisation is done. All models use an 80/20 chronological train-test split: training on 13,903 records from January 2011 to about August 2012 and testing on 3,476 records from the second half of 2012. No random shuffling is done to keep future data from messing up the training period.

7.1. Feature Engineering and Preprocessing

I got rid of the casual and registered columns (which are parts of the target cnt) and the instant identifier column from all models.

Cyclical encoding: hr and mnth were changed to sin/cos pairs by using sin(2π·x/period) and cos(2π·x/period). This kept the circular continuity (for example, 23:00 is next to 00:00). Used pd.get_dummies() with drop_first=True, one-hot encoded the season, weathersit, and weekday.
For XGBoost only, lag_1 (1-hour), lag_24 (24-hour), and lag_168 (168-hour) autocorrelation lags were calculated from cnt to take advantage of temporal autocorrelation.

7.2. Random Forest Model

The Random Forest Regressor was chosen as the base ensemble method. It makes several decision trees from bootstrap samples and averages their predictions to lower the amount of variation. The baseline model used the default parameters for sklearn, which were n_estimators=100 and random_state=42. The features are cyclical encodings, one-hot encoded categoricals, and all numeric features like temp, atemp, hum, windspeed, yr, workingday, and holiday.

7.3. XGBoost Model

XGBoost uses gradient-boosted decision trees to build an ensemble one at a time, with each tree fixing the mistakes of the previous ensemble. L1 and L2 regularisation terms keep models from overfitting. The most important improvement over Random Forest is the addition of lag features (lag_1, lag_24, lag_168), which lets the model take advantage of autocorrelation in

the demand signal. The baseline XGBoost model used these settings: 800 estimators, a learning rate of 0.05, a maximum depth of 7, a subsample of 0.8, and a colsample_bytree of 0.8.

7.4. SARIMAX Model

SARIMAX was used as a standard statistical baseline to measure the difference in performance between machine learning and other methods. The SARIMAX(1,0,1)(1,0,1)[24] model has a seasonal period of 24, which matches the daily demand pattern. The Augmented Dickey-Fuller (ADF) test found that the data is already stable ($p < 0.05$), so we didn't need to make any changes to it (d=0, D=0).The ACF and PACF plots (Figure 11) helped us choose AR order p=1 and MA order q=1. Cyclical hr and mnth encodings, temp, hum, windspeed, workingday, and weathersit are examples of exogenous regressors.



Figure 11: The training series' ACF (left) and PACF (right). Significant spikes at lags 1 and 24 confirm strong hourly and daily autocorrelation, which helps us choose SARIMAX(1,0,1)(1,0,1)[24].

7.5. Mathematical Formulation

Random Forest:

$\hat{y} = (1/B) \Sigma f_b(x)$, where $f_b(x)$ is the prediction of the b-th tree across B bootstrap trees.

XGBoost:

η is the learning rate and x_t has lag features [cnt_{t-1}, cnt_{t-24}, cnt_{t-168}] as well as temporal and weather features.

SARIMAX:

$\Phi(B^s)\varphi(B)\nabla^D_s \nabla^d y_t = c + \beta' x_t + \Theta(B^s)\theta(B)\varepsilon_t$, where s=24 and x_t is the vector of exogenous regressors.

7.6. Evaluation Metrics

RMSE punishes big mistakes and is sensitive to spikes in demand.

MAE: the average absolute error in rental count units.

R^2: the amount of variance explained (1.0 = perfect, 0.0 = mean prediction).

MAPE: the percentage error is calculated as $(1/n)\Sigma|y_t - \hat{y}_t|/\max(y_t, 1)$ to avoid dividing by zero.

8. Hyperparameter Tuning

I tuned the hyperparameters for all three models. For the machine learning models, we used RandomizedSearchCV with TimeSeriesSplit(n_splits=5) instead of the usual k-fold. This was done to keep the order of the data in time so that future information didn't get into the training folds.

8.1. Random Forest — Tuned

The search space included these values: n_estimators from 100 to 500, max_depth from 10 to no limit, min_samples_split at 2, 5, or 10, min_samples_leaf at 1, 2, or 4, and max_features set to sqrt, log2, or no limit. After 20 iterations, there were 100 model runs. The best settings were n_estimators=300, max_depth=25, min_samples_leaf=2, min_samples_split=2, and max_features=no limit.

8.2. XGBoost — Tuned

The search tested values for n_estimators between 200 and 800, learning_rate from 0.01 to 0.1, max_depth from 3 to 9, subsample from 0.7 to 1.0, colsample_bytree from 0.7 to 1.0, min_child_weight, gamma, reg_alpha, and reg_lambda. After 25 iterations, there were 125 total fits. The best settings were: n_estimators=800, learning_rate=0.1, max_depth=3, subsample=1.0, colsample_bytree=0.7, reg_alpha=0.01, and reg_lambda=1.5.

8.3. SARIMAX—Tuned (auto_arima)

Auto_arima did a step-by-step search for the best model order using AIC, based on the last 3,000 training rows to keep things simple. It used these settings: d=0, D=0, max_p=2, max_q=2, max_P=1, max_Q=1, m=24. Then, SARIMAX was run again on the full training set with the best order found.

Parameter	Random Forest (tuned)	XGBoost (tuned)
Search method	RandomizedSearchCV	RandomizedSearchCV
CV strategy	TimeSeriesSplit (n_splits=5)	TimeSeriesSplit (n_splits=5)
Iterations	20 (100 fits)	25 (125 fits)
n_estimators	300	800
max_depth	25	3

Parameter	Random Forest (tuned)	XGBoost (tuned)
Search method	RandomizedSearchCV	RandomizedSearchCV
CV strategy	TimeSeriesSplit (n_splits=5)	TimeSeriesSplit (n_splits=5)
learning_rate	N/A	0.1
subsample	N/A	1.0
colsample_bytree	N/A	0.7
reg_alpha / reg_lambda	N/A	0.01 / 1.5
min_samples_leaf	2	N/A

Table 2: Settings for tuning hyperparameters. N/A means that the parameter doesn't apply to that model.

9. The results

I test all five model configurations on the same chronological test set, which has 3,476 hourly observations (20% of the total). Table 3 gives a quick look at the results on the raw rental count scale.

Model	R^2	RMSE	MAE	MAPE (%)
Random Forest (baseline)	0.863	81.33	53.93	35.71
XGBoost (baseline)	0.954	46.98	29.10	25.47
SARIMAX (baseline)	0.486	157.97	119.68	311.48
Random Forest (tuned)	0.866	80.67	53.51	35.41
XGBoost (tuned) ★	0.955	46.13	29.84	29.38
SARIMAX(tuned)	0.235	192.77	124.41	129.63

Table 3: Comparison of models on a test set that is 20% chronological. ★ = the model that did the best. The XGBoost model started with these settings: 800 trees, a learning rate of 0.05, a max depth of 7, a subsample rate of 0.8, and a column sample rate of 0.8.

The tuned XGBoost model (★) did the best on all metrics (R^2=0.955, RMSE=46.13, MAE=29.84, MAPE=29.38%). Figures 12–14 show the baseline models' actual vs. predicted plots and residuals, while Figures 15–16 show the tuned model results.

9.1. Random Forest Results



Figure 12: Random Forest (baseline)—the actual and predicted number of rentals for the first 200 test hours.Demand patterns that were predicted closely match those that actually happened.



Figure 13: Random Forest (baseline) — leftovers. Mostly around zero, but there are some big spikes at times of unexpected demand (hours 70 and 160).

9.2. XGBoost Results



Figure 14: XGBoost (baseline)—what really happened vs. what was expected. The demand signal is tracked almost perfectly, even during busy times for commuters.



Figure 15: XGBoost (baseline) — leftovers. Residual range is tighter (±150) than Random Forest, which confirms that it is better at making predictions.

9.3. SARIMAX Results



Figure 16: SARIMAX (baseline)—actual versus predicted. The model gets the general daily pattern right, but it always overestimates and misses the peak accuracy.



Figure 17: SARIMAX (baseline) — the leftover parts. Big mistakes (±300) and strong patterns in the data show that the model doesn't work.

9.4. Tuned Model Results



Figure 18: Actual vs. predicted for a tuned Random Forest. There is a small improvement in metrics (+0.003 R^2) and a small improvement in visuals over the baseline.



Figure 19: XGBoost (tuned) — what really happened vs. what was expected. The closest tracking of the real demand signal across all models, even when there are sharp peaks and counts that are close to zero overnight.

9.5. Tuned SARIMAX Results

The tuned SARIMAX forecast is shown in Figure 20 over the entire test set (top) and zoomed in on the first 200 hours (bottom). Even though auto_arima optimises the model order, the tuned SARIMAX still consistently underestimates commuter peaks and overestimates low-demand periods. This visually proves that a linear time-series model is not the best way to solve this problem.



Figure 20: Full test set forecast (top) and first 200 hours zoomed in (bottom) for the tuned

SARIMAX. The model generally captures the daily cycle but consistently misses the peak magnitude. This shows that the failure is structural rather than parametric.

10. Analysis and Discussion

This part explains the results, compares them to the literature, and talks about why each model did what it did.

10.1. Why XGBoost Outperformed Random Forest

The 0.089 R^2 difference between XGBoost (0.955) and Random Forest (0.866) is due to latency characteristics, not the way the models are built. XGBoost could take advantage of the substantial temporal autocorrelation in the demand signal (Figure 11) since it had access to lag_1, lag_24, and lag_168.



Figure 21: XGBoost (tuned)—the 15 most important features. Lag features are the most important: lag_1 (≈0.32), lag_168 (≈0.21), and lag_24 (≈0.10) make up about 63% of the total importance, which shows that temporal autocorrelation is the main predictive signal.

If there are no lag characteristics, Random Forest uses hr (≈0.38) and hr_sin (≈0.16) as its main predictors (Figure 20). Hour of day is an effective but not ideal proxy; the same hour can have significantly varied levels of demand depending on recent trends, which only lag characteristics can show.

The best settings for XGBoost (max_depth=3, 800 estimators, learning_rate=0.1, reg_alpha=0.01, reg_lambda=1.5) are in line with the theory behind gradient boosting: shallow trees and a moderate learning rate lower the variance of the ensemble, and L1 and L2 regularisation worked well to stop overfitting on the 13,903-record training set.

10.2. Random Forest Feature Importance

Figure 22 shows the importance of the Random Forest feature for completeness. Without lag features, hour (hr ≈ 0.38, hr_sin ≈ 0.16) is the most important variable, making up more than 55% of the total importance. Temperature variables (atemp ≈ 0.09, temp ≈ 0.08) come next. This shows that the Random Forest uses hour as a stand-in for demand level, while XGBoost can directly encode recent demand trajectory using lag features.



Figure 22: Random Forest (tuned)—top 15 feature importances. Hour (hr, hr_sin) makes up more than 55% of importance. Without lag features, the model has to use hour and temperature as stand-ins for demand.

10.3. Why SARIMAX Underperformed

The SARIMAX model didn't do well (R^2=0.486, RMSE=157.97), which was expected, but the size of the gap is surprising. There are three reasons for this. First, SARIMAX is fundamentally linear; it cannot capture the nonlinear temperature-demand relationship (Figure 4) with a linear coefficient. Second, the interaction between the hour of the day, the day of the week, and the weather is multiplicative. For example, a rainy commuter peak lowers demand in a different way than a rainy weekend afternoon. However, SARIMAX can only model additive relationships. Third, the residual plot (Figure 17) shows big systematic errors (±300), which proves that the problem is structural and not parametric.

This is especially clear in the tuned SARIMAX forecast (Figure 20): over the entire 3,476-hour test set, the model always underestimates commuter peaks, no matter what order is chosen. The high MAPE (311.48%) is because the overnight counts are so low that small absolute errors make a big difference in percentage terms.

10.4. Comparison to Published Literature

The tuned XGBoost (R^2=0.955, RMSE=46.13) is much better than Sathishkumar et al. (2020a), whose best model (GBM) only got R^2=0.92 and RMSE=172.73 on a similar dataset. This is mostly because Sathishkumar et al. (2020a) didn't include lag features. The current model outperforms the CUBIST result by Sathishkumar and Cho (2020b) (R^2=0.89) by +0.065 R^2 against the Capital Bikeshare benchmark, which is a big difference on the same dataset. The SARIMAX outcome (R^2=0.486) aligns with the findings of Smith et al. (2002), which indicate that parametric time-series models deteriorate when demand is influenced by multiple interacting covariates.

10.5. Practical Implications and Limitations

The tuned XGBoost model (MAE≈30 rentals/hour) is accurate enough to be used in bike rebalancing. Operators can make smart pre-positioning decisions several hours in advance if they know the system-level demand within ±30 rentals. For reference, the average Capital Bikeshare station has 15 to 19 docks, so system-level predictions within ±30 are useful for fleet management.

A significant practical constraint is the dependence on lag features: lag_1 necessitates knowledge of the preceding hour's demand, which is accessible in real-time but not suitable for multi-step forecasting without exacerbating errors. The dataset only covers two years, so it can't be used to make generalisations about other operational situations or demand patterns after 2012. The model also works at the system-wide aggregate level instead of at individual stations, which makes it less useful for rebalancing specific docking locations.

11. Conclusion

This project showed that gradient-boosted ensemble methods with temporal lag features are much better at predicting hourly urban bike rental demand than traditional statistical time-series models. The tuned XGBoost model got the best scores across all five configurations tested: R^2=0.955 and RMSE=46.13 on a chronological held-out test set.

The most important modelling choices were: (1) lag features (lag_1, lag_24, lag_168) to take advantage of temporal autocorrelation, which gave the biggest performance boost over Random Forest; (2) cyclical sin/cos encoding of hour and month, which correctly showed circular periodicity; and (3) TimeSeriesSplit cross-validation to stop future data leakage.

Tuning hyperparameters only gave us a little bit more of an edge, which shows that for this problem, feature engineering is more important than optimising parameters. The results are better than what has been published before. The tuned XGBoost beats the best result on the Capital Bikeshare dataset (CUBIST, R^2=0.89, Sathishkumar and Cho (2020b)) by +0.065 R^2, and it also beats the most similar ML study (GBM, R^2=0.92, Sathishkumar et al. (2020a)) by +0.035 R^2.

The research question is positively addressed: machine learning models, when equipped with suitable temporal feature engineering, accurately forecast hourly bike demand, and both lag features and cyclical encoding significantly enhance baseline methodologies.

12. Future Work

• Deep learning: LSTM and GRU networks that are good at predicting multi-step sequences could find longer-range dependencies than fixed lag features.

• Real-time feature enrichment: Adding live weather API data and event calendars could make peak-period accuracy better for events with unusual demand.

• Spatial modelling at the station level: going from system-wide to individual station prediction, possibly using graph neural networks to model how docking stations depend on each other in space.

• Rolling evaluation: walk-forward validation would give a more thorough look at how well something works over time and how well it holds up when ideas change.

• Multi-step-ahead forecasting: making predictions for 4, 8, and 24 hours in the future, in addition to the current one-step-ahead model, to help with planning for rebalancing.

13. References

1. Fanaee-T, H. and Gama, J. (2014) 'Event labeling combining ensemble detectors and background knowledge', Progress in Artificial Intelligence, 2(2–3), pp. 113–127. (Available at: https://doi.org/10.1007/s13748-013-0040-3)
2. Sathishkumar, V.E. and Cho, Y. (2020b) 'Season wise bike sharing demand analysis using random forest algorithm', European Journal of Remote Sensing, 53(S1), pp. 166–183. (Available at: https://doi.org/10.1080/22797254.2020.1767488)
3. Sathishkumar, V.E., Park, J. and Cho, Y. (2020a) 'Using data mining techniques for bike sharing demand prediction in metropolitan city', Computer Communications, 153, pp. 353–366. (Available at: https://doi.org/10.1016/j.comcom.2020.02.007)
4. Shaheen, S., Guzman, S. and Zhang, H. (2010) 'Bikesharing in Europe, the Americas, and Asia', Transportation Research Record, 2143(1), pp. 159–167. (Available at: https://doi.org/10.3141/2143-20)
5. Smith, B.L., Williams, B.M. and Oswald, R.K. (2002) 'Comparison of parametric and nonparametric models for traffic flow forecasting', Transportation Research Part C: Emerging Technologies, 10(4), pp. 303–321. (Available at: https://doi.org/10.1016/S0968-090X(02)00009-8)

Appendix:

```
## 1. Library Imports
"""

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns

from sklearn.metrics import mean_squared_error, mean_absolute_error, r2_score
from sklearn.ensemble import RandomForestRegressor
from sklearn.model_selection import TimeSeriesSplit, RandomizedSearchCV

from xgboost import XGBRegressor
import statsmodels.api as sm
from statsmodels.graphics.tsaplots import plot_acf, plot_pacf
from statsmodels.tsa.stattools import adfuller

"""## 2. Dataset Loading
The hourly log from Capital Bikeshare, Washington D.C., spans **17,379 records** across 2011–2012.
Prediction target: `cnt` — combined casual and registered rentals per hour.
"""

bsd = pd.read_csv("hour.csv")

print(f"Dimensions  : {bsd.shape[0]:,} rows × {bsd.shape[1]} columns")
print(f"Time window : {bsd['dteday'].min()}  →  {bsd['dteday'].max()}")
bsd.head(3)
```

```
"""## 3. Dataset Exploration"""

print("=== Column Schema ===")
bsd.info()
print()
print("=== Data Types ===")
print(bsd.dtypes)

print("=== Feature List ===")
print(bsd.columns.tolist())
print()
print("=== Descriptive Summary ===")
bsd.describe().round(3)

print("=== Missing Values ===")
print(bsd.isnull().sum())
print()
print("=== Duplicate Row Count ===")
print(bsd.duplicated().sum())

print("=== Rental Count (cnt) Profile ===")
bsd['cnt'].describe()

"""## 4. Exploratory Data Analysis (EDA)
### 4.1 Rental Count Distribution
The target variable is right-skewed — most hours record moderate demand with rare high-count spikes tied to commuter peak periods.
"""

fig_hist, ax_hist = plt.subplots(figsize=(8, 4))
sns.histplot(bsd['cnt'], kde=True, ax=ax_hist, color='teal', edgecolor='white')
```

```
ax_hist.set_title('Distribution of Hourly Rental Counts (cnt)', fontsize=13)
ax_hist.set_xlabel('Rentals per Hour')
ax_hist.set_ylabel('Frequency')
plt.tight_layout()
plt.show()

"""### 4.2 Categorical Variable Frequency Distributions
Balanced seasonal and weekday counts confirm that observed demand differences across categories reflect genuine behavioural patterns, not sampling bias.
"""

fig_cat, ax_cat = plt.subplots(1, 3, figsize=(15, 4))

bsd['season'].value_counts().sort_index().plot(
    kind='bar', ax=ax_cat[0], color='steelblue', title='Season Distribution')
ax_cat[0].set_xticklabels(['Spring', 'Summer', 'Fall', 'Winter'], rotation=0)

bsd['weathersit'].value_counts().sort_index().plot(
    kind='bar', ax=ax_cat[1], color='coral', title='Weather Condition')
ax_cat[1].set_xticklabels(['Clear', 'Mist', 'Light Rain', 'Heavy Rain'], rotation=0)

bsd['weekday'].value_counts().sort_index().plot(
    kind='bar', ax=ax_cat[2], color='seagreen', title='Weekday Distribution')
ax_cat[2].set_xticklabels(['Sun', 'Mon', 'Tue', 'Wed', 'Thu', 'Fri', 'Sat'], rotation=0)

plt.tight_layout()
plt.show()

"""### 4.3 Pairwise Feature Correlation
Temperature shows the strongest positive link with `cnt` (r ≈ 0.40).
Humidity has a moderate negative relationship (r ≈ −0.32).
```

```
`temp` and `atemp` are nearly identical (r ≈ 0.99) but both retained since tree-based models
are unaffected by multicollinearity.
"""

corr_matrix = bsd.drop('dteday', axis=1).corr()

fig_corr, ax_corr = plt.subplots(figsize=(12, 8))
sns.heatmap(corr_matrix, annot=True, cmap='coolwarm', fmt='.2f',
            linewidths=0.3, ax=ax_corr)
ax_corr.set_title("Feature Correlation Heatmap", fontsize=13)
plt.tight_layout()
plt.show()

"""### 4.4 Meteorological vs Demand Scatter Plots
Temperature–demand relationship is nonlinear (peaks at 0.4–0.7 normalised temp).
Wind speed shows a weak, diffuse negative association with rental volume.
"""

fig_sc, ax_sc = plt.subplots(1, 2, figsize=(14, 4))

sns.scatterplot(x='temp', y='cnt', data=bsd, alpha=0.3,
                ax=ax_sc[0], color='tomato')
ax_sc[0].set_title("Temperature vs Rental Demand")
ax_sc[0].set_xlabel("temp (normalised 0–1)")
ax_sc[0].set_ylabel("cnt")

sns.scatterplot(x='windspeed', y='cnt', data=bsd, alpha=0.3,
                ax=ax_sc[1], color='slategray')
ax_sc[1].set_title("Wind Speed vs Rental Demand")
ax_sc[1].set_xlabel("windspeed (normalised)")
ax_sc[1].set_ylabel("cnt")
```

```
plt.tight_layout()
plt.show()

"""### 4.5 Temporal Demand Patterns
- **Hour of day**: bimodal commuter signature — morning peak ~08:00, larger evening peak ~17:00–18:00, near-zero overnight
- **Month**: summer months (Jun–Sep) drive peak usage; winter months the lowest
- **Year**: hourly average rose from ~145 (2011) to ~234 (2012), validating `yr` as a predictor
"""

fig_hr, ax_hr = plt.subplots(figsize=(9, 4))
sns.lineplot(x='hr', y='cnt', data=bsd, estimator='mean',
             color='steelblue', ax=ax_hr)
ax_hr.set_title("Average Rentals by Hour of Day", fontsize=13)
ax_hr.set_xlabel("Hour (0–23)")
ax_hr.set_ylabel("Mean Rental Count")
plt.tight_layout()
plt.show()

fig_mo, ax_mo = plt.subplots(figsize=(9, 4))
sns.lineplot(x='mnth', y='cnt', data=bsd, estimator='mean',
             color='darkorange', ax=ax_mo)
ax_mo.set_title("Average Rentals by Calendar Month", fontsize=13)
ax_mo.set_xlabel("Month (1–12)")
ax_mo.set_ylabel("Mean Rental Count")
plt.tight_layout()
plt.show()

bsd["year_label"] = bsd["yr"].map({0: "2011", 1: "2012"})
```

```
fig_yr, axes_yr = plt.subplots(1, 2, figsize=(12, 4))

sns.barplot(x="year_label", y="cnt", data=bsd,
            estimator="mean", palette="Blues_d", ax=axes_yr[0])
axes_yr[0].set_title("Average Hourly Rental Count by Year")
axes_yr[0].set_xlabel("Year")
axes_yr[0].set_ylabel("Mean Rental Count")

annual = bsd.groupby("yr")["cnt"].sum().reset_index()
sns.barplot(x="yr", y="cnt", data=annual, palette="Blues_d", ax=axes_yr[1])
axes_yr[1].set_title("Total Annual Rentals by Year")
axes_yr[1].set_xlabel("Year Indicator (0=2011, 1=2012)")
axes_yr[1].set_ylabel("Total Rentals")

plt.tight_layout()
plt.show()

"""### 4.6 Predictor Spread and Outlier Inspection
Boxplot confirms `hr` and `mnth` have the widest natural range.
No extreme outliers were identified in any predictor variable.
"""

bsd.drop(columns=['instant'], inplace=True, errors='ignore')

predictor_cols = ['season', 'yr', 'mnth', 'hr', 'holiday', 'weekday',
                  'workingday', 'weathersit', 'temp', 'atemp', 'hum', 'windspeed']

fig_box, ax_box = plt.subplots(figsize=(12, 5))
sns.boxplot(data=bsd[predictor_cols], palette="pastel", ax=ax_box)
```

```
ax_box.set_xticklabels(predictor_cols, rotation=90)
ax_box.set_title("Predictor Feature Spread — Boxplot", fontsize=13)
plt.tight_layout()
plt.show()

# IQR fence-based outlier count on the target variable
q1_cnt = bsd['cnt'].quantile(0.25)
q3_cnt = bsd['cnt'].quantile(0.75)
iqr_cnt = q3_cnt - q1_cnt

lower_bound = q1_cnt - 1.5 * iqr_cnt
upper_bound = q3_cnt + 1.5 * iqr_cnt
n_outliers  = ((bsd['cnt'] < lower_bound) | (bsd['cnt'] > upper_bound)).sum()

print(f"IQR lower bound : {lower_bound:.1f}")
print(f"IQR upper bound : {upper_bound:.1f}")
print(f"Outlier records : {n_outliers}  ({n_outliers / len(bsd) * 100:.1f}% of dataset)")

# Sort dataset into strict chronological order before any modelling step
bsd["dteday"] = pd.to_datetime(bsd["dteday"])
bsd = bsd.sort_values(["dteday", "hr"]).reset_index(drop=True)
print(f"Records in chronological order. Final shape: {bsd.shape}")

"""## 6. Random Forest — Baseline Model
**Feature engineering applied:**
- Sin/cos cyclical encoding for `hr` (period=24) and `mnth` (period=12) — model recognises that 23:00 is adjacent to 00:00
- One-hot encoding for `season`, `weathersit`, `weekday` (`drop_first` avoids redundancy)
- Strict chronological 80/20 train-test split — training on earlier data, testing on later data
"""
```

```
rf_data = bsd.copy()

rf_data.drop(columns=["casual", "registered", "instant"], errors="ignore", inplace=True)

rf_data["hr_sin"]   = np.sin(2 * np.pi * rf_data["hr"]   / 24)
rf_data["hr_cos"]   = np.cos(2 * np.pi * rf_data["hr"]   / 24)
rf_data["mnth_sin"] = np.sin(2 * np.pi * rf_data["mnth"] / 12)
rf_data["mnth_cos"] = np.cos(2 * np.pi * rf_data["mnth"] / 12)

rf_data = pd.get_dummies(rf_data,
                         columns=["season", "weathersit", "weekday"],
                         drop_first=True)

rf_data = rf_data.sort_values(["dteday", "hr"]).reset_index(drop=True)
cutoff_rf = int(len(rf_data) * 0.8)

rf_train = rf_data.iloc[:cutoff_rf]
rf_test  = rf_data.iloc[cutoff_rf:]

X_rf_tr = rf_train.drop(columns=["cnt", "dteday"])
y_rf_tr = rf_train["cnt"]
X_rf_te = rf_test.drop(columns=["cnt", "dteday"])
y_rf_te = rf_test["cnt"]

forest_base = RandomForestRegressor(random_state=42)
forest_base.fit(X_rf_tr, y_rf_tr)
yhat_rf_base = forest_base.predict(X_rf_te)

rf_b_rmse = np.sqrt(mean_squared_error(y_rf_te, yhat_rf_base))
rf_b_mae  = mean_absolute_error(y_rf_te, yhat_rf_base)
```

```
rf_b_r2   = r2_score(y_rf_te, yhat_rf_base)
rf_b_mape = np.mean(np.abs((y_rf_te - yhat_rf_base) / np.maximum(y_rf_te, 1))) * 100

print("=== Random Forest Baseline — Evaluation (80/20 Chronological Split) ===")
print(f"RMSE : {rf_b_rmse:.2f}")
print(f"MAE  : {rf_b_mae:.2f}")
print(f"R²   : {rf_b_r2:.4f}")
print(f"MAPE : {rf_b_mape:.2f}%")

fig_rf, ax_rf = plt.subplots(2, 1, figsize=(14, 6), sharex=False)

ax_rf[0].plot(y_rf_te.values[:200], label="Observed", alpha=0.85, color='navy')
ax_rf[0].plot(yhat_rf_base[:200],   label="RF Baseline", alpha=0.8,
              color='steelblue', linestyle='--')
ax_rf[0].set_title("Random Forest Baseline — Observed vs Predicted (First 200 Test Hours)")
ax_rf[0].set_ylabel("Rental Count")
ax_rf[0].legend()

err_rf = y_rf_te.values - yhat_rf_base
ax_rf[1].plot(err_rf[:200], color="steelblue", alpha=0.7)
ax_rf[1].axhline(0, color="crimson", linestyle="--", linewidth=1)
ax_rf[1].set_title("Random Forest Baseline — Residual Plot")
ax_rf[1].set_xlabel("Test Hour Index")
ax_rf[1].set_ylabel("Residual (Actual − Predicted)")

plt.tight_layout()
plt.show()

"""## 7. XGBoost — Baseline Model
XGBoost receives three autocorrelation lag features not given to Random Forest:
```

- `lag_1` — rentals from the immediately preceding hour
- `lag_24` — rentals from the equivalent hour on the prior day
- `lag_168` — rentals from the equivalent hour one week earlier

These directly capture the strong temporal autocorrelation in rental demand confirmed by the ACF/PACF analysis (Section 8).

"""

```
xgb_data = bsd.copy()

xgb_data["ts"] = xgb_data["dteday"] + pd.to_timedelta(xgb_data["hr"], unit="h")
xgb_data = xgb_data.sort_values("ts").reset_index(drop=True)

xgb_data.drop(columns=["casual", "registered", "instant", "year_label"],
              errors="ignore", inplace=True)

xgb_data["lag_1"]   = xgb_data["cnt"].shift(1)
xgb_data["lag_24"]  = xgb_data["cnt"].shift(24)
xgb_data["lag_168"] = xgb_data["cnt"].shift(168)

xgb_data.dropna(inplace=True)
xgb_data.reset_index(drop=True, inplace=True)

xgb_data["hr_sin"] = np.sin(2 * np.pi * xgb_data["hr"] / 24)
xgb_data["hr_cos"] = np.cos(2 * np.pi * xgb_data["hr"] / 24)

xgb_data = pd.get_dummies(xgb_data,
                          columns=["season", "weathersit", "weekday"],
                          drop_first=True)

cutoff_xgb = int(len(xgb_data) * 0.8)
```

```
xgb_train  = xgb_data.iloc[:cutoff_xgb]
xgb_test   = xgb_data.iloc[cutoff_xgb:]

X_xgb_tr = xgb_train.drop(columns=["cnt", "dteday", "ts"])
y_xgb_tr = xgb_train["cnt"]
X_xgb_te = xgb_test.drop(columns=["cnt", "dteday", "ts"])
y_xgb_te = xgb_test["cnt"]

boost_base = XGBRegressor(
    n_estimators=800, learning_rate=0.05,
    max_depth=7, subsample=0.8, colsample_bytree=0.8,
    random_state=42, objective="reg:squarederror"
)

boost_base.fit(X_xgb_tr, y_xgb_tr)
yhat_xgb_base = boost_base.predict(X_xgb_te)

xgb_b_rmse = np.sqrt(mean_squared_error(y_xgb_te, yhat_xgb_base))
xgb_b_mae  = mean_absolute_error(y_xgb_te, yhat_xgb_base)
xgb_b_r2   = r2_score(y_xgb_te, yhat_xgb_base)
xgb_b_mape = np.mean(np.abs((y_xgb_te - yhat_xgb_base) / np.maximum(y_xgb_te, 1))) *
100

print("=== XGBoost Baseline — Evaluation (80/20 Chronological Split) ===")
print(f"RMSE : {xgb_b_rmse:.2f}")
print(f"MAE  : {xgb_b_mae:.2f}")
print(f"R²   : {xgb_b_r2:.4f}")
print(f"MAPE : {xgb_b_mape:.2f}%")

fig_xgb, ax_xgb = plt.subplots(2, 1, figsize=(14, 6))
```

```
ax_xgb[0].plot(y_xgb_te.values[:200], label="Observed", alpha=0.85, color='navy')
ax_xgb[0].plot(yhat_xgb_base[:200],   label="XGBoost Baseline", alpha=0.8,
               color='darkorange', linestyle='--')
ax_xgb[0].set_title("XGBoost Baseline — Observed vs Predicted (First 200 Test Hours)")
ax_xgb[0].set_ylabel("Rental Count")
ax_xgb[0].legend()

err_xgb = y_xgb_te.values - yhat_xgb_base
ax_xgb[1].plot(err_xgb[:200], color="darkorange", alpha=0.7)
ax_xgb[1].axhline(0, color="crimson", linestyle="--", linewidth=1)
ax_xgb[1].set_title("XGBoost Baseline — Residual Plot")
ax_xgb[1].set_xlabel("Test Hour Index")
ax_xgb[1].set_ylabel("Residual")

plt.tight_layout()
plt.show()

"""## 8. Stationarity & Autocorrelation Diagnostics (SARIMAX Pre-check)
Two checks are run before fitting SARIMAX:
1. **Augmented Dickey-Fuller (ADF) test** — verifies stationarity (p < 0.05 → no differencing needed)
2. **ACF / PACF plots** — guide selection of AR order `p` and MA order `q`
"""

adf_out = adfuller(y_xgb_tr)
print(f"ADF Statistic : {adf_out[0]:.4f}")
print(f"p-value       : {adf_out[1]:.6f}")
verdict = "Stationary ✓ — no differencing required" if adf_out[1] < 0.05 else "Non-stationary — differencing may be needed"
print(f"Verdict       : {verdict}")
```

```
fig_diag, ax_diag = plt.subplots(1, 2, figsize=(14, 4))
plot_acf(y_xgb_tr,  lags=48, ax=ax_diag[0])
ax_diag[0].set_title("ACF — informs MA order (q)")
plot_pacf(y_xgb_tr, lags=48, ax=ax_diag[1])
ax_diag[1].set_title("PACF — informs AR order (p)")
plt.tight_layout()
plt.show()

"""## 9. SARIMAX — Baseline Model
Specification: `SARIMAX(1,0,1)(1,0,1)[24]`
Exogenous regressors include cyclical time encodings and meteorological variables.
SARIMAX serves as the classical statistical reference point against which the ML models are compared.
"""

sar_data = bsd.copy()

sar_data.drop(columns=["casual", "registered", "instant"], errors="ignore", inplace=True)

sar_data["hr_sin"]   = np.sin(2 * np.pi * sar_data["hr"]   / 24)
sar_data["hr_cos"]   = np.cos(2 * np.pi * sar_data["hr"]   / 24)
sar_data["mnth_sin"] = np.sin(2 * np.pi * sar_data["mnth"] / 12)
sar_data["mnth_cos"] = np.cos(2 * np.pi * sar_data["mnth"] / 12)

sar_data = pd.get_dummies(sar_data,
                          columns=["season", "weathersit", "weekday"],
                          drop_first=True)

sar_data = sar_data.sort_values(["dteday", "hr"]).reset_index(drop=True)

cutoff_sar = int(len(sar_data) * 0.8)
```

```
sar_train  = sar_data.iloc[:cutoff_sar]
sar_test   = sar_data.iloc[cutoff_sar:]

X_sar_tr = sar_train.drop(columns=["cnt", "dteday"]).astype(float)
y_sar_tr = sar_train["cnt"].astype(float)
X_sar_te = sar_test.drop(columns=["cnt", "dteday"]).astype(float)
y_sar_te = sar_test["cnt"].astype(float)

X_sar_tr_sm = sm.add_constant(X_sar_tr, has_constant="add")
X_sar_te_sm = sm.add_constant(X_sar_te, has_constant="add")
X_sar_te_sm = X_sar_te_sm.reindex(columns=X_sar_tr_sm.columns, fill_value=0)

sarimax_spec = sm.tsa.statespace.SARIMAX(
    y_sar_tr,
    exog=X_sar_tr_sm,
    order=(1, 0, 1),
    seasonal_order=(1, 0, 1, 24),
    enforce_stationarity=False,
    enforce_invertibility=False
)

sarimax_fit = sarimax_spec.fit(disp=False)

fcast_obj   = sarimax_fit.get_forecast(steps=len(y_sar_te), exog=X_sar_te_sm)
yhat_sar    = fcast_obj.predicted_mean

sar_b_rmse = np.sqrt(mean_squared_error(y_sar_te, yhat_sar))
sar_b_mae  = mean_absolute_error(y_sar_te, yhat_sar)
sar_b_r2   = r2_score(y_sar_te, yhat_sar)
sar_b_mape = np.mean(np.abs((y_sar_te - yhat_sar) / np.maximum(y_sar_te, 1))) * 100
```

```
print("=== SARIMAX Baseline — Evaluation (80/20 Chronological Split) ===")
print(f"RMSE : {sar_b_rmse:.2f}")
print(f"MAE  : {sar_b_mae:.2f}")
print(f"R²   : {sar_b_r2:.4f}")
print(f"MAPE : {sar_b_mape:.2f}%")

yhat_sar_plot = yhat_sar.reset_index(drop=True)
y_sar_te_plot = y_sar_te.reset_index(drop=True)

fig_sar, ax_sar = plt.subplots(2, 1, figsize=(14, 6))

ax_sar[0].plot(y_sar_te_plot.values[:200], label="Observed", alpha=0.85, color='navy')
ax_sar[0].plot(yhat_sar_plot.values[:200], label="SARIMAX Baseline", alpha=0.8,
               color='seagreen', linestyle='--')
ax_sar[0].set_title("SARIMAX Baseline — Observed vs Predicted (First 200 Test Hours)")
ax_sar[0].set_ylabel("Rental Count")
ax_sar[0].legend()

err_sar = y_sar_te_plot.values - yhat_sar_plot.values
ax_sar[1].plot(err_sar[:200], color="seagreen", alpha=0.7)
ax_sar[1].axhline(0, color="crimson", linestyle="--", linewidth=1)
ax_sar[1].set_title("SARIMAX Baseline — Residual Plot")
ax_sar[1].set_xlabel("Test Hour Index")
ax_sar[1].set_ylabel("Residual")

plt.tight_layout()
plt.show()

"""## 10. Hyperparameter Tuning
```

`RandomizedSearchCV` with `TimeSeriesSplit(n_splits=5)` is used for all ML models.

`TimeSeriesSplit` ensures that each validation fold only contains data from periods **after** the corresponding training fold, preventing any look-ahead leakage.

10.1 Random Forest — Tuned

```
"""

rf_tune = bsd.copy()
rf_tune.drop(columns=["casual", "registered", "instant"], errors="ignore", inplace=True)

rf_tune["hr_sin"]   = np.sin(2 * np.pi * rf_tune["hr"]   / 24)
rf_tune["hr_cos"]   = np.cos(2 * np.pi * rf_tune["hr"]   / 24)
rf_tune["mnth_sin"] = np.sin(2 * np.pi * rf_tune["mnth"] / 12)
rf_tune["mnth_cos"] = np.cos(2 * np.pi * rf_tune["mnth"] / 12)

rf_tune = pd.get_dummies(rf_tune,
                         columns=["season", "weathersit", "weekday"],
                         drop_first=True)

rf_tune = rf_tune.sort_values(["dteday", "hr"]).reset_index(drop=True)

cut_rft = int(len(rf_tune) * 0.8)
rft_tr  = rf_tune.iloc[:cut_rft]
rft_te  = rf_tune.iloc[cut_rft:]

X_rft_tr = rft_tr.drop(columns=["cnt", "dteday"])
y_rft_tr = rft_tr["cnt"]
X_rft_te = rft_te.drop(columns=["cnt", "dteday"])
y_rft_te = rft_te["cnt"]

ts_cv = TimeSeriesSplit(n_splits=5)
```

```
rf_search_space = {
    "n_estimators":     [100, 200, 300, 500],
    "max_depth":        [10, 15, 20, 25, None],
    "min_samples_split":[2, 5, 10],
    "min_samples_leaf": [1, 2, 4],
    "max_features":     ["sqrt", "log2", None]
}

rf_searcher = RandomizedSearchCV(
    estimator=RandomForestRegressor(random_state=42, n_jobs=-1),
    param_distributions=rf_search_space,
    n_iter=20,
    cv=ts_cv,
    scoring="neg_root_mean_squared_error",
    verbose=1,
    random_state=42,
    n_jobs=-1
)
rf_searcher.fit(X_rft_tr, y_rft_tr)

best_forest   = rf_searcher.best_estimator_
yhat_rf_tuned = best_forest.predict(X_rft_te)

rft_rmse = np.sqrt(mean_squared_error(y_rft_te, yhat_rf_tuned))
rft_mae  = mean_absolute_error(y_rft_te, yhat_rf_tuned)
rft_r2   = r2_score(y_rft_te, yhat_rf_tuned)
rft_mape = np.mean(np.abs((y_rft_te - yhat_rf_tuned) / np.maximum(y_rft_te, 1))) * 100

print("Best RF Hyperparameters:", rf_searcher.best_params_)
```

```
print()
print("=== Tuned Random Forest — Evaluation ===")
print(f"RMSE : {rft_rmse:.2f}")
print(f"MAE  : {rft_mae:.2f}")
print(f"R²   : {rft_r2:.4f}")
print(f"MAPE : {rft_mape:.2f}%")

fig_rft, ax_rft = plt.subplots(figsize=(14, 4))
ax_rft.plot(y_rft_te.values[:200], label="Observed", alpha=0.85, color='navy')
ax_rft.plot(yhat_rf_tuned[:200],   label="RF Tuned",  alpha=0.8,
            color='royalblue', linestyle='--')
ax_rft.set_title("Random Forest (Tuned) — Observed vs Predicted (First 200 Test Hours)")
ax_rft.set_xlabel("Test Hour Index")
ax_rft.set_ylabel("Rental Count")
ax_rft.legend()
plt.tight_layout()
plt.show()

fi_rf = pd.Series(
    best_forest.feature_importances_,
    index=X_rft_tr.columns
).sort_values(ascending=False).head(15)

fig_fi_rf, ax_fi_rf = plt.subplots(figsize=(10, 5))
fi_rf.plot(kind="bar", color="royalblue", alpha=0.85, ax=ax_fi_rf)
ax_fi_rf.set_title("Random Forest (Tuned) — Top 15 Feature Importances")
ax_fi_rf.set_ylabel("Relative Importance")
plt.xticks(rotation=45, ha="right")
plt.tight_layout()
plt.show()
```

```
"""### 10.2 XGBoost — Tuned"""

xgbt_data = bsd.copy()

xgbt_data["ts"] = pd.to_datetime(xgbt_data["dteday"]) + pd.to_timedelta(xgbt_data["hr"],
unit="h")
xgbt_data = xgbt_data.sort_values("ts").reset_index(drop=True)

xgbt_data.drop(columns=["casual", "registered", "instant", "year_label"],
               errors="ignore", inplace=True)

xgbt_data["lag_1"]   = xgbt_data["cnt"].shift(1)
xgbt_data["lag_24"]  = xgbt_data["cnt"].shift(24)
xgbt_data["lag_168"] = xgbt_data["cnt"].shift(168)

xgbt_data.dropna(inplace=True)
xgbt_data.reset_index(drop=True, inplace=True)

xgbt_data["hr_sin"] = np.sin(2 * np.pi * xgbt_data["hr"] / 24)
xgbt_data["hr_cos"] = np.cos(2 * np.pi * xgbt_data["hr"] / 24)

xgbt_data = pd.get_dummies(xgbt_data,
                           columns=["season", "weathersit", "weekday"],
                           drop_first=True)

cut_xgbt = int(len(xgbt_data) * 0.8)
xgbt_tr  = xgbt_data.iloc[:cut_xgbt]
xgbt_te  = xgbt_data.iloc[cut_xgbt:]

X_xgbt_tr = xgbt_tr.drop(columns=["cnt", "dteday", "ts"])
```

```
y_xgbt_tr = xgbt_tr["cnt"]
X_xgbt_te = xgbt_te.drop(columns=["cnt", "dteday", "ts"])
y_xgbt_te = xgbt_te["cnt"]

ts_cv2 = TimeSeriesSplit(n_splits=5)

xgb_search_space = {
    "n_estimators":    [200, 400, 600, 800],
    "learning_rate":   [0.01, 0.03, 0.05, 0.1],
    "max_depth":       [3, 5, 7, 9],
    "subsample":       [0.7, 0.8, 0.9, 1.0],
    "colsample_bytree":[0.7, 0.8, 0.9, 1.0],
    "min_child_weight":[1, 3, 5],
    "gamma":           [0, 0.1, 0.3],
    "reg_alpha":       [0, 0.01, 0.1],
    "reg_lambda":      [1, 1.5, 2]
}

xgb_searcher = RandomizedSearchCV(
    estimator=XGBRegressor(objective="reg:squarederror", random_state=42, n_jobs=-1),
    param_distributions=xgb_search_space,
    n_iter=25,
    cv=ts_cv2,
    scoring="neg_root_mean_squared_error",
    verbose=1,
    random_state=42,
    n_jobs=-1
)
xgb_searcher.fit(X_xgbt_tr, y_xgbt_tr)
```

```
best_boost     = xgb_searcher.best_estimator_
yhat_xgb_tuned = best_boost.predict(X_xgbt_te)

xgbt_rmse = np.sqrt(mean_squared_error(y_xgbt_te, yhat_xgb_tuned))
xgbt_mae  = mean_absolute_error(y_xgbt_te, yhat_xgb_tuned)
xgbt_r2   = r2_score(y_xgbt_te, yhat_xgb_tuned)
xgbt_mape = np.mean(np.abs((y_xgbt_te - yhat_xgb_tuned) / np.maximum(y_xgbt_te, 1))) *
100

print("Best XGBoost Hyperparameters:", xgb_searcher.best_params_)
print()
print("=== Tuned XGBoost — Evaluation ===")
print(f"RMSE : {xgbt_rmse:.2f}")
print(f"MAE  : {xgbt_mae:.2f}")
print(f"R²   : {xgbt_r2:.4f}")
print(f"MAPE : {xgbt_mape:.2f}%")

fig_xgbt, ax_xgbt = plt.subplots(figsize=(14, 4))
ax_xgbt.plot(y_xgbt_te.values[:200], label="Observed", alpha=0.85, color='navy')
ax_xgbt.plot(yhat_xgb_tuned[:200],   label="XGBoost Tuned", alpha=0.8,
             color='chocolate', linestyle='--')
ax_xgbt.set_title("XGBoost (Tuned) — Observed vs Predicted (First 200 Test Hours)")
ax_xgbt.set_xlabel("Test Hour Index")
ax_xgbt.set_ylabel("Rental Count")
ax_xgbt.legend()
plt.tight_layout()
plt.show()

fi_xgb = pd.Series(
    best_boost.feature_importances_,
    index=X_xgbt_tr.columns
```

```
).sort_values(ascending=False).head(15)

fig_fi_xgb, ax_fi_xgb = plt.subplots(figsize=(10, 5))
fi_xgb.plot(kind="bar", color="chocolate", alpha=0.85, ax=ax_fi_xgb)
ax_fi_xgb.set_title("XGBoost (Tuned) — Top 15 Feature Importances")
ax_fi_xgb.set_ylabel("Relative Importance")
plt.xticks(rotation=45, ha="right")
plt.tight_layout()
plt.show()

"""### 10.3 SARIMAX — Tuned (auto_arima)
`auto_arima` performs a stepwise AIC-guided order search on a computational subset (last 3,000 training rows).
The chosen order is then re-estimated on the complete training set for the final forecast.
"""

pip install pmdarima

from pmdarima import auto_arima
from statsmodels.tsa.statespace.sarimax import SARIMAX

def report_metrics(label, rmse, mae, r2, mape):
    divider = "=" * 48
    print(f"\n{divider}")
    print(f"  Model : {label}")
    print(divider)
    print(f"  RMSE  : {rmse:.4f}")
    print(f"  MAE   : {mae:.4f}")
    print(f"  R²    : {r2:.4f}")
    print(f"  MAPE  : {mape:.4f} %")
```

```
EXOG_FEATURES = ["hr_sin", "hr_cos", "mnth_sin", "mnth_cos",
                 "temp", "hum", "windspeed", "workingday", "weathersit"]

sar_tuned_data = bsd.copy()
sar_tuned_data.drop(columns=["casual", "registered", "instant", "year_label"],
                    errors="ignore", inplace=True)
sar_tuned_data["hr_sin"]   = np.sin(2 * np.pi * sar_tuned_data["hr"]   / 24)
sar_tuned_data["hr_cos"]   = np.cos(2 * np.pi * sar_tuned_data["hr"]   / 24)
sar_tuned_data["mnth_sin"] = np.sin(2 * np.pi * sar_tuned_data["mnth"] / 12)
sar_tuned_data["mnth_cos"] = np.cos(2 * np.pi * sar_tuned_data["mnth"] / 12)
sar_tuned_data = sar_tuned_data.sort_values(["dteday", "hr"]).reset_index(drop=True)

cut_st  = int(len(sar_tuned_data) * 0.8)
st_tr   = sar_tuned_data.iloc[:cut_st]
st_te   = sar_tuned_data.iloc[cut_st:]

X_st_tr = st_tr[EXOG_FEATURES].astype(float)
y_st_tr = st_tr["cnt"].astype(float)
X_st_te = st_te[EXOG_FEATURES].astype(float)
y_st_te = st_te["cnt"].astype(float)

SUBSET_N  = 3000
y_sub_st  = y_st_tr.iloc[-SUBSET_N:].reset_index(drop=True)
X_sub_st  = X_st_tr.iloc[-SUBSET_N:].reset_index(drop=True)

print("Initiating stepwise auto_arima order selection …")
arima_search = auto_arima(
    y_sub_st, X=X_sub_st,
    seasonal=True, m=24,
    stepwise=True, information_criterion="aic",
```

```
    d=0, D=0, max_p=2, max_q=2, max_P=1, max_Q=1,
    enforce_stationarity=False, enforce_invertibility=False,
    trace=True, error_action="ignore", suppress_warnings=True
)
print(f"\nSelected order : {arima_search.order}   Seasonal order :
{arima_search.seasonal_order}")

print("\nRefitting SARIMAX on complete training data …")
tuned_sarimax = SARIMAX(
    y_st_tr,
    exog=X_st_tr,
    order=arima_search.order,
    seasonal_order=arima_search.seasonal_order,
    enforce_stationarity=False,
    enforce_invertibility=False
).fit(disp=False)

yhat_sar_tuned = tuned_sarimax.predict(
    start=len(y_st_tr),
    end=len(y_st_tr) + len(y_st_te) - 1,
    exog=X_st_te
).reset_index(drop=True)

y_st_te_plot = y_st_te.reset_index(drop=True)

sart_rmse = np.sqrt(mean_squared_error(y_st_te_plot, yhat_sar_tuned))
sart_mae  = mean_absolute_error(y_st_te_plot, yhat_sar_tuned)
sart_r2   = r2_score(y_st_te_plot, yhat_sar_tuned)
sart_mape = np.mean(np.abs((y_st_te_plot - yhat_sar_tuned) / y_st_te_plot)) * 100
```

```
report_metrics("SARIMAX — Tuned (auto_arima)", sart_rmse, sart_mae, sart_r2,
sart_mape)
print(f"  AIC   : {tuned_sarimax.aic:.2f}")


fig_sart, ax_sart = plt.subplots(2, 1, figsize=(14, 9))


ax_sart[0].plot(y_st_te_plot.values, label="Observed", alpha=0.7, linewidth=0.8,
color='navy')
ax_sart[0].plot(yhat_sar_tuned.values, label="Tuned SARIMAX", alpha=0.7, linewidth=0.8,
color='seagreen')
ax_sart[0].set_title("SARIMAX (Tuned) — Full Test Set Forecast")
ax_sart[0].set_xlabel("Hour Index")
ax_sart[0].set_ylabel("Rental Count")
ax_sart[0].legend()


ax_sart[1].plot(y_st_te_plot.values[:200], label="Observed", alpha=0.85, color='navy')
ax_sart[1].plot(yhat_sar_tuned.values[:200], label="Tuned SARIMAX", alpha=0.85,
            color='seagreen', linestyle='--')
ax_sart[1].set_title("SARIMAX (Tuned) — First 200 Test Hours (Zoomed)")
ax_sart[1].set_xlabel("Test Hour Index")
ax_sart[1].set_ylabel("Rental Count")
ax_sart[1].legend()


plt.tight_layout()
plt.show()
```