

PDF 3: JavaScript

1. JavaScript was originally developed by:

- a) Microsoft in 1999
- b) Google in 2005
- c) Netscape in 1995
- d) Oracle in 2000

Answer: c

2. JavaScript is best described as:

- a) A statically typed, compiled language
- b) A high-level, dynamically typed, event-driven scripting language
- c) A database query language
- d) A server-only language

Answer: b

3. Which keyword is block-scoped and cannot be re-declared in the same scope?

- a) var
- b) let
- c) const
- d) Both b and c

Answer: d

4. What does typeof null return in JavaScript?

- a) "null"
- b) "undefined"
- c) "object"
- d) "boolean"

Answer: c

5. Which equality operator checks both value AND type?

- a) ==

- b) !=
- c) ===
- d) =

Answer: c

6. What is the result of `5 == "5"` in JavaScript?

- a) false
- b) true
- c) Error
- d) undefined

Answer: b

7. What is hoisting in JavaScript?

- a) Moving HTML elements to the top of the page
- b) JavaScript's behavior of moving variable declarations to the top of their scope before execution
- c) Automatically converting data types
- d) Loading scripts asynchronously

Answer: b

8. Which of the following is a non-primitive (reference) data type?

- a) Number
- b) Boolean
- c) String
- d) Object

Answer: d

9. How do you access an object property using a variable key?

- a) `obj.key`
- b) `obj->key`
- c) `obj[key]`

- d) obj::key

Answer: c

10. Which array method removes and returns the last element?

- a) push()
- b) shift()
- c) pop()
- d) splice()

Answer: c

11. What does myArray.push(value) do?

- a) Removes the first element
- b) Adds a new element to the beginning of the array
- c) Adds a new element to the end of the array
- d) Sorts the array

Answer: c

12. Arrays in JavaScript are zero-based. What does color[0] return for ["red","green","blue"]?

- a) "green"
- b) "blue"
- c) undefined
- d) "red"

Answer: d

13. Which loop iterates over the properties (keys) of an object?

- a) for...of
- b) while
- c) for...in
- d) do...while

Answer: c

14. What is the ternary operator syntax in JavaScript?

- a) if condition ? value1 : value2
- b) condition ? value_if_true : value_if_false
- c) condition : value_if_true ? value_if_false
- d) (condition) => value1 | value2

Answer: b

15. Which of the following values is falsy in JavaScript?

- a) "0"
- b) []
- c) {}
- d) 0

Answer: d

16. What is the recommended modern way to declare variables in JavaScript?

- a) var for all variables
- b) let for variables, const for fixed values
- c) Only const for everything
- d) var and let interchangeably

Answer: b

17. Which JavaScript method creates a new object using an existing object as its prototype?

- a) new Object()
- b) Object.create()
- c) Object.make()
- d) new Class()

Answer: b

18. What does Object.is(NaN, NaN) return?

- a) false
- b) undefined

- c) true
- d) Error

Answer: c

19. Which is the best practice for placing JavaScript in an HTML file?

- a) Inside <head> only
- b) Inline in every element
- c) In an external .js file, referenced just before </body>
- d) Inside <meta> tags

Answer: c

20. What does var differ from let in JavaScript?

- a) var is block-scoped, let is function-scoped
- b) var is function-scoped and can be re-declared; let is block-scoped and cannot
- c) var cannot be updated, let can
- d) There is no difference

Answer: b

21. In an ES6 class, what is the purpose of constructor()?

- a) It declares class-level constants
- b) It initializes a new instance of the class when created with new
- c) It creates static methods
- d) It destroys the object after use

Answer: b

22. How is a regular expression written using literal notation in JavaScript?

- a) re = "ab+c"
- b) re = /ab+c/
- c) re = regex(ab+c)
- d) re = <ab+c>

Answer: b

23. What is the difference between Java and JavaScript inheritance?

- a) Java uses prototype-based inheritance; JavaScript uses class-based
- b) Java uses class-based inheritance; JavaScript uses prototype-based
- c) Both use class-based inheritance
- d) Neither supports inheritance

Answer: b

24. What is the output of `typeof "hello"`?

- a) "text"
- b) "String"
- c) "string"
- d) "object"

Answer: c

25. JavaScript's event loop makes it:

- a) Multi-threaded
- b) Single-threaded, handling tasks asynchronously via an event queue
- c) Synchronous only
- d) Dependent on Java threads

Answer: b

26. Which of the following correctly creates an array with 3 elements?

- a) `new Array(3)` — creates 3 empty slots
- b) `["a","b","c"]` — creates an array with 3 values
- c) Both a and b are valid but do different things
- d) Neither is valid

Answer: c

27. What does the `finally` block in exception handling do?

- a) Runs only if no exception is thrown

- b) Runs only when an exception is caught
- c) Always runs, whether or not an exception occurred
- d) Re-throws the exception

Answer: c

28. Which statement about null and undefined in JavaScript is true?

- a) null === undefined is true
- b) null == undefined is true but null === undefined is false
- c) Both are exactly the same
- d) null is a number type

Answer: b

29. What does implicitly declared variable mean in JavaScript?

- a) A variable declared with const
- b) A variable assigned a value without var, let, or const — treated as global
- c) A variable declared inside a function
- d) A variable with the private keyword

Answer: b

30. Which JavaScript feature allows functions to be values, passed as arguments?

- a) Prototype chaining
- b) Event bubbling
- c) First-class functions
- d) Hoisting

Answer: c