

API Documentation

- Send Template
- Fetch Templates
- Template Structure
- Track Message(API)

/api/send/bytemplate

Description

This endpoint allows you to send WhatsApp message templates to specified phone numbers using pre-approved templates. You can send to single or multiple recipients, include variables for template customization, and attach media files. The user's credit balance is validated before sending, and one credit is deducted per message recipient.

Request Parameters

Parameter	Type	Required	Description	Example Value
api-key	String	Yes	Your API key for authentication	YOUR_API_KEY
templateName	String	Yes	The name of the pre-approved WhatsApp template to use	Your_Template_Name
phoneNumber	String	Yes	Recipient phone number(s) with country code, comma-separated for multiple recipients	919876453210,
phoneNumberId	String	Yes	WhatsApp Business API phone	123456789012345

Parameter	Type	Required	Description	Example Value
			number ID to send from	
csvVariables	String	No	Comma-separated variables to be inserted into template placeholders	John Smith,March 30 2025,10:00 AM
variables	JSON (URL-encoded)	No	JSON object with named variables for templates (URL-encoded)	%7B%22body1%22%3A%22AB123%22%2C%22bo
media	String	No	URL(s) for media attachments, comma-separated for multiple items in carousel	https://example.com/image.jpg
tags	String	No	Names of premade tag to tag numbers	tag1 ,tag2
groups	String	No	Names of group to add number to group	group1,group2

Response Fields

Field	Type	Description	Example Value
success	Boolean	Indicates whether the request was successful	true/false
message	String	A message indicating the status of the request	Template sent successfully to 2 recipients

Field	Type	Description	Example Value
error	String	Error message (only present if success is false)	Invalid template name or Template not approved

Example Requests

Basic Template Sending

```
https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate?api-key=YOUR_API_KEY&templateName=welcome_temp
```

Multiple Recipients (comma-separated)

```
https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate?api-key=YOUR_API_KEY&templateName=welcome_temp
```

With CSV Variables

```
https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate?api-key=YOUR_API_KEY&templateName=appointment_
```

With Media Attachment

```
https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate?api-key=YOUR_API_KEY&templateName=product_promo
```

With Multiple Media for Carousel

```
https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate?api-key=YOUR_API_KEY&templateName=product_cata
```

With JSON Variables (URL-encoded)

```
https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate?api-key=YOUR_API_KEY&templateName=order_confir
```

Combined - CSV Variables, Media and Multiple Recipients

```
https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate?api-key=YOUR_API_KEY&templateName=your_templat
```

Example JavaScript Request

```
fetch('https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate', {
  method: 'GET',
  headers: {
    'Content-Type': 'application/json',
    'api-key': 'YOUR_API_KEY'
  }
})
.then(response => response.json())
.then(data => console.log(data))
.catch(error => console.error('Error:', error));
```

Example Python Request

```
import requests

url = "https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate"
params = {
```

```
"api-key": "YOUR_API_KEY",
"templateName": "welcome_template",
"phoneNumber": "919876543210,918765432109",
"phoneNumberId": "123456789012345",
"csvVariables": "John Smith,March 30 2025,10:00 AM",
"media": "https://example.com/images/product.jpg"
}

response = requests.get(url, params=params)
print(response.json())
```

Example PHP Request

```
<?php

$apiUrl = "https://verifiedwhatsapp.admarksolution.com/api/send/bytemplate";
$apiKey = "YOUR_API_KEY";

// Query parameters
$params = [
    "templateName" => "welcome_template",
    "phoneNumber" => "919876543210,918765432109",
    "phoneNumberId" => "123456789012345",
    "csvVariables" => "John Smith,March 30 2025,10:00 AM",
    "media" => "https://example.com/images/product.jpg"
];

// Build the full URL with query string
$urlWithParams = $apiUrl . '?' . http_build_query($params);

// Initialize cURL
$ch = curl_init();

curl_setopt($ch, CURLOPT_URL, $urlWithParams);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_HTTPHEADER, [
    "Content-Type: application/json",
    "api-key: $apiKey"
]);

// Execute the request
$response = curl_exec($ch);

// Check for errors
if (curl_errno($ch)) {
    echo "cURL Error: " . curl_error($ch);
} else {
    // Decode and print the response
    $data = json_decode($response, true);
    print_r($data);
}

// Close cURL session
curl_close($ch);
?>
```

Example Successful Response

```
{
  "success": true,
```

```
"message": "Template sent successfully to 2 recipients",
"requestId": "1679558245-123456789012345-919876543210"
}
```

Example Error Response

```
{
  "success": false,
  "message": "Failed to send template",
  "error": "Template 'welcome_template' not found or not approved"
}
```

Notes

- All template messages must be pre-approved by WhatsApp before they can be sent.
- The `phoneNumberId` must be associated with your WhatsApp business account.
- Template variables must match the expected format and number of variables in your template.
- For media attachments, use either `csvVariables` OR `variables` but not both in the same request.
- Media URLs must be publicly accessible and contain valid image, video, or document files.
- Each recipient counts as one message for credit deduction purposes.
- Carousels require at least 2 media items and support up to 10 items.

/templates

Description

This endpoint returns a list of all your WhatsApp templates along with their approval status, creation date, and other metadata. This allows you to see which templates are available for sending, which are pending approval, and which have been rejected.

Request Parameters

Parameter	Type	Required	Description	Example Value
api-key	String	Yes	Your API key for authentication	YOUR_API_KEY

Response Fields

Field	Type	Description
name	String	The name of the template
status	String	Approval status (APPROVED, PENDING, REJECTED)
category	String	Template category (MARKETING, UTILITY, AUTHENTICATION)
language	String	Template language code (e.g., "en_US", "es_ES")

Field	Type	Description
createdAt	String (ISO date)	Date and time when the template was created
components	Array	Components of the template (header, body, footer, buttons)

Example Request

```
https://verifiedwhatsapp.admarksolution.com/templates?api-key=YOUR_API_KEY
```

Example JavaScript Request

```
fetch('https://verifiedwhatsapp.admarksolution.com/templates', {
  method: 'GET',
  headers: {
    'Content-Type': 'application/json',
    'api-key': 'YOUR_API_KEY'
  }
})
.then(response => response.json())
.then(data => console.log(data))
.catch(error => console.error('Error:', error));
```

Example Successful Response

```
[
  {
    "_id": "67dd18a21b66f756d68afd63",
    "dbuser": "YourUsername",
    "name": "welcome_message",
    "templateid": "1526692434687354",
    "components": [],
    "status": "APPROVED",
    "createdAt": "2025-03-21T07:43:30.037Z",
    "__v": 0
  },
  {
    "_id": "67dd18a21b66f756d68afd66",
    "dbuser": "YourUsername",
    "name": "order_confirmation",
    "templateid": "640442955223274",
    "components": [],
    "status": "APPROVED",
    "createdAt": "2025-03-21T07:43:30.056Z",
    "__v": 0
  },
  {
    "_id": "67dd18a21b66f756d68afd72",
    "dbuser": "YourUsername",
    "name": "promotional_offer",
    "templateid": "1951076651969699",
    "components": [],
    "status": "REJECTED",
    "createdAt": "2025-03-21T07:43:30.120Z",
    "__v": 0
  },
  {
```

```
    "_id": "67dd5cb6ff4aefa3fdb46559",
    "dbuser": "YourUsername",
    "name": "text_only_template",
    "templateid": "1254563059571849",
    "components": [],
    "status": "APPROVED",
    "createdAt": "2025-03-21T12:33:58.031Z",
    "__v": 0
  },
  {
    "_id": "67de9731d173ac79f99ec803",
    "dbuser": "YourUsername",
    "name": "product_image",
    "templateid": "647133754586844",
    "components": [],
    "status": "APPROVED",
    "createdAt": "2025-03-22T10:55:45.325Z",
    "__v": 0
  }
]
```

/template-byname

Description

This endpoint returns detailed information about a specific template, including its structure, variables, components, and current approval status. This is useful for understanding how to correctly format variables when sending messages with this template.

Request Parameters

Parameter	Type	Required	Description	Example Value
api-key	String	Yes	Your API key for authentication	YOUR_API_KEY
name	String	Yes	The name of the template to retrieve	welcome_template

Response Fields

Field	Type	Description
name	String	The name of the template
status	String	Approval status of the template
category	String	Template category
language	String	Template language code
components	Array	Detailed breakdown of template components
variables	Object	Information about required variables and their format

Example Request

```
https://verifiedwhatsapp.admarksolution.com/template-byname?name=welcome_template&api-key=YOUR_API_KEY
```

Example JavaScript Request

```
fetch('https://verifiedwhatsapp.admarksolution.com/template-byname?name=welcome_template', {
  method: 'GET',
  headers: {
    'Content-Type': 'application/json',
    'api-key': 'YOUR_API_KEY'
  }
})
.then(response => response.json())
.then(data => console.log(data))
.catch(error => console.error('Error:', error));
```

Example Successful Response

```
{
  "_id": "67dd18a11b66f756d68afceb",
  "dbuser": "YourUsername",
  "name": "carousel_template",
  "templateid": "664014936161690",
  "components": [
    {
      "type": "BODY",
      "text": "Check out our latest products"
    },
    {
      "type": "CAROUSEL",
      "cards": [
        {
          "components": [
            {
              "type": "HEADER",
              "format": "IMAGE",
              "example": {
                "header_handle": [
                  "https://example.com/images/product1.jpg"
                ]
              }
            },
            {
              "type": "BODY",
              "text": "Premium Product One"
            },
            {
              "type": "BUTTONS",
              "buttons": [
                {
                  "type": "QUICK_REPLY",
                  "text": "Get Details"
                },
                {
                  "type": "URL",
                  "text": "Shop Now",
                  "url": "https://yourstore.com/product1"
                }
              ]
            }
          ]
        }
      ]
    }
  ]
}
```



```

    ]
  },
  {
    "components": [
      {
        "type": "HEADER",
        "format": "IMAGE",
        "example": {
          "header_handle": [
            "https://example.com/images/product2.jpg"
          ]
        }
      },
      {
        "type": "BODY",
        "text": "Premium Product Two"
      },
      {
        "type": "BUTTONS",
        "buttons": [
          {
            "type": "QUICK_REPLY",
            "text": "Learn More"
          },
          {
            "type": "URL",
            "text": "Shop Now",
            "url": "https://yourstore.com/product2"
          }
        ]
      }
    ]
  }
]
},
{
  "status": "APPROVED",
  "createdAt": "2025-03-21T07:43:29.346Z",
  "_v": 0
}
}

```

Example Error Response

```

{
  "success": false,
  "error": "Template not found",
  "message": "The requested template 'nonexistent_template' was not found in your account"
}

```

/api/trackId/:trackId

Description

This endpoint allows you to retrieve detailed information about a specific message by its tracking ID. You can use this to check the status of sent messages, verify delivery, and access the original request and response data for debugging or record-keeping purposes.

Request Parameters

Parameter	Type	Required	Description	Example Value
trackId	String	Yes	The tracking ID of the message (URL path parameter)	1679558245-12345678901234
api-key	String	Yes	Your API key for authentication	YOUR_API_KEY

Response Fields

Field	Type	Description	Example Value
success	Boolean	Indicates whether the request was successful	true/false
trackId	String	The tracking ID of the message	1679558245-12345678901234
apiUrl	String	The API endpoint that was called	/api/send/bytemplate
requestData	Object	Original request data sent to the API	{templateName: "welcome_template", ...}
responseData	Object	Response data received from the API	{success: true, message: "Template sent..."}
calledAt	String (ISO date)	Timestamp when the API was called	2025-04-12T14:23:45.123Z
error	String	Error message (only present if success is false)	Track ID not found

Example Request

https://verifiedwhatsapp.admarksolution.com/api/trackId/1679558245-12345678901234?api-key=YOUR_API_KEY

Example JavaScript Request

```
fetch('https://verifiedwhatsapp.admarksolution.com/api/trackId/1679558245-12345678901234', {
  method: 'GET',
  headers: {
    'Content-Type': 'application/json',
    'api-key': 'YOUR_API_KEY'
  }
})
.then(response => response.json())
.then(data => console.log(data))
.catch(error => console.error('Error:', error));
```

Example Python Request

```
import requests

url = "https://verifiedwhatsapp.admarksolution.com/api/trackId/1679558245-12345678901234"
headers = {
    "Content-Type": "application/json",
    "api-key": "YOUR_API_KEY"
}

response = requests.get(url, headers=headers)
print(response.json())
```

Example PHP Request

```
<?php

$apiUrl = "https://verifiedwhatsapp.admarksolution.com/api/trackId/1679558245-12345678901234";
$apiKey = "YOUR_API_KEY";

// Initialize cURL
$ch = curl_init();

curl_setopt($ch, CURLOPT_URL, $apiUrl);
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_HTTPHEADER, [
    "Content-Type: application/json",
    "api-key: $apiKey"
]);

// Execute the request
$response = curl_exec($ch);

// Check for errors
if (curl_errno($ch)) {
    echo "cURL Error: " . curl_error($ch);
} else {
    // Decode and print the response
    $data = json_decode($response, true);
    print_r($data);
}

// Close cURL session
curl_close($ch);
?>
```

Example Successful Response

```
{
  "success": true,
  "trackId": "1679558245-12345678901234",
  "apiUrl": "/api/send/bytemplate",
  "requestData": {
    "templateName": "welcome_template",
    "phoneNumber": "919876543210",
    "phoneNumberId": "123456789012345",
    "csvVariables": "John Smith,Premium Plan"
  },
  "responseData": {
    "success": true,
    "message": "Template sent successfully to 1 recipients",
  }
}
```

```
"requestId": "1679558245-123456789012345-919876543210"  
},  
"calledAt": "2025-04-12T14:23:45.123Z"  
}
```

Example Error Response

```
{  
  "success": false,  
  "error": "Track ID not found"  
}
```

Notes

- You can only track messages that were sent using your API key.
- Track IDs are provided in the response when sending messages and should be stored for future reference.
- Message history data is retained for a limited time period.
- This endpoint is useful for verifying message delivery and troubleshooting issues with message sending.