STICK-ONN ADHESIVE

MATERIAL SAFETY DATA SHEET

SO/SDS/CLD3/01 | Rev. 00 | 29/10/2026 | GHS format

Stick-Onn Clout D3 Adhesive

White viscous liquid

GHS STATUS	TRANSPORT	EMERGENCY	SUPPLIER
Not classified	**Not regulated**	**+91 93716 35312**	**Synergy Bonding Solutions**

01 IDENTIFICATION

Product name	**Stick-Onn Clout D3 Adhesive**
Recommended use	**D3-grade cross-linked PVA wood adhesive for furniture, flush doors and laminates. Professional use.**
Supplier	**Synergy Bonding Solutions Pvt. Ltd., 205, 4th Floor, Mont Vert Spectra, Pallod Farms, Baner, Pune – 411045, Maharashtra, India**
Contact	**contact@stickonn.in · +91 90210 86995 · www.stickonn.in**
Emergency telephone	**+91 93716 35312 / +91 90210 86995 (Mon–Sat, 9:30 am – 6:30 pm IST)**

02 HAZARD IDENTIFICATION

GHS classification

- Not classified as hazardous according to GHS (UN Rev. 9) criteria.

Signal word

NO SIGNAL WORD

No hazard pictogram required.

Hazard statements

– No hazard statements.

Precautionary statements

- P102 Keep out of reach of children.
- P262 Do not get in eyes, on skin, or on clothing.
- P280 Wear protective gloves and eye protection when handling large quantities.

Other hazards: Not expected to present a significant hazard under normal conditions of use. Wet product is slippery when spilled.

03 COMPOSITION / INFORMATION ON INGREDIENTS

Mixture.

Component	CAS No.	% w/w
Polyvinyl acetate copolymer (cross-linking)	9003-20-7	40 – 55
Water	7732-18-5	40 – 55
Additives (cross-linker, preservative)	Proprietary	< 5
Residual vinyl acetate monomer	108-05-4	≤ 0.3

04 FIRST-AID MEASURES

Inhalation	**Not expected to be an inhalation hazard. Move to fresh air if discomfort occurs.**
Skin contact	**Wash with soap and plenty of water. Remove dried film by peeling.**
Eye contact	**Rinse cautiously with water for at least 15 minutes, holding eyelids open. Seek medical advice if irritation persists.**
Ingestion	**Rinse mouth with water. Do not induce vomiting. Seek medical advice if a large quantity is swallowed.**

Most important symptoms: May cause temporary mild irritation to eyes. No delayed effects known.

Note to physician: Treat symptomatically.

05 FIRE-FIGHTING MEASURES

Suitable extinguishing media	**Water spray, foam, dry chemical or CO_2. The product itself is water-based and non-flammable.**
Specific hazards	**Dried film is combustible. Burning may produce carbon monoxide, carbon dioxide and acetic acid vapours.**
Protective equipment	**Wear self-contained breathing apparatus and full protective clothing in a fire.**

06 ACCIDENTAL RELEASE MEASURES

Contain spill with sand, earth or other inert absorbent. Scrape up and place in a labelled container. Rinse residue with water. Prevent entry into drains and watercourses.

07 HANDLING AND STORAGE

Safe handling	**Avoid contact with eyes. Use in a well-ventilated area. Wash hands after use. Do not eat, drink or smoke while working.**
Storage conditions	**Store in tightly closed original containers between 5°C and 35°C. Protect from freezing and direct sunlight. Keep away from strong oxidisers.**

08 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits: No occupational exposure limits established for the product. Vinyl acetate (residual monomer): TLV-TWA 10 ppm (ACGIH).

Engineering controls: Provide general and, where necessary, local exhaust ventilation.

Eyes	**Safety glasses with side shields.**
Hands	**Nitrile or PVC gloves for prolonged contact.**
Respiratory	**Not normally required with adequate ventilation.**
Body	**Normal work clothing / apron.**

09 PHYSICAL AND CHEMICAL PROPERTIES

Physical state	**Liquid (emulsion)**
Colour	**White**
Odour	**Mild**
pH	**3 – 5**
Viscosity	**150 – 250 Poise**
Density	**approx. 1.05 – 1.10 g/cm^3**
Flash point	**Not applicable (water-based)**
Solubility in water	**Dilutable when wet**

10 STABILITY AND REACTIVITY

Reactivity / stability	**Stable under recommended storage conditions. Hazardous polymerisation will not occur.**
Conditions to avoid	**Freezing, temperatures above 40°C.**
Incompatible materials	**Strong oxidising agents, strong alkalis.**
Hazardous decomposition	**On burning: CO, CO_2, acetic acid vapours.**

11 TOXICOLOGICAL INFORMATION

Acute toxicity	**Not classified. Low order of acute toxicity expected.**
Skin corrosion / irritation	**Not classified. Prolonged contact may cause mild irritation.**
Eye damage / irritation	**Not classified. May cause transient mild irritation.**
Sensitisation	**Not classified.**
CMR effects	**Not classified.**

12 ECOLOGICAL INFORMATION

Not classified as hazardous to the aquatic environment. Polymer is not readily biodegradable but is removed by flocculation in effluent treatment. Do not discharge undiluted product into drains.

13 DISPOSAL CONSIDERATIONS

Dispose of waste and residues in accordance with local and state regulations. Dried adhesive may be disposed of as non-hazardous industrial solid waste. Empty containers may be recycled after cleaning.

14 TRANSPORT INFORMATION

UN number	**Not regulated**
Proper shipping name	**Not regulated**
Transport hazard class	**Not classified**
Packing group	**—**
Marine pollutant	**No**

15 REGULATORY INFORMATION

Classified and labelled in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS, UN Rev. 9). Users should comply with the Manufacture, Storage and Import of Hazardous Chemical Rules, 1989 (India) and the Factories Act, 1948, where applicable.

16 OTHER INFORMATION

Revision: 00 · Date of issue: 29/10/2026 · Document no.: SO/SDS/CLD3/01

The information in this Safety Data Sheet is based on our present knowledge and is given in good faith. It describes the product with regard to safety requirements and does not constitute a guarantee of product properties. Users are responsible for ensuring safe handling and compliance with applicable laws. Refer to the Technical Data Sheet for application information.