STICK-ONN ADHESIVE

MATERIAL SAFETY DATA SHEET

SO/SDS/HMEVA/01 | Rev. 00 | 29/10/2026 | GHS format

Stick-Onn Hot Melt Adhesive (EVA Granules)

Solid granules (white / yellow, grade dependent)

GHS STATUS	TRANSPORT	EMERGENCY	SUPPLIER
Not classified	**Not regulated**	**+91 93716 35312**	**Synergy Bonding Solutions**

01 IDENTIFICATION

Product name	**Stick-Onn Hot Melt Adhesive (EVA Granules)**
Recommended use	**EVA hot melt granules for wood-to-PVC edge banding on manual, automatic and spring-pocket lines. Industrial use.**
Supplier	**Synergy Bonding Solutions Pvt. Ltd., 205, 4th Floor, Mont Vert Spectra, Pallod Farms, Baner, Pune – 411045, Maharashtra, India**
Contact	**contact@stickonn.in · +91 90210 86995 · www.stickonn.in**
Emergency telephone	**+91 93716 35312 / +91 90210 86995 (Mon–Sat, 9:30 am – 6:30 pm IST)**

02 HAZARD IDENTIFICATION

GHS classification

- Not classified as hazardous according to GHS (UN Rev. 9) criteria.

Signal word

NO SIGNAL WORD

No hazard pictogram required.

Hazard statements

– No hazard statements.

Precautionary statements

- P280 Wear heat-resistant gloves and eye protection when handling molten adhesive.
- P271 Use only in a well-ventilated area.

Other hazards: Molten adhesive causes thermal burns. Overheating can release irritating fumes.

03 COMPOSITION / INFORMATION ON INGREDIENTS

Mixture.

Component	CAS No.	% w/w
Ethylene-vinyl acetate copolymer	24937-78-8	30 – 50
Tackifying resin	Proprietary	20 – 40
Calcium carbonate (filled grades)	471-34-1	0 – 40
Wax and antioxidant	Proprietary	< 10

04 FIRST-AID MEASURES

Inhalation	**If fumes from overheated material are inhaled, move to fresh air. Seek medical advice if symptoms persist.**
Skin contact (molten)	**Immediately cool the affected area under cold running water for at least 15 minutes. Do NOT peel solidified adhesive from skin. Seek medical attention for burns.**
Eye contact	**Molten product: flush with cold water and seek immediate medical attention. Solid granules: rinse with water.**
Ingestion	**Unlikely route of exposure. Rinse mouth. Seek medical advice.**

Most important symptoms: Thermal burns from molten material. Fumes from overheated product may irritate eyes and respiratory tract.

Note to physician: Treat symptomatically.

05 FIRE-FIGHTING MEASURES

Suitable extinguishing media	**Water spray, foam, dry chemical or CO_2.**
Specific hazards	**Combustible solid. Burning produces dense smoke, CO, CO_2 and acetic acid vapours.**
Protective equipment	**Wear self-contained breathing apparatus and full protective clothing.**

06 ACCIDENTAL RELEASE MEASURES

Sweep up granules to avoid slip hazard. Allow molten spills to solidify, then scrape up. Place in a labelled container for reuse or disposal.

07 HANDLING AND STORAGE

Safe handling	**Do not exceed the maximum working temperature. Provide local exhaust ventilation over glue pots. Avoid contact with molten adhesive.**
Storage conditions	**Store in original packing in a cool, dry place below 35°C, away from direct sunlight and sources of ignition.**

08 EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits: No occupational exposure limits established for the product.

Engineering controls: Provide general and, where necessary, local exhaust ventilation.

Eyes	**Safety glasses or face shield when working with molten adhesive.**
Hands	**Heat-resistant gloves.**
Respiratory	**Not required with adequate ventilation. Use local exhaust over melt tanks.**
Body	**Long sleeves to protect against molten splashes.**

09 PHYSICAL AND CHEMICAL PROPERTIES

Physical state	**Solid granules**
Colour	**White / yellow (grade dependent)**
Odour	**Faint when molten**
Softening point	**70 – 110°C**
Working temperature	**130 – 210°C**
Flash point	**> 250°C**
Solubility in water	**Insoluble**

10 STABILITY AND REACTIVITY

Reactivity / stability	**Stable under normal conditions of storage and use.**
Conditions to avoid	**Prolonged heating above the maximum working temperature; open flames.**
Incompatible materials	**Strong oxidising agents.**
Hazardous decomposition	**On overheating: acetic acid, aldehydes, CO, CO_2.**

11 TOXICOLOGICAL INFORMATION

Acute toxicity	**Not classified.**
Skin corrosion / irritation	**Not classified (solid). Molten product causes thermal burns.**
Eye damage / irritation	**Not classified (solid).**
Sensitisation	**Not classified.**
CMR effects	**Not classified.**

12 ECOLOGICAL INFORMATION

Not classified as hazardous to the aquatic environment. Product is insoluble in water and not expected to be bioavailable.

13 DISPOSAL CONSIDERATIONS

Dispose of as non-hazardous industrial solid waste in accordance with local regulations. Recycle packaging where possible.

14 TRANSPORT INFORMATION

UN number	**Not regulated**
Proper shipping name	**Not regulated**
Transport hazard class	**Not classified**
Packing group	**—**
Marine pollutant	**No**

15 REGULATORY INFORMATION

Classified and labelled in accordance with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS, UN Rev. 9). Users should comply with the Manufacture, Storage and Import of Hazardous Chemical Rules, 1989 (India) and the Factories Act, 1948, where applicable.

16 OTHER INFORMATION

Revision: 00 · Date of issue: 29/10/2026 · Document no.: SO/SDS/HMEVA/01

The information in this Safety Data Sheet is based on our present knowledge and is given in good faith. It describes the product with regard to safety requirements and does not constitute a guarantee of product properties. Users are responsible for ensuring safe handling and compliance with applicable laws. Refer to the Technical Data Sheet for application information.