STICK-ONN ADHESIVE

TECHNICAL DATA SHEET

SO/TDS/AQUA/01 | Rev. 00 | 29/10/2026

Stick-Onn AQUA+ Waterproof Adhesive

Waterproof Wood-Working Adhesive — 3× Faster Dry

01 PRODUCT DESCRIPTION

Stick-Onn AQUA+ is a specialised waterproof adhesive that protects furniture from de-bonding even when exposed to water. It prevents the opening of joints and lifting of laminates in kitchens, bathrooms and humid interiors — failures that occur even when good-quality board material is used.

02 KEY FEATURES

- 2-hour boiling-water-proof performance
- 72-hour normal-water-proof performance
- High-strength cross-linking adhesive
- Excellent spreadability and high coverage per kg
- Low-odour, water-based formulation
- 3× faster drying than conventional wood glue

03 APPLICATIONS

Kitchen furniture | Bathroom furniture | Laminate, ply & veneer | Humid interiors

04 DIRECTIONS FOR USE

1. Ensure surfaces are clean, dry and free from dust, oil and grease.
2. Stir the adhesive well before use.
3. Apply evenly on one surface and press firmly.
4. Keep under pressure until initial set; full waterproof strength develops in 24 hours.

05 CLEANING

Clean tools and wet adhesive with water. Cured adhesive must be removed mechanically.

06 STORAGE

Store in a cool, shaded, frost-free place between 5°C and 35°C. Keep the container tightly closed. Protect from freezing.

07 TYPICAL TECHNICAL DATA

Base / chemistry	**Cross-linking PVA copolymer emulsion**
Appearance	**White viscous liquid**
Viscosity	**150 – 250 Poise**
pH value	**3 – 5**
Free monomer	**0.3% max**
Coverage	**50 – 55 sq.ft / kg**
Boiling water resistance	**2 hours**
Normal water resistance	**72 hours**
Shelf life	**6 months from the date of manufacture in original sealed packing.**

Values are typical and indicative; not to be used as specification limits.

08 COMPATIBLE SUBSTRATES

Plywood | Laminate | Veneer | Particle board | MDF | Solid wood

09 PACK SIZES

800 g | 4 kg | 8 kg | 16 kg | 60 kg

10 HEALTH & SAFETY

Read the label and the Material Safety Data Sheet (MSDS) before use. Keep out of reach of children. MSDS available at **www.stickonn.in/downloads**.

Disclaimer: The information and recommendations in this data sheet are based on our tests and experience and are believed to be reliable. As conditions and methods of use are beyond our control, users should determine the suitability of the product for their purpose before full-scale use. Products are sold subject to the company's standard terms and conditions of sale. Specifications are subject to change without notice.

Synergy Bonding Solutions Pvt. Ltd. · An ISO 9001:2015 Certified Company
205, 4th Floor, Mont Vert Spectra, Pallod Farms, Baner, Pune – 411045, Maharashtra, India
contact@stickonn.in · +91 90210 86995 · www.stickonn.in
www.synergybonding.in