Predicting Mobile Application Success Using Machine Learning

Sajal Pandey IPM06057

Integrated Programme in Management, IIM Rohtak

IT Applications

Dr. Karan Verma

March 12, 2026

Abstract

The growth of apps has made the digital market very competitive. Many apps compete for users on platforms like the Google Play Store. So it's a problem for developers, investors and platform managers to predict which apps will be successful.

This study uses machine learning to predict the success of apps. We look at data from the Google Play Store like user ratings, reviews, price, app category and type of app. We want to find patterns that make some apps do better than others.

We prepare the data by fixing errors converting categories into numbers and creating a measure of success based on the number of installs. Apps with over one million installs are considered successful while those below are not.

We use a Random Forest classifier to see how app characteristics relate to success. We check how well the model works using measures like accuracy, confusion matrix and ROC curve analysis. We also use techniques like K-Means clustering and Principal Component Analysis (PCA) to explore patterns in the app ecosystem.

The results show that user engagement, like review count and app ratings is important, for predicting app success. Our findings can help developers design competitive apps and understand the digital market better.

Introduction

The mobile application industry has experienced its most substantial growth during the last ten years. The Google Play Store and Apple App Store together provide access to millions of applications which users can download for various entertainment and productivity and finance and education and health purposes. Developers now face intensified competition because they must secure user downloads and user engagement to compete in the expanding market.

Digital marketplaces offer a vast collection of applications yet only a tiny portion of them manage to attain broad user acceptance. Users do not show significant interest in most applications that developers create. Research studies need to examine application success factors because they have become essential elements in digital economics and data science research.

The success of an application depends on multiple factors which include application quality and pricing strategy and category placement and user engagement metrics. User ratings and reviews provide insights into user satisfaction which helps predict how popular an application will become.

Descriptive statistics and market analysis form the foundation of traditional business analysis methods which companies use to assess product performance. The emergence of extensive datasets together with machine learning breakthroughs enables researchers to create advanced predictive models which can discover intricate data relationships.

The analysis of digital marketplace data requires machine learning algorithms because these algorithms can process extensive observation data to find nonlinear connections between different features and resulting outcomes. The Random Forest classifier algorithm serves as a popular tool in predictive modeling because it maintains strong performance while working with diverse data types.

The objective of this research project is to create a machine learning system which can forecast the download success of mobile applications through their visible features. The research investigates dataset clustering patterns to discover how applications group together based on their performance metrics. The research uses supervised learning techniques together with exploratory data analysis to study the factors which determine the success of mobile applications.

Methodology

The methodological approach adopted in this study follows a structured machine learning workflow consisting of several stages:

1. Data collection and preprocessing
2. Feature construction and transformation
3. Model development using supervised learning
4. Model evaluation and interpretation
5. Exploratory analysis using clustering techniques

This structured approach ensures that the predictive model is both statistically valid and interpretable.

Data Source and Sample Description

The dataset used in this study is derived from publicly available Google Play Store data. The dataset contains information about thousands of mobile applications across multiple categories.

Each observation in the dataset represents an individual mobile application and contains attributes such as:

- Application category
- User rating
- Number of reviews
- Number of installs
- Application price
- Application type (free or paid)

These variables provide information regarding both the popularity and economic characteristics of each application.

The dataset contains several inconsistencies such as missing values, formatting issues, and non-numeric entries. Therefore, extensive preprocessing was performed before conducting the analysis.

Data Preprocessing

Data preprocessing plays a crucial role in preparing raw datasets for machine learning analysis. The data underwent cleaning and transformation through multiple implemented steps.

The installs variable first contained textual formatting which included commas and plus signs. The removal of these symbols enabled the transformation of the installs variable into numerical values.

The price variable required currency symbol removal before the conversion process to numeric form could proceed.

The dataset maintained its statistical representative nature through median imputation which addressed missing values in rating and review variables.

Label encoding techniques were used to convert categorical variables including application category and type into numerical formats which machine learning models could process.

The dataset underwent standardization through feature scaling which prevents measurement distortion from different scale variables during the modeling process.

Construction of the Success Variable

To convert the problem into a classification task, a binary target variable named **Success** was constructed.

Applications with more than one million installs were classified as successful applications, while those with lower installation counts were classified as non-successful applications.

This binary variable serves as the dependent variable for the supervised learning models implemented in the study.

The classification approach allows the machine learning algorithm to identify patterns associated with successful applications.

Machine Learning Model

A Random Forest classifier was implemented as the primary predictive model in this study. Random Forest is an ensemble learning method that constructs multiple decision trees and aggregates their predictions to produce a final classification outcome.

Random Forest models are widely used in machine learning because they offer several advantages:

- Ability to model nonlinear relationships
- Resistance to overfitting
- Robust performance on high-dimensional datasets
- Capability to measure feature importance

The dataset was divided into training and testing subsets to evaluate the model's predictive performance. Approximately 80 percent of the data was used to train the model, while the remaining portion was reserved for testing.

The model learns patterns from the training dataset and then generates predictions on the unseen test dataset.

Model Evaluation

The researchers assessed machine learning model performance through multiple classification metric assessments. The confusion matrix provides a summary of correct and incorrect predictions generated by the model. From the confusion matrix, performance metrics such as accuracy, precision, and recall can be derived.

Accuracy measures the proportion of correctly classified observations relative to the total number of observations. Precision measures how many predicted positive cases were actually positive, while recall measures the ability of the model to identify true positive cases. The researchers evaluated model performance through a Receiver Operating Characteristic (ROC) curve which assessed the model's ability to discriminate between classes at various classification thresholds.

A ROC curve that lies significantly above the diagonal reference line indicates strong predictive performance.





Exploratory Analysis Using Clustering

Unsupervised learning methods together with supervised learning methods were used to discover patterns that existed in the dataset. K-Means clustering was used to group applications into clusters based on their attributes.

The Elbow Method which analyzes within-cluster sum of squares reduction found its optimal cluster count through studying how this metric decreased when more clusters were added. The researchers used Principal Component Analysis (PCA) to create two-dimensional visualizations of the dataset while maintaining its original dimensions.

The clustering analysis showed that applications grouped together based on their user engagement patterns which included three types of applications: low-review applications moderately successful applications and highly popular applications. The analysis explains additional details about how the application market functions.





Feature Importance Analysis

The Random Forest model provides an estimate of the relative importance of each feature in predicting application success.

The results indicate that user engagement metrics such as the number of reviews and application ratings are among the most important predictors of success.

Applications with higher ratings and a large number of user reviews tend to have significantly higher installation counts.

Price and application category also contribute to the prediction process, although their influence is relatively smaller compared to engagement-related variables.

These findings highlight the importance of user satisfaction and visibility in driving application adoption.

Results and Discussion

The analysis results show that machine learning models successfully detect patterns which lead to mobile application success. Applications that receive strong user feedback through ratings and reviews are significantly more likely to achieve high installation levels.

The finding demonstrates that users who experience positive interactions with the product will share their experience to others which will lead to more users downloading the product. The clustering analysis shows that applications can be divided into three different performance groups. Some clusters contain applications with minimal user engagement while others represent highly successful applications with large user bases.

The combination of supervised learning and unsupervised learning methods enables researchers to fully understand how applications perform throughout their operational lifetime. The research shows that digital marketplace behavior can be understood better through data-driven methods.

```
Accuracy: 0.9455719557195572
              precision    recall  f1-score   support

           0       0.96      0.96      0.96      1615
           1       0.90      0.89      0.89       553

    accuracy                           0.95      2168
   macro avg       0.93      0.93      0.93      2168
weighted avg       0.95      0.95      0.95      2168
```

Conclusion

The research created a machine learning framework to assess and forecast mobile application success within the Google Play Store system. The Random Forest classifier utilized application metadata which included ratings, reviews, price, and category information to determine the probability of an application reaching high installation numbers.

The study demonstrates that user engagement metrics function as effective indicators for predicting application performance. The review count together with application ratings establishes the probability of an application achieving widespread usage.

The study used predictive modeling together with clustering analysis to identify distinct application groups which shared similar engagement patterns. The study results demonstrate that digital marketplaces exhibit different performance patterns which the research identified through its analysis.

The study results demonstrate how machine learning methods help researchers study the factors that lead to mobile application success. The research could be expanded by including new variables which involve how frequently applications receive updates and how developers are perceived and how users continue to use the platform.

By leveraging data-driven approaches, developers and platform managers can gain valuable insights that may improve decision-making and enhance the competitiveness of mobile applications.