



DESIGN FOR PROPOSED NEW INTEGRATED TERMINAL AND ASSOCIATED WORKS AT AGARTALA AIRPORT

PMC :



ARCHITECTS :



PRECEDENT

AGARTALA , TRIPURA - GREEN/FORESTS , LOCAL BAMBOO MATERIAL , TRIBAL ART

3

EXTENSIVE GREEN & FOREST COVER



FORESTS IN TRIPURA

LOCALLY USED BAMBOO MATERIAL



BAMBOO PLANTATIONS IN TRIPURA

LOCAL TRIBAL STONE SCULPTURES



UNAKOTI HILL , AGARTALA



FORESTS NEAR AGARTALA



BAMBOO HANDICRAFTS MADE
IN AGARTALA



TRIPURA STATE REPRESENTATION
ON REPUBLIC DAY







MATERIALS:- CANOPY - 16 CELL POLYCARBONATE SHEETS

FACADE - LAMINATED GLAZING + GFRC IN BAMBOO FINISH

ROOF - INSULATED STANDING SEAM ROOF CLADDING



FLORAL PATTERN JAALI DEPICTING LOCAL FORESTS & GREENS







- | | | | |
|-------------------------------|-------------------------|------------------------------------|----------------------------|
| 1 ENTRY & EXIT | 6 CONNECTING CROSS-WAY | 11 LAWN WITH ROCKS | 16 PAGODA STRUCTURE |
| 2 DRIVEWAY | 7 OUTDOOR CAFE | 12 PAVED AREA | 17 PLANTING ALONG DRIVEWAY |
| 3 PATHWAY | 8 PAVED PLAZA | 13 ROW OF PALM PLANTING | 18 GREEN ISLAND |
| 4 ENTRANCE MOUND WITH SIGNAGE | 9 CENTRAL WATER FEATURE | 14 ARTISTIC HEDGES | |
| 5 TRIBES OF TRIPURA | 10 TREE COURT | 15 MOUND WITH TRADITIONAL ROCK ART | |


8

RETAIL AREA = 2000 SQ.M (11%)



MEZZANINE FLOOR PLAN

FLOOR AREA = 8500 SQ.M
RETAIL AREA = 1050 SQ.M (12.5%)





BASEMENT FLOOR PLAN


FLOOR AREA = 5,500 SQ.M



SECTIONS



SECTION AA'



SECTION BB'




Proposed Areas for Primary Processing and Waiting

12

DEPARTURE

Visitors Concourse Area	660 sq m	
Check-in-counters (Domestic) No. of Counters	22 nos.	16 required + 5 future expansion
Check-in-counters (International) No. of Counters	6 nos.	5 required + 3 future expansion
Check-in Queue Area	400 sq m	
Security Checkpoint No. of Lanes (Domestic)	3 nos.	2 required + 1 future expansion
Security Checkpoint Screening Area (Domestic)	200 sq m	
Security Checkpoint Queue Area (Domestic)	250 sq m	
Security Checkpoint No. of Lanes (International)	3 nos.	2 required + 1 future expansion
Security Checkpoint Screening Area (International)	110 sq m	
Security Checkpoint Queue Area (International)	150 sq m	
Outbound Baggage Screening Devices	6 nos.	5 required + 1 future expansion
Holdrooms (Domestic) Area	1040 sq m	
Holdrooms (International) Area	700 sq m	

ARRIVAL		
Baggage Claim Devices (Domestic) No. of Belts	3 nos.	2 required + 1 future expansion
Baggage Claim Devices (International) No. of Belts	1 no.	1 required
Positive baggage Claim area (Domestic)	3000 sq m	
Positive baggage Claim area (International)	900 sq m	
Visitors Concourse Area	920 sq m	



**VISITOR
CONCOURSE**



**CHECK IN
AREA**




**HOLD ROOM
DOMESTIC**



**HOLD ROOM
INT.**



**SECURITY
CHECK**



**VISITOR
CONCOURSE**

**BAGGAGE
CLAIM DOM.**

**BAGGAGE
CLAIM INT.**

Normative Planning Data for Primary Processing and Waiting Areas

	Input values	Units	Remarks	Formula
DEPARTURE AREAS				
Visitors Concourse	Peak hour Departing passengers	600	Given	$600 \times 2 = \text{No. of visitors} = 1200$
	No. of visitors per passenger	2	Assumption	$1200 \times .33 \text{ dwell time in minutes} = \text{number of visitors in area} = 396$
	Dwell time of the visitors in minutes	15	Based on 60 minutes total dept dwell time	$396 \times 1.7 \text{ sm per passenger} = \text{area required for visitors concourse}$
	Area per visitor (sq.m)	1.70	IATA Standards	Visitor concourse = 673.2 sq.m
Check-in-counters (domestic)	Peak hour Departing passengers	500	Given	IATA Formula
	Check-in processing rate in minutes	2	Industry Std for Domestic	$500 \text{ pax} \times (2 \text{ mins per pax} / 60 \text{ mins})$
				No. of Check-in Counters = 16
Check-in-counters (international)	Peak hour Departing passengers	100	Given	IATA Formula
	Check-in processing rate in minutes	3	Industry Standard for International	$100 \text{ pax} \times (3 \text{ mins per pax} / 60 \text{ mins})$
				No. of Check-in Counters = 5
				TOTAL No. OF CHECK-IN COUNTERS = 21
Check-in Counters	Linear meter per counter width (lm)	1.52	Industry Standard	Area required for the Check-in Counter and Queue
	Lm per counter and work area depth	3.65	Industry Standard	Length of counter/work area X width of counter X no. of counters
				$(3.65 \times 1.52) \times 21 = \text{area(excluding circulation area)}$
				CHECK-IN COUNTERS Area requirement = 116.5 sq.m
Check-in Queue	Sq.m per passenger	1.7	IATA	$1.7 \text{ sq.m per person} \times 140 \text{ persons}$
	25 minutes max waiting time	140	Design for 10 minutes queue	CHECK-IN Queue area = 238 sq.m

	Input values	Units	Remarks	Formula
Security Checkpoint Lanes (Domestic)	Peak hour Departing Pax	500	Given	500 divided by 250pax per hour per lane = 2
	Screening Processing Rate	250	IATA	TOTAL No. OF SECURITY SCREENING CHECKPOINTS = 2
Security Checkpoint area (Domestic)	Linear meter width of lane	5		5m x 14m x 2 lanes=140 sm
	Depth of lane	14		SECURITY Screening area = 140 sq.m
Security Checkpoint queue (Domestic)	Sq.m per passenger	1.7	IATA	1.7 sq.m / person x 125
	Max 25% of peak hour passengers assumed	125	Design for 10 minutes queue in queue as per IATA	SECURITY Queue area = 212.5 say 210 sq.m
Security Checkpoint Lanes (International)	Peak hour Departing Pax	100	Given	100 divided by 250pax per hour per lane = 1
	Screening Processing Rate	250	IATA	TOTAL No. OF SECURITY SCREENING CHECKPOINTS = 1
Security Checkpoint area (International)	Linear meter width of lane	5		5m x 14m x 1 lanes=70 sq.m
	Depth of lane	14		SECURITY Screening area = 70 sq.m
Security Checkpoint queue (International)	Sm per passenger	1.7	IATA	1.7 sq.m / person x 25
	Max 25% of peak hour passengers assumed	25	Design for 10 minutes queue in queue as per IATA	SECURITY Queue area = 42.5 say 45 sq.m
Outbound Baggage Screening Devices	Peak hour Departing Pax	600	Given	600 pax X 2 bags per pax/250 bags per hr
	Baggage Screening rate per device	250	Design for 10 minutes queue in queue as per IATA	No. of EDS in-line screening devices = 4.8 say 5 machines
	Bags per pax	2		
Holdrooms (Domestic)	Maximum no. of departing passengers at a given time.	500	Given	Number of passengers x area per pax = 500 x 1.7 = 850
	Area per pax (sq.m)	1.7	IATA	HOLDROOM - Area of I holdroom = 850 sq.m
Holdrooms (International)	Maximum no. of departing passengers at a given time.	100	Given	Number of passengers x area per pax= 100 x 1.7 =170
	Area per pax (sq.m)	1.7	IATA	HOLDROOM - Area of I holdroom = 170 sq.m

	Input values	Units	Remarks	
ARRIVAL AREAS				
Baggage Claim Devices (Domestic)	Peak hour Arriving passengers	500	Given	70% of 500 = 350
	Percentage pax in the claim hall	70	At one time	350 pax / 4 pax per meter = 87.5 m of claim frontage
	Number of pax per metre of claim	4	In queue around the belt	Yields .8 belt at 55 meters
				Number of baggage claim devices = 2
Baggage Claim Devices (International)	Peak hour Arriving passengers	100	Given	70% of 100 = 70
	Percentage pax in the claim hall	70	At one time	70 pax/ 4 pax per meter= 17.5 m of claim frontage
	Number of pax per metre of claim	4	In queue around the belt	Yields .3 belt at 55 meters
				Number of baggage claim devices = 1
Positive baggage claim area (Domestic)	Area per unit of 55m belt (sq.m)	585	Actual	585 sq.m per belt x 2 belt=1170 sq.m
	Area per Pax (sq.m)	1.7	IATA Standards	350 x 1.7 = 5955 sq.m
				1170 + 595 = 1765 sq.m
				Area Required = 1765 sq.m
Positive baggage claim area (International)	Area per unit of 55m belt (sq.m)	585	Actual	585 sq.m per belt x 1 belt = 585 sq.m
	Area per Pax (sq.m)	1.7	IATA Standards	70 x 1.7 = 119 sq.m
				585 + 120 = 705 sq.m
				Area Required = 705 sq.m
Visitors Concourse	Peak hour arriving pax	600	Given	600 x 1 = 600
	Visitor per pax	1	Assumption	600 x 20min/60min = 200 visitors
	Dwell time in minutes	20	Per Industry Standards	200 x 1.7 per pax = area required for the visior concourse
	Area per Visitor (sq.m)	1.7	IATA	Visitor Concourse= 340 sq.m

INTERIOR VIEW - FLUIDITY IN PLAN FOR EASE OF PASSENGER MOVEMENT & DEFINATION OF BULK HEADS TO ENHANCE RETAIL

VIEW 01

19



MATERIALS :-

1. CEILING - PERFORATED METAL CEILING BAMBOO FINISH , TENSILE MEMBRANE
2. FLOORING - WHITE GRANITE, RUBY RED (POLISHED/FLAMED), BLACK GRANITE



- MODERN DEPICTION OF LOCAL ART

- UNAKOTI HILLS IN AGARTALA



INTERIOR VIEW - BAGGAGE RECLAIM AREA

VIEW 03

22




- MATERIALS :-**
- 1. CEILING - PERFORATED METAL CEILING
BAMBOO FINISH, TENSILE MEMBRANE
 - 2. FLOORING- WHITE GRANITE, BLACK GRANITE
RUBY RED (POLISHED/FLAMED),
 - 3. BULKHEAD- ACP PANELS WITH MOTIF INLAY



INTERIOR VIEW - LOCAL MOTIF DEPICTED IN METAL CLADDING TO CREATE VIBERANCY
VIEW 04 - USE OF METAL CLADDING AND PERFORATED SCREENS IN INTERIOR AREAS

23



INTERIOR VIEW – VIP LOUNGE

VIEW 05

24



VIP LOUNGE



MATERIALS :- 1. CEILING - PERFORATED METAL CEILING BAMBOO TEXTURE , MINERAL FIBRE BOARD CEILING
2. BAMBOO LANDSCAPE FEATURE IN GLASS CASING