

```
      85 6.069168      71.192.34.104      64.233.169.104      HTTP      689      GET / HTTP/1.1
Frame 85: 689 bytes on wire (5512 bits), 689 bytes captured (5512 bits)
Ethernet II, Src: Dell_4f:36:23 (00:08:74:4f:36:23), Dst: Cisco_bf:6c:01 (00:0e:d6:bf:6c:01)
Internet Protocol Version 4, Src: 71.192.34.104, Dst: 64.233.169.104
Transmission Control Protocol, Src Port: 4335, Dst Port: 80, Seq: 1, Ack: 1, Len: 635
  Source Port: 4335
  Destination Port: 80
  [Stream index: 2]
  [TCP Segment Len: 635]
  Sequence number: 1      (relative sequence number)
  [Next sequence number: 636      (relative sequence number)]
  Acknowledgment number: 1      (relative ack number)
  Header Length: 20 bytes
  Flags: 0x018 (PSH, ACK)
    000. .... = Reserved: Not set
    ...0 .... = Nonce: Not set
    .... 0... = Congestion Window Reduced (CWR): Not set
    .... .0.. = ECN-Echo: Not set
    .... ..0. = Urgent: Not set
    .... ...1 .... = Acknowledgment: Set
    .... .... 1... = Push: Set
    .... .... .0.. = Reset: Not set
    .... .... ..0. = Syn: Not set
    .... .... ...0 = Fin: Not set
    [TCP Flags: .....AP...]
  Window size value: 65044
  [Calculated window size: 260176]
  [Window size scaling factor: 4]
  Checksum: 0x386d [unverified]
  [Checksum Status: Unverified]
  Urgent pointer: 0
  [SEQ/ACK analysis]
Hypertext Transfer Protocol
```