ROADSENSE | Infrastructure Intelligence

DATE: November 10, 2026
STANDARDS: ASTM D6433 | IRC:SP:77 / IRC:82

ASTM D6433 CONDITION	ROUGHNESS INDEX (IRI)	MATERIAL REQUIRED	ESTIMATED REPAIR BUDGET
10.0 / 100 **Serious / Failed**	**4.32** m/km ASTM E1926	**157.3 kg** Cold-Mix Bitumen	**Rs. 8877** ($162.23)

Hazard Classification & Severity Breakdown

Hazard Category	Impact Severity	Count	Recommended Municipal Action
Pothole	Severe (Z >= 3.0)	1	Immediate Cold Patching / Asphalt Mill & Infill (<48h)
Pothole	Moderate (Z 2.0-3.0)	0	Scheduled Maintenance (<14 days)
Pothole	Minor / Anomaly (Z < 2.0)	5	Surface Seal Coating / Monitor
Speedbreaker	Standard Deflection	1	Verify Regulatory Height & Signage Painting

Priority Maintenance Dispatch Table (Top Critical Hazards)

#01	**Speedbreaker** Severe	**Cat Category C (Structural Base / Sub-base Failure)** IRC:82-Clause 6.4	12.92240, 77.50160	958cm² depth 8.8cm	**9.9 kg**	Rs.745	Deep milling, granular sub-base recompaction & DBM overlay
#02	**Pothole** Low	**Cat Category C (Structural Base / Sub-base Failure)** IRC:82-Clause 6.4	0.00000, 0.00000	25000cm² depth 3.4cm	**99.9 kg**	Rs.4795	Deep milling, granular sub-base recompaction & DBM overlay
#03	**Pothole** Low	**Cat Category B (Standard Pothole Cavity)** IRC:SP:77-Clause 4.1	12.92240, 77.50160	2963cm² depth 3.4cm	**11.8 kg**	Rs.833	Square cut, edge priming & Cold-Mix Bituminous Patching
#04	**Pothole** Low	**Cat Category B (Standard Pothole Cavity)** IRC:SP:77-Clause 4.1	12.92240, 77.50160	2380cm² depth 3.4cm	**9.5 kg**	Rs.728	Square cut, edge priming & Cold-Mix Bituminous Patching

#05	**Pothole** Low	**Cat Category B (Standard Pothole Cavity)** IRC:SP:77-Clause 4.1	0.00000, 0.00000	3720cm² depth 3.4cm	**14.8 kg**	Rs.968	Square cut, edge priming & Cold-Mix Bituminous Patching
#06	**Pothole** Low	**Cat Category B (Standard Pothole Cavity)** IRC:SP:77-Clause 4.1	12.92240, 77.50160	2830cm² depth 3.4cm	**11.3 kg**	Rs.808	Square cut, edge priming & Cold-Mix Bituminous Patching

Camera Ground-Truth Evidence (AI Detection Bounding Boxes)

Visual verification frames captured by vehicle optical sensors at timestamp of impact.







