ROADSENSE | Infrastructure Intelligence

DATE: November 07, 2026
STANDARD: ASTM D6433 / IRI

ASTM D6433 CONDITION	ROUGHNESS INDEX (IRI)	SURVEY DISTANCE	DEFECT DENSITY
100.0 / 100 **Good**	**1.2** m/km World Bank Std.	**0.72** km (722.1 m)	**0** hazards 0.0 / km

Hazard Classification & Severity Breakdown

Hazard Category	Impact Severity	Count	Recommended Municipal Action
Pothole	Severe (Z >= 3.0)	0	Immediate Cold Patching / Asphalt Mill & Infill (<48h)
Pothole	Moderate (Z 2.0-3.0)	0	Scheduled Maintenance (<14 days)
Pothole	Minor / Anomaly (Z < 2.0)	0	Surface Seal Coating / Monitor
Speedbreaker	Standard Deflection	0	Verify Regulatory Height & Signage Painting

Priority Maintenance Dispatch Table (Top Critical Hazards)

ID	Type	Severity	Latitude	Longitude	Est. Area	Est. Depth	Action
—	None	—	—	—	—	—	No critical defects logged

Camera Ground-Truth Evidence (AI Detection Bounding Boxes)

Visual verification frames captured by vehicle optical sensors at timestamp of impact.






Pothole: 70%


Pothole: 80%