1. `toHaveText()` vs `toContainText()`

Both assertions verify the **visible text** of an element, but they differ in how strictly they compare the text.

Feature	`toHaveText()`	`toContainText()`
Comparison	Exact text	Partial text
Match Type	Full match	Substring match
Best Used When	You know the complete expected text	You only need to verify part of the text
Ignores extra spaces	✅ Yes	✅ Yes

`toHaveText()` (Exact Match)

Checks whether the element's text **exactly matches** the expected text.

Example

```
import { test, expect } from '@playwright/test';

  test('toHaveText Example', async ({ page }) => {

      await page.goto('https://demowebshop.tricentis.com/');

      const welcomeMsg = page.locator('.topic-html-content-header');

      await expect(welcomeMsg).toHaveText('Welcome to our store');
  });
```

✅ Passes only if the text is exactly:

```
Welcome to our store
```

❌ Fails if the text is:

```
Welcome to our online store
```

`toContainText()` (Partial Match)

Checks whether the element's text **contains** the expected text.

Example

```
import { test, expect } from '@playwright/test';

  test('toContainText Example', async ({ page }) => {

      await page.goto('https://demowebshop.tricentis.com/');

      const welcomeMsg = page.locator('.topic-html-content-header');

      await expect(welcomeMsg).toContainText('Welcome');
  });
```

This passes for:

```
Welcome to our store
```

```
Welcome to our online store
```

```
Welcome
```

Summary

Suppose the actual text is:

```
Welcome to our store
```

Assertion	Expected	Result
`toHaveText()`	`Welcome to our store`	✅ Pass
`toHaveText()`	`Welcome`	❌ Fail
`toContainText()`	`Welcome`	✅ Pass
`toContainText()`	`our store`	✅ Pass
`toContainText()`	`Hello`	❌ Fail

---

2. `toHaveText()` vs `toHaveValue()`

These assertions verify **different properties** of an element.

Feature	`toHaveText()`	`toHaveValue()`
Verifies	Visible text	Value attribute
Used For	Headings, labels, links, buttons, paragraphs, divs	Textboxes, textareas, dropdowns
Checks	Text displayed on screen	User-entered or selected value

---

`toHaveText()` Example

Checks the visible text of an element.

```
const heading = page.locator('.topic-html-content-header');

  await expect(heading).toHaveText('Welcome to our store');
```

HTML:

```
<h1>Welcome to our store</h1>
```

`toHaveValue()` Example

Checks the value inside an input field.

```
await page.goto('https://demowebshop.tricentis.com/login');

  const email = page.locator('#Email');

  await email.fill('admin@example.com');

  await expect(email).toHaveValue('admin@example.com');
```

HTML:

```
<input id="Email" value="admin@example.com">
```

Another Example (Dropdown)

```
const sortBy = page.locator('#products-orderby');

  await sortBy.selectOption('10');

  await expect(sortBy).toHaveValue('10');
```

Visual Difference

`toHaveText()`

```
## Welcome to our store
```

Checks:

```
Welcome to our store
```

`toHaveValue()`

```
<input value="Pavan Kumar">
```

Checks:

```
Pavan Kumar
```

Quick Comparison

Assertion	Checks	Common Elements	Match Type
`toHaveText()`	Complete visible text	Heading, Label, Link, Button, Div	Exact
`toContainText()`	Partial visible text	Heading, Label, Link, Button, Div	Partial
`toHaveValue()`	`value` attribute	Input, Textarea, Select	Exact

When to Use Which?

- ✅ Use `toHaveText()` when you want to verify the **entire visible text**.
- ✅ Use `toContainText()` when you only need to verify that the text **includes a specific word or phrase**.
- ✅ Use `toHaveValue()` when verifying the **current value of an input field, textarea, or selected option in a dropdown**.