GOOGLE CLOUD PLATFORM ARCHITECTURE STYLE • MOVEINSYNC HIRING EVALUATION

MoveInSync Hierarchical Tenant Configuration Platform

Advanced Backend Engineering Track — Case Study 2: Live Propagation Engine

Saksham Gupta
Reg No: **230911186** • B.Tech IT, MIT Manipal (**Rank 1 / Top 5%**, CGPA: **9.12**)
saksham77779@gmail.com
GitHub: moveinsync-config-platform

IN-MEMORY READ LATENCY (P50) ▲ 60x FASTER
0.166 µs (166 ns)
100,000 reads • **5,431,644 ops/sec/thread** (SLA < 10 µs)


200-CLIENT LIVE SSE LATENCY ▲ 18x FASTER
278 ms (p50)
Fleet p99: **320 ms** • **4,680 ms Headroom** (SLA < 5,000 ms)

EVALUATOR INVARIANT SUITE ✔ 100% PASS
24 / 24 Green
Hard `kill -9`, Atomic Read, Gap Sync, Storm Verified

ARCHITECTURAL PRINCIPLES & CRITICAL ENGINEERING DECISIONS

PRODUCTION-GRADE SPRING BOOT 3

- **Language & Runtime:** Java 17 LTS + Spring Boot 3.3.4. Selected strictly to reflect MoveInSync's core backend ecosystem.
- **Zero-Lock In-Memory Cache:** Client holds immutable `ConfigSnapshot` inside `AtomicReference`. Multi-key queries bind pointer once, ensuring **0 partial states** during active writes with **0 synchronized locks**.
- **4-Tier Hierarchy Resolution:** Evaluates `SHIFT > OFFICE > CLIENT > GLOBAL > Default` with audit trail `explain()` breakdown.
- **Contiguous Monotonic Deltas (Option A):** Out-of-scope offices during canary rollouts receive contiguous empty deltas (`empty=true`) to advance local version counters without triggering false gap re-sync storms.
- **Durability Before ACK:** SQLite WAL with `PRAGMA synchronous = FULL;` guarantees fsync before write ACK, surviving hard `SIGKILL (kill -9)`.
- **Backoff & Slow Consumer Guard:** AWS Full Jitter backoff; bounded 100-event subscriber queues with automatic eviction to protect server heap.



EMPIRICAL BENCHMARK VERIFICATION (HOTSPOT C2 JIT-WARMED ON APPLE SILICON)

BENCHMARK SUITE PASSING

In-Memory 4-Tier Read Latency (100,000 Operations)

Percentile	Measured Latency	Evaluator Requirement	Performance Margin
Min	0.041 µs (41 ns)	—	—
p50 (Median)	**0.166 µs (166 ns)**	< 10 µs	60X FASTER
p90	0.208 µs (208 ns)	< 10 µs	48X FASTER
p95	0.209 µs (209 ns)	< 10 µs	47X FASTER
p99	**0.250 µs (250 ns)**	< 10 µs	40X FASTER
Throughput	**5,431,644 ops/sec**	> 100,000 ops/sec	54X HIGHER

200-Client Live SSE Fleet Propagation (Broadcast Engine)

Metric Target	Empirically Measured	SLA Requirement	Evaluator Result
Active Fleet	200 Concurrent Clients	200 Clients	100% CONNECTED
p50 Latency	**278 ms**	< 5,000 ms (5s)	18X FASTER
p90 Latency	320 ms	< 5,000 ms (5s)	15X FASTER
p95 Latency	320 ms	< 5,000 ms (5s)	15X FASTER
p99 Latency	**320 ms**	< 5,000 ms (5s)	15X FASTER
Max Latency	**320 ms**	< 5,000 ms (5s)	4,680 MS HEADROOM

GOOGLE CLOUD PLATFORM ARCHITECTURE STYLE • MOVEINSYNC RESILIENCE & FAULT TOLERANCE

MoveInSync Platform: Resilience, Fault Tolerance & Verification

Failure Analysis, Concurrency Guarantees, Security Isolation & Automated Test Matrix

Saksham Gupta
Reg No: **230911186** • MIT Manipal • **24 / 24 Tests Green**

All Invariants Verified | SIGKILL -9 Tested

EXHAUSTIVE FAILURE MODE & AUTOMATED RECOVERY MATRIX

8 PRODUCTION FAULT SCENARIOS

Failure Scenario	Catastrophic Risk	Architectural Mitigation & Recovery Mechanism	Verification
Server Power Loss / Crash	Committed changeset lost from disk cache; clients desynchronized	SQLite WAL mode with `PRAGMA synchronous = FULL;` guarantees fsync before ACK. On reboot, state is 100% intact.	KILL -9 PASSED
Network Drop & Reordering	Client receives v43 before v42, leaving local state inconsistent	Gap detector catches `v > current + 1`, rejects non-contiguous delta, and pulls missing deltas via `?since_version=`.	TEST PASSED
Duplicate Stale Deltas	Re-transmitted older packet overwrites newer configuration	Strict monotonic check: Any delta where `version <= currentVersion` is silently dropped as a no-op.	TEST PASSED
Staged Canary Rollout	Non-canary offices skip version, triggering endless gap storm	**Option A:** Server emits contiguous empty deltas (`empty=true`) to out-of-scope offices, advancing version cleanly.	TEST PASSED
Invalid Compound Key	Partial update committed (e.g. valid key passes, negative cutoff fails)	All-or-nothing atomic validation: If 1 key fails validation, entire changeset is rejected; zero keys mutate.	TEST PASSED
Slow SSE Consumer	Unresponsive vehicle tablet causes memory leak on server heap	Bounded `ArrayBlockingQueue(100)`. On overflow, slow client is evicted immediately (`completeWithError`) to protect heap.	TEST PASSED
Cold Boot Without WAN	Vehicle device starts in underground parking without connectivity	Hydrates from locally persisted `snapshot.json` written atomically via temporary file and atomic rename.	TEST PASSED
200 Fleet Reconnect Storm	All devices reconnect simultaneously after network recovery	AWS Full Jitter exponential backoff prevents thundering herd. Server utilizes delta-only transmission.	TEST PASSED

CONCURRENCY & ATOMIC READ ISOLATION

ZERO-LOCK ATOMIC

- **Atomic Reference Swap:** The client stores state in `AtomicReference<ConfigSnapshot>`. Multi-key queries read from a single immutable instance.
- **Writer Ordering Guarantee:** Server acquires a single `ReentrantLock` across `[Assign Version → SQLite Fsync → SSE Enqueue]`. Deltas are published in strict monotonic sequence without interleaving.
- **Concurrency Proof:** 50 reader threads executed **1,366,000+ continuous reads** during active compound updates. **0 partial state violations observed**.

RBAC, TENANT ISOLATION & PII PROTECTION

STRICT DATA ENCLAVE

- **Role Matrix:** `ADMIN` (full CRUD & rollback), `OPERATOR` (tenant changeset authoring), `EMPLOYEE` (read-only snapshot & SSE streams).
- **Cross-Tenant Wall:** Tokens are validated against target tenant. Client A is strictly forbidden from querying or receiving Client B's configurations via REST or SSE.
- **PII Policy:** Zero request bodies or employee identifiers logged. Only operational metrics (client ID, office, version, timing) are recorded.

AUTOMATED VERIFICATION CATALOG (24 TESTS • 100% GREEN SUITE)

MAVEN TEST REACTOR PASSING

Module	Test Suite Class	Target Requirement / Invariant Verified	Evaluator Result
`config-core`	`HierarchyResolverTest` (5 tests)	Strict 4-tier resolution precedence & audit trail `explain()` mode	5 / 5 PASS
`config-core`	`SettingValidatorTest` (6 tests)	Negative duration rejection (-30m), start!=end window, bounds checking	6 / 6 PASS
`config-client-sdk`	`ConfigClientTest` (2 tests)	Contiguous versioning, empty deltas, and cold-boot disk hydration	2 / 2 PASS
`config-server`	`CompoundValidationRejectionTest`	Atomic all-or-nothing validation: 1 bad key rejects full compound changeset	✔ PASS
`config-server`	`ConcurrencyAtomicReadTest`	50 threads, 1,366,000+ reads during active publish; 0 partial states	✔ PASS
`config-server`	`StagedRolloutAndPromoteTest`	Canary isolation, empty contiguous deltas to non-canary, promotion expansion	✔ PASS
`config-server`	`RollbackDiffTest`	Safe forward rollback commit with dry-run diff calculation preview	✔ PASS
`config-server`	`TenantIsolationTest`	Employee read-only enforcement; cross-tenant REST & SSE boundary isolation	✔ PASS
`config-server`	`OutOfOrderAndGapSyncTest`	Network reordering gap healing (V43 on V41 triggers REST sync); drops stale dupes	✔ PASS
`config-server`	`ServerKillFaultInjectionTest`	Real `SIGKILL (kill -9)` of server process; committed change survives on restart	✔ PASS
`config-server`	`ReconnectStormTest`	200 concurrent client instances connect, receive live deltas, 0 dropped events	✔ PASS
`config-server`	`BenchmarkRunnerTest`	Empirical JIT-warmed benchmark runner validating read & propagation SLAs	✔ PASS

COMPLEXITY ANALYSIS, OPERATIONAL BOUNDARIES & SCALING ROADMAP

HORIZONTAL BLUEPRINT

Algorithmic Complexity Guarantees:

- **In-Memory Read:** `O(1)` hash map lookup across 4 tiers. Zero locks, zero synchronization contention overhead.
- **Changeset Commit:** `O(K)` where `K` is number of keys in changeset. Single SQLite write transaction with WAL fsync.
- **Live Broadcast:** `O(S)` where `S` is active SSE subscribers. Dispatched asynchronously across thread pool.

Production Horizontal Scaling Roadmap:

- **Write Boundary:** SQLite single-writer handles ~2,500 changesets/sec. For higher multi-region throughput, migrate to PostgreSQL with read replicas.
- **Streaming Boundary:** Single node supports 10,000–15,000 concurrent SSE connections. For 50,000+ fleet vehicles, scale horizontally using Redis Pub/Sub or Kafka with tenant-consistent hashing.