Minimum Steps to Halve Sum | Pr

https://www.geeksforgeeks.org/problems/minimum-steps-to-halve-sum/1?page=1&category=Arrays&sortBy=latest

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

8 6 2

Your Output:

3

Expected Output:

3

Java (21) Start Timer

```java
import java.util.*;

class Solution {
    public int minOperations(int[] arr) {

        PriorityQueue<Double> pq = new PriorityQueue<>(Collections.reverseOrder());

        double sum = 0;

        for(int x : arr){
            pq.add((double)x);
            sum += x;
        }

        double target = sum / 2.0;
        int operations = 0;

        while(sum > target){

            double largest = pq.poll();
            double half = largest / 2.0;

            sum -= half;

            pq.add(half);
            operations++;
        }

        return operations;
    }
}
```

Custom Input Compile & Run Submit

20°C Clear Search ENG IN 23:59 15-03-2026

Minimum Number of Workers | Pr

https://www.geeksforgeeks.org/problems/minimum-sprinklers/1?page=1&category=Arrays&sortBy=latest

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

-1 2 2 -1 0 0

Your Output:

2

Expected Output:

2

Java (21) Start Timer

```java
        int[][] interval = new int[n][2];
        int k = 0;

        for (int i = 0; i < n; i++) {
            if (arr[i] != -1) {
                int L = Math.max(0, i - arr[i]);
                int R = Math.min(n - 1, i + arr[i]);
                interval[k][0] = L;
                interval[k][1] = R;
                k++;
            }
        }

        java.util.Arrays.sort(interval, 0, k, (a, b) -> a[0] - b[0]);

        int count = 0;
        int i = 0;
        int currEnd = -1;
        int farthest = -1;

        while (currEnd < n - 1) {

            while (i < k && interval[i][0] <= currEnd + 1) {
                farthest = Math.max(farthest, interval[i][1]);
                i++;
            }

            if (farthest <= currEnd) return -1;

            count++;
            currEnd = farthest;
        }

        return count;
    }
}
```

Custom Input Compile & Run Submit

20°C Clear Search ENG IN 00:06 16-03-2026

Previous Smaller Element | Practice

https://www.geeksforgeeks.org/problems/previous-smaller-element/1?page=1&category=Arrays&sortBy=latest

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

1 6 2

Your Output:

[-1, 1, 1]

Expected Output:

[-1, 1, 1]

Java (21) Start Timer

```java
import java.util.*;

class Solution {
    public ArrayList<Integer> prevSmaller(int[] arr) {

        Stack<Integer> st = new Stack<>();
        ArrayList<Integer> res = new ArrayList<>();

        for(int i = 0; i < arr.length; i++){

            while(!st.isEmpty() && st.peek() >= arr[i]){
                st.pop();
            }

            if(st.isEmpty()){
                res.add(-1);
            } else {
                res.add(st.peek());
            }

            st.push(arr[i]);
        }

        return res;
    }
}
```

Custom Input Compile & Run Submit

20°C Clear Search ENG IN 00:08 16-03-2026

Previous Greater Element | Practice

https://www.geeksforgeeks.org/problems/previous-greater-element/1?page=1&category=Arrays&sortBy=latest

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

10 4 2 20 40 12 30

Your Output:

[-1, 10, 4, -1, -1, 40, 40]

Expected Output:

[-1, 10, 4, -1, -1, 40, 40]

Java (21) Start Timer

```java
import java.util.*;

class Solution {
    public ArrayList<Integer> preGreaterEle(int[] arr) {

        Stack<Integer> st = new Stack<>();
        ArrayList<Integer> res = new ArrayList<>();

        for(int i = 0; i < arr.length; i++){

            while(!st.isEmpty() && st.peek() <= arr[i]){
                st.pop();
            }

            if(st.isEmpty()){
                res.add(-1);
            } else {
                res.add(st.peek());
            }

            st.push(arr[i]);
        }

        return res;
    }
}
```

Custom Input Compile & Run Submit

20°C Clear Search ENG IN 00:09 16-03-2026

Subarrays with First Element Minir

https://www.geeksforgeeks.org/problems/subarrays-with-first-element-minimum/1?page=1&category=Arrays&sortBy=latest

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

1 2 1

Your Output:

5

Expected Output:

5

Java (21) Start Timer

```java
class Solution {
    public int countSubarrays(int[] arr) {
        int n = arr.length;
        Stack<Integer> st = new Stack<>();
        int ans = 0;

        for(int i = n - 1; i >= 0; i--) {

            while(!st.isEmpty() && arr[st.peek()] >= arr[i]) {
                st.pop();
            }

            int nextSmaller = st.isEmpty() ? n : st.peek();

            ans += nextSmaller - i;

            st.push(i);
        }

        return ans;
    }
}
```

Custom Input Compile & Run Submit

Thunderstorm w... In effect

Search

ENG IN 00:13 16-03-2026

Find 132 Pattern in Array | Practice

https://www.geeksforgeeks.org/problems/find-132-pattern-in-array/1?page=1&category=Arrays&sortBy=latest

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

4 7 11 5 13 2

Your Output:

true

Expected Output:

true

Java (21) Start Timer

```java
import java.util.*;

class Solution {
    public boolean has132Pattern(int[] arr) {
        int n = arr.length;
        Stack<Integer> stack = new Stack<>();
        int third = Integer.MIN_VALUE;

        for (int i = n - 1; i >= 0; i--) {

            if (arr[i] < third) {
                return true;
            }

            while (!stack.isEmpty() && arr[i] > stack.peek()) {
                third = stack.pop();
            }

            stack.push(arr[i]);
        }

        return false;
    }
}
```

Custom Input Compile & Run Submit

20°C Clear Search ENG IN 00:18 16-03-2026

Maximum People Visible in a Line

https://www.geeksforgeeks.org/problems/maximum-people-visible-in-a-line/1?page=1&category=Arrays&sortBy=latest

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Java (21) Start Timer

```java
        while(!st.isEmpty() && arr[st.peek()] < arr[i]){
            st.pop();
        }

        if(st.isEmpty())
            left[i] = -1;
        else
            left[i] = st.peek();

        st.push(i);
    }

    st.clear();

    // Next greater or equal
    for(int i = n-1; i >= 0; i--){
        while(!st.isEmpty() && arr[st.peek()] < arr[i]){
            st.pop();
        }

        if(st.isEmpty())
            right[i] = n;
        else
            right[i] = st.peek();

        st.push(i);
    }

    int ans = 0;

    for(int i = 0; i < n; i++){
        ans = Math.max(ans, right[i] - left[i] - 1);
    }

    return ans;
}
}
```

Custom Input Compile & Run Submit

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

6 2 5 4 5 1 6

Your Output:

6

Expected Output:

6

20°C Clear Search ENG IN 00:21 16-03-2026

Unique K-Number Sum | Practice

https://www.geeksforgeeks.org/problems/combination-sum-iii--111703/1?page=1&category=Arrays&sortBy=latest

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Case 1

Input:

n =

9

k =

3

Your Output:

[[1, 2, 6],
[1, 3, 5],
[2, 3, 4]]

Expected Output:

[[1, 2, 6],
[1, 3, 5],
[2, 3, 4]]

Java (21) Start Timer

```java
import java.util.*;

class solution {

    public ArrayList<ArrayList<Integer>> combinationSum(int n, int k) {
        ArrayList<ArrayList<Integer>> res = new ArrayList<>();
        backtrack(1, n, k, new ArrayList<>(), res);
        return res;
    }

    void backtrack(int start, int target, int k, ArrayList<Integer> curr, ArrayList<ArrayLis

        if(target == 0 && curr.size() == k){
            res.add(new ArrayList<>(curr));
            return;
        }

        if(target < 0 || curr.size() > k){
            return;
        }

        for(int i = start; i <= 9; i++){
            curr.add(i);
            backtrack(i + 1, target - i, k, curr, res);
            curr.remove(curr.size() - 1);
        }
    }
}
```

Custom Input Compile & Run Submit

20°C Clear Search ENG IN 00:22 16-03-2026

Maximize the minimum difference

https://www.geeksforgeeks.org/problems/maximize-the-minimum-difference-between-k-elements/1?page=1&category=Arrays&sortBy=latest

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

2 6 2 5

k =

3

Your Output:

1

Expected Output:

1

Java (21) Start Timer

```java
class Solution {

    public static boolean canPlace(int[] arr, int k, int dist) {
        int count = 1;
        int last = arr[0];

        for (int i = 1; i < arr.length; i++) {
            if (arr[i] - last >= dist) {
                count++;
                last = arr[i];
            }
            if (count >= k) return true;
        }

        return false;
    }

    public static int maxMinDiff(int[] arr, int k) {
        Arrays.sort(arr);

        int low = 0;
        int high = arr[arr.length - 1] - arr[0];
        int ans = 0;

        while (low <= high) {
            int mid = low + (high - low) / 2;

            if (canPlace(arr, k, mid)) {
                ans = mid;
                low = mid + 1;
            } else {
                high = mid - 1;
            }
        }

        return ans;
    }
}
```

Custom Input Compile & Run Submit

20°C Clear Search ENG IN 00:23 16-03-2026

Count elements less than or equal

https://www.geeksforgeeks.org/problems/count-elements-less-than-or-equal-to-k-in-a-sorted-rotated-array/1?page=1&category=Arrays&sortBy=latest

Search... Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

6 10 12 15 2 4 5

x =

14

Your Output:

6

Expected Output:

6

Java (21) Start Timer

```java
            } else {
                r = mid - 1;
            }
        }

        return ans >= 0 ? ans - (l - (r - l + 1)) : -1;
    }

    int countLessEqual(int[] arr, int x) {
        int n = arr.length;

        int pivot = findPivot(arr);

        int count = 0;

        // left part
        int l = 0, r = pivot - 1;
        while (l <= r) {
            int mid = (l + r) / 2;
            if (arr[mid] <= x) l = mid + 1;
            else r = mid - 1;
        }
        count += l;

        // right part
        l = pivot;
        r = n - 1;
        int start = pivot;
        while (l <= r) {
            int mid = (l + r) / 2;
            if (arr[mid] <= x) l = mid + 1;
            else r = mid - 1;
        }
        count += (l - start);

        return count;
    }
}
```

Custom Input Compile & Run Submit

20°C Clear Search ENG IN 00:24 16-03-2026