



PES
UNIVERSITY

DATA STRUCTURES AND ITS APPLICATIONS

**BST Implementation using Dynamic
Allocation : Insertion**

Shylaja S S & Kusuma K V

Department of Computer Science
& Engineering

DATA STRUCTURES AND ITS APPLICATIONS

BST Implementation using Dynamic Allocation: Insertion

Shylaja S S

Department of Computer Science & Engineering

DATA STRUCTURES AND ITS APPLICATIONS

Binary Search Tree – An Application of Binary Tree



Background

Problem : find a target key in a list of elements

Sequential: Potentially enumerate every key

Ordered List: Searching can be done on $\log n$

Frequent insertions and deletions : Ordered List is much slower

Solution: Binary Trees provide an excellent solution to this by organizing every element in the list as a node in the tree

DATA STRUCTURES AND ITS APPLICATIONS

Binary Search Tree: Definition



A Binary Search Tree is a binary tree which has the following properties:


- all the elements in the left subtree of a node **n** are less than the contents of node **n**
- all the elements in the right subtree of a node **n** are greater than or equal to the contents of node **n**

DATA STRUCTURES AND ITS APPLICATIONS

Binary Search Tree – An Application of Binary Tree



A Binary Search Tree with the nodes inserted in the order:
5, 3, 6, 4, 2, 8, 1, 7, 9



DATA STRUCTURES AND ITS APPLICATIONS

Binary Search Tree - Implementation



Linked implementation

Here every node will have its own **info** along with the **links to left child** and **right child**

```
typedef struct tree_linked  
{  
    int info;  
    struct tree_linked *left,*right;  
}NODE;
```



`NODE *root=NULL;` //root points to Root of the tree and initially it is null

DATA STRUCTURES AND ITS APPLICATIONS

Binary Search Tree - Implementation




Linked implementation: 5, 3, 7, 8, 1, 4



DATA STRUCTURES AND ITS APPLICATIONS

Binary Search Tree - Implementation


Linked implementation: 5, 3, 7, 8, 1, 4



DATA STRUCTURES AND ITS APPLICATIONS

Binary Search Tree - Implementation

Linked implementation: 5, 3, 7, 8, 1, 4



1. Which of the following is the defining property of a Binary Search Tree (BST)?

- A) All left child nodes have keys greater than their parent.
- B) All right child nodes have keys smaller than their parent.
- C) The left subtree of a node contains only nodes with keys less than the node's key, and the right subtree contains only nodes with keys greater.
- D) Nodes are always stored in level-order.

1. Which of the following is the defining property of a Binary Search Tree (BST)?

- A) All left child nodes have keys greater than their parent.
- B) All right child nodes have keys smaller than their parent.
- C) The left subtree of a node contains only nodes with keys less than the node's key, and the right subtree contains only nodes with keys greater.
- D) Nodes are always stored in level-order.

2. When inserting a new key into a BST:

- A) It always becomes a leaf node.
- B) It always replaces the root if smaller.
- C) It is inserted at the leftmost or rightmost node directly.
- D) It must be inserted only in the left subtree.

2. When inserting a new key into a BST:

- A) It always becomes a leaf node.
- B) It always replaces the root if smaller.
- C) It is inserted at the leftmost or rightmost node directly.
- D) It must be inserted only in the left subtree.

3. If the node to be deleted in a BST has two children, how is deletion handled?

- A) Node is simply removed, and its children are discarded.
- B) Replace the node with its inorder predecessor or inorder successor.
- C) Replace the node with the root node.
- D) Deletion is not possible for such a node.

3. If the node to be deleted in a BST has two children, how is deletion handled?

- A) Node is simply removed, and its children are discarded.
- B) Replace the node with its inorder predecessor or inorder successor.**
- C) Replace the node with the root node.
- D) Deletion is not possible for such a node.

4. Which of the following is NOT a typical application of BSTs?

- A) Searching
- B) Sorting
- C) Priority Queue implementation
- D) Symbol Table in Compilers

4. Which of the following is NOT a typical application of BSTs?

- A) Searching
- B) Sorting
- C) Priority Queue implementation**
- D) Symbol Table in Compilers

5. Which of the following is a balanced version of a BST?

- A) AVL Tree
- B) Red-Black Tree
- C) B-Tree
- D) All of the above

5. Which of the following is a balanced version of a BST?

- A) AVL Tree
- B) Red-Black Tree
- C) B-Tree
- D) All of the above**



THANK YOU

Shylaja S S

Department of Computer Science
& Engineering

shylaja.sharath@pes.edu

+91 9449867804