







Reminders

- **Representatives:** nomination until today COB
- Next week:
 - Drop-in session for LP
 - LP Quiz on **Friday**

Linear Programming 4

COMP4691 / 8691



LP Topic Outline

- LP Introduction
- Modelling and solving
- Feasible region and convexity
- **Simplex algorithm**
 - Alternative Simplex algorithm
 - Degeneracy
 - Complexity
 - Bootstrapping
 - BFS forms
- Relaxations and approximations
- The dual of a linear program




Solving an LP

Simplex algorithm: hop from vertex to neighbouring vertex so long as there is an improvement in objective

1947 George Dantzig (not polynomial time but performance typically good)

Interior point algorithm: traverse the interior of the feasible region following gradient of objective while avoiding the boundaries

1947 John von Neumann (not polynomial time, and typically worse than simplex)



Will explore recent (polynomial time) version in convex optimisation topic

Simplex Algorithm Forms

Many different mathematically equivalent formulations. Most work with LPs in following form:

$$\min_{x \in \mathbb{R}^n} c^T x$$

$$\text{s.t. } Ax = b$$

$$\underline{x \geq 0}$$

- **Standard** Simplex Algorithm: ~~tableau manipulation~~
- **Revised** Simplex Algorithm: matrix manipulation

We'll initially break convention in order to give a better geometric intuition, by focusing on solving LPs in this form:



$$\min_{x \in \mathbb{R}^n} c^T x$$

$$\text{s.t. } \underline{Ax \leq b}$$

- **Alternative** Simplex Algorithm: matrix manipulation

SINGLE
WFMOST
INFES (4-18 SOL)
UNBOUNDED

Simplex Algorithm




Infinite number of optimal solutions: still at least one of them is on a vertex!

LPs: if the **problem** is feasible and bounded, then there exists at least one extreme point (vertex of polyhedron) that is optimal.

Simplex insight: if we want an optimal solution, let's "just" search the vertices!

Finding Vertices

How can we (algorithmically) find vertices?



$$\min_{x \in \mathbb{R}^n} c^T x$$

$$\text{s.t. } Ax \leq b$$

A vertex in \mathbb{R}^n is defined by the intersection of n linearly independent hyperplanes (associated with n equality or active inequality constraints)

Will all constraint combinations form vertices of the feasible region?

$$m = 4$$

$$n = 2$$

An Approach to Finding Vertices

$$\min_{x \in \mathbb{R}^n} c^T x$$

$$\text{s.t. } Ax \leq b$$

① \rightarrow $A = \begin{bmatrix} 1 & 4 \\ 2 & 5 \\ 3 & 6 \end{bmatrix}$

$$\bar{A} = \begin{bmatrix} 1 & 4 \\ 3 & 6 \end{bmatrix}$$

$$b = \begin{bmatrix} 1 \\ 1 \end{bmatrix} \leftarrow \begin{bmatrix} 1 \\ 1 \end{bmatrix} - \bar{b}$$

1. Pick n linearly independent constraints

2. Find their intercept by solving the $n \times n$ system:

$$\bar{A}x^* = \bar{b}$$

\bar{A}, \bar{b} have rows for non-active constraints removed

3. Check if candidate x^* is a vertex of the feasible region:

$m > n$ $\left[Ax^* \leq b \right]$
 6Q?

SUBSET OF n THAT IS AN GA


IF FEAS $\rightarrow c^T x^*$

How many Vertices are there?

Can we just enumerate them?

This approach requires checking **m choose n** combinations.

Even if we could limit ourselves to true vertices, their number can still **grow exponentially** in the problem size:



Brute forcing it will lead to sorrow!

Simplex Algorithm


The **Simplex algorithm** is smarter than this. It moves from **vertex to vertex**, picking a new neighbour (sharing all but one constraint) each time that improves the objective function.

Assuming there are no “degenerate” vertices (for later):

- **If there are no neighbouring vertices that improve the objective, then our current vertex is optimal** —
- If we only move to vertices that improve the objective, we will converge to an optimal solution in a finite number of steps.

Simplex Algorithm

Min



ASSUME WE
HAVE A
VERTEX
TO START

3-D Example

“Alternative” Simplex Overview

$$\min_{x \in \mathbb{R}^n} c^\top x$$

$$\text{s.t. } Ax \leq b$$

$$A \in \mathbb{R}^{m \times n}$$

$$A_{i,j} \in \mathbb{R} \quad \text{element}$$

$$A_i \in \mathbb{R}^{1 \times n} \quad \text{i-th row}$$

$$A_{:j} \in \mathbb{R}^{m \times 1} \quad \text{j-th column}$$

At the k -th iteration, **a vertex is represented by S_k** , the **active constraint set**:

$$S_k \subseteq \{1, \dots, m\} \quad |S_k| = n$$

INDEXES OF ACTIVE CONSTRAINTS

Find a constraint to leave S_k and a new one to enter to get S_{k+1} , i.e., the vertex at the next iteration. This is called **pivoting**.

But how do we do this so:

- the objective improves? \triangleleft
- the new active constraint set is a vertex of the feasible region? \triangleleft

Vertex Position

Active constraint set for each iteration k : $S_k \subseteq \{1, \dots, m\}$

$$|S_k| = n$$

rows in A
with index
 S_k

Vertex position:

$$Ax \leq b$$

$$\bar{A}x_k \equiv \bar{b}$$

$n \times n$ system
to solve

Take rows of current
active constraint set

Zero slack when
active so equality

Vertex Position from 3-D Example

REAL WORLD 4-MOST OF TIME

$A =$

-0.80804753	-0.58025801	0.10178351
-0.50084776	-0.71380377	0.48952585
-0.08048842	-0.09915476	0.99181145
-0.09627039	0.0453119	0.99432325
-0.17546873	0.20627031	0.96263349
-0.75252348	0.64080679	-0.1519043
-0.95336509	0.1294336	-0.27265716
-0.26776844	-0.72117537	-0.63891017
-0.34649301	-0.61552572	-0.70786339
-0.49174464	-0.7193774	0.49059495
-0.19321021	-0.77477372	-0.60199296
0.04926607	-0.39601576	0.91692108
0.98859793	0.01616362	0.14970967
0.77713436	0.18456472	0.60166258
-0.01748661	0.08323177	0.99637675
0.07115179	-0.40672514	0.91077548
0.88839614	-0.24955757	0.38532227
0.99100763	-0.03015041	0.13036372
-0.1961358	0.78581196	0.58654082
-0.19422084	0.83695108	0.51165545
-0.22796361	0.91862208	0.32274759
-0.62808508	0.74864495	-0.21222581
-0.21458624	0.75690502	-0.6172905
-0.11244072	0.65154088	-0.75023437
-0.06446069	-0.79907358	-0.59776777
0.55077285	0.32070059	-0.77058434
0.55246085	0.3186858	-0.77021194
0.57675749	-0.43490228	-0.6915279
0.41864392	-0.72648567	0.54493666
0.94824499	0.31748062	-0.00612433
0.97529268	-0.07944221	-0.20613866
-0.02390716	0.99852639	-0.04871828

\checkmark SPARSE

$c = \begin{bmatrix} 0.5 \\ 0.5 \\ 0.0 \end{bmatrix}$

$S_k = \{15, 16, 28\}$

$\bar{A} = \begin{bmatrix} 0.07115179 & -0.40672514 & 0.91077548 \\ 0.88839614 & -0.24955757 & 0.38532227 \\ 0.41864392 & -0.72648567 & 0.54493666 \end{bmatrix}$

$\bar{b} = \begin{bmatrix} 0.68881921 \\ 1.01392535 \\ 0.611702 \end{bmatrix}$

Solve:

$\bar{A}x_k = \bar{b}$

$x_k = \begin{bmatrix} 0.86530995 \\ 0.26049233 \\ 0.80502786 \end{bmatrix}$

For most real, high-dimensional problems this is actually sparse.

Edges Lead to Neighbours

If we move along an edge we will sooner or later reach another vertex (assuming a bounded problem).

Edges (lines) connected to our current vertex are represented by a \mathbb{R}^2 subset of **$n - 1$ constraints**:

$$S_k \setminus \{u\}$$


Example: $S_k = \{2, 4\}$

1: $y \geq -x + 2$

2: $2y \geq x - 1$

3: $y \leq x + 1$

4: $y \leq -2x + 8$



Valuing Edges 3-D Example

Edge

$$\bar{A}d_u = 1e_u$$

$$\mu_u = d_u^\top c$$


$u = 15$: $d_u = \begin{bmatrix} -0.40992586 \\ 0.91933208 \\ 1.54053601 \end{bmatrix}$

$$\mu_u = 0.255$$

$u = 16$: $d_u = \begin{bmatrix} 1.25316418 \\ 0.97546654 \\ 0.33771428 \end{bmatrix}$

$$\mu_u = 1.114$$

GOOD OPTIONS
TO WALK



Valuing All Edges

Edge

$$\bar{A}d_u = 1e_u$$

$$\mu_u = d_u^T c$$

$$\bar{A}x_k = \bar{b}$$

$$d_u$$

$$\bar{A}x^* = \bar{b} + 1e_u$$

For all active constraints at once:


$$\bar{D} \in \mathbb{R}^{n \times n} \quad \mu \in \mathbb{R}^n$$

$$\bar{A}D = I \implies D = \bar{A}^{-1}$$


$$\mu = D^T c = \bar{A}^{-T} c$$

$$\implies \bar{A}^T \mu = c$$

SYS OF
LIN EQ



Valuing All Edges 3-D Example




3-D Example

Pivoting

The act of picking a **constraint to remove** from the active set (which edge to move along), and then picking a **constraint to replace it**.

$$\bar{A}^T \mu = c$$

For a problem in form, any elements of μ that are positive represent constraints we could kick out of S_k .


$$\begin{array}{ll} \min_{x \in \mathbb{R}^n} & c^T x \\ \text{s.t.} & Ax \leq b \end{array}$$

What if none are positive?

- We have **the optimal value**, so can stop.

→ What if max?
(conventions may vary)

When there are multiple, then **pivot selection rules** are utilised, which are important for guaranteeing convergence when there is **degeneracy**.

Following Edge to Neighbour

Edge

$$Ax \leq b$$

FEAS POINT
DECISION TO REMOVE PLUS

$$-d_u$$

$$\bar{A}d_u = 1e_u$$

$$\bar{A}x_k = \bar{b}$$

$$s_v = b_v - A_v x_k$$

Slack at k-th vertex

$$r_v = -A_v d_u$$

Rate at which moving along edge **reduces slack**

Non-active constraints

$$s = \tilde{b} - \tilde{A}x_k$$

SLACK & INAC

$$r = -\tilde{A}d_u$$

RATE & INAC

What if no r elements are strictly positive?

Candidates:

$$\arg \min_{v \notin S_k | \underline{r_v} > 0} \frac{s_v}{r_v}$$

Could move along edge indefinitely = **unbounded problem**

$$A_v$$

$v \notin S_k$

$$u \in S_k$$

$$A_u$$

$$A_v$$

$$A_w$$

$$-d_u$$

Following Edge 3D Example

Edge

$-d_u$

$$\bar{A}d_u = 1e_u$$

$$\bar{A}x_k = \bar{b}$$

$$s = \tilde{b} - \tilde{A}x_k$$

$$r = -\tilde{A}d_u$$

$$u = 15$$

$$s = \begin{bmatrix} 0.56940747 \\ 0.29707086 \\ \vdots \end{bmatrix}$$

$$r = \begin{bmatrix} 0.04540906 \\ -0.30321995 \\ \vdots \end{bmatrix}$$

$$u \in S_k$$

$$A_u$$

$$A_v$$

$$v \notin S_k$$

$$\arg \min_{v \notin S_k | r_v > 0} \frac{s_v}{r_v}$$

$$= \{17, 24, 27, 30\}$$

DEGENERACY

3-D Example

Alternative Simplex Summary

Current active constraint set: S_k

Each is a system of linear equations to be solved

Vertex position: $\bar{A}x = \bar{b}$ ✓

LU DECOMP.

Pick leaving constraint:
(otherwise optimal)

$\bar{A}^\top \mu = c$ ✓ $\rightarrow \textcircled{u} \in \{u | \underline{\mu_u} > 0\}$

Pick joining constraint:
(otherwise unbounded)

$\bar{A}d_u = 1e_u$ ✓ $\rightarrow \underline{s} = \tilde{b} - \tilde{A}x$
 $\underline{r} = -\tilde{A}d_u \rightarrow \textcircled{v} \in \arg \min_{\underline{v \notin S_k | r_v > 0}} \underline{s_v} / \underline{r_v}$

Next active constraint set: $S_{k+1} := (\underline{S_k} \setminus \{\underline{u}\}) \cup \{\underline{v}\}$

Degenerate Vertices

Multiple **coincident vertices**. μ indicates it is worth pivoting, but we don't actually move anywhere because we immediately hit another constraint.


Why does it matter?

- It can slow down progress ↗
- Certain pivot rules can enter into cycles and never converge

$S_1 = \{1, 2\} \rightarrow \{2, 3\} \rightarrow \{1, 3\} \rightarrow \{3, 4\} \rightarrow \{4, 5\}$

The **pivot rule is critical**, not just to avoid cycling but to achieve good performance, some options for selecting between candidates (where $\mu_u > 0$):

- The most positive μ_u ↗
- Randomly (eventually avoids cycling) ↗
- Try from smallest index (avoids cycling) ↗



Finding a Starting Vertex

$$\min_{x \in \mathbb{R}^n} c^T x$$

$$\text{s.t. } Ax \leq b$$

Solve a modified LP, with obvious starting vertex, whose optimal solution is a vertex of the original LP.

Call this new LP **the feasibility problem**.

Finding this first feasible point, potentially as difficult as then finding the optimal.

Relax constraints by introducing **slack variables**:

$$\min_{x \in \mathbb{R}^n, s \in \mathbb{R}^m} 1^T s$$

$$\text{s.t. } Ax - s \leq b$$

$$s \geq 0$$

If $s^* = 0$, then $Ax^* \leq b$ i.e., vertex of the original!

Start the active constraint set for the original LP with a subset of n constraints where:

$$A_i x^* = b_i$$

Optimal: x^*, s^*

→ What if $s^* \neq 0$? Original problem is infeasible!

$n+m$

Act. CONST

Break the Chicken-Egg Cycle

WHEN $s^* = \vec{0}$ WHY x^* IS A VERTEX OF $AX \leq b$

We still need a starting vertex for the **feasibility problem...**

regarding A of the original problem

FGAS PR. w/ ∞ OPT SOL

Feasibility problem has $n + m$ **variables**,
 $2m$ **constraints**.

($m > n$ most of the time)

$$\min_{x \in \mathbb{R}^n, s \in \mathbb{R}^m} 1^T s$$

$$\text{s.t. } Ax - s \leq b$$

$$s \geq 0$$

\mathbb{R}^{n+m}
 $n+m$ ACT

Pick n linearly independent original constraints to be active.

Assume the first n :

$$\forall i \in \{1, \dots, n\}$$

$$A_i x = b_i \implies A_i x - s_i \leq b_i$$

n ACTIVE CONST

$$s_i \geq 0 \text{ active}$$

ASSIGN

$$\text{Solve: } A_{1:n} x^* = b_{1:n}$$

$$\forall i \in \{n+1, \dots, m\}$$

BUILDING
 S_0 FOR FEAS. PR
 remaining constr of the original LP

$2n$ active constraints, need $m - n$ more for a vertex

	$s_i \geq 0$	$A_i x - s_i \leq b_i$
$A_i x^* > b_i$	inactive ($s_i > 0$)	active
$A_i x^* \leq b_i$	active	inactive

Reminders

- **Representatives:** nomination until today COB
- Next week:
 - Drop-in session for LP
 - LP Quiz on **Friday**

Complexity

Simplex Algorithm

No known pivot rule that can in general avoid visiting an exponential number of vertices.

As far as we know the **simplex algorithm** is worst-case exponential.

In practice for most problems it performs very well: often low-order polynomial number of pivots.

Ellipsoidal Algorithm

1979 Leonid Khachiyan proved that an ellipsoidal algorithm can solve any LP in polynomial time.

The problem of **solving a Linear Program** is polynomial!

In practice this algorithm performs poorly: higher degree polynomial for typical problems.

Interior-Point Algorithm

1947 John von Neumann (not polynomial time)

1984 Narendra Karmarkar developed an interior-point algorithm, Karmarkar's algorithm, for LPs that is polynomial time.

In practice this and more modern interior-point algorithms are competitive with simplex and don't have the worst-case exponential performance!

These two don't work with vertices, so avoid their combinatorial nature

Simplex Formulations

$$\min_{x \in \mathbb{R}^n} c^T x$$

$$\text{s.t. } Ax = b$$

$$x \geq 0$$

($m < n$ most of the time)

- **Standard** Simplex Algorithm: tableau manipulation
- **Revised** Simplex Algorithm: matrix manipulation

Work with **“basic” variables** in the “basis” set B_k , $|B_k| = m$

- B_k maps to a set of n active constraints
- All **m equalities always active**
- **Need $n - m$ inequalities to be active** (i.e., $x_i = 0$)
- B_k represents the remaining set of $n - (n - m) = m$ vars
 - only variables in B_k can be non-zero (inactive constr)

$$\min_{x \in \mathbb{R}^n} c^T x$$

$$\text{s.t. } Ax \leq b$$

- ✓ **“Alternative”** Simplex Algorithm: matrix manipulation

Work with **active constraint** set S_k , $|S_k| = n$

Basic Feasible Solution (BFS)

Basic feasible solution (BFS): just another way of saying a vertex of the feasible polyhedron.

Basis:

$$\rightarrow B_k \subseteq \{1, \dots, n\}, \quad |B_k| = m$$

Basic variables:

$$x_j \geq 0 \quad \forall j \in B_k$$


Non-basic variables:

$$x_j = 0 \quad \forall j \notin B_k$$

$\leftarrow n - m$ ACT CONS
m ACT CONS $Ax = b$

Visualising New BFS Form

$$\begin{aligned} \min_{x \in \mathbb{R}^n} \quad & c^T x \\ \text{s.t.} \quad & Ax = b \\ & \underline{x} \leq x \leq \overline{x} \end{aligned}$$




Basis: $|B_k| = m$

Basic variables: $x_j \geq 0 \quad \forall j \in B_k$

Non-basic variables: $x_j = 0 \quad \forall j \notin B_k$

Revised Simplex Summary



Standard Simplex

Put coefficients of problem into a “**tableau**” (~a matrix), which is mutated by doing row operations to move from one BFS to the next.

Commonly taught, you should be aware it exists but we'll skip over it. It is OK for working small problems by hand, but implementation is less efficient than the matrix-based simplex formulations.

$$\begin{array}{ll}\min_{x,z} & z \\ \text{s.t.} & z - x_1 - 3x_2 = 0\end{array}$$

$$x_1 + 2x_2 - 4x_3 + x_4 = 5$$

$$x_1 + 3x_3 - 2x_4 = 6$$

$$x \geq 0$$



z	x_1	x_2	x_3	x_4	b
1	-1	-3	0	0	0
0	1	2	-4	1	5
0	1	0	3	-2	6

Next

- LP Introduction
 - Modelling and solving
 - Feasible region and convexity
 - Simplex algorithm
 - **Relaxations and approximations**
 - Approximations
 - Convex relaxations
 - Battery scheduling example
 - Optimality gap
 - **The dual of a linear program**
- 