

```
create table Customers(  
  c_id int PRIMARY KEY,  
  Name varchar(50),  
  city varchar(50)  
);
```

```
create table Orders(  
  order_id int PRIMARY KEY,  
  c_id int,  
  order_date date,  
  amount decimal(10,2),  
  FOREIGN KEY (c_id) references Customers(c_id)  
);
```

```
create table Products(  
  productID int primary key,  
  name varchar(50),  
  price decimal(10,2)  
);
```

```
insert into Customers values  
(1,"Alice","Delhi"),  
(2,"Bob","Mumbai"),  
(3,"Eve","Benglure"),  
(4,"Alex","NY"),  
(5,"Daisy","New Jersy");
```

```
insert into Products values
```

```
(1,"Laptop",70000.00),  
(2,"Mobile",25000.00),  
(3,"Tablet",10000.00),  
(4,"Keyboard",1500.00),  
(5,"Monitor",80000.00);
```

```
insert into Orders values  
(101,1,"2024-01-10",250.00),  
(102,2,"2023-05-11",5000.00),  
(103,3,"2022-25-12",2000.00),  
(104,4,"2024-01-10",25000.00),  
(105,5,"2025-14-03",30000.00)
```

```
select customers.name, orders.order_id,orders.amount  
from Customers  
inner join orders on customers.c_id=Orders.c_id;
```

```
select Customers.name, orders.order_id  
from customers  
left join orders on Customers.c_id = Orders.c_id;
```

```
select Customers.name  
from Customers  
left join orders on Customers.c_id = Orders.c_id  
where orders.order_id is NULL;
```

```
select avg(amount) from Orders;  
select * from Orders  
where amount >( select avg(amount) from Orders);
```

```
select * from Products where price = (select max(price) from products);
```

```
with customerTotal as (
```

```
    select c_id, sum(amount) from Orders group by c_id
```

```
)
```

```
select * from customerTotal
```