

MySQL Shell 8.0.43

Copyright (c) 2016, 2025, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates.

Other names may be trademarks of their respective owners.

Type '\help' or '?' for help; '\quit' to exit.

MySQL JS > sql

sql is not defined (ReferenceError)

MySQL JS > \sql

Switching to SQL mode... Commands end with ;

MySQL SQL > \connect root@localhost

Creating a session to 'root@localhost'

Please provide the password for 'root@localhost': *****

MySQL Error 2005: No such host is known 'localhost'

MySQL SQL > \connect root@localhost

Creating a session to 'root@localhost'

Fetching global names for auto-completion... Press ^C to stop.

Your MySQL connection id is 56 (X protocol)

Server version: 8.0.43 MySQL Community Server - GPL

No default schema selected; type \use <schema> to set one.

MySQL localhost:33060+ ssl SQL > show databases

-> show databases;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'show databases' at line 2

MySQL localhost:33060+ ssl SQL > show databases;

+-----+

| Database |

+-----+

| collage |

| information_schema |

```
| mysql      |
| performance_schema |
| rrgi       |
| rrgi1      |
| rrgroup    |
| rsb        |
| sys        |
```

```
+-----+
```

9 rows in set (0.0013 sec)

MySQL localhost:33060+ ssl SQL > use rrgroup

Default schema set to `rrgroup`.

Fetching global names, object names from `rrgroup` for auto-completion... Press ^C to stop.

MySQL localhost:33060+ ssl rrgroup SQL > use rrgroup;

Default schema set to `rrgroup`.

Fetching global names, object names from `rrgroup` for auto-completion... Press ^C to stop.

MySQL localhost:33060+ ssl rrgroup SQL > show tables;

```
+-----+
```

```
| Tables_in_rrgroup |
```

```
+-----+
```

```
| employeeedetails |
```

```
| studentdetails   |
```

```
+-----+
```

2 rows in set (0.0023 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails;

```
+----+-----+-----+-----+-----+-----+
```

```
| eid | ename  | ecity  | edepartment | eage | esalary |
```

```
+----+-----+-----+-----+-----+-----+
```

```
| 101 | sakshi | lucknow | CSE        | 21 | 500000 |
```

```
| 102 | muskan | varanshi | biotech    | 19 | 50000  |
```

```
| 103 | arkshika | sultanpur | CSE       | 22 | 55000  |
```

```
| 104 | nikku  | gorkhpur | IT         | 21 | 45000  |
```

+-----+-----+-----+-----+-----+-----+

4 rows in set (0.0015 sec)

MySQL localhost:33060+ ssl rrgroup SQL > update employeeedetails set esalary = 500000 where
eid = 102 ;

Query OK, 1 row affected (0.0357 sec)

Rows matched: 1 Changed: 1 Warnings: 0

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails;

+-----+-----+-----+-----+-----+-----+

| eid | ename | ecity | edepartment | eage | esalary |

+-----+-----+-----+-----+-----+-----+

| 101 | sakshi | lucknow | CSE | 21 | 500000 |

| 102 | muskan | varanshi | biotech | 19 | 500000 |

| 103 | arkshika | sultanpur | CSE | 22 | 55000 |

| 104 | nikku | gorkhpur | IT | 21 | 45000 |

+-----+-----+-----+-----+-----+-----+

4 rows in set (0.0008 sec)

MySQL localhost:33060+ ssl rrgroup SQL > insert (eid,ename,ecity,edepartment,eage,esalary)
values (105,"teja","Amethi" ,
"CSE",22,20000),(106,"ayush","lucknow","IT",19,30000),(107,"sona","mau","civil",22,75000),(108,"d
ivyanshu","kanpur","CSE",23,55000);

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your
MySQL server version for the right syntax to use near '(eid,ename,ecity,edepartment,eage,esalary)
values (105,"teja","Amethi" , "CSE",2' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > insert into employeeedeatils
(eid,ename,ecity,edepartment,eage,esalary) values (105,"teja","Amethi" ,
"CSE",22,20000),(106,"ayush","lucknow","IT",19,30000),(107,"sona","mau","civil",22,75000),(108,"d
ivyanshu","kanpur","CSE",23,55000);

ERROR: 1146: Table 'rrgroup.employeeedeatils' doesn't exist

MySQL localhost:33060+ ssl rrgroup SQL > insert into employeeedetails
(eid,ename,ecity,edepartment,eage,esalary) values (105,"teja","Amethi" ,
"CSE",22,20000),(106,"ayush","lucknow","IT",19,30000),(107,"sona","mau","civil",22,75000),(108,"d
ivyanshu","kanpur","CSE",23,55000);

Query OK, 4 rows affected (0.0329 sec)

Records: 4 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails;

eid	ename	ecity	edepartment	eage	esalary
101	sakshi	lucknow	CSE	21	500000
102	muskan	varanshi	biotech	19	500000
103	arkshika	sultanpur	CSE	22	55000
104	nikku	gorkhpur	IT	21	45000
105	teja	Amethi	CSE	22	20000
106	ayush	lucknow	IT	19	30000
107	sona	mau	civil	22	75000
108	divyanshu	kanpur	CSE	23	55000

8 rows in set (0.0007 sec)

MySQL localhost:33060+ ssl rrgroup SQL > delete from employeeedetails where eid=107;

Query OK, 1 row affected (0.0318 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails;

eid	ename	ecity	edepartment	eage	esalary
101	sakshi	lucknow	CSE	21	500000
102	muskan	varanshi	biotech	19	500000
103	arkshika	sultanpur	CSE	22	55000
104	nikku	gorkhpur	IT	21	45000
105	teja	Amethi	CSE	22	20000
106	ayush	lucknow	IT	19	30000
108	divyanshu	kanpur	CSE	23	55000

7 rows in set (0.0007 sec)

MySQL localhost:33060+ ssl rrgroup SQL > update employeeedetails set esalary = 250000 where eid=105;

Query OK, 1 row affected (0.0309 sec)

Rows matched: 1 Changed: 1 Warnings: 0

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails ;

```
+-----+-----+-----+-----+-----+-----+
| eid | ename  | ecity  | edepartment | eage | esalary |
+-----+-----+-----+-----+-----+-----+
| 101 | sakshi  | lucknow | CSE        | 21 | 500000 |
| 102 | muskan  | varanshi | biotech    | 19 | 500000 |
| 103 | arkshika | sultanpur | CSE        | 22 | 55000 |
| 104 | nikku   | gorkhpur | IT         | 21 | 45000 |
| 105 | teja    | Amethi  | CSE        | 22 | 250000 |
| 106 | ayush   | lucknow | IT         | 19 | 30000 |
| 108 | divyanshu | kanpur  | CSE        | 23 | 55000 |
+-----+-----+-----+-----+-----+-----+
```

7 rows in set (0.0015 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where esalary>50,000;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ',000' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where esalary>50,000 ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near ',000' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where esalary >50000;

```
+-----+-----+-----+-----+-----+-----+
| eid | ename  | ecity  | edepartment | eage | esalary |
+-----+-----+-----+-----+-----+-----+
| 101 | sakshi  | lucknow | CSE        | 21 | 500000 |
| 102 | muskan  | varanshi | biotech    | 19 | 500000 |
| 103 | arkshika | sultanpur | CSE        | 22 | 55000 |
| 105 | teja    | Amethi  | CSE        | 22 | 250000 |

```

```
| 108 | divyanshu | kanpur | CSE | 23 | 55000 |
```

```
+-----+-----+-----+-----+-----+-----+
```

5 rows in set (0.0010 sec)

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where edepartment = "IT" ;
```

```
+-----+-----+-----+-----+-----+-----+
```

```
| eid | ename | ecity | edepartment | eage | esalary |
```

```
+-----+-----+-----+-----+-----+-----+
```

```
| 104 | nikku | gorkhpur | IT | 21 | 45000 |
```

```
| 106 | ayush | lucknow | IT | 19 | 30000 |
```

```
+-----+-----+-----+-----+-----+-----+
```

2 rows in set (0.0008 sec)

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where ecity = "lucknow";
```

```
+-----+-----+-----+-----+-----+-----+
```

```
| eid | ename | ecity | edepartment | eage | esalary |
```

```
+-----+-----+-----+-----+-----+-----+
```

```
| 101 | sakshi | lucknow | CSE | 21 | 500000 |
```

```
| 106 | ayush | lucknow | IT | 19 | 30000 |
```

```
+-----+-----+-----+-----+-----+-----+
```

2 rows in set (0.0009 sec)

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where ename starts with = A%";
```

```
"> select * from employeeedetails where ename like 'A%';
```

```
"> select * from employeeedetails where ename like '%a';
```

```
">
```

```
">
```

```
"> select * from employeeedetails where edepartment = "IT";
```

```
"> select * from employeeedetails where edepartment = "IT";
```

```
"> "
```

```
-> ^C
```

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where ename like '%a';
```

```
+-----+-----+-----+-----+-----+-----+
```

eid	ename	ecity	edepartment	eage	esalary
-----	-------	-------	-------------	------	---------

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

103	arkshika	sultanpur	CSE	22	55000
-----	----------	-----------	-----	----	-------

105	teja	Amethi	CSE	22	250000
-----	------	--------	-----	----	--------

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

2 rows in set (0.0010 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeedetails where ename like 'a%'

-> ^C

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeedetails where ename like '%a' ;

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

eid	ename	ecity	edepartment	eage	esalary
-----	-------	-------	-------------	------	---------

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

103	arkshika	sultanpur	CSE	22	55000
-----	----------	-----------	-----	----	-------

105	teja	Amethi	CSE	22	250000
-----	------	--------	-----	----	--------

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

2 rows in set (0.0007 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeedetails where ename like '%a' ;

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

eid	ename	ecity	edepartment	eage	esalary
-----	-------	-------	-------------	------	---------

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

103	arkshika	sultanpur	CSE	22	55000
-----	----------	-----------	-----	----	-------

105	teja	Amethi	CSE	22	250000
-----	------	--------	-----	----	--------

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

2 rows in set (0.0008 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeedetails where ename like 'A%' ;

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

eid	ename	ecity	edepartment	eage	esalary
-----	-------	-------	-------------	------	---------

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

103	arkshika	sultanpur	CSE	22	55000
-----	----------	-----------	-----	----	-------

106	ayush	lucknow	IT	19	30000
-----	-------	---------	----	----	-------

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

2 rows in set (0.0008 sec)

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where esalary(40000 ,60000);
```

ERROR: 1305: FUNCTION rrgroup.esalary does not exist

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where esalary 40000 , 60000 ;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '40000 , 60000' at line 1

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where esalary 40000 , 60000 ;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '40000 , 60000' at line 1

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where esalary in ( 40000 , 60000) ;
```

Empty set (0.0008 sec)

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where esalary between 40000 and 60000 ;
```

```
+----+-----+-----+-----+----+-----+
| eid | ename  | ecity  | edepartment | eage | esalary |
+----+-----+-----+-----+----+-----+
| 103 | arkshika | sultanpur | CSE      | 22 | 55000 |
| 104 | nikku   | gorkhpur | IT       | 21 | 45000 |
| 108 | divyanshu | kanpur  | CSE      | 23 | 55000 |
+----+-----+-----+-----+----+-----+
```

3 rows in set (0.0270 sec)

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where edepartemnt in ("IT or "HR");
```

"> ^C

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where edpartment in "IT" or "CSE" ;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '"IT" or "CSE"' at line 1

```
MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where edpartment in ("IT" , "CSE") ;
```

ERROR: 1054: Unknown column 'edpartment' in 'where clause'

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where edepartment in ("IT" , "CSE");

eid	ename	ecity	edepartment	eage	esalary
101	sakshi	lucknow	CSE	21	500000
103	arkshika	sultanpur	CSE	22	55000
104	nikku	gorkhpur	IT	21	45000
105	teja	Amethi	CSE	22	250000
106	ayush	lucknow	IT	19	30000
108	divyanshu	kanpur	CSE	23	55000

6 rows in set (0.0246 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails where eage >20 and esalary >50000;

eid	ename	ecity	edepartment	eage	esalary
101	sakshi	lucknow	CSE	21	500000
103	arkshika	sultanpur	CSE	22	55000
105	teja	Amethi	CSE	22	250000
108	divyanshu	kanpur	CSE	23	55000

4 rows in set (0.0009 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select * from employeeedetails order by esalary DESC ;

eid	ename	ecity	edepartment	eage	esalary
101	sakshi	lucknow	CSE	21	500000
102	muskan	varanshi	biotech	19	500000
105	teja	Amethi	CSE	22	250000
103	arkshika	sultanpur	CSE	22	55000

108	divyanshu	kanpur	CSE	23	55000
-----	-----------	--------	-----	----	-------

104	nikku	gorkhpur	IT	21	45000
-----	-------	----------	----	----	-------

106	ayush	lucknow	IT	19	30000
-----	-------	---------	----	----	-------

+-----+	-----+	-----+	-----+	-----+	-----+
---------	--------	--------	--------	--------	--------

7 rows in set (0.0012 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select count from edepartment ;

ERROR: 1146: Table 'rrgroup.edepartment' doesn't exist

MySQL localhost:33060+ ssl rrgroup SQL > select count(*) from edepartment ;

ERROR: 1146: Table 'rrgroup.edepartment' doesn't exist

MySQL localhost:33060+ ssl rrgroup SQL > select count(edepartment)from employeeedetails ;

+-----+

count(edepartment)

+-----+

7

+-----+

1 row in set (0.0009 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select avg(esalary) from employeeedetails;

+-----+

avg(esalary)

+-----+

205000.0000

+-----+

1 row in set (0.0028 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select max(esalary)from employeeedetails ;

+-----+

max(esalary)

+-----+

500000

+-----+

1 row in set (0.0282 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) from employeeedetails ;

ERROR: 1140: In aggregated query without GROUP BY, expression #1 of SELECT list contains nonaggregated column 'rrgroup.employeeedetails.edepartment'; this is incompatible with sql_mode=only_full_group_by

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment ;

```
+-----+-----+
| edepartment | avg_esalary |
+-----+-----+
| CSE        | 215000.0000 |
| biotech    | 500000.0000 |
| IT         | 37500.0000  |
+-----+-----+
```

3 rows in set (0.0278 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,max(esalary) as max_esalary from employeeedetails group by edepartment ;

```
+-----+-----+
| edepartment | max_esalary |
+-----+-----+
| CSE        | 500000      |
| biotech    | 500000      |
| IT         | 45000       |
+-----+-----+
```

3 rows in set (0.0009 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select edpartment where esalary>60000 from employeeedetails ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'from employeeedetails' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment where esalary > 60000;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'where esalary > 60000' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetail where esalary > 60000;

ERROR: 1146: Table 'rrgroup.employeeedetail' doesn't exist

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails where esalary > 60000;

ERROR: 1140: In aggregated query without GROUP BY, expression #1 of SELECT list contains nonaggregated column 'rrgroup.employeeedetails.edepartment'; this is incompatible with sql_mode=only_full_group_by

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment having avg (esalary)>60000;

```
+-----+-----+
| edepartment | avg_esalary |
+-----+-----+
| CSE        | 215000.0000 |
| biotech    | 500000.0000 |
+-----+-----+
```

2 rows in set (0.0305 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment ,count(*) as total_employees from employeeedetails group by edepartment having count (*)>5;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '*)>5' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment ,count(*) as total_employees from employeeedetails group by edepartment having count(*)> 5 ;

Empty set (0.0008 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment ,count(*) as total_employees from employeeedetails group by edepartment having count(*)> 2 ;

```
+-----+-----+
| edepartment | total_employees |
+-----+-----+
| CSE        | 4               |
+-----+-----+
```

1 row in set (0.0009 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment order by avg_salary DESE ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'DESE' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment order by avg_esalary DESE ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'DESE' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment order by avg_esalary ASE ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'ASE' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment order by avg_esalary desc'

'> ^C

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment order by avg_salary decs ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'decs' at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment order by avg_salary desc'

'> ^C

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment order by avg_salary desc ;

ERROR: 1054: Unknown column 'avg_salary' in 'order clause'

MySQL localhost:33060+ ssl rrgroup SQL > select edepartment,avg(esalary) as avg_esalary from employeeedetails group by edepartment order by avg_esalary desc ;

```
+-----+-----+
| edepartment | avg_esalary |
+-----+-----+
| biotech    | 500000.0000 |
| CSE        | 215000.0000 |
| IT         | 37500.0000  |
+-----+-----+
```

3 rows in set (0.0010 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select ecity,count(*) as count from employeeedetails group by ecity ;

```
+-----+-----+
| ecity | count |
+-----+-----+
```

```
| lucknow | 2 |
| varanshi | 1 |
| sultanpur | 1 |
| gorkhpur | 1 |
| Amethi | 1 |
| kanpur | 1 |
```

```
+-----+-----+
```

6 rows in set (0.0011 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select count (*) as total_employees from
employeeedetails ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your
MySQL server version for the right syntax to use near '*) as total_employees from employeeedetails'
at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select count (*) as total_employees from
employeeedetails ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your
MySQL server version for the right syntax to use near '*) as total_employees from employeeedetails'
at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select count (ename) as total_employees from
employeeedetails ;

ERROR: 1630: FUNCTION rrgroup.count does not exist. Check the 'Function Name Parsing and
Resolution' section in the Reference Manual

MySQL localhost:33060+ ssl rrgroup SQL > select count (emp_name) as total_employees from
employeeedetails ;

ERROR: 1630: FUNCTION rrgroup.count does not exist. Check the 'Function Name Parsing and
Resolution' section in the Reference Manual

MySQL localhost:33060+ ssl rrgroup SQL > select count (*) as total_employees from
employeeedetails ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your
MySQL server version for the right syntax to use near '*) as total_employees from employeeedetails'
at line 1

MySQL localhost:33060+ ssl rrgroup SQL > select count(*) from employeeedetails ;

```
+-----+
```

```
| count(*) |
```

```
+-----+
```

```
| 7 |
```

+-----+

1 row in set (0.0310 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select max(esalary) from employeedeails ;

ERROR: 1146: Table 'rrgroup.employeedeails' doesn't exist

MySQL localhost:33060+ ssl rrgroup SQL > select max(esalary) from employeeedetails ;

+-----+

| max(esalary) |

+-----+

| 500000 |

+-----+

1 row in set (0.0006 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select avg(esalary) from employeeedetails ;

+-----+

| avg(esalary) |

+-----+

| 205000.0000 |

+-----+

1 row in set (0.0009 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select avg(esalary) from employeeedetails where
edepartment = "IT" ;

+-----+

| avg(esalary) |

+-----+

| 37500.0000 |

+-----+

1 row in set (0.0008 sec)

MySQL localhost:33060+ ssl rrgroup SQL > select min(esalary) from employeeedetails ;

+-----+

| min(esalary) |

+-----+

| 30000 |

+-----+

1 row in set (0.0271 sec)

MySQL localhost:33060+ ssl rrgroup SQL >