

# Master's Theorem, Quick Sort and Full History Recurrences

Subhabrata Samajder



IIIT, Delhi  
Winter Semester,  
15<sup>th</sup> March, 2023

## Recurrences: Divide and Conquer

## Divide and Conquer Relations: The Basic Idea

- The original problem is divided into smaller subproblems.

# Divide and Conquer Relations: The Basic Idea

- The original problem is divided into smaller subproblems.
- Each subproblem is solved **recursively**.

# Divide and Conquer Relations: The Basic Idea

- The original problem is divided into smaller subproblems.
- Each subproblem is solved *recursively*.
- A *combine* algorithm is used to solve the original problem.

# Divide and Conquer Relations: Problem Statement

## Assumptions:

- # Subproblems:  $a$
- Size of Each Subproblem:  $1/b$  of the original problem
- Combine Algorithm: Takes time  $cn^k$

where  $a$ ,  $b$ ,  $c$ , and  $k$  are some constant.

# Divide and Conquer Relations: Problem Statement

## Assumptions:

- # Subproblems:  $a$
- Size of Each Subproblem:  $1/b$  of the original problem
- Combine Algorithm: Takes time  $cn^k$

where  $a$ ,  $b$ ,  $c$ , and  $k$  are some constant.

Then,

$$T(n) = aT(n/b) + cn^k.$$

# Divide and Conquer Relations: Problem Statement

## Assumptions:

- # Subproblems:  $a$
- Size of Each Subproblem:  $1/b$  of the original problem
- Combine Algorithm: Takes time  $cn^k$

where  $a$ ,  $b$ ,  $c$ , and  $k$  are some constant.

Then,

$$T(n) = aT(n/b) + cn^k.$$

**For Simplicity:** Further assume that  $n = b^m$ , so that  $n/b$  is always an integer ( $b$  is an integer greater than 1).



## Divide and Conquer Relations (Cont.)

**Expand:**

$$T(n) = a\{aT(n/b^2) + c(n/b)^k\} + c(n)^k$$

## Divide and Conquer Relations (Cont.)

**Expand:**

$$\begin{aligned} T(n) &= a\{aT(n/b^2) + c(n/b)^k\} + c(n)^k \\ &= a\{a\{aT(n/b^3) + c(n/b^2)^k\} + c(n/b)^k\} + cn^k \end{aligned}$$

## Divide and Conquer Relations (Cont.)

**Expand:**

$$\begin{aligned} T(n) &= a\{aT(n/b^2) + c(n/b)^k\} + c(n)^k \\ &= a\{a\{aT(n/b^3) + c(n/b^2)^k\} + c(n/b)^k\} + cn^k \\ &\vdots \\ &= a\{a\{a\{\cdots\{aT(n/b^m) + c(n/b^{m-1})^k\} + \cdots\} + cn^k, \end{aligned}$$

where  $n/b^m = 1$ .

## Divide and Conquer Relations (Cont.)

**Expand:**

$$\begin{aligned} T(n) &= a\{aT(n/b^2) + c(n/b)^k\} + c(n)^k \\ &= a\{a\{aT(n/b^3) + c(n/b^2)^k\} + c(n/b)^k\} + cn^k \\ &\vdots \\ &= a\{a\{a\{\cdots\{aT(n/b^m) + c(n/b^{m-1})^k\} + \cdots\} + cn^k, \end{aligned}$$

where  $n/b^m = 1$ .

**Assume:**  $T(1) = c$ .

## Divide and Conquer Relations (Cont.)

**Expand:**

$$\begin{aligned} T(n) &= a\{aT(n/b^2) + c(n/b)^k\} + c(n)^k \\ &= a\{a\{aT(n/b^3) + c(n/b^2)^k\} + c(n/b)^k\} + cn^k \\ &\vdots \\ &= a\{a\{a\{\cdots\{aT(n/b^m) + c(n/b^{m-1})^k\} + \cdots\} + cn^k, \end{aligned}$$

where  $n/b^m = 1$ .

**Assume:**  $T(1) = c$ .

**Remark:** A different value would change the end result by only a constant.

## Divide and Conquer Relations (Cont.)

$$\therefore T(n) = ca^m + ca^{m-1}b^k + ca^{m-2}b^{2k} + \dots + cb^{mk}$$

## Divide and Conquer Relations (Cont.)

$$\begin{aligned}\therefore T(n) &= ca^m + ca^{m-1}b^k + ca^{m-2}b^{2k} + \dots + cb^{mk} \\ &= c \sum_{i=0}^m a^{m-i} b^{ik} = ca^m \sum_{i=0}^m \left(\frac{b^k}{a}\right)^i,\end{aligned}$$

## Divide and Conquer Relations (Cont.)

$$\begin{aligned}\therefore T(n) &= ca^m + ca^{m-1}b^k + ca^{m-2}b^{2k} + \dots + cb^{mk} \\ &= c \sum_{i=0}^m a^{m-i} b^{ik} = ca^m \sum_{i=0}^m \left(\frac{b^k}{a}\right)^i,\end{aligned}$$

which is a simple geometric series.



## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
  - The factor of the geometric series is less than 1.

## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
  - The factor of the geometric series is less than 1.
  - So the series converges to a constant as  $m \rightarrow \infty$ .

## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
  - The factor of the geometric series is less than 1.
  - So the series converges to a constant as  $m \rightarrow \infty$ .
  - Therefore,

$$T(n) = \mathcal{O}(a^m) = \mathcal{O}(a^{\log_b n}) = \mathcal{O}(n^{\log_b a}),$$

as  $m = \log_b n$ .

## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
- $a = b^k$ :
  - The factor of the geometric series is equal to 1.

## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
- $a = b^k$ :
  - The factor of the geometric series is equal to 1.
  - Thus

$$T(n) = \mathcal{O}(a^m m) = \mathcal{O}(n^k \log n),$$

since,  $a = b^k \Rightarrow \log_b a = k$  and  $m = \log_b n$ .

## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
- $a = b^k$ :
- $a < b^k$ :
  - The factor of the geometric series is greater than 1.

## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
- $a = b^k$ :
- $a < b^k$ :
  - The factor of the geometric series is greater than 1.
  - Let  $F = b^k/a$  ( $F$  is a constant).

## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
- $a = b^k$ :
- $a < b^k$ :
  - The factor of the geometric series is greater than 1.
  - Let  $F = b^k/a$  ( $F$  is a constant).
  - First element of the series is  $a^m$ , therefore we obtain

$$T(n) = \frac{a^m(F^{m+1} - 1)}{F - 1}$$



## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
- $a = b^k$ :
- $a < b^k$ :
  - The factor of the geometric series is greater than 1.
  - Let  $F = b^k/a$  ( $F$  is a constant).
  - First element of the series is  $a^m$ , therefore we obtain

$$\begin{aligned} T(n) &= \frac{a^m(F^{m+1} - 1)}{F - 1} \\ &= \mathcal{O}(a^m F^m) = \mathcal{O}((b^k)^m) = \mathcal{O}((b^m)^k) \end{aligned}$$

## Divide and Conquer Relations (Cont.)

The following cases may arise:

- $a > b^k$ :
- $a = b^k$ :
- $a < b^k$ :
  - The factor of the geometric series is greater than 1.
  - Let  $F = b^k/a$  ( $F$  is a constant).
  - First element of the series is  $a^m$ , therefore we obtain

$$\begin{aligned} T(n) &= \frac{a^m(F^{m+1} - 1)}{F - 1} \\ &= \mathcal{O}(a^m F^m) = \mathcal{O}((b^k)^m) = \mathcal{O}((b^m)^k) \\ &= \mathcal{O}(n^k). \end{aligned}$$

# Master's Theorem: A Simpler Version

## Theorem

*The solution of the recurrence relation  $T(n) = aT(n/b) + cn^k$ , where  $a$  and  $b$  are integer constants,  $a \geq 1$ ,  $b \geq 2$ , and  $c$  and  $k$  are positive constants, is*

$$T(n) = \begin{cases} \mathcal{O}(n^{\log_b a}) & \text{if } a > b^k \\ \mathcal{O}(n^k \log n) & \text{if } a = b^k \\ \mathcal{O}(n^k) & \text{if } a < b^k \end{cases}$$

## Merge Sort: Cost Analysis

## Cost Analysis

$$T(n) = 2T(\lceil n/2 \rceil) + \mathcal{O}(n) = \mathcal{O}(n \log n) \quad [\text{By Master's theorem}].$$

## Cost Analysis

$$T(n) = 2T(\lceil n/2 \rceil) + \mathcal{O}(n) = \mathcal{O}(n \log n) \quad [\text{By Master's theorem}].$$

**Note:** The number of data movements is  $\mathcal{O}(n \log n)!!$

## Cost Analysis

$$T(n) = 2T(\lceil n/2 \rceil) + \mathcal{O}(n) = \mathcal{O}(n \log n) \quad [\text{By Master's theorem}].$$

**Note:** The number of data movements is  $\mathcal{O}(n \log n)$ !!

### Drawbacks:

- Not as easy to implement.
- Additional storage required during each merge step.
- Thus, mergesort is **not** an **in-place algorithm**.
- This copying must be done every time two smaller sets are merged, making the procedure **slower**.

## Cost Analysis

$$T(n) = 2T(\lceil n/2 \rceil) + \mathcal{O}(n) = \mathcal{O}(n \log n) \quad [\text{By Master's theorem}].$$

**Note:** The number of data movements is  $\mathcal{O}(n \log n)!!$

### Drawbacks:

- Not as easy to implement.
- Additional storage required during each merge step.
- Thus, mergesort is **not** an **in-place algorithm**.
- This copying must be done every time two smaller sets are merged, making the procedure **slower**.

**Home Work:** Write the algorithm for Mergesort and implement it in C.



# Quicksort

# Motivation

## Recall:

- Mergesort needs **extra storage**.
- It is **not** possible to **predict** where each element will end up in the final order.

# Motivation

## Recall:

- Mergesort needs **extra storage**.
- It is **not** possible to **predict** where each element will end up in the final order.

**Question:** Can we somehow perform a different divide and conquer so that the position of the elements can be determined?

# Motivation

## Recall:

- Mergesort needs **extra storage**.
- It is **not** possible to **predict** where each element will end up in the final order.

**Question:** Can we somehow perform a different divide and conquer so that the position of the elements can be determined?

## Basic Idea of Quicksort:

- Spend most of the effort in the divide step and
- very little in the conquer step!

# The Divide and Combine Step

- **The Divide Step:**

- Suppose that we know a number  $x$  such that *one-half* of the elements are  $> x$  and the *other-half* of the elements are  $\leq x$ .
- Compare all elements to  $x$ .
- Partition the sequence into two parts according to the answer.
- This partition requires  $n - 1$  comparisons.
- One part can occupy the first half of the array and the other the second half.
- $\therefore$  can be done *in-place*.

# The Divide and Combine Step

- **The Divide Step:**
  - Suppose that we know a number  $x$  such that *one-half* of the elements are  $> x$  and the *other-half* of the elements are  $\leq x$ .
  - Compare all elements to  $x$ .
  - Partition the sequence into two parts according to the answer.
  - This partition requires  $n - 1$  comparisons.
  - One part can occupy the first half of the array and the other the second half.
  - $\therefore$  can be done *in-place*.
- Then sort each subsequence recursively.

# The Divide and Combine Step

- **The Divide Step:**

- Suppose that we know a number  $x$  such that *one-half* of the elements are  $> x$  and the *other-half* of the elements are  $\leq x$ .
- Compare all elements to  $x$ .
- Partition the sequence into two parts according to the answer.
- This partition requires  $n - 1$  comparisons.
- One part can occupy the first half of the array and the other the second half.
- $\therefore$  can be done *in-place*.

- Then sort each subsequence recursively.

- **The Combine Step:** *Trivial!*

- The two parts already occupy the correct positions in the array.
- Therefore, no additional space is required.

## How To Find $x$ ?

- Till now, it was assumed that the value of  $x$  is known.
- However,  $x$  is usually unknown.



## How To Find $x$ ?

- Till now, it was assumed that the value of  $x$  is known.
- However,  $x$  is usually unknown.
- **Note:** It is easy to see, that the same algorithm will work no matter which number is used for the *partition*.
- Call the number  $x$  as the *pivot*.

## How To Find $x$ ?

- Till now, it was assumed that the value of  $x$  is known.
- However,  $x$  is usually unknown.
- **Note:** It is easy to see, that the same algorithm will work no matter which number is used for the *partition*.
- Call the number  $x$  as the *pivot*.
- Our purpose is to partition the array into *two parts*,
  - one with numbers  $>$  than the pivot and
  - the other with numbers  $\leq$  the pivot.
- This is achieved via the *partitioning algorithm*.


# Quicksort: An Example

## The Partitioning Phase:

6	2	8	5	10	9	12	1	15	7	3	13	4	11	16	14
---	---	---	---	----	---	----	---	----	---	---	----	---	----	----	----


# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:



# Quicksort: An Example


## The Partitioning Phase:






# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:



# Quicksort: An Example


## The Partitioning Phase:






# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:




# Quicksort: An Example

## The Partitioning Phase:



# Quicksort: An Example

## The Partitioning Phase:





# The Partition Algorithm

- Use two pointers to the array,  $L$  and  $R$ .
- Initially,
  - $L$  points to the left side of the array and
  - $R$  points to the right side of the array.
- The pointers “move” in opposite directions toward each other.
- $\text{Swap}(x_L, x_R)$ : If  $x_L > \text{pivot}$  and  $x_R \leq \text{pivot}$ .

## Quicksort: An Example (Cont.)

### Recursive Phase:

6	2	8	5	10	9	12	1	15	7	3	13	4	11	16	14
---	---	---	---	----	---	----	---	----	---	---	----	---	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

6	2	8	5	10	9	12	1	15	7	3	13	4	11	16	14
---	---	---	---	----	---	----	---	----	---	---	----	---	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

1	2	4	5	3	6	12	9	15	7	10	13	8	11	16	14
---	---	---	---	---	---	----	---	----	---	----	----	---	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	2	4	5	3	⑥	12	9	15	7	10	13	8	11	16	14
---	---	---	---	---	---	----	---	----	---	----	----	---	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	4	5	3	⑥	12	9	15	7	10	13	8	11	16	14
---	---	---	---	---	---	----	---	----	---	----	----	---	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	3	④	5	⑥	12	9	15	7	10	13	8	11	16	14
---	---	---	---	---	---	----	---	----	---	----	----	---	----	----	----

**Note:** When a single number appears between two pivots it is obviously in the **right position**.

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	3	④	5	⑥	8	9	11	7	10	⑫	13	15	16	14
---	---	---	---	---	---	---	---	----	---	----	---	----	----	----	----



## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	3	④	5	⑥	7	⑧	11	9	10	⑫	13	15	16	14
---	---	---	---	---	---	---	---	----	---	----	---	----	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	3	④	5	⑥	7	⑧	11	9	10	⑫	13	15	16	14
---	---	---	---	---	---	---	---	----	---	----	---	----	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	3	④	5	⑥	7	⑧	10	9	⑪	⑫	13	15	16	14
---	---	---	---	---	---	---	---	----	---	---	---	----	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	3	④	5	⑥	7	⑧	9	⑩	⑪	⑫	13	15	16	14
---	---	---	---	---	---	---	---	---	---	---	---	----	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	3	④	5	⑥	7	⑧	9	⑩	⑪	⑫	⑬	15	16	14
---	---	---	---	---	---	---	---	---	---	---	---	---	----	----	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	3	④	5	⑥	7	⑧	9	⑩	⑪	⑫	⑬	14	⑮	16
---	---	---	---	---	---	---	---	---	---	---	---	---	----	---	----

## Quicksort: An Example (Cont.)

### Recursive Phase:

①	②	3	④	5	⑥	7	⑧	9	⑩	⑪	⑫	⑬	14	⑮	16
---	---	---	---	---	---	---	---	---	---	---	---	---	----	---	----

**Home Work:** Write the Quicksort algorithm and implement it in C.

## Correctness

- Guaranteed by the following *loop invariant*:  
“At step  $k$  of the algorithm,  $pivot \geq x_i$  for all  $i$  such that  $i < L$ ,  
and  $pivot < x_j$  for all  $j$  such that  $j > R$ ”.



## Correctness

- Guaranteed by the following *loop invariant*:  
“At step  $k$  of the algorithm,  $pivot \geq x_i$  for all  $i$  such that  $i < L$ ,  
and  $pivot < x_j$  for all  $j$  such that  $j > R$ ”.

**Home Work:** Prove it using mathematical induction.

## Correctness

- Guaranteed by the following *loop invariant*:  
“At step  $k$  of the algorithm,  $pivot \geq x_i$  for all  $i$  such that  $i < L$ ,  
and  $pivot < x_j$  for all  $j$  such that  $j > R$ ”.

**Home Work:** Prove it using mathematical induction.

- **Termination:** When  $L = R$ .

## Choosing a Good Pivot

- Divide-and-conquer algorithms work best when the parts have **equal sizes**.
- $\therefore$  the closer the pivot is to the middle, the faster the algorithm.
- It is possible to find the median of the sequence (using the *Median finding algorithm*), but it is not worth the effort.
- In fact, choosing a uniform random element suffices.
- If the sequence is in a *uniformly random order*, then we might as well choose the **first element** as the pivot.

## Cost Analysis

- **Running time:** Depends on the **input sequence** and **pivot**.
- If the pivot always partitions the list into **two equal parts**, then

$$\begin{aligned} T(n) &= 2T(n/2) + \mathcal{O}(n), \quad T(2) = 1, \\ \Rightarrow T(n) &= \mathcal{O}(n \log n). \end{aligned}$$

## Cost Analysis

- **Running time:** Depends on the **input sequence** and **pivot**.
- If the pivot always partitions the list into **two equal parts**, then

$$\begin{aligned} T(n) &= 2T(n/2) + \mathcal{O}(n), \quad T(2) = 1, \\ \Rightarrow T(n) &= \mathcal{O}(n \log n). \end{aligned}$$

- But we can get  $\mathcal{O}(n \log n)$  even under much ***weaker conditions!***

## Cost Analysis

- **Running time:** Depends on the **input sequence** and **pivot**.
- If the pivot always partitions the list into **two equal parts**, then

$$\begin{aligned} T(n) &= 2T(n/2) + \mathcal{O}(n), \quad T(2) = 1, \\ \Rightarrow T(n) &= \mathcal{O}(n \log n). \end{aligned}$$

- But we can get  $\mathcal{O}(n \log n)$  even under much ***weaker conditions!***
- However, if the pivot is very close to one side of the sequence, then the running time is much higher.

## Cost Analysis

- **Running time:** Depends on the **input sequence** and **pivot**.
- If the pivot always partitions the list into **two equal parts**, then

$$\begin{aligned} T(n) &= 2T(n/2) + \mathcal{O}(n), \quad T(2) = 1, \\ \Rightarrow T(n) &= \mathcal{O}(n \log n). \end{aligned}$$

- But we can get  $\mathcal{O}(n \log n)$  even under much ***weaker conditions!***
- However, if the pivot is very close to one side of the sequence, then the running time is much higher.

### Example:

- If the sequence is already sorted.
- **Time Complexity:**  $\mathcal{O}(n^2)$ .

## Cost Analysis (Cont.)

- ...
- The quadratic worst case for (almost) sorted sequences can be eliminated
  - by comparing the first, last, and middle elements,
  - and then taking their median (the second largest) as the pivot.



## Cost Analysis (Cont.)

- ...
- The quadratic worst case for (almost) sorted sequences can be eliminated
  - by comparing the first, last, and middle elements,
  - and then taking their median (the second largest) as the pivot.
- **Safer method:** Choose the pivot **randomly** from among the elements in the sequence.
- **Worst-case complexity:**  $\mathcal{O}(n^2)$  (since there is still a chance that the pivot is the smallest element in the sequence.)

## Cost Analysis (Cont.)

- ...
- The quadratic worst case for (almost) sorted sequences can be eliminated
  - by comparing the first, last, and middle elements,
  - and then taking their median (the second largest) as the pivot.
- **Safer method:** Choose the pivot **randomly** from among the elements in the sequence.
- **Worst-case complexity:**  $\mathcal{O}(n^2)$  (since there is still a chance that the pivot is the smallest element in the sequence.)
- However, the likelihood that this worst case occur is very small.

## Average-case Complexity

Given a sequence  $x_1, \dots, x_n$ , assume that each of the  $x_i$  has the same probability of being selected as the pivot.

## Average-case Complexity

Given a sequence  $x_1, \dots, x_n$ , assume that each of the  $x_i$  has the same probability of being selected as the pivot.

Running time when  $i^{th}$  smallest element is the pivot:

$$T(n) = \underbrace{n-1}_{\text{partitioning}} + T(i-1) + T(n-i).$$

## Average-case Complexity

Given a sequence  $x_1, \dots, x_n$ , assume that each of the  $x_i$  has the same probability of being selected as the pivot.

Running time when  $i^{th}$  smallest element is the pivot:

$$T(n) = \underbrace{n-1}_{\text{partitioning}} + T(i-1) + T(n-i).$$

The **average-case time complexity** is then given by

$$\begin{aligned} T(n) &= n-1 + \frac{1}{n} \sum_{i=1}^n (T(i-1) + T(n-i)) \\ &= n-1 + \frac{2}{n} \sum_{i=0}^{n-1} T(i) \quad [\text{Full history recurrence}] \end{aligned}$$

## Full History Recurrences

# Full History Recurrence

## Definition

A **full-history recurrence relation** is one that depends on **all** the previous values of the function, not just on a few of them.

## A Simplest Full-history Recurrence Relation

Consider

$$T(n) = c + \sum_{i=1}^{n-1} T(i),$$

where  $c$  is a constant and  $T(1)$  is given.



## A Simplest Full-history Recurrence Relation

Consider

$$T(n) = c + \sum_{i=1}^{n-1} T(i),$$

where  $c$  is a constant and  $T(1)$  is given.

**Solution:**

- We use a method that cancels most of the intermediate terms.

## A Simplest Full-history Recurrence Relation

Consider

$$T(n) = c + \sum_{i=1}^{n-1} T(i),$$

where  $c$  is a constant and  $T(1)$  is given.

### Solution:

- We use a method that cancels most of the intermediate terms.
- Sometimes called *elimination of history*.

## A Simplest Full-history Recurrence Relation

Consider

$$T(n) = c + \sum_{i=1}^{n-1} T(i),$$

where  $c$  is a constant and  $T(1)$  is given.

### Solution:

- We use a method that cancels most of the intermediate terms.
- Sometimes called *elimination of history*.
- Compare  $T(n+1)$  with  $T(n)$  and subtract to get

$$T(n+1) - T(n) = T(n) \Rightarrow T(n+1) = 2T(n) \Rightarrow T(n+1) = T(1)2^n.$$

## A Simplest Full-history Recurrence Relation

Consider

$$T(n) = c + \sum_{i=1}^{n-1} T(i),$$

where  $c$  is a constant and  $T(1)$  is given.

### Solution:

- We use a method that cancels most of the intermediate terms.
- Sometimes called *elimination of history*.
- Compare  $T(n+1)$  with  $T(n)$  and subtract to get

$$T(n+1) - T(n) = T(n) \Rightarrow T(n+1) = 2T(n) \Rightarrow T(n+1) = T(1)2^n.$$

- **Note:**

- The claim is true for  $T(1)$ ,  $\because T(1) = T(0+1) = T(1)2^0 = T(1)$ .

## A Simplest Full-history Recurrence Relation

Consider

$$T(n) = c + \sum_{i=1}^{n-1} T(i),$$

where  $c$  is a constant and  $T(1)$  is given.

### Solution:

- We use a method that cancels most of the intermediate terms.
- Sometimes called *elimination of history*.
- Compare  $T(n+1)$  with  $T(n)$  and subtract to get

$$T(n+1) - T(n) = T(n) \Rightarrow T(n+1) = 2T(n) \Rightarrow T(n+1) = T(1)2^n.$$

- **Note:**

- The claim is true for  $T(1)$ ,  $\because T(1) = T(0+1) = T(1)2^0 = T(1)$ .
- **Induction step:** If the claim is true for  $T(n)$ , then

$$T(n+1) = 2T(n) = T(1)2^n.$$

## A Simplest Full-history Recurrence Relation (Cont.)

**Correct?**

## A Simplest Full-history Recurrence Relation (Cont.)

**Correct? No!!**

## A Simplest Full-history Recurrence Relation (Cont.)

**Correct? No!!**

**Example:** Set  $T(1) = 1$  and  $c = 5$ , s.t.,  $T(2) = 6 \neq 2T(1) = 2$ .



## A Simplest Full-history Recurrence Relation (Cont.)

**Correct? No!!**

**Example:** Set  $T(1) = 1$  and  $c = 5$ , s.t.,  $T(2) = 6 \neq 2T(1) = 2$ .

**Reason:**

- This is an example of carelessly going through an induction proof *ignoring the base case*.

## A Simplest Full-history Recurrence Relation (Cont.)

**Correct? No!!**

**Example:** Set  $T(1) = 1$  and  $c = 5$ , s.t.,  $T(2) = 6 \neq 2T(1) = 2$ .

**Reason:**

- This is an example of carelessly going through an induction proof *ignoring the base case*.
- **Note:** The proof does not work for  $T(2)$ , since  $T(2) - T(1) = c$  **may not** be equal to  $T(1)$ .

## A Simplest Full-history Recurrence Relation (Cont.)

**Correct? No!!**

**Example:** Set  $T(1) = 1$  and  $c = 5$ , s.t.,  $T(2) = 6 \neq 2T(1) = 2$ .

**Reason:**

- This is an example of carelessly going through an induction proof *ignoring the base case*.
- **Note:** The proof does not work for  $T(2)$ , since  $T(2) - T(1) = c$  **may not** be equal to  $T(1)$ .
- **Warning:** *One should be very suspicious when a parameter ( $c$  in this case) that appears in the expression does not appear in the final solution.*

## A Simplest Full-history Recurrence Relation (Cont.)

**Correct? No!!**

**Example:** Set  $T(1) = 1$  and  $c = 5$ , s.t.,  $T(2) = 6 \neq 2T(1) = 2$ .

**Reason:**

- This is an example of carelessly going through an induction proof *ignoring the base case*.
- **Note:** The proof does not work for  $T(2)$ , since  $T(2) - T(1) = c$  **may not** be equal to  $T(1)$ .
- **Warning:** *One should be very suspicious when a parameter ( $c$  in this case) that appears in the expression does not appear in the final solution.*
- **Correct Solution:** Note that  $T(2) = T(1) + c$  (by definition), and that the proof above is correct for all  $n \geq 2$ .

## A Simplest Full-history Recurrence Relation (Cont.)

**Correct? No!!**

**Example:** Set  $T(1) = 1$  and  $c = 5$ , s.t.,  $T(2) = 6 \neq 2T(1) = 2$ .

**Reason:**

- This is an example of carelessly going through an induction proof *ignoring the base case*.
- **Note:** The proof does not work for  $T(2)$ , since  $T(2) - T(1) = c$  **may not** be equal to  $T(1)$ .
- **Warning:** *One should be very suspicious when a parameter ( $c$  in this case) that appears in the expression does not appear in the final solution.*
- **Correct Solution:** Note that  $T(2) = T(1) + c$  (by definition), and that the proof above is correct for all  $n \geq 2$ .
- $\therefore T(n+1) = (T(1) + c)2^{n-1}$ .

## Books Consulted

- 1 Chapter 6, Section 4.3 & 4.4 of *Introduction to Algorithms: A Creative Approach* by [Udi Manber](#).

Thank You for your kind attention!