

# Other Asymptotic Notations and Recursion

Subhabrata Samajder



IIIT, Delhi  
Winter Semester,  
10<sup>th</sup> March, 2023

## Recap: Algorithms

- **Algorithm:** It is a finite sequence of elementary operations with the objective of performing some (computational) task.

## Recap: Algorithms

- **Algorithm:** It is a **finite sequence** of **elementary operations** with the objective of performing some (computational) task.
  - **Elementary operations:** Arithmetic and logical operations.
  - **Finiteness:** It must stop.

## Recap: Algorithms

- **Algorithm:** It is a finite sequence of elementary operations with the objective of performing some (computational) task.
- **Input and Output:** Can take *several* inputs but produces a *single* output.
- **Efficiency:** Requiring little 'resources'.
  - **Resources:** Time and space.

## Recap: Algorithms

- **Algorithm:** It is a finite sequence of elementary operations with the objective of performing some (computational) task.
- **Input and Output:** Can take *several* inputs but produces a *single* output.
- **Efficiency:** Requiring little 'resources'.
  - **Resources:** Time and space.
  - $\text{Time} \propto \text{Size of Inputs}$ .

## Recap: Algorithms

- **Algorithm:** It is a finite sequence of elementary operations with the objective of performing some (computational) task.
- **Input and Output:** Can take *several* inputs but produces a *single* output.
- **Efficiency:** Requiring little 'resources'.
  - **Resources:** Time and space.
  - Time  $\propto$  Size of Inputs.
  - **Size of Inputs:** Function from set of all possible inputs to  $\mathbb{N} \cup \{0\}$ .
  - But for the same input size  $n$ ,  $t(n)$  varies across different inputs!

# Recap: Algorithms

- **Two Possible Way Outs:**
  - Worst-case Complexity
  - Average-case Complexity

## Recap: Algorithms

- **Two Possible Way Outs:**
  - Worst-case Complexity
  - Average-case Complexity
- **Asymptotic Comparison:** Big-oh notation.



## Other Asymptotic Notations

## $\Omega$ Notation

### Definition

If there exist constants  $c$  and  $N$ , such that for all  $n > N$  the number of steps  $T(n)$  required to solve the problem for input size  $n$  is at least  $cg(n)$ , i.e.,

$$T(n) \geq cg(n),$$

then we say that  $T(n) = \Omega(g(n))$ .

## $\Omega$ Notation

### Definition

If there exist constants  $c$  and  $N$ , such that for all  $n > N$  the number of steps  $T(n)$  required to solve the problem for input size  $n$  is at least  $cg(n)$ , i.e.,

$$T(n) \geq cg(n),$$

then we say that  $T(n) = \Omega(g(n))$ .

- **Example:**  $n^2 = \Omega(n^2 - 100)$ ,  $n = \Omega(n^{0.9})$ .

## $\Omega$ Notation

### Definition

If there exist constants  $c$  and  $N$ , such that for all  $n > N$  the number of steps  $T(n)$  required to solve the problem for input size  $n$  is at least  $cg(n)$ , i.e.,

$$T(n) \geq cg(n),$$

then we say that  $T(n) = \Omega(g(n))$ .

- **Example:**  $n^2 = \Omega(n^2 - 100)$ ,  $n = \Omega(n^{0.9})$ .
- The  $\Omega$  notation thus correspond to the “ $\geq$ ” relation.

## $\Theta$ Notation

### Definition

If a certain function  $f(n)$  satisfies both  $f(n) = \mathcal{O}(g(n))$  and  $f(n) = \Omega(g(n))$ , then we say that  $f(n) = \Theta(g(n))$ .

- **Example:**  $5n \log_2 n - 10 = \Theta(n \log n)$ .

## $\Theta$ Notation

### Definition

If a certain function  $f(n)$  satisfies both  $f(n) = \mathcal{O}(g(n))$  and  $f(n) = \Omega(g(n))$ , then we say that  $f(n) = \Theta(g(n))$ .

- **Example:**  $5n \log_2 n - 10 = \Theta(n \log n)$ .
- The constants used to prove the  $\mathcal{O}$  part and the  $\Omega$  part need not be the same.

## Small-oh or Little-oh Notation

- The  $\mathcal{O}$ ,  $\Omega$  and  $\Theta$  correspond (loosely) to “ $\leq$ ”, “ $\geq$ ”, and “ $=$ ”.
- Sometimes we need notation corresponding to “ $<$ ” and “ $>$ ”.

### Definition

We say that  $f(n) = o(g(n))$  (pronounced “ $f(n)$  is little oh of  $g(n)$ ”) if

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0.$$

## Small-oh or Little-oh Notation

- The  $\mathcal{O}$ ,  $\Omega$  and  $\Theta$  correspond (loosely) to “ $\leq$ ”, “ $\geq$ ”, and “ $=$ ”.
- Sometimes we need notation corresponding to “ $<$ ” and “ $>$ ”.

### Definition

We say that  $f(n) = o(g(n))$  (pronounced “ $f(n)$  is little oh of  $g(n)$ ”) if

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0.$$

**Example:**  $n / \log_2 n = o(n)$ , but  $n/10 \neq o(n)$ .



## $\omega$ Notation

### Definition

Similarly, we say that  $f(n) = \omega(g(n))$  (small omega) if

$$g(n) = o(f(n)).$$

In other words,  $f(n) = \omega(g(n))$  means that for any positive constant  $c$ , there exists a constant  $N$ , such that

$$0 \leq cg(n) < f(n)$$

for all  $n \geq N$ . The value of  $N$  must not depend on  $n$ , but may depend on  $c$ .

## Recursion: A Recap

# Recursion

## Definition

A “function” is said to be **recursive** if it calls itself, either directly or indirectly.

# Recursion

## Definition

A “function” is said to be **recursive** if it calls itself, either directly or indirectly.

- In its simplest form, the idea of recursion is straight-forward.

# Recursion

## Definition

A “function” is said to be **recursive** if it calls itself, either directly or indirectly.

- In its simplest form, the idea of recursion is straight-forward.

## Example:

```
#include <stdio.h>

int main(void) {
    printf(“ The universe is never ending! ”);
    main();
    return 0; }
```

# Recursion

## Definition

A “function” is said to be **recursive** if it calls itself, either directly or indirectly.

- In its simplest form, the idea of recursion is straight-forward.

## Example:

```
int sum(int n) {  
    if (n <= 1)  
        return n;  
    else  
        return (n + sum(n - 1)); }
```

Example: `sum(4)`

## Example: `sum(4)`

Function call	Value returned		
<code>sum(1)</code>	1		
<code>sum(2)</code>	$2 + \text{sum}(1)$	or	$2 + 1$
<code>sum(3)</code>	$3 + \text{sum}(2)$	or	$3 + 2 + 1$
<code>sum(4)</code>	$4 + \text{sum}(3)$	or	$4 + 3 + 2 + 1$

- The base case is considered,



## Example: $\text{sum}(4)$

Function call	Value returned		
$\text{sum}(1)$	1		
$\text{sum}(2)$	$2 + \text{sum}(1)$	or	$2 + 1$
$\text{sum}(3)$	$3 + \text{sum}(2)$	or	$3 + 2 + 1$
$\text{sum}(4)$	$4 + \text{sum}(3)$	or	$4 + 3 + 2 + 1$

- The base case is considered,
- then working out from the base case, the other cases are considered.

## Recursion (Cont.)

**Simple recursive routines follow a standard pattern!**

## Recursion (Cont.)

**Simple recursive routines follow a standard pattern!**

- The problem is broken into sub-problem(s).

## Recursion (Cont.)

**Simple recursive routines follow a standard pattern!**

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).

## Recursion (Cont.)

**Simple recursive routines follow a standard pattern!**

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.

## Recursion (Cont.)

### **Simple recursive routines follow a standard pattern!**

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.
- Then there is a general recursive case in which one of the variables, often an integer, is passed as an argument in such a way as to ultimately lead to the base case.

## Recursion (Cont.)

**Simple recursive routines follow a standard pattern!**

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.
- Then there is a general recursive case in which one of the variables, often an integer, is passed as an argument in such a way as to ultimately lead to the base case.

**Example:** `sum()`

## Recursion (Cont.)

**Simple recursive routines follow a standard pattern!**

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.
- Then there is a general recursive case in which one of the variables, often an integer, is passed as an argument in such a way as to ultimately lead to the base case.

**Example:** `sum()`

- $\text{sum}(n) = n + (n - 1) + \cdots + 1 = n + \text{sum}(n - 1).$



## Recursion (Cont.)

### Simple recursive routines follow a standard pattern!

- The problem is broken into sub-problem(s).
- Typically, there is a base case (or cases).
- The base case is tested for upon entry to the function.
- Then there is a general recursive case in which one of the variables, often an integer, is passed as an argument in such a way as to ultimately lead to the base case.

### Example: `sum()`

- $\text{sum}(n) = n + (n - 1) + \cdots + 1 = n + \text{sum}(n - 1)$ .
- The variable  $n$  is reduced by 1 each time until
- the base case with  $n = 1$  is reached.

## Examples: Factorial

$$0! = 1, \quad n! = n(n-1) \cdots 3 \cdot 2 \cdot 1 \quad \text{for } n > 0$$

or equivalently,

$$0! = 1, \quad n! = n \cdot ((n-1)!) \quad \text{for } n > 0$$

## Examples: Factorial

$$0! = 1, \quad n! = n(n-1) \cdots 3 \cdot 2 \cdot 1 \quad \text{for } n > 0$$

or equivalently,

$$0! = 1, \quad n! = n \cdot ((n-1)!) \quad \text{for } n > 0$$

**For example:**  $5! = 5 \cdot 4 \cdot 3 \cdot 2 \cdot 1 = 120$ .

## Examples: Factorial

$$0! = 1, \quad n! = n(n-1) \cdots 3 \cdot 2 \cdot 1 \quad \text{for } n > 0$$

or equivalently,

$$0! = 1, \quad n! = n \cdot ((n-1)!) \quad \text{for } n > 0$$

**For example:**  $5! = 5 \cdot 4 \cdot 3 \cdot 2 \cdot 1 = 120$ .

- **Base Case:**  $0! = 1$  and  $1! = 1$ .

## Examples: Factorial

$$0! = 1, \quad n! = n(n-1) \cdots 3 \cdot 2 \cdot 1 \quad \text{for } n > 0$$

or equivalently,

$$0! = 1, \quad n! = n \cdot ((n-1)!) \quad \text{for } n > 0$$

**For example:**  $5! = 5 \cdot 4 \cdot 3 \cdot 2 \cdot 1 = 120$ .

- **Base Case:**  $0! = 1$  and  $1! = 1$ .
- **Recursive Case:**  $n! = n \cdot (n-1)!$ .

## Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

## Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

### Note:

- Works properly within the limits of [integer precision](#).

## Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

### Note:

- Works properly within the limits of [integer precision](#).
- Factorial function grows very rapidly!



## Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

### Note:

- Works properly within the limits of **integer precision**.
- Factorial function grows very rapidly!
- **RecFactorial(n)** runs only a few values of  $n$  (upto  $n = 12!!$ ).

## Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

### Note:

- Works properly within the limits of [integer precision](#).
- Factorial function grows very rapidly!
- [RecFactorial\(n\)](#) runs only a few values of  $n$  (upto  $n = 12!!$ ).
- For  $n > 12$ , incorrect values are returned.

## Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

### Note:

- Works properly within the limits of **integer precision**.
- Factorial function grows very rapidly!
- **RecFactorial(n)** runs only a few values of  $n$  (upto  $n = 12!!$ ).
- For  $n > 12$ , incorrect values are returned.
- **This type of programming error is common!!**

## Factorial: Recursive Version

```
int RecFactorial (int n) {      /* recursive version */  
    if (n <= 1)  
        return 1;  
    else  
        return (n * RecFactorial (n - 1)); }
```

**Take Away:** Functions that are logically correct can return incorrect values if the logical operations in the body of the function are beyond the integer precision available to the system!!

## Factorial: Iterative Version

### Note:

- As in `sum()`, `RecFactorial()` activates  $n$  **nested copies** of the function before returning level by level to the original call.

## Factorial: Iterative Version

### Note:

- As in `sum()`, `RecFactorial()` activates  $n$  **nested copies** of the function before returning level by level to the original call.
- Thus  $n$  **function calls** are used for this computation.
- This is **“costly”** !!

## Factorial: Iterative Version

### Note:

- As in `sum()`, `RecFactorial()` activates  $n$  **nested copies** of the function before returning level by level to the original call.
- Thus  $n$  **function calls** are used for this computation.
- This is **“costly”** !!

**“What to do?”**

## Factorial: Iterative Version

### Note:

- As in `sum()`, `RecFactorial()` activates  $n$  **nested copies** of the function before returning level by level to the original call.
- Thus  $n$  **function calls** are used for this computation.
- This is **“costly”** !!

**“What to do?”**

**Way out:** Rewrite them as **iterative functions**.



## Factorial: Iterative Version

### Note:

- As in `sum()`, `RecFactorial()` activates  $n$  **nested copies** of the function before returning level by level to the original call.
- Thus  $n$  **function calls** are used for this computation.
- This is **“costly”** !!

### “What to do?”

**Way out:** Rewrite them as **iterative functions**.

```
int IterFactorial (int n) {      /* iterative version */
    int product = 1;
    for ( ; n > 1; --n)
        product *= n;
    return product; }
```

## Factorial: Iterative Version

### Note:

- As in `sum()`, `RecFactorial()` activates  $n$  **nested copies** of the function before returning level by level to the original call.
- Thus  $n$  **function calls** are used for this computation.
- This is **“costly”** !!

### “What to do?”

**Way out:** Rewrite them as **iterative functions**.

```
int IterFactorial (int n) {      /* iterative version */
    int product = 1;
    for ( ; n > 1; --n)
        product *= n;
    return product; }
```

**IterFactorial(n):** Takes only 1 function call.

# Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

## Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

**“Then why bother?”**

# Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

**“Then why bother?”**

- Recursion is more elegant.

# Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

**“Then why bother?”**

- Recursion is more elegant.
- Requires fewer variables to make the same calculation.

# Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

**“Then why bother?”**

- Recursion is more elegant.
- Requires fewer variables to make the same calculation.
- Takes care of its bookkeeping by stacking arguments and variables for each invocation.

# Efficiency Considerations

Many algorithms have both **iterative** and **recursive** formulations.

## “Then why bother?”

- Recursion is more elegant.
- Requires fewer variables to make the same calculation.
- Takes care of its bookkeeping by stacking arguments and variables for each invocation.
- *This stacking of arguments, while invisible to the user, is still costly in time and space.*



## Books Consulted

- ① *Introduction to Algorithms: A Creative Approach* by [Udi Manber](#).
- ② *Introduction to Algorithms* by [Thomas H Cormen](#), [Charles E Leiserson](#), [Ronald L Rivest](#), [Clifford Stein](#).

Thank You for your kind attention!