## Introduction to Algorithms

Subhabrata Samajder



IIIT, Delhi Winter Semester, 1<sup>st</sup> March, 2023

### About Myself

Name: Subhabrata Samajder

#### **Research Interests:**

- Lattice based cryptography
- Statistical aspects of symmetric key cryptanalysis
- Searchable Symmetric Encryption (SSE)
- e-Voting
- Broadcast Encryption
- Blockchain
- Random graphs

### About Myself

Name: Subhabrata Samajder

E-mail: subhabrata@iiitd.ac.in

Office: B-505 (R & D Block)

Office Hours: By appointment

Course Webpage: On Google classroom

Class Code: I4o5nrw

## Academic Integrity Policy

Anyone caught cheating or copying will be penalised.

Plagiarism cases will be dealt strictly.

Take this opportunity to stay away from plagiarism forever.

# Grading plan: Tentative Grading Components

Components	Number	Weightage
MidSem Theory	1	30%
EndSem Theory	1	35%
Weekly Coding Assignments	≥ 6	20%
Quiz and/or Homework	<u>&gt; 4</u>	15%
Bonus (Lab attendance $+$ Lab Tests)	NA	5%

Introduction to Algorithms


## Algorithms: In Our Daily Lives













**Work Commute** 




**Online Shopping** 

# Algorithms: Rubik's Cube



# Algorithms: Rubik's Cube



# Introduction of Algorithms

"What is an algorithm?"

### Introduction of Algorithms

"What is an algorithm?"

**Intuitive answer:** It is a finite sequence of elementary operations with the objective of performing some (computational) task.

### Introduction of Algorithms

"What is an algorithm?"

**Intuitive answer:** It is a finite sequence of elementary operations with the objective of performing some (computational) task.

## **Elementary Operations**

"How elementary is 'elementary'?"

### **Elementary Operations**

"How elementary is 'elementary'?"

The elementary operations that we will consider will be at a higher level and include arithmetic and logical operations.

### **Finiteness**

**Algorithms:** Finiteness  $\Rightarrow$  an algorithm must stop.

• **Example:** Compute (a + b) \* (c + d)

$$t_1 = a + b;$$
  $t_2 = c + d;$   $t_3 = t_1 * t_2.$ 

### **Finiteness**

**Algorithms:** Finiteness  $\Rightarrow$  an algorithm must stop.

• **Example:** Compute (a + b) \* (c + d)

$$t_1 = a + b;$$
  $t_2 = c + d;$   $t_3 = t_1 * t_2.$ 

**Computational Method:** A procedure that has all of the characteristics of an algorithm except that it possibly *lacks finiteness*.

• Example:  $while(1)\{\}$ 

### Sequence

$$t_1 = a + b$$
;  $t_2 = c + d$ ;  $t_3 = t_1 * t_2$ .

We emphasise on the sequential nature of the procedure.

- Any permutation of this sequence does not give the same desired output.
  - **Example:**  $t_3 = t_1 * t_2$ ;  $t_2 = c + d$ ;  $t_1 = a + b$ , is not the same as the algorithm above.

$$t_1 = a + b$$
;  $t_2 = c + d$ ;  $t_3 = t_1 * t_2$ .

**Note:** Sometimes different orderings of the operations may give rise to the *same* result.

#### • Example:

$$t_1 = a + b;$$
  $t_2 = c + d;$   $t_3 = t_1 * t_2;$  and  $t_2 = c + d;$   $t_1 = a + b;$   $t_3 = t_1 * t_2.$ 

$$t_1 = a + b$$
;  $t_2 = c + d$ ;  $t_3 = t_1 * t_2$ .

**Note:** Sometimes different orderings of the operations may give rise to the *same* result.

#### • Example:

$$t_1 = a + b;$$
  $t_2 = c + d;$   $t_3 = t_1 * t_2;$  and  $t_2 = c + d;$   $t_1 = a + b;$   $t_3 = t_1 * t_2.$ 

- Note:  $t_1 = a + b$  and  $t_2 = c + d$  can be executed independently of each other.
- Single computing unit (a processor): Sequential execution.
- Two computing unit: Can be executed simultaneously!

$$t_1 = a + b$$
;  $t_2 = c + d$ ;  $t_3 = t_1 * t_2$ .

**Note:** Sometimes different orderings of the operations may give rise to the *same* result.

#### • Example:

$$t_1 = a + b;$$
  $t_2 = c + d;$   $t_3 = t_1 * t_2;$  and  $t_2 = c + d;$   $t_1 = a + b;$   $t_3 = t_1 * t_2.$ 

- Note:  $t_1 = a + b$  and  $t_2 = c + d$  can be executed independently of each other.
- Single computing unit (a processor): Sequential execution.
- **Two computing unit:** Can be executed simultaneously! Give rise to the area of *parallel algorithms*.

$$t_1 = a + b$$
;  $t_2 = c + d$ ;  $t_3 = t_1 * t_2$ .

**Note:** Sometimes different orderings of the operations may give rise to the *same* result.

#### • Example:

$$t_1 = a + b;$$
  $t_2 = c + d;$   $t_3 = t_1 * t_2;$  and  $t_2 = c + d;$   $t_1 = a + b;$   $t_3 = t_1 * t_2.$ 

- Note:  $t_1 = a + b$  and  $t_2 = c + d$  can be executed independently of each other.
- Single computing unit (a processor): Sequential execution.
- **Two computing unit:** Can be executed simultaneously! Give rise to the area of *parallel algorithms*.

We would only be concentrating on sequential algorithms!!

**Recall:** The purpose of an algorithm is to perform some task.

Recall: The purpose of an algorithm is to perform some task.

**Inputs:** Can take *several* inputs.

• *Example: a*, *b*, *c*, *d*.

Output: Algorithms produce an output.

• Example: (a + b) \* (c + d).

**Recall:** The purpose of an algorithm is to perform some task.

**Inputs:** Can take *several* inputs.

• *Example: a*, *b*, *c*, *d*.

**Output:** Algorithms produce *an* output.

- Example: (a + b) \* (c + d).
- The relation of the output to the input defines the *computational task* of the algorithm.

**Recall:** The purpose of an algorithm is to perform some task.

**Inputs:** Can take *several* inputs.

• *Example: a*, *b*, *c*, *d*.

Output: Algorithms produce an output.

- Example: (a + b) \* (c + d).
- The relation of the output to the input defines the *computational task* of the algorithm.
- Simplest case: Binary valued output (*Decision problem*).

• Simplest case: Binary valued output (Decision problem).

**Example:** Searching Problem

- I/P: A list L of integer values and another value v.
- **Question:** Does  $v \in L$ ?
- O/P: 'yes' if  $v \in L$ ; else it returns 'no'.

**Note:** Decision problems appear rather simple but much of the sophistication of the area of algorithms can be discovered by studying such algorithms!!

'Efficient algorithms?

• **High level view:** Efficiency = requiring little 'resources'.

'Efficient algorithms?

• **High level view:** Efficiency = requiring little 'resources'.

Here, resources 
 ≡ the time of execution and the space required by the algorithm.

- **Time:** # steps required by the algorithm to produce its output.
  - **Assumption:** Each elementary operation requires *unit time*.
  - ∴ # steps = time required by the algorithm.

- **Time:** # steps required by the algorithm to produce its output.
  - **Assumption:** Each elementary operation requires *unit time*.
  - ∴ # steps = time required by the algorithm.

• **Space:** # temporary variables.

- **Time:** # steps required by the algorithm to produce its output.
  - Assumption: Each elementary operation requires unit time.
  - ∴ # steps = time required by the algorithm.

• **Space:** # temporary variables.

**Example:** Our algorithm for finding (a + b) \* (c + d).

- Temporary variables =  $t_1$ ,  $t_2$  and  $t_3$ .
- : space required is 3.

- **Time:** # steps required by the algorithm to produce its output.
  - Assumption: Each elementary operation requires unit time.
  - ∴ # steps = time required by the algorithm.
- **Space:** # temporary variables.

**Example:** Our algorithm for finding (a + b) \* (c + d).

- Temporary variables =  $t_1$ ,  $t_2$  and  $t_3$ .
- .: space required is 3.
- Other resources: For example, power consumption is important for battery operated devices.

### **Books Consulted**

Chapter 2 of A Course on Cooperative Game Theory by Satya
R. Chakravarty, Palash Sarkar and Manipushpak Mitra.

Introduction to Algorithms: A Creative Approach by Udi Manber. Thank You for your kind attention!