

# Tutorial 4

## Linked Lists

## Lab 3 Solutions

Q1.) Write a `removeDuplicates()` function which takes a list and deletes any duplicate nodes from the list. Assume that the list is not sorted.

For example if the linked list is 12->11->12->21->41->43->21 then `removeDuplicates()` should convert the list to 12->11->21->41->43.

## A Simple Approach

1. Use 2 loops
2. Outer loop picks elements of linked list one by one
3. Inner loop compares the element picked by the outer loop with rest of the elements

```

void remove_duplicates() {
    Node ptr1 = null, ptr2 = null, dup =
null;
    ptr1 = head;

    /* Pick elements one by one */
    while (ptr1 != null && ptr1.next != null)
    {
        ptr2 = ptr1;

        /* Compare the picked element
with rest of the elements */

```

```

        while (ptr2.next != null) {

            /* If duplicate then delete it */
            if (ptr1.data == ptr2.next.data) {

                /* sequence of steps is
important here */
                dup = ptr2.next;
                ptr2.next = ptr2.next.next;
                System.gc();
            } else /* This is tricky */ {
                ptr2 = ptr2.next;
            }
        }
        ptr1 = ptr1.next;
    }
}

```

<https://www.geeksforgeeks.org/remove-duplicates-from-an-unsorted-linked-list/>

## Q2. Reverse alternate K nodes in a Singly Linked List

Example:

Inputs: 1->2->3->4->5->6->7->8->9->NULL and k = 3

Output: 3->2->1->4->5->6->9->8->7->NULL.

## Method

kAltReverse(struct node \*head, int k)

- 1) Reverse first k nodes.
- 2) In the modified list head points to the kth node. So change next of head to (k+1)th node
- 3) Move the current pointer to skip next k nodes.
- 4) Call the kAltReverse() recursively for rest of the  $n - 2k$  nodes.
- 5) Return new head of the list.

```

/* Reverses alternate k nodes and
   returns the pointer to the new head
   node */
Node kAltReverse(Node node, int k) {
    Node current = node;
    Node next = null, prev = null;
    int count = 0;

    /*1) reverse first k nodes of
    the linked list */
    while (current != null && count
    < k) {
        next = current.next;
        current.next = prev;
        prev = current;
        current = next;
        count++;
    }
    /* 2) Now head points to the kth node.
    So change next
       of head to (k+1)th node*/
    if (node != null) {
        node.next = current;
    }
}

```

```

/* 3) We do not want to reverse next k
nodes. So move the current
   pointer to skip next k nodes */
count = 0;
while (count < k - 1 && current
!= null) {
    current = current.next;
    count++;
}

/* 4) Recursively call for the
list starting from current->next.
And make rest of the list as
next of first node */
if (current != null) {
    current.next =
kAltReverse(current.next, k);
}

/* 5) prev is new head of the
input list */
return prev;
}

https://www.geeksforgeeks.org/reverse-alternate-k-nodes-in-a-singly-linked-list/

```



Q3.) Write a function to check if a singly linked list is palindrome or not

Example:

A->B->C->B->A

Palindrome

## Method

- 1) Get the middle of the linked list.
- 2) Reverse the second half of the linked list.
- 3) Check if the first half and second half are identical.
- 4) Construct the original linked list by reversing the second half again and attaching it back to the first half

## Q4.) Append one list at the end of another list

Try yourself [ Refer the lecture slides]

Q5.) Merge 2 sorted lists to get a single sorted list

## Q5.) Merge 2 sorted lists to get a single sorted list

```
Node merge( Node p, Node q ) {  
    if ( p == null)  
        return q;  
    else if ( q == null)  
        return p;  
    else if (p.item < q.item) {  
        p.next = merge( p.next, q );  
        return p;  
    }  
    else {  
        q.next = merge( p, q.next );  
        return q;  
    }  
}
```

## Homework Question

Pairwise swap elements of a given linked list

Input: 1->2->3->4->5

Output: 2->1->4->3->5,

Input: 1->2->3->4->5->6

Output: 2->1->4->3->6->5