

Exp.No: 6

Import a JSON file from the command line. Apply the following actions with the data present in the JSON file where, projection, aggregation, remove, count, limit, skip and sort

AIM:

To import a JSON file from the command line and apply the following actions with the data present in the JSON file where, projection, aggregation, remove, count, limit, skip and sort using jq tool.

PROCEDURE:

- Create a json file 'emp.json' and provide data in it.

```
[
  {
    "name" : "Anu",
    "age":12,
    "dept": "Computer",
    "salary":10000
  },
  {
    "name" : "Bob",
    "age" :14,
    "dept" : "HR",
    "salary":15000
  },
  {
    "name": "Jane Smith",
    "age": 25,
    "department": "IT",
    "salary": 60000
  },
  {
    "name": "Alice Johnson",
    "age": 35,
    "department": "Finance",
```


```
"salary": 70000
},
{
  "name": "Bob Brown",
  "age": 28,
  "department": "Marketing",
  "salary": 55000
}
]
```

- Open the command prompt.
- Navigate to the folder where emp.json is stored.
- Load and view the JSON data with jq.
- Use the jq commands for projection, aggregation, removal, counting, limiting, and sorting operations.

OUTPUT:

Running jq queries:


1. Projection:



A terminal window titled 'vboxuser@ubuntu-22: ~/JSON' showing a jq command and its output. The command is `jq ".[]" | {name: .name, salary: .salary}" /home/vboxuser/JSON/emp.json`. The output is a JSON array of objects, each containing 'name' and 'salary' fields. The objects are: {"name": "Anu", "salary": 10000}, {"name": "Bob", "salary": 15000}, {"name": "Jane Smith", "salary": 60000}, {"name": "Alice Johnson", "salary": 70000}, {"name": "Bob Brown", "salary": 55000}.

```
vboxuser@ubuntu-22: ~/JSON
vboxuser@ubuntu-22: ~
vboxuser@ubuntu-22: ~/JSON$ jq ".[]" | {name: .name, salary: .salary}" /home/vboxuser/JSON/emp.json
[
  {
    "name": "Anu",
    "salary": 10000
  },
  {
    "name": "Bob",
    "salary": 15000
  },
  {
    "name": "Jane Smith",
    "salary": 60000
  },
  {
    "name": "Alice Johnson",
    "salary": 70000
  },
  {
    "name": "Bob Brown",
    "salary": 55000
  }
]
vboxuser@ubuntu-22: ~/JSON$
```


2. Aggregation:



A terminal window titled 'vboxuser@ubuntu-22: ~/JSON' showing a jq command being executed. The command is 'jq "[.[] | .salary] | add" /home/vboxuser/JSON/emp.json'. The output is '210000'. The prompt is 'vboxuser@ubuntu-22:~/JSON\$'.

```
vboxuser@ubuntu-22: ~/JSON
vboxuser@ubuntu-22:~/JSON$ jq "[.[] | .salary] | add" /home/vboxuser/JSON/emp.json
210000
vboxuser@ubuntu-22:~/JSON$
```


3. Remove:



A terminal window titled 'vboxuser@ubuntu-22: ~/JSON' showing a jq command being executed. The command is 'jq "del(.[] | .age)" /home/vboxuser/JSON/emp.json'. The output is a JSON array of employee objects. The prompt is 'vboxuser@ubuntu-22:~/JSON\$'.


```
vboxuser@ubuntu-22:~/JSON$ jq "del(.[] | .age)" /home/vboxuser/JSON/emp.json
[
  {
    "name": "Anu",
    "dept": "Computer",
    "salary": 10000
  },
  {
    "name": "Bob",
    "dept": "HR",
    "salary": 15000
  },
  {
    "name": "Jane Smith",
    "department": "IT",
    "salary": 60000
  },
  {
    "name": "Alice Johnson",
    "department": "Finance",
    "salary": 70000
  },
  {
    "name": "Bob Brown",
    "department": "Marketing",
    "salary": 55000
  }
]
vboxuser@ubuntu-22:~/JSON$
```

4. Count:




```
vboxuser@ubuntu-22: ~/JSON
vboxuser@ubuntu-22: ~
vboxuser@ubuntu-22:~/JSON$ jq ". | length" /home/vboxuser/JSON/emp.json
5
vboxuser@ubuntu-22:~/JSON$
```

5. Limit:




```
vboxuser@ubuntu-22: ~/JSON
vboxuser@ubuntu-22: ~
vboxuser@ubuntu-22:~/JSON$ jq ".[0:3]" /home/vboxuser/JSON/emp.json
[
  {
    "name": "Anu",
    "age": 12,
    "dept": "Computer",
    "salary": 10000
  },
  {
    "name": "Bob",
    "age": 14,
    "dept": "HR",
    "salary": 15000
  },
  {
    "name": "Jane Smith",
    "age": 25,
    "department": "IT",
    "salary": 60000
  }
]
vboxuser@ubuntu-22:~/JSON$
```

6. Skip:



```
vboxuser@ubuntu-22: ~/JSON
vboxuser@ubuntu-22: ~
vboxuser@ubuntu-22:~/JSON$ jq ".[2:]" /home/vboxuser/JSON/emp.json
[
  {
    "name": "Jane Smith",
    "age": 25,
    "department": "IT",
    "salary": 60000
  },
  {
    "name": "Alice Johnson",
    "age": 35,
    "department": "Finance",
    "salary": 70000
  },
  {
    "name": "Bob Brown",
    "age": 28,
    "department": "Marketing",
    "salary": 55000
  }
]
vboxuser@ubuntu-22:~/JSON$
```

7. Sort:

A terminal window titled 'vboxuser@ubuntu-22: ~/JSON' shows a command being executed. The command is 'jq "sort_by(.age)" /home/vboxuser/JSON/emp.json'. The output is a JSON array of five employee objects, sorted by their 'age' property in ascending order. The employees are Anu (age 12), Bob (age 14), Jane Smith (age 25), Bob Brown (age 28), and Alice Johnson (age 35).

```
vboxuser@ubuntu-22: ~/JSON
vboxuser@ubuntu-22: ~
vboxuser@ubuntu-22: ~/JSON$ jq "sort_by(.age)" /home/vboxuser/JSON/emp.json
[
  {
    "name": "Anu",
    "age": 12,
    "dept": "Computer",
    "salary": 10000
  },
  {
    "name": "Bob",
    "age": 14,
    "dept": "HR",
    "salary": 15000
  },
  {
    "name": "Jane Smith",
    "age": 25,
    "department": "IT",
    "salary": 60000
  },
  {
    "name": "Bob Brown",
    "age": 28,
    "department": "Marketing",
    "salary": 55000
  },
  {
    "name": "Alice Johnson",
    "age": 35,
    "department": "Finance",
    "salary": 70000
  }
]
vboxuser@ubuntu-22: ~/JSON$
```

RESULT:

Thus to import a JSON file from the command line and apply the following actions with the data present in the JSON file where, projection, aggregation, remove, count, limit, skip and sort using jq tool is completed successfully