Text Generation using Long-Short Term Memory (LSTM) Model


1. Prepare & Explore Dataset

```
In [2]: ► from tensorflow import keras
            from keras.callbacks import LambdaCallback
            from keras.models import Sequential
            from keras.layers import Dense
            from keras.layers import LSTM
            from keras.optimizers import RMSprop
            from keras.utils.data_utils import get_file
            import numpy as np
            import random
            import sys
            import io
In [3]: ▶ #read the corpus dataset
            path = get_file(
                'nietzsche.txt'
                origin='https://s3.amazonaws.com/text-datasets/nietzsche.txt')
            with io.open(path, encoding='utf-8') as f:
               text = f.read().lower()
            print('corpus length:', len(text))
            Downloading data from https://s3.amazonaws.com/text-datasets/nietzsche.txt (https://s3.amazonaws.com/tex
            t-datasets/nietzsche.txt)
            606208/600901 [========== ] - 1s 1us/step
            corpus length: 600893
In [4]: ▶ #prepare charachter-based model
            chars = sorted(list(set(text)))
            print('total chars:', len(chars))
            char_indices = dict((c, i) for i, c in enumerate(chars))
            indices_char = dict((i, c) for i, c in enumerate(chars))
            total chars: 57
In [5]: ▶ # cut the text in semi-redundant sequences of maxlen characters
            maxlen = 40
            step = 3
            sentences = []
            next_chars = []
            for i in range(0, len(text) - maxlen, step):
                sentences.append(text[i: i + maxlen])
                next_chars.append(text[i + maxlen])
            print('nb sequences:', len(sentences))
            print('Vectorization...')
            x = np.zeros((len(sentences), maxlen, len(chars)), dtype=np.bool)
            y = np.zeros((len(sentences), len(chars)), dtype=np.bool)
            for i, sentence in enumerate(sentences):
                for t, char in enumerate(sentence):
                   x[i, t, char_indices[char]] = 1
               y[i, char_indices[next_chars[i]]] = 1
            nb sequences: 200285
            Vectorization...
```

2. Define the neural network architecture

```
In [6]:  # build the model: using single LSTM
    model = Sequential()
    model.add(LSTM(128, input_shape=(maxlen, len(chars))))
    model.add(Dense(len(chars), activation='softmax'))
```

3. Compile the neural net



4. Fit / train the neural net

```
In [9]: ► def sample(preds, temperature=1.0):
                # helper function to sample an index from a probability array
                preds = np.asarray(preds).astype('float64')
                preds = np.log(preds) / temperature
                exp_preds = np.exp(preds)
                preds = exp_preds / np.sum(exp_preds)
                probas = np.random.multinomial(1, preds, 1)
                return np.argmax(probas)
In [10]: ▶ def on_epoch_end(epoch, _):
                # Function invoked at end of each epoch. Prints generated text.
                print()
                print('---- Generating text after Epoch: %d' % epoch)
                start_index = random.randint(0, len(text) - maxlen - 1)
                for diversity in [0.2, 0.5, 1.0, 1.2]:
                    print('---- diversity:', diversity)
                    generated = ''
                    sentence = text[start_index: start_index + maxlen]
                    generated += sentence
                   print('---- Generating with seed: "' + sentence + '"')
                    sys.stdout.write(generated)
                    for i in range(400):
                       x_pred = np.zeros((1, maxlen, len(chars)))
                       for t, char in enumerate(sentence):
                           x_pred[0, t, char_indices[char]] = 1.
                       preds = model.predict(x_pred, verbose=0)[0]
                       next_index = sample(preds, diversity)
                       next_char = indices_char[next_index]
                       sentence = sentence[1:] + next char
                       sys.stdout.write(next_char)
                       sys.stdout.flush()
                    print()
model.fit(x, y,
                      batch_size=128,
                      epochs=12.
```

```
callbacks=[print_callback])
theoreminged, and popsticion and now a gradanity philosophy and
the prates the givent: by it courous
rigate, and rack are inactulton for ous aspen
truild or all repariting lowaldess these concratence, who ascompine even ans afcentity of the uest. n
ow religious impain for menity, -vonewantly good.
270 mube for a mesible that is make
who farthard see that chorost
---- diversity: 1.2
---- Generating with seed: "od."--this mode of reasoning savours of "
od."--this mode of reasoning savours of live:--this wouss
theolfy: cen supeiviag, but rache, this oul exferde, a certain and with
a consciouded, in even so eff-cceiry a hi
dlesless, anol only which is never tizgthl. therey reador and exmanterhasowitn meas! to weingry, come
no think
naclet,
or no cruak he is
coldo sucling schole be nehightly facce, were that the inserve, and they stard reselteng--wis, has, w
```