

Apply filters to SQL queries

Project description

Our Team is strengthening the security of our departments machines by updating their systems, below are the examples of doing security related tasks using SQL.

Retrieve after hours failed login attempts

The Team detected a potential security incident after the Office hours 18:00, so we used sql query to extract and filter the login attempts after the Office hours.

Query: `SELECT *`

`FROM log_in_attempts`

`WHERE login_time > '18:00' AND success = FALSE;`

Output:

```
MariaDB [organization]> clear
MariaDB [organization]> SELECT *
->
-> FROM log_in_attempts
->
-> WHERE login_time > '18:00' AND success = FALSE;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	aestrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0
127	abellmas	2022-05-09	21:20:51	CANADA	192.168.70.122	0
131	bisles	2022-05-09	20:03:55	US	192.168.113.171	0
155	cgriffin	2022-05-12	22:18:42	USA	192.168.236.176	0
160	jclark	2022-05-10	20:49:00	CANADA	192.168.214.49	0
199	yappiah	2022-05-11	19:34:48	MEXICO	192.168.44.232	0

```
19 rows in set (0.002 sec)

MariaDB [organization]>
```

This query uses WHERE, AND keywords, the first keyword is WHERE which is used for conditional statements like in this query 'WHERE login_time > '18:00' AND success = FALSE; ' all the conditional statements are written after WHERE, after WHERE '>' is an operator which used to get data greater than or less than the current data like in this query, finally 'AND' operator is a logical operator which connects two or more conditional statements like in this query, AND requires both of the statements to be true, other operators OR requires only one of them to be true, NOT negates True to False and vice versa. This query simply selects all the columns/fields from the 'log_in_attempts' table but we filtered using '>' operator and 'And' logical operator, 'login_time ? 18:00' means that this query will only return the login_time after or greater than 18:00 and the second part 'And success = FALSE '. So the whole part translates only return data which are after or greater 18:00 and their success ends up failing.

Retrieve login attempts on specific dates

The Team detected a suspicious event occurred on 2022-05-09. Now to investigate this event the team used sql query to extract data on this day and the day before.

Query:

```
SELECT *
```

```
FROM log_in_attempts
```

```
WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
```

Output:

```
MariaDB [organization]> SELECT *
->
-> FROM log_in_attempts
->
-> WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-09	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
30	yappiah	2022-05-09	03:22:22	MEX	192.168.124.48	1
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1
38	sbaelish	2022-05-09	14:40:01	USA	192.168.60.42	1
39	yappiah	2022-05-09	07:56:40	MEXICO	192.168.57.115	1
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
43	mcouliba	2022-05-08	02:35:34	CANADA	192.168.16.208	0
44	daquino	2022-05-08	07:02:35	CANADA	192.168.168.144	0
47	dkot	2022-05-08	05:06:45	US	192.168.233.24	1
49	asundara	2022-05-08	14:00:01	US	192.168.173.213	0
53	nmason	2022-05-08	11:51:38	CAN	192.168.133.188	1
56	acook	2022-05-08	04:56:30	CAN	192.168.209.130	1
58	ivelasco	2022-05-09	17:20:54	CAN	192.168.57.162	0
61	dtanaka	2022-05-09	09:45:18	USA	192.168.98.221	1
65	aalonso	2022-05-09	23:42:12	MEX	192.168.52.37	1
66	aestrada	2022-05-08	21:58:32	MEX	192.168.67.223	1
67	abernard	2022-05-09	11:53:41	MEX	192.168.118.29	1
68	mrah	2022-05-08	17:16:13	US	192.168.42.248	1
70	tmitchel	2022-05-09	10:55:17	MEXICO	192.168.87.199	1
71	mcouliba	2022-05-09	06:57:42	CAN	192.168.55.169	0
72	alevitsk	2022-05-08	12:09:10	CANADA	192.168.139.176	1
79	abernard	2022-05-09	11:41:15	MEX	192.168.158.170	0
80	cjackson	2022-05-08	02:18:10	CANADA	192.168.33.140	1
83	lrodriqu	2022-05-08	08:10:23	USA	192.168.67.69	1
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
90	gesparza	2022-05-09	00:49:05	CANADA	192.168.87.201	0
92	pwashing	2022-05-08	00:36:12	US	192.168.247.219	0

The query is almost the same as previous query but the difference is in filter part 'WHERE login_date = '2022-05-09' OR login_date = '2022-05-08'; this means that the query will filter and return all the data in the table from these two dates and nothing else. This makes it easy for us to see what happened in these two days without having to analyze one by one.

Retrieve login attempts outside of Mexico

Now the team has determined that this suspicious didn't come from Mexico, so we will use sql query to filter login attempts outside of Mexico.

Query:

```
SELECT *
FROM log_in_attempts
WHERE NOT country LIKE 'MEX%';
```

Output:

```
MariaDB [organization]> SELECT *
->
-> FROM log_in_attempts
->
-> WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
10	jrafael	2022-05-12	09:33:19	CANADA	192.168.228.221	0
11	sgilmore	2022-05-11	10:16:29	CANADA	192.168.140.81	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
13	mrah	2022-05-11	09:29:34	USA	192.168.246.135	1
14	sbaelish	2022-05-10	10:20:18	US	192.168.16.99	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
16	mcouliba	2022-05-11	06:44:22	CAN	192.168.172.189	1
17	pwashing	2022-05-11	02:33:02	USA	192.168.81.89	1
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
19	jhill	2022-05-12	13:09:04	US	192.168.142.245	1
21	iuduike	2022-05-11	17:50:00	US	192.168.131.147	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
29	bisles	2022-05-11	01:21:22	US	192.168.85.186	0
31	acook	2022-05-12	17:36:45	CANADA	192.168.58.232	0
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
33	zbernal	2022-05-11	02:52:10	US	192.168.72.59	1
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1
37	eraab	2022-05-10	06:03:41	CANADA	192.168.152.148	0
38	sbaelish	2022-05-09	14:40:01	USA	192.168.60.42	1
41	apatel	2022-05-10	17:39:42	CANADA	192.168.46.207	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
43	mcouliba	2022-05-08	02:35:34	CANADA	192.168.16.208	0
44	daquino	2022-05-08	07:02:35	CANADA	192.168.168.144	0
45	dtanaka	2022-05-11	10:28:54	US	192.168.223.157	1
46	eraab	2022-05-11	11:29:27	CAN	192.168.24.12	0

So we got 144 rows from this query. Now the filter part of the query 'WHERE NOT country LIKE 'MEX%';', in this part of the query we NOT logical operator and use LIKE (which is used when we need to use wildcards) with 'MEX%' where % is a wildcard so when we write 'MEX%' it means that return me any data that starts with word MEX followed by any character. So the entire filter part means to give me data which does NOT belong to Mexico.

Retrieve employees in Marketing

Our team wants to update security of a specific employee machines in the Marketing department where it is located in the East building using sql query.

Query:

```
SELECT *
```

```
FROM employees
```

WHERE department = 'Marketing' AND office LIKE 'East%';

Output:

```
MariaDB [organization]> SELECT *  
->  
-> FROM employees  
->  
-> WHERE department = 'Marketing' AND office LIKE 'East%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

```
7 rows in set (0.120 sec)
```

The filter part of this query 'WHERE department = 'Marketing' AND office LIKE 'East%';' is same as the previous query with LIKE and % wild card , this simply means give me data only where department is Marketing AND their office is located in the EAST building no matter what comes after EAST , simply the data should be from EAST.

Retrieve employees in Finance or Sales

Now after Marketing our teams want to update security on machines for employees in the Sales and Finance departments using sql query.

Query:

SELECT *

FROM employees

WHERE department = 'Finance' OR department = 'Sales';

Output:

```
MariaDB [organization]> SELECT *
->
-> FROM employees
->
-> WHERE department = 'Finance' OR department = 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1029	d336e475f676	ivelasco	Finance	East-156
1035	j236k303l245	bisles	Sales	South-171
1039	n253o917p623	cjackson	Sales	East-378
1041	p929q222r778	cgriffin	Sales	North-208
1044	s429t157u159	tbarnes	Finance	West-415
1045	t567u844v434	pwashing	Finance	East-115
1046	u429v921w138	daquino	Finance	West-280
1047	v109w587x644	cward	Finance	West-373
1048	w167x592y375	tmitchel	Finance	South-288
1049	NULL	jreckley	Finance	Central-295
1050	y132z930a114	csimmons	Finance	North-468
1057	f370g535h632	mscott	Sales	South-270
1062	k367l639m697	redwards	Finance	North-180
1063	l686m140n569	lpope	Sales	East-226
1066	o678p794q957	ttyrell	Sales	Central-444
1069	NULL	jpark	Finance	East-110
1071	t244u829v723	zdutchma	Sales	West-348
1072	u905v920w694	esmith	Sales	East-421
1076	y347z204a710	fgarcia	Finance	Central-270
1078	a667b270c984	sharley	Sales	North-418
1081	d647e310f618	qcorbit	Finance	South-290
1082	e840g812h544	rkeahi	Finance	West-165

This query is almost the same as the previous one. It simply connects two conditions using the AND logical operator so it means give me data from the Sales and Finance department.

Retrieve all employees not in IT

Now our team needs to update the machines for employees who are not in IT department using sql query.

Query:

```
SELECT *
```

```
FROM employees
```

```
WHERE NOT department = 'Information Technology';
```

Output:

```

MariaDB [organization]> SELECT *
->
-> FROM employees
->
-> WHERE NOT department = 'Information Technology';

```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1020	u899v381w363	arutley	Marketing	South-351
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1026	a998b568c863	apatel	Human Resources	West-320
1027	b806c503d354	mrah	Marketing	West-246
1028	c603d749e374	aestrada	Human Resources	West-121
1029	d336e475f676	ivelasco	Finance	East-156
1030	e391f189g913	mabadi	Marketing	West-375
1031	f419g188h578	dkot	Marketing	West-408
1034	i679j565k940	bsand	Human Resources	East-484
1035	j236k303l245	bisles	Sales	South-171
1036	k550l533m205	rjensen	Marketing	Central-239
1038	m873n636o225	btang	Human Resources	Central-260
1039	n253o917p623	cjackson	Sales	East-378
1040	o783p832q294	dtarly	Human Resources	East-237
1041	p929q222r778	cgriffin	Sales	North-208
1042	q175r338s833	acook	Human Resources	West-381
1044	s429t157u159	tbarnes	Finance	West-415
1045	t567u844v434	pwashing	Finance	East-115
1046	u429v921w138	daquino	Finance	West-280

It simply uses NOT with department='Information Technology' which means do not select data from the IT department other than this all data is acceptable.

Summary

So through SQL our team was able to perform security related tasks using filtering techniques like using WHERE for conditional statements , using logical operators AND,OR,NOT for connecting multiple conditions and with them used wildcards e.g 'LIKE MEX%, LIKE _a_'for more specific search.