



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	Earlier today our company experienced a DOS attack or ICMP flood attack. The attack compromised the company's internal network and all the critical network services suddenly stopped responding or crashed due to a flood of ICMP packets. The network resources became unavailable for the employees. The incident management team blocked the ICMP flood packets by blocking the unknown IP address which was sending them. Then they took all the non-critical network services offline, and finally restored critical network services. This took them two hours to resolve. The impact was not serious as no confidential information was stolen or leaked.
Identify	The malicious actor used ICMP flooding to overflow the internal network so this was a DOS attack. The DOS attack was done through an unconfigured firewall.
Protect	The incident response team addressed the unconfigured firewall by implementing a rate limiting rule to limit the incoming ICMP packets and furthermore they implemented an IDS or IPS system to filter out suspicious traffic.
Detect	The incident response team implemented Network monitoring software like SIEM tools wireshark, tcpdumps etc, to detect abnormal traffic patterns. The

	response team also implemented source IP verification configuration on the firewall so that spoofed IP addresses on incoming traffic can be detected easily.
Respond	For future incidents, the team can create subnets for the internal network like if one part is compromised then other will not be affected. This will help because we can easily isolate it without interrupting normal business operations. Network logs or audits or employee monitoring on a regular basis can help us identify any abnormal behavior on the traffic or within the organization. Regular back up of data of the internal network so that data loss cannot occur.
Recover	To recover from an ICMP flood attack we need to first isolate the compromised network, then look for the root cause which was an unconfigured firewall. Implement rate limiting to stop flood attacks. All non-critical services should be offline. After the attack is completely neutralized the critical services should be restored then all non-critical services should be brought back.

Reflections/Notes: Monitoring on employees is also important because disgruntled employees can cause these attacks. System up-to-date, regular audits of pentesting to discover new vulnerabilities.