

# Python - Magic Methods

Magic methods in Python are the special methods which add "magic" to your class. Magic methods are not meant to be invoked directly by you, but the invocation happens internally from the class on a certain action. For example, when you add two numbers using the + operator, internally, the `__add__()` method will be called.

Built-in classes in Python define many magic methods. Use the `dir()` function to see the number of magic methods inherited by a class. For example, the following lists all the attributes and methods defined in the `int` class.

```
>>> dir(int)
['_abs_', '__add__', '__and__', '__bool__', '__ceil__',
'__class__', '__delattr__', '__dir__', '__divmod__', '__doc__',
'__eq__', '__float__', '__floor__', '__floordiv__',
'__format__', '__ge__', '__getattribute__', '__getnewargs__',
'__gt__', '__hash__', '__index__', '__init__',
'__init_subclass__', '__int__', '__invert__', '__le__',
'__lshift__', '__lt__', '__mod__', '__mul__', '__ne__',
'__neg__', '__new__', '__or__', '__pos__', '__pow__',
'__radd__', '__rand__', '__rdivmod__', '__reduce__',
'__reduce_ex__', '__repr__', '__rfloordiv__', '__rlshift__',
'__rmod__', '__rmul__', '__ror__', '__round__', '__rpow__',
'__rrshift__', '__rshift__', '__rsub__', '__rtruediv__',
'__rxor__', '__setattr__', '__sizeof__', '__str__', '__sub__',
'__subclasshook__', '__truediv__', '__trunc__', '__xor__',
'bit_length', 'conjugate', 'denominator', 'from_bytes', 'imag',
'numerator', 'real', 'to_bytes']
```

As you can see above, the `int` class includes various magic methods surrounded by double underscores. For example, the `__add__` method is a magic method which gets called when we add two numbers using the + operator. Consider the following example.

```
>>> num=10
>>> num + 5
15
>>> num.__add__(5)
15
```

As you can see, when you do `num+10`, the + operator calls the `__add__(10)` method. You can also call `num.__add__(5)` directly which will give the same result. However, as mentioned before, magic methods are not meant to be called directly, but internally, through some other methods or actions.

Magic methods are most frequently used to define overloaded behaviours of predefined operators in Python. For instance, arithmetic operators by default operate upon numeric operands. This

means that numeric objects must be used along with operators like +, -, \*, /, etc. The + operator is also defined as a concatenation operator in string, list and tuple classes. We can say that the + operator is overloaded.

In order to make the overloaded behaviour available in your own custom class, the corresponding magic method should be overridden. For example, in order to use the + operator with objects of a user-defined class, it should include the `__add__()` method.

Let's see how to implement and use some of the important magic methods.

## **`__new__()` method**

Languages such as Java and C# use the new operator to create a new instance of a class. In Python the `__new__()` magic method is implicitly called before the `__init__()` method. The `__new__()` method returns a new object, which is then initialized by `__init__()`.

Example: `__new__()`

```
class employee:
    def __new__(cls):
        print ("__new__ magic method is called")
        inst = object.__new__(cls)
        return inst
    def __init__(self):
        print ("__init__ magic method is called")
        self.name='Satya'
```

The above example will produce the following output when you create an instance of the Employee class.

```
>>> e1=employee()
__new__ magic method is called
__init__ magic method is called
```

Thus, the `__new__()` method is called before the `__init__()` method.

## **`__str__()` method**

Another useful magic method is `__str__()`. It is overridden to return a printable string representation of any user defined class. We have seen `str()` built-in function which returns a string from the object parameter. For example, `str(12)` returns '12'. When invoked, it calls the `__str__()` method in the int class.

```
>>> num=12
>>> str(num)
'12'
>>> #This is equivalent to
```

```
>>> int.__str__(num)
'12'
```

Let us now override the `__str__()` method in the employee class to return a string representation of its object.

Example:

```
class employee:
    def __init__(self):
        self.name='Swati'
        self.salary=10000
    def __str__(self):
        return 'name='+self.name+' salary=$'+str(self.salary)
```

See how the `str()` function internally calls the `__str__()` method defined in the employee class. This is why it is called a magic method!

```
>>> e1=employee()
>>> print(e1)
name=Swati salary=$10000
```

## **`__add__()` method**

In following example, a class named distance is defined with two instance attributes - ft and inch. The addition of these two distance objects is desired to be performed using the overloading + operator.

To achieve this, the magic method `__add__()` is overridden, which performs the addition of the ft and inch attributes of the two objects. The `__str__()` method returns the object's string representation.

Example: `__add__()`

```
class distance:
    def __init__(self, x=None, y=None):
        self.ft=x
        self.inch=y
    def __add__(self, x):
        temp=distance()
        temp.ft=self.ft+x.ft
        temp.inch=self.inch+x.inch
        if temp.inch>=12:
            temp.ft+=1
            temp.inch-=12
        return temp
    def __str__(self):
        return 'ft:'+str(self.ft)+' in: '+str(self.inch)
```

Run the above Python script to verify the overloaded operation of the + operator.

```
>>> d1=distance(3,10)
>>> d2=distance(4,4)
>>> print("d1= {} d2={}".format(d1, d2))
d1= ft:3 in: 10 d2=ft:4 in: 4
>>>d3=d1+d2
>>>print(d3)
ft:8 in: 2
```

## **\_\_ge\_\_() method**

The following method is added in the distance class to overload the >= operator.

Example: \_\_ge\_\_()

```
class distance:
    def __init__(self, x=None,y=None):
        self.ft=x
        self.inch=y
        def __ge__(self, x):
            val1=self.ft*12+self.inch
            val2=x.ft*12+x.inch
            if val1>=val2:
                return True
            else:
                return False
```

This method gets invoked when the >= operator is used and returns True or False. Accordingly, the appropriate message can be displayed

```
>>>d1=distance(2,1)
>>>d2=distance(4,10)
>>>d1>=d2
False
```

## **Important Magic Methods**

The following tables list important magic methods in Python 3.

### **Initialization and Construction**

### **Description**

<code>__new__(cls, other)</code>	To get called in an object's instantiation.
<code>__init__(self, other)</code>	To get called by the <code>__new__</code> method.
<code>__del__(self)</code>	Destructor method.

### **Unary operators and functions**

### **Description**

<code>__pos__(self)</code>	To get called for unary positive e.g. +someobject.
<code>__neg__(self)</code>	To get called for unary negative e.g. -someobject.
<code>__abs__(self)</code>	To get called by built-in abs() function.

**Initialization and Construction****Description**

<code>__invert__(self)</code>	To get called for inversion using the ~ operator.
<code>__round__(self,n)</code>	To get called by built-in round() function.
<code>__floor__(self)</code>	To get called by built-in math.floor() function.
<code>__ceil__(self)</code>	To get called by built-in math.ceil() function.
<code>__trunc__(self)</code>	To get called by built-in math.trunc() function.

**Augmented  
Assignment****Description**

<code>__iadd__(self, other)</code>	To get called on addition with assignment e.g. <code>a += b</code> .
<code>__isub__(self, other)</code>	To get called on subtraction with assignment e.g. <code>a -= b</code> .
<code>__imul__(self, other)</code>	To get called on multiplication with assignment e.g. <code>a *= b</code> .
<code>__ifloordiv__(self, other)</code>	To get called on integer division with assignment e.g. <code>a //= b</code> .
<code>__idiv__(self, other)</code>	To get called on division with assignment e.g. <code>a /= b</code> .
<code>__itruediv__(self, other)</code>	To get called on true division with assignment
<code>__imod__(self, other)</code>	To get called on modulo with assignment e.g. <code>a %= b</code> .
<code>__ipow__(self, other)</code>	To get called on exponents with assignment e.g. <code>a **= b</code> .
<code>__lshift__(self, other)</code>	To get called on left bitwise shift with assignment e.g. <code>a &lt;&lt;= b</code> .
<code>__rshift__(self, other)</code>	To get called on right bitwise shift with assignment e.g. <code>a &gt;&gt;= b</code> .
<code>__iand__(self, other)</code>	To get called on bitwise AND with assignment e.g. <code>a &amp;= b</code> .
<code>__ior__(self, other)</code>	To get called on bitwise OR with assignment e.g. <code>a  = b</code> .
<code>__ixor__(self, other)</code>	To get called on bitwise XOR with assignment e.g. <code>a ^= b</code> .

**Type Conversion Magic Methods****Description**

<code>__int__(self)</code>	To get called by built-in int() method to convert a type to an int.
<code>__float__(self)</code>	To get called by built-in float() method to convert a type to float.
<code>__complex__(self)</code>	To get called by built-in complex() method to convert a type to complex.
<code>__oct__(self)</code>	To get called by built-in oct() method to convert a type to octal.
<code>__hex__(self)</code>	To get called by built-in hex() method to convert a type to hexadecimal.
<code>__index__(self)</code>	To get called on type conversion to an int when the object is used in a slice expression.
<code>__trunc__(self)</code>	To get called from math.trunc() method.

**String Magic Methods****Description**

<b>String Magic Methods</b>	<b>Description</b>
<code>__str__(self)</code>	To get called by built-in <code>str()</code> method to return a string representation of a type.
<code>__repr__(self)</code>	To get called by built-in <code>repr()</code> method to return a machine readable representation of a type.
<code>__unicode__(self)</code>	To get called by built-in <code>unicode()</code> method to return an unicode string of a type.
<code>__format__(self, formatstr)</code>	To get called by built-in <code>string.format()</code> method to return a new style of string.
<code>__hash__(self)</code>	To get called by built-in <code>hash()</code> method to return an integer.
<code>__nonzero__(self)</code>	To get called by built-in <code>bool()</code> method to return True or False.
<code>__dir__(self)</code>	To get called by built-in <code>dir()</code> method to return a list of attributes of a class.
<code>__sizeof__(self)</code>	To get called by built-in <code>sys.getsizeof()</code> method to return the size of an object.

<b>Attribute Magic Methods</b>	<b>Description</b>
<code>__getattr__(self, name)</code>	Is called when the accessing attribute of a class that does not exist.
<code>__setattr__(self, name, value)</code>	Is called when assigning a value to the attribute of a class.
<code>__delattr__(self, name)</code>	Is called when deleting an attribute of a class.

<b>Operator Magic Methods</b>	<b>Description</b>
<code>__add__(self, other)</code>	To get called on add operation using <code>+</code> operator
<code>__sub__(self, other)</code>	To get called on subtraction operation using <code>-</code> operator.
<code>__mul__(self, other)</code>	To get called on multiplication operation using <code>*</code> operator.
<code>__floordiv__(self, other)</code>	To get called on floor division operation using <code>//</code> operator.
<code>__div__(self, other)</code>	To get called on division operation using <code>/</code> operator.
<code>__mod__(self, other)</code>	To get called on modulo operation using <code>%</code> operator.
<code>__pow__(self, other[, modulo])</code>	To get called on calculating the power using <code>**</code> operator.
<code>__lt__(self, other)</code>	To get called on comparison using <code>&lt;</code> operator.
<code>__le__(self, other)</code>	To get called on comparison using <code>&lt;=</code> operator.
<code>__eq__(self, other)</code>	To get called on comparison using <code>==</code> operator.
<code>__ne__(self, other)</code>	To get called on comparison using <code>!=</code> operator.
<code>__ge__(self, other)</code>	To get called on comparison using <code>&gt;=</code> operator.

Thus, you can use the appropriate magic methods to add various functionalities in your custom class.