

```
import numpy as np
import cv2
import scipy.io
import os
from numpy.linalg import norm
from matplotlib import pyplot as plt
from numpy.linalg import det
from numpy.linalg import inv
from scipy.linalg import rq
from numpy.linalg import svd
import matplotlib.pyplot as plt
import numpy as np
import math
import random
import sys
from scipy import ndimage, spatial
from tqdm.notebook import tqdm, trange

import torch
import torch.nn as nn
import torch.optim as optim
from torch.optim import lr_scheduler
from torch.autograd import Variable
import torchvision
from torchvision import datasets, models, transforms
from torch.utils.data import Dataset, DataLoader, ConcatDataset
from skimage import io, transform, data
from torchvision import transforms, utils
import numpy as np
import math
import glob
import matplotlib.pyplot as plt
import time
import os
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

```
from os.path import exists
import pandas as pd
import PIL
import random
from google.colab import drive
from sklearn.metrics.cluster import completeness_score
from sklearn.cluster import KMeans
from tqdm import tqdm, tqdm_notebook
from functools import partial
from torchsummary import summary
from torchvision.datasets import ImageFolder
```

```
from torch.utils.data.sampler import SubsetRandomSampler
```

```
from google.colab import drive
```

```
# This will prompt for authorization.  
drive.mount('/content/drive')
```

Drive already mounted at /content/drive; to attempt to forcibly remount, call drive.mount(..., force_remount=True)

```
!pip install opencv-python==3.4.2.17  
!pip install opencv-contrib-python==3.4.2.17
```

```
Requirement already satisfied: opencv-python==3.4.2.17 in /usr/local/lib/python3.7/dist-packages  
Requirement already satisfied: numpy>=1.14.5 in /usr/local/lib/python3.7/dist-packages (from opencv-python==3.4.2.17)  
Requirement already satisfied: opencv-contrib-python==3.4.2.17 in /usr/local/lib/python3.7/dist-packages (from opencv-contrib-python==3.4.2.17)  
Requirement already satisfied: numpy>=1.14.5 in /usr/local/lib/python3.7/dist-packages (from opencv-contrib-python==3.4.2.17)
```

```
class Image:  
    def __init__(self, img, position):
```

```
        self.img = img  
        self.position = position
```

```
inlier_matchset = []
```

```
def features_matching(a, keypointlength, threshold):
```

```
    #threshold=0.2
```

```
    bestmatch=np.empty((keypointlength),dtype= np.int16)
```

```
    img1index=np.empty((keypointlength),dtype=np.int16)
```

```
    distance=np.empty((keypointlength))
```

```
    index=0
```

```
    for j in range(0,keypointlength):
```

```
        #For a descriptor fa in Ia, take the two closest descriptors fb1 and fb2 in Ib
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
itemindex1 = listx.index(minval1)          #index of min val  
itemindex2 = listx.index(minval2)          #index of second min value  
ratio=minval1/minval2                      #Ratio Test
```

```
if ratio<threshold:
```

```
    #Low distance ratio: fb1 can be a good match
```

```
    bestmatch[index]=itemindex1
```

```
    distance[index]=minval1
```

```
    img1index[index]=j
```

```
    index=index+1
```

```
return [cv2.DMatch(img1index[i],bestmatch[i].astype(int),distance[i]) for i in range(0,ind
```

```

def compute_Homography(im1_pts,im2_pts):
    """
    im1_pts and im2_pts are 2xn matrices with
    4 point correspondences from the two images
    """
    num_matches=len(im1_pts)
    num_rows = 2 * num_matches
    num_cols = 9
    A_matrix_shape = (num_rows,num_cols)
    A = np.zeros(A_matrix_shape)
    a_index = 0
    for i in range(0,num_matches):
        (a_x, a_y) = im1_pts[i]
        (b_x, b_y) = im2_pts[i]
        row1 = [a_x, a_y, 1, 0, 0, 0, -b_x*a_x, -b_x*a_y, -b_x] # First row
        row2 = [0, 0, 0, a_x, a_y, 1, -b_y*a_x, -b_y*a_y, -b_y] # Second row

        # place the rows in the matrix
        A[a_index] = row1
        A[a_index+1] = row2

        a_index += 2

    U, s, Vt = np.linalg.svd(A)

    #s is a 1-D array of singular values sorted in descending order
    #U, Vt are unitary matrices
    #Rows of Vt are the eigenvectors of A^TA.
    #Columns of U are the eigenvectors of AA^T.
    H = np.eye(3)
    H = Vt[-1].reshape(3,3) # take the last row of the Vt matrix
    return H

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

plt.imshow(cv2.cvtColor(img, cv2.COLOR_BGR2RGB))
plt.show()

```

```

def get_inliers(f1, f2, matches, H, RANSACthresh):
    inlier_indices = []
    for i in range(len(matches)):
        queryInd = matches[i].queryIdx
        trainInd = matches[i].trainIdx

```

```
#queryInd = matches[i][0]
#trainInd = matches[i][1]

queryPoint = np.array([f1[queryInd].pt[0], f1[queryInd].pt[1], 1]).T
trans_query = H.dot(queryPoint)

comp1 = [trans_query[0]/trans_query[2], trans_query[1]/trans_query[2]] # normalize with r
comp2 = np.array(f2[trainInd].pt)[:2]

if(np.linalg.norm(comp1-comp2) <= RANSACthresh): # check against threshold
    inlier_indices.append(i)
return inlier_indices
```

```
def RANSAC_alg(f1, f2, matches, nRANSAC, RANSACthresh):
```

```
minMatches = 4
nBest = 0
best_inliers = []
H_estimate = np.eye(3,3)
global inlier_matchset
inlier_matchset=[]
for iteration in range(nRANSAC):

    #Choose a minimal set of feature matches.
    matchSample = random.sample(matches, minMatches)

    #Estimate the Homography implied by these matches
    im1_pts=np.empty((minMatches,2))
    im2_pts=np.empty((minMatches,2))
    for i in range(0,minMatches):
        m = matchSample[i]
        im1_pts[i] = f1[m.queryIdx].pt
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
# Calculate the inliers for the H
inliers = get_inliers(f1, f2, matches, H_estimate, RANSACthresh)

# if the number of inliers is higher than previous iterations, update the best estimate
if len(inliers) > nBest:
    nBest= len(inliers)
    best_inliers = inliers

print("Number of best inliers",len(best_inliers))
```

```

for i in range(len(best_inliers)):
    inlier_matchset.append(matches[best_inliers[i]])

# compute a homography given this set of matches
im1_pts=np.empty((len(best_inliers),2))
im2_pts=np.empty((len(best_inliers),2))
for i in range(0,len(best_inliers)):
    m = inlier_matchset[i]
    im1_pts[i] = f1[m.queryIdx].pt
    im2_pts[i] = f2[m.trainIdx].pt
    #im1_pts[i] = f1[m[0]].pt
    #im2_pts[i] = f2[m[1]].pt

M=compute_Homography(im1_pts,im2_pts)
return M, best_inliers

```

```

files_all=[]
for file in os.listdir("/content/drive/MyDrive/RGB-img/img"):
    if file.endswith(".JPG"):
        files_all.append(file)

files_all.sort()
folder_path = '/content/drive/MyDrive/RGB-img/img/'

centre_file = folder_path + files_all[15]
left_files_path_rev = []
right_files_path = []

for file in files_all[:61]:
    left_files_path_rev.append(folder_path + file)

left_files_path = left_files_path_rev[::-1]

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

```

from PIL import Image
def get_exif(filename):
    image = Image.open(filename)
    image.verify()
    return image._getexif()

def get_labeled_exif(exif):
    labeled = {}
    for (key, val) in exif.items():
        labeled[TAGS.get(key)] = val

```

```
return labeled
```

```
def get_geotagging(exif):
    if not exif:
        raise ValueError("No EXIF metadata found")

    geotagging = {}
    for (idx, tag) in TAGS.items():
        if tag == 'GPSInfo':
            if idx not in exif:
                raise ValueError("No EXIF geotagging found")

            for (key, val) in GPSTAGS.items():
                if key in exif[idx]:
                    geotagging[val] = exif[idx][key]
    return geotagging
```

```
def get_decimal_from_dms(dms, ref):
```

```
    degrees = dms[0][0] / dms[0][1]
    minutes = dms[1][0] / dms[1][1] / 60.0
    seconds = dms[2][0] / dms[2][1] / 3600.0
```

```
    if ref in ['S', 'W']:
        degrees = -degrees
        minutes = -minutes
        seconds = -seconds
```

```
    return round(degrees + minutes + seconds, 5)
```

```
def get_coordinates(geotags):
```

```
    lat = get_decimal_from_dms(geotags['GPSLatitude'], geotags['GPSLatitudeRef'])
```

```
    lon = get_decimal_from_dms(geotags['GPSLongitude'], geotags['GPSLongitudeRef'])
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

(idsize))

```
images_left_bgr = []
images_right_bgr = []
```

```
images_left = []
images_right = []
```

```
for file in tqdm(left_files_path):
    left_image_sat= cv2.imread(file)
    lab = cv2.cvtColor(left_image_sat, cv2.COLOR_BGR2LAB)
    lab[...,0] = clahe.apply(lab[...,0])
```

```

left_image_sat = cv2.cvtColor(lab, cv2.COLOR_LAB2BGR)
left_img = cv2.resize(left_image_sat, None, fx=0.35, fy=0.35, interpolation = cv2.INTER_CUBIC
images_left.append(cv2.cvtColor(left_img, cv2.COLOR_BGR2GRAY).astype('float32')/255.)
images_left_bgr.append(left_img)

for file in tqdm(right_files_path):
    right_image_sat= cv2.imread(file)
    lab = cv2.cvtColor(right_image_sat, cv2.COLOR_BGR2LAB)
    lab[...,0] = clahe.apply(lab[...,0])
    right_image_sat = cv2.cvtColor(lab, cv2.COLOR_LAB2BGR)
    right_img = cv2.resize(right_image_sat, None, fx=0.35,fy=0.35, interpolation = cv2.INTER_CUBIC
images_right.append(cv2.cvtColor(right_img, cv2.COLOR_BGR2GRAY).astype('float32')/255.)
images_right_bgr.append(right_img)

100%|██████████| 61/61 [01:06<00:00,  1.10s/it]
100%|██████████| 61/61 [01:06<00:00,  1.09s/it]

```

```

images_left_bgr_no_enhance = []
images_right_bgr_no_enhance = []

```

```

for file in tqdm(left_files_path):
    left_image_sat= cv2.imread(file)
    left_img = cv2.resize(left_image_sat, None, fx=0.35, fy=0.35, interpolation = cv2.INTER_CUBIC
images_left_bgr_no_enhance.append(left_img)

```

```

for file in tqdm(right_files_path):
    right_image_sat= cv2.imread(file)
    right_img = cv2.resize(right_image_sat, None, fx=0.35,fy=0.35, interpolation = cv2.INTER_CUBI
images_right_bgr_no_enhance.append(right_img)

```

```

100%|██████████| 61/61 [00:25<00:00,  2.39it/s]
100%|██████████| 61/61 [00:25<00:00,  2.42it/s]

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

self.sift_extractor = cv2.DescriptorExtractor_create()
self.sift = cv2.xfeatures2d.SIFT_create()

def compute(self, image, kps, eps=1e-7):
    # compute SIFT descriptors
    (kps, desc) = self.sift.compute(image, kps)

    # if there are no keypoints or descriptors, return an empty tuple
    if len(kps) == 0:
        return ([], None)

    # apply the Hellinger kernel by first L1-normalizing, taking the

```

```

# square-root, and then L2-normalizing
descs /= (np.linalg.norm(descs, axis=0, ord=2) + eps)
descs /= (descs.sum(axis=0) + eps)
descs = np.sqrt(descs)
#descs /= (np.linalg.norm(descs, axis=0, ord=2) + eps)

# return a tuple of the keypoints and descriptors
return (kps, descs)

sift = cv2.xfeatures2d.SIFT_create()
rootsift = RootSIFT()
keypoints_all_left_rootsift = []
descriptors_all_left_rootsift = []
points_all_left_rootsift=[]

keypoints_all_right_rootsift = []
descriptors_all_right_rootsift = []
points_all_right_rootsift=[]

for imgs in tqdm(images_left_bgr):
    kpt = sift.detect(imgs,None)
    kpt,descrip = rootsift.compute(imgs, kpt)
    keypoints_all_left_rootsift.append(kpt)
    descriptors_all_left_rootsift.append(descrip)
    points_all_left_rootsift.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))

for imgs in tqdm(images_right_bgr):
    kpt = sift.detect(imgs,None)
    kpt,descrip = rootsift.compute(imgs, kpt)
    keypoints_all_right_rootsift.append(kpt)
    descriptors_all_right_rootsift.append(descrip)
    points_all_right_rootsift.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))
```

100% |██████████| 61/61 [03:18<00:00, 3.25s/it]
100% |██████████| 60/60 [03:14<00:00, 3.24s/it+1]

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

sift = cv2.xfeatures2d.SIFT_create()
keypoints_all_left_sift = []
descriptors_all_left_sift = []
points_all_left_sift=[]

keypoints_all_right_sift = []
descriptors_all_right_sift = []
points_all_right_sift=[]

for imgs in tqdm(images_left_bgr):
    knt = sift.detect(imgs,None)
```

```

kpt, descrip = sift.compute(imgs, kpt)
keypoints_all_left_sift.append(kpt)
descriptors_all_left_sift.append(descrip)
points_all_left_sift.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))


for imgs in tqdm(images_right_bgr):
    kpt = sift.detect(imgs, None)
    kpt, descrip = sift.compute(imgs, kpt)
    keypoints_all_right_sift.append(kpt)
    descriptors_all_right_sift.append(descrip)
    points_all_right_sift.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))
```

100%|██████████| 61/61 [03:22<00:00, 3.32s/it]
100%|██████████| 61/61 [03:09<00:00, 3.11s/it]

```

def compute_homography_fast(matched_pts1, matched_pts2, thresh=4):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
                                    cv2.RANSAC, ransacReprojThreshold =thresh)
    inliers = inliers.flatten()
    return H, inliers

def compute_homography_fast_other(matched_pts1, matched_pts2):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

def get_Hmatrix(imgs, keypts, pts, descriptors, ratio=0.8, thresh=4, disp=False):
    FLANN_INDEX_KDTREE = 2
    index_params = dict(algorithm=FLANN_INDEX_KDTREE, trees=5)
    search_params = dict(checks=50)
    flann = cv2.FlannBasedMatcher(index_params, search_params)
    #flann = cv2.BFMatcher()

    lff1 = np.float32(descriptors[0])
    lff = np.float32(descriptors[1])
```

```
matches_lf1_lf = cv2.BFMatcher(cv2.NORM_HAMMING, crossCheck=True)
```

```
print("\nNumber of matches",len(matches_lf1_lf))
```

```
matches_4 = []
ratio = ratio
# loop over the raw matches
for m in matches_lf1_lf:
    # ensure the distance is within a certain ratio of each
    # other (i.e. Lowe's ratio test)
    if len(m) == 2 and m[0].distance < m[1].distance * ratio:
        #matches_1.append((m[0].trainIdx, m[0].queryIdx))
        matches_4.append(m[0])
```

```
print("Number of matches After Lowe's Ratio",len(matches_4))
```

```
matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
...  
# Estimate homography 1
```

```
#Compute H1
```

```
# Estimate homography 1
```

```
#Compute H1
```

```
imm1_pts=np.empty((len(matches_4),2))
imm2_pts=np.empty((len(matches_4),2))
for i in range(0,len(matches_4)):
    m = matches_4[i]
    (a_x, a_y) = keypts[0][m.queryIdx].pt
    (b_x, b_y) = keypts[1][m.trainIdx].pt
    imm1_pts[i]=(a_x, a_y)
    imm2_pts[i]=(b_x, b_y)
```

```
H=compute_Homography(imm1_pts,imm2_pts)
```

```
#Robustly estimate Homography 1 using RANSAC
```

```
inlier_matchset=RANSAC(inliers=100, keypoints[0], keypoints[1], matches_4, nRANSAC=1000, RANSACthresh=6)
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
print("Number of Robust matches",len(inlier_matchset))
print("\n")
...
if len(inlier_matchset)<50:
    matches_4 = []
    ratio = 0.67
    # loop over the raw matches
    for m in matches_lf1_lf:
        # ensure the distance is within a certain ratio of each
        # other (i.e. Lowe's ratio test)
        if len(m) == 2 and m[0].distance < m[1].distance * ratio:
```

```

#matches_1.append((m[0].trainIdx, m[0].queryIdx))
matches_4.append(m[0])
print("Number of matches After Lowe's Ratio New",len(matches_4))

matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
Hn,inliers = compute_homography_fast_other(imm1_pts,imm2_pts)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches New",len(inlier_matchset))
print("\n")
'''

#H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
#Hn=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1500, RANSACthresh=6)

#global inlier_matchset

if disp==True:
    dispimg1=cv2.drawMatches(imgs[0], keypts[0], imgs[1], keypts[1], inlier_matchset, None,fl
    displayplot(dispimg1,'Robust Matching between Reference Image and Right Image ')

return Hn/Hn[2,2], len(matches_lf1_lf), len(inlier_matchset)

```

```

from functools import partial
from tqdm import tqdm
tqdm = partial(tqdm, position=0, leave=True)

```

```
print(left_files_path)
```

```
['/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0061.JPG', '/content/drive/MyDrive/
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

H_left_root sift = []
H_right_root sift = []

num_matches_root sift = []
num_good_matches_root sift = []

for j in tqdm(range(len(images_left))):
    if j==len(images_left)-1:
        break

```

6/25/2021

120_image_stitching_with_mser+sift_agast+sift.ipynb - Colaboratory

```
H_a,matches,gd_matches = get_Hmatrix(images_left_bgr[j:j+2][::-1],keypoints_all_left_roots)
H_left_root sift.append(H_a)
num_matches_root sift.append(matches)
num_good_matches_root sift.append(gd_matches)
```

```
for j in tqdm(range(len(images_right))):
```

```
    if j==len(images_right)-1:
        break
```

```
H_a,matches,gd_matches = get_Hmatrix(images_right_bgr[j:j+2][::-1],keypoints_all_right_root)
H_right_root sift.append(H_a)
#num_matches.append(matches)
#num_good_matches.append(gd_matches)
```

```
Number of matches 44723
```

```
Number of matches After Lowe's Ratio 1476
```

```
Number of Robust matches 703
```

```
40%|██████| 24/60 [02:52<05:24, 9.00s/it]
```

```
Number of matches 41727
```

```
Number of matches After Lowe's Ratio 3019
```

```
Number of Robust matches 1279
```

```
42%|██████| 25/60 [03:04<05:41, 9.77s/it]
```

```
Number of matches 46928
```

```
Number of matches After Lowe's Ratio 456
```

```
Number of Robust matches 159
```

```
43%|██████| 26/60 [03:16<05:52, 10.38s/it]
```

```
Number of matches 39889
```

```
Number of matches After Lowe's Ratio 2699
```

```
Number of Robust matches 1143
```

```
45%|██████| 27/60 [03:26<05:37, 10.23s/it]
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
Number of matches 33707
```

```
Number of matches After Lowe's Ratio 3668
```

```
Number of Robust matches 1386
```

```
48%|██████| 29/60 [03:42<04:40, 9.05s/it]
```

```
Number of matches 32337
```

```
Number of matches After Lowe's Ratio 3243
```

```
Number of Robust matches 1282
```

```
50%|██████| 30/60 [03:49<04:15, 8.50s/it]
```

```
Number of matches 31634
```

Number of matches After Lowe's Ratio 3377

Number of Robust matches 1319

52%|██████ | 31/60 [03:56<03:56, 8.15s/it]

Number of matches 31779

Number of matches After Lowe's Ratio 3825

Number of Robust matches 1533

53%|██████ | 32/60 [04:04<03:43, 7.99s/it]

Number of matches 32533

Number of matches After Lowe's Ratio 6199

Number of Robust matches 2625

55%|██████ | 33/60 [04:12<03:37, 8.06s/it]

```
H_left_sift = []
```

```
H_right_sift = []
```

```
num_matches_sift = []
```

```
num_good_matches_sift = []
```

```
for j in tqdm(range(len(images_left))):
```

```
    if j==len(images_left)-1:
```

```
        break
```

```
H_a,matches,gd_matches = get_Hmatrix(images_left_bgr[j:j+2][::-1],keypoints_all_left_sift[j]
H_left_sift.append(H_a)
#num_matches.append(matches)
#num_good_matches.append(gd_matches)
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
H_a,matches,gd_matches = get_Hmatrix(images_right_bgr[j:j+2][::-1],keypoints_all_right_sift
H_right_sift.append(H_a)
#num_matches.append(matches)
#num_good_matches.append(gd_matches)
```

39%|██████ | 24/61 [02:51<05:20, 8.67s/it]

Number of matches 44723

Number of matches After Lowe's Ratio 281

Number of Robust matches 179

41% | [██████] | 25/61 [03:02<05:39, 9.43s/it]

Number of matches 41727

Number of matches After Lowe's Ratio 507

Number of Robust matches 231

43% | [██████] | 26/61 [03:13<05:40, 9.73s/it]

Number of matches 46928

Number of matches After Lowe's Ratio 40

Number of Robust matches 40

44% | [██████] | 27/61 [03:24<05:45, 10.17s/it]

Number of matches 39889

Number of matches After Lowe's Ratio 537

Number of Robust matches 268

46% | [██████] | 28/61 [03:33<05:26, 9.88s/it]

Number of matches 38074

Number of matches After Lowe's Ratio 1359

Number of Robust matches 681

48% | [██████] | 29/61 [03:41<04:59, 9.36s/it]

Number of matches 33707

Number of matches After Lowe's Ratio 1185

Number of Robust matches 669

49% | [██████] | 30/61 [03:48<04:28, 8.66s/it]

Number of matches 32337

Number of matches After Lowe's Ratio 970

Number of Robust matches 488

51% | [██████] | 31/61 [03:55<04:02, 8.07s/it]

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

Number of matches 31779

Number of matches After Lowe's Ratio 1392

Number of Robust matches 668

54% | [██████] | 33/61 [04:08<03:26, 7.36s/it]

Number of matches 32533

Number of matches After Lowe's Ratio 2590

Number of Robust matches 1357

```
def warpImages(images_left, images_right,H_left,H_right):
```

```
#img1-centre,img2-left,img3-right

h, w = images_left[0].shape[:2]

pts_left = []
pts_right = []

pts_centre = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)

for j in range(len(H_left)):
    pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
    pts_left.append(pts)

for j in range(len(H_right)):
    pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
    pts_right.append(pts)

pts_left_transformed=[]
pts_right_transformed=[]

for j,pts in enumerate(pts_left):
    if j==0:
        H_trans = H_left[j]
    else:
        H_trans = H_trans@H_left[j]
    pts_ = cv2.perspectiveTransform(pts, H_trans)
    pts_left_transformed.append(pts_)

for j,pts in enumerate(pts_right):
    if j==0:
        H_trans = H_right[j]
    else:
        H_trans = H_trans@H_right[j]
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

```
#pts = np.concatenate((pts1, pts2_), axis=0)

pts_concat = np.concatenate((pts_centre,np.concatenate(np.array(pts_left_transformed),axis=0),pts_right))

[xmin, ymin] = np.int32(pts_concat.min(axis=0).ravel() - 0.5)
[xmax, ymax] = np.int32(pts_concat.max(axis=0).ravel() + 0.5)
t = [-xmin, -ymin]
Ht = np.array([[1, 0, t[0]], [0, 1, t[1]], [0, 0, 1]]) # translate

print('Step2:Done')
```

```

return xmax,xmin,ymax,ymin,t,h,w,Ht

def final_steps_left(images_left,images_right,H_left,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):
    warp_imgs_left = []

    for j,H in enumerate(H_left):
        if j==0:
            H_trans = Ht@H
        else:
            H_trans = H_trans@H
        result = cv2.warpPerspective(images_left[j+1], H_trans, (xmax-xmin, ymax-ymin))

        if j==0:
            result[t[1]:h+t[1], t[0]:w+t[0]] = images_left[0]

        warp_imgs_left.append(result)

    print('Step31:Done')

    return warp_imgs_left

def final_steps_right(images_left,images_right,H_left,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):
    warp_imgs_right = []

    for j,H in enumerate(H_right):
        if j==0:
            H_trans = Ht@H
        else:
            H_trans = H_trans@H
    
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

(xmax-xmin, ymax-ymin))

[View runtime logs](#)

```

    return warp_imgs_right

def final_steps_union(warp_imgs_left,warp_imgs_right):
    #Union

    warp_images_all = warp_imgs_left + warp_imgs_right

    warp_img_init = warp_images_all[0]

```

```
#warp_final_all=[]

for j,warp_img in enumerate(warp_images_all):
    if j==len(warp_images_all)-1:
        break
    black_pixels = np.where((warp_img_init[:, :, 0] == 0) & (warp_img_init[:, :, 1] == 0) &
                           warp_img_init[:, :, 2] == 0)
    warp_img_init[black_pixels] = warp_images_all[j+1][black_pixels]

#warp_final = np.maximum(warp_img_init,warp_images_all[j+1])
#warp_img_init = warp_final
#warp_final_all.append(warp_final)

print('Step4:Done')

return warp_img_init

def final_steps_left_union(images_left,H_left,xmax,xmin,ymax,ymin,t,h,w,Ht):

    for j,H in enumerate(H_left):
        if j==0:
            H_trans = Ht@H
        else:
            H_trans = H_trans@H
        input_img = images_left[j+1]
        result = np.zeros((ymax-ymin,xmax-xmin,3),dtype='uint8')

        cv2.warpPerspective(src = np.uint8(input_img), M = H_trans, dsize = (xmax-xmin, ymax-ymin))
        warp_img_init_curr = result

        if j==0:
            Your session crashed after using all available
            RAM. If you are interested in access to high-
            RAM runtimes, you may want to check out
            Colab Pro.
            X
            View runtime logs
            }) & (warp_img_init_prev[:, :, :
```

warp_img_init_prev[black_pixels] = warp_img_init_curr[black_pixels]

print('Step31:Done')

return warp_img_init_prev

```
def final_steps_right_union(warp_img_prev,images_right,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):

    for j,H in enumerate(H_right):
        if j==0:
            H_trans = Ht@H
```

```

    H_trans = H_trans@H
else:
    H_trans = H_trans@H
input_img = images_right[j+1]
result = np.zeros((ymax-ymin,xmax-xmin,3),dtype='uint8')

cv2.warpPerspective(src = np.uint8(input_img), M = H_trans, dsize = (xmax-xmin, ymax-ym
warp_img_init_curr = result

black_pixels = np.where((warp_img_prev[:, :, 0] == 0) & (warp_img_prev[:, :, 1] == 0) &
warp_img_prev[black_pixels] = warp_img_init_curr[black_pixels]

print('Step32:Done')

return warp_img_prev

```

```
xmax,xmin,ymax,ymin,t,h,w,Ht = warpnImages(images_left_bgr_no_enhance, images_right_bgr_no_en
```

```
Step1:Done
Step2:Done
```

```
warp_imgs_left = final_steps_left_union(images_left_bgr_no_enhance,H_left_root sift,xmax,xmin,
```

```
warp_imgs_all_root sift = final_steps_right_union(warp_imgs_left,images_right_bgr_no_enhance,H_
```

```
Step32:Done
```

```
fig,ax=plt.subplots()
fig.set_size_inches(20,20)
ax.imshow(cv2.cvtColor(warp_imgs_all_root sift , cv2.COLOR_BGR2RGB))
ax.set_title('120-Images Mosaic-ROOTSIFT')
```


Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)


Text(0.5, 1.0, '120-Images Mosaic-ROOTSIFT')

120-Images Mosaic-ROOTSIFT



Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)



Step1:Done
Step2:Done

```
warp_imgs_left = final_steps_left_union(images_left_bgr_no_enhance,H_left_sift,xmax,xmin,ymax
```

Step31:Done

```
warp_imgs_all_sift = final_steps_right_union(warp_imgs_left,images_right_bgr_no_enhance,H_rig
```

Step32:Done


```
fig,ax =plt.subplots()  
fig.set_size_inches(20,20)  
ax.imshow(cv2.cvtColor(warp_imgs_all_sift , cv2.COLOR_BGR2RGB))  
ax.set_title('120-Images Mosaic-SIFT')
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

```
Text(0.5, 1.0, '120-Images Mosaic-SIFT')
```



```
akaze = cv2.AKAZE_create()
```

```
keypoints_all_left_akaze = []
descriptors_all_left_akaze = []
points_all_left_akaze = []
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
for imgs in tqdm(images_left_bgr):
    kpt = akaze.detect(imgs, None)
    kpt, descrip = akaze.compute(imgs, kpt)
    keypoints_all_left_akaze.append(kpt)
    descriptors_all_left_akaze.append(descrip)
    points_all_left_akaze.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))
```

```
for imgs in tqdm(images_right_bgr):
    kpt = akaze.detect(imgs, None)
    kpt, descrip = akaze.compute(imgs, kpt)
    keypoints_all_right_akaze.append(kpt)
    descriptors_all_right_akaze.append(descrip)
```

```

descriptors_all_right_akaze.append(descrip)
points_all_right_akaze.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))


100%|██████████| 61/61 [01:29<00:00, 1.47s/it]
100%|██████████| 61/61 [01:28<00:00, 1.45s/it]

```

```

def compute_homography_fast(matched_pts1, matched_pts2, thresh=4):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
                                    cv2.RANSAC, ransacReprojThreshold =thresh)
    inliers = inliers.flatten()
    return H, inliers

def compute_homography_fast_other(matched_pts1, matched_pts2):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
                                    0)
    inliers = inliers.flatten()
    return H, inliers

```

```

def get_Hmatrix(imgs, keypoints, pts, descriptors, ratio=0.8, thresh=4, disp=False):
    FLANN_INDEX_KDTREE = 2
    index_params = dict(algorithm=FLANN_INDEX_KDTREE, trees=5)
    search_params = dict(checks=50)
    flann = cv2.FlannBasedMatcher(index_params, search_params)
    #flann = cv2.BFMatcher()

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

matches_lf1_lf = flann.knnMatch(lff1, lff, k=2)

print("\nNumber of matches", len(matches_lf1_lf))

matches_4 = []
ratio = ratio
# loop over the raw matches
for m in matches_lf1_lf:
    # ensure the distance is within a certain ratio of each
    # other (i.e. Lowe's ratio test)
    if len(m) == 2 and m[0].distance < m[1].distance * ratio:

```

```

#matches_1.append((m[0].trainIdx, m[0].queryIdx))
matches_4.append(m[0])

print("Number of matches After Lowe's Ratio",len(matches_4))

matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
...
# Estimate homography 1
#Compute H1
# Estimate homography 1
#Compute H1
imm1_pts=np.empty((len(matches_4),2))
imm2_pts=np.empty((len(matches_4),2))
for i in range(0,len(matches_4)):
    m = matches_4[i]
    (a_x, a_y) = keypts[0][m.queryIdx].pt
    (b_x, b_y) = keypts[1][m.trainIdx].pt
    imm1_pts[i]=(a_x, a_y)
    imm2_pts[i]=(b_x, b_y)
H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
Hn, best_inliers=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1000, RANSACthresh=6)
...

```

```

Hn,inliers = compute_homography_fast(imm1_pts,imm2_pts,thresh)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches",len(inlier_matchset))
print("\n")
...
if len(inlier_matchset)<50:
    matches_4 = []

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

if len(m) == 2 and m[0].distance < m[1].distance * ratio:
    #matches_1.append((m[0].trainIdx, m[0].queryIdx))
    matches_4.append(m[0])
print("Number of matches After Lowe's Ratio New",len(matches_4))

```

```

matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
Hn,inliers = compute_homography_fast_other(imm1_pts,imm2_pts)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches New",len(inlier_matchset))

```

```

print("\n")
'''

#H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
#Hn=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1500, RANSACthresh=6)

#global inlier_matchset

if disp==True:
    dispimg1=cv2.drawMatches(imgs[0], keypts[0], imgs[1], keypts[1], inlier_matchset, None,f1
    displayplot(dispimg1,'Robust Matching between Reference Image and Right Image ')

return Hn/Hn[2,2], len(matches_lf1_lf), len(inlier_matchset)

from functools import partial
from tqdm import tqdm
tqdm = partial(tqdm, position=0, leave=True)

print(left_files_path)

['/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0064.JPG', '/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0063.JPG']

print(right_files_path)

['/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0063.JPG', '/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0064.JPG']

H_left_akaze = []
H_right_akaze = []

num_matches_akaze = 11

Your session crashed after using all available
RAM. If you are interested in access to high-
RAM runtimes, you may want to check out
Colab Pro.
X
View runtime logs

H_a,matches,gd_matches = get_Hmatrix(images_left_bgr[j:j+2][::-1],keypoints_all_left_akaze[
H_left_akaze.append(H_a)
num_matches_akaze.append(matches)
num_good_matches_akaze.append(gd_matches)

for j in tqdm(range(len(images_right))):
    if j==len(images_right)-1:
        break

H_a,matches,gd_matches = get_Hmatrix(images_right_bgr[j:j+2][::-1],keypoints_all_right_akaze

```

```
H_right_akaze.append(H_a)
#num_matches.append(matches)
#num_good_matches.append(gd_matches)

39%|██████| 24/61 [00:48<01:33, 2.52s/it]
Number of matches 24561
Number of matches After Lowe's Ratio 1224
Number of Robust matches 427
```

```
41%|██████| 25/61 [00:51<01:28, 2.45s/it]
Number of matches 22164
Number of matches After Lowe's Ratio 2307
Number of Robust matches 889
```

```
43%|██████| 26/61 [00:53<01:22, 2.35s/it]
Number of matches 20348
Number of matches After Lowe's Ratio 2242
Number of Robust matches 922
```

```
44%|██████| 27/61 [00:55<01:14, 2.18s/it]
Number of matches 19519
Number of matches After Lowe's Ratio 1953
Number of Robust matches 863
```

```
46%|██████| 28/61 [00:56<01:07, 2.04s/it]
Number of matches 20911
Number of matches After Lowe's Ratio 2006
Number of Robust matches 690
```

```
48%|██████| 29/61 [00:58<01:03, 2.00s/it]
Number of matches 20565
Number of matches After Lowe's Ratio 1822
Number of Robust matches 767
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
51%|██████| 31/61 [01:02<00:58, 1.96s/it]
Number of matches 22441
Number of matches After Lowe's Ratio 1806
Number of Robust matches 762
```

```
52%|██████| 32/61 [01:04<00:57, 1.99s/it]
Number of matches 21870
Number of matches After Lowe's Ratio 3182
Number of Robust matches 1483
```

54% |██████| 33/61 [01:06<00:55, 1.98s/it]

Number of matches 20671

Number of matches After Lowe's Ratio 2331

Number of Robust matches 1177

```
def warpnImages(images_left, images_right,H_left,H_right):
    #img1-centre,img2-left,img3-right

    h, w = images_left[0].shape[:2]

    pts_left = []
    pts_right = []

    pts_centre = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)

    for j in range(len(H_left)):
        pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
        pts_left.append(pts)

    for j in range(len(H_right)):
        pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
        pts_right.append(pts)

    pts_left_transformed=[]
    pts_right_transformed=[]

    for j,pts in enumerate(pts_left):
        if j==0:
            H_trans = H_left[j]
        else:
            H_trans = H_trans@H_left[j]
        nts_ = cv2.perspectiveTransform(nts_, H_trans)
        pts_left_transformed.append(nts_)

    Your session crashed after using all available
    RAM. If you are interested in access to high-
    RAM runtimes, you may want to check out
    Colab Pro.

    else:
        H_trans = H_trans@H_right[j]
        pts_ = cv2.perspectiveTransform(pts_, H_trans)
        pts_right_transformed.append(pts_)

    print('Step1:Done')

    #pts = np.concatenate((pts1, pts2_), axis=0)
```

[View runtime logs](#)

```

pts_concat = np.concatenate((pts_centre,np.concatenate(np.array(pts_left_transformed),axis=0),axis=0)

[xmin, ymin] = np.int32(pts_concat.min(axis=0).ravel() - 0.5)
[xmax, ymax] = np.int32(pts_concat.max(axis=0).ravel() + 0.5)
t = [-xmin, -ymin]
Ht = np.array([[1, 0, t[0]], [0, 1, t[1]], [0, 0, 1]]) # translate

print('Step2:Done')

```

```
return xmax,xmin,ymax,ymin,t,h,w,Ht
```

```
def final_steps_left(images_left,images_right,H_left,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):
```

```
warp_imgs_left = []
```

```
for j,H in enumerate(H_left):
```

```
if j==0:
```

```
    H_trans = H@H
```

```
else:
```

```
    H_trans = H_trans@H
```

```
result = cv2.warpPerspective(images_left[j+1], H_trans, (xmax-xmin, ymax-ymin))
```

```
if j==0:
```

```
    result[t[1]:h+t[1], t[0]:w+t[0]] = images_left[0]
```

```
warp_imgs_left.append(result)
```

```
print('Step31:Done')
```

```
return warp_imgs_left
```

```
def final_steps_right(images_left,images_right,H_left,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

```
else:
```

```
    H_trans = H_trans@H
```

```
result = cv2.warpPerspective(images_right[j+1], H_trans, (xmax-xmin, ymax-ymin))
```

```
warp_imgs_right.append(result)
```

```
print('Step32:Done')
```

```
return warp_imgs_right
```

```
def final_steps_union(warp_imgs_left,warp_imgs_right):
```

```
#Union
```

```
warp_images_all = warp_imgs_left + warp_imgs_right

warp_img_init = warp_images_all[0]

#warp_final_all=[]

for j,warp_img in enumerate(warp_images_all):
    if j==len(warp_images_all)-1:
        break
    black_pixels = np.where((warp_img_init[:, :, 0] == 0) & (warp_img_init[:, :, 1] == 0) &

    warp_img_init[black_pixels] = warp_images_all[j+1][black_pixels]

#warp_final = np.maximum(warp_img_init,warp_images_all[j+1])
#warp_img_init = warp_final
#warp_final_all.append(warp_final)

print('Step4:Done')

return warp_img_init
```

```
def final_steps_left_union(images_left,H_left,xmax,xmin,ymax,ymin,t,h,w,Ht):
```

```
for j,H in enumerate(H_left):
    if j==0:
        H_trans = Ht@H
    else:
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
if j==0:
    result[t[1]:h+t[1], t[0]:w+t[0]] = images_left[0]
    warp_img_init_prev = result
    continue

black_pixels = np.where((warp_img_init_prev[:, :, 0] == 0) & (warp_img_init_prev[:, :, 1] == 0))
warp_img_init_prev[black_pixels] = warp_img_init_curr[black_pixels]

print('Step31:Done')
```

```
return warp_img_init_prev
```

```
def final_steps_right_union(warp_img_prev,images_right,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):

    for j,H in enumerate(H_right):
        if j==0:
            H_trans = Ht@H
        else:
            H_trans = H_trans@H
        input_img = images_right[j+1]
        result = np.zeros((ymax-ymin,xmax-xmin,3),dtype='uint8')

        cv2.warpPerspective(src = np.uint8(input_img), M = H_trans, dsize = (xmax-xmin, ymax-ym
        warp_img_init_curr = result

        black_pixels = np.where((warp_img_prev[:, :, 0] == 0) & (warp_img_prev[:, :, 1] == 0) &
        warp_img_prev[black_pixels] = warp_img_init_curr[black_pixels]

    print('Step32:Done')

    return warp_img_prev
```

```
xmax,xmin,ymax,ymin,t,h,w,Ht = warpnImages(images_left_bgr_no_enhance, images_right_bgr_no_en
```

```
Step1:Done  
Step2:Done
```

```
warp_imgs_left = final_steps_left_union(images_left_bgr_no_enhance,H_left_akaze,xmax,xmin,ymax,y
```

```
warp_imgs_all_akaze = final_steps_right_union(warp_imgs_left,images_right_bgr_no_enhance,H_right_a
```


Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
)  
ax.set_title('101-Images Mosaic-AKAZE')
```


Text(0.5, 1.0, '101-Images Mosaic-AKAZE')

101-Images Mosaic-AKAZE



Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)



```

Threshl=60;
Octaves=8;
#PatternScales=1.0f;
brisk = cv2.BRISK_create(Threshl,Octaves)

keypoints_all_left_brisk = []
descriptors_all_left_brisk = []
points_all_left_brisk=[]

keypoints_all_right_brisk = []
descriptors_all_right_brisk = []
points_all_right_brisk=[]

for imgs in tqdm(images_left_bgr):
    kpt = brisk.detect(imgs,None)
    kpt,descrip = brisk.compute(imgs, kpt)
    keypoints_all_left_brisk.append(kpt)
    descriptors_all_left_brisk.append(descrip)
    points_all_left_brisk.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))

for imgs in tqdm(images_right_bgr):
    kpt = brisk.detect(imgs,None)
    kpt,descrip = brisk.compute(imgs, kpt)
    keypoints_all_right_brisk.append(kpt)
    descriptors_all_right_brisk.append(descrip)
    points_all_right_brisk.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))


100%|██████████| 61/61 [01:04<00:00, 1.05s/it]
100%|██████████| 61/61 [00:55<00:00, 1.10it/s]

```

```

def compute_homography_fast(matched_pts1, matched_pts2, thresh=4):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

cv2.RANSAC, ransacReprojThreshold =thresh)
inliers = inliers.flatten()
return H, inliers

```

```

def compute_homography_fast_other(matched_pts1, matched_pts2):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

```

```

# Estimate the homography between the matches using RANSAC
H, inliers = cv2.findHomography(matched_pts1,
                                matched_pts2,

```

```

        0)

inliers = inliers.flatten()
return H, inliers

def get_Hmatrix(imgs, keypoints, pts, descriptors, ratio=0.8, thresh=4, disp=False):
    FLANN_INDEX_KDTREE = 2
    index_params = dict(algorithm=FLANN_INDEX_KDTREE, trees=5)
    search_params = dict(checks=50)
    flann = cv2.FlannBasedMatcher(index_params, search_params)
    #flann = cv2.BFM Matcher()

    lff1 = np.float32(descriptors[0])
    lff = np.float32(descriptors[1])

    matches_lf1_lf = flann.knnMatch(lff1, lff, k=2)

    print("\nNumber of matches", len(matches_lf1_lf))

    matches_4 = []
    ratio = ratio
    # loop over the raw matches
    for m in matches_lf1_lf:
        # ensure the distance is within a certain ratio of each
        # other (i.e. Lowe's ratio test)
        if len(m) == 2 and m[0].distance < m[1].distance * ratio:
            #matches_1.append((m[0].trainIdx, m[0].queryIdx))
            matches_4.append(m[0])

    print("Number of matches After Lowe's Ratio", len(matches_4))

    matches_idx = np.array([m.queryIdx for m in matches_4])
    imm1_pts = np.array([keypoints[0][idx].pt for idx in matches_idx])
    matches_idx = np.array([m.trainIdx for m in matches_4])
    imm2_pts = np.array([keypoints[1][idx].pt for idx in matches_idx])

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out Colab Pro. X
```

[View runtime logs](#)

```

imm1_pts=np.empty((len(matches_4),2))
imm2_pts=np.empty((len(matches_4),2))
for i in range(0,len(matches_4)):
    m = matches_4[i]
    (a_x, a_y) = keypoints[0][m.queryIdx].pt
    (b_x, b_y) = keypoints[1][m.trainIdx].pt
    imm1_pts[i]=(a_x, a_y)
    imm2_pts[i]=(b_x, b_y)
H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
Hn, best_inliers=RANSAC_alg(keypoints[0] ,keypoints[1], matches_4, nRANSAC=1000, RANSACthresh=6)
```

```

...
Hn,inliers = compute_homography_fast(imm1_pts,imm2_pts,thresh)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches",len(inlier_matchset))
print("\n")
...
if len(inlier_matchset)<50:
    matches_4 = []
    ratio = 0.67
    # loop over the raw matches
    for m in matches_lf1_lf:
        # ensure the distance is within a certain ratio of each
        # other (i.e. Lowe's ratio test)
        if len(m) == 2 and m[0].distance < m[1].distance * ratio:
            #matches_1.append((m[0].trainIdx, m[0].queryIdx))
            matches_4.append(m[0])
    print("Number of matches After Lowe's Ratio New",len(matches_4))

    matches_idx = np.array([m.queryIdx for m in matches_4])
    imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
    matches_idx = np.array([m.trainIdx for m in matches_4])
    imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
    Hn,inliers = compute_homography_fast_other(imm1_pts,imm2_pts)
    inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
    print("Number of Robust matches New",len(inlier_matchset))
    print("\n")
...
#H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
#Hn=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1500, RANSACthresh=6)

#global inlier_matchset

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

from functools import partial
from tqdm import tqdm
tqdm = partial(tqdm, position=0, leave=True)

print(left_files_path)

['/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0064.JPG', '/content/drive/MyDrive/

```

```
print(right_files_path)

['/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0063.JPG', '/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0064.JPG']

H_left_brisk = []
H_right_brisk = []

num_matches_brisk = []
num_good_matches_brisk = []

for j in tqdm(range(len(images_left))):
    if j==len(images_left)-1:
        break

    H_a,matches,gd_matches = get_Hmatrix(images_left_bgr[j:j+2][::-1],keypoints_all_left_brisk[0])
    H_left_brisk.append(H_a)
    num_matches_brisk.append(matches)
    num_good_matches_brisk.append(gd_matches)

for j in tqdm(range(len(images_right))):
    if j==len(images_right)-1:
        break

    H_a,matches,gd_matches = get_Hmatrix(images_right_bgr[j:j+2][::-1],keypoints_all_right_brisk[0])
    H_right_brisk.append(H_a)
    #num_matches.append(matches)
    #num_good_matches.append(gd_matches)

    39%|██████| 24/61 [01:36<03:15, 5.29s/it]
    Number of matches 36711
    Number of matches After Lowe's Ratio 5239
    Number of Robust matches 735
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
43%|██████| 26/61 [01:45<02:48, 4.82s/it]
Number of matches 32321
Number of matches After Lowe's Ratio 6686
Number of Robust matches 1366
```

```
44%|██████| 27/61 [01:49<02:31, 4.46s/it]
Number of matches 28452
Number of matches After Lowe's Ratio 5818
Number of Robust matches 1052
```

46% |███████ | 28/61 [01:52<02:12, 4.02s/it]

Number of matches 26073

Number of matches After Lowe's Ratio 5197

Number of Robust matches 650

48% |███████ | 29/61 [01:54<01:55, 3.60s/it]

Number of matches 27594

Number of matches After Lowe's Ratio 5471

Number of Robust matches 763

49% |███████ | 30/61 [01:57<01:44, 3.38s/it]

Number of matches 29922

Number of matches After Lowe's Ratio 7017

Number of Robust matches 1670

51% |███████ | 31/61 [02:00<01:41, 3.38s/it]

Number of matches 31761

Number of matches After Lowe's Ratio 5996

Number of Robust matches 827

52% |███████ | 32/61 [02:04<01:40, 3.46s/it]

Number of matches 28598

Number of matches After Lowe's Ratio 6297

Number of Robust matches 1768

54% |███████ | 33/61 [02:08<01:38, 3.51s/it]

Number of matches 32677

Number of matches After Lowe's Ratio 6856

Number of Robust matches 1469

```
def warpnImages(images_left, images_right,H_left,H_right):
    #img1-centre,img2-left,img3-right
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
pts_centre = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)

for j in range(len(H_left)):
    pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
    pts_left.append(pts)

for j in range(len(H_right)):
    pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
    pts_right.append(pts)

pts_left_transformed=[ ]
```

```
pts_right_transformed=[]
```

```
for j,pts in enumerate(pts_left):
    if j==0:
        H_trans = H_left[j]
    else:
        H_trans = H_trans@H_left[j]
    pts_ = cv2.perspectiveTransform(pts, H_trans)
    pts_left_transformed.append(pts_)
```

```
for j,pts in enumerate(pts_right):
    if j==0:
        H_trans = H_right[j]
    else:
        H_trans = H_trans@H_right[j]
    pts_ = cv2.perspectiveTransform(pts, H_trans)
    pts_right_transformed.append(pts_)
```

```
print('Step1:Done')
```

```
#pts = np.concatenate((pts1, pts2_), axis=0)
```

```
pts_concat = np.concatenate((pts_centre,np.concatenate(np.array(pts_left_transformed),axis=0),np.array(pts_right_transformed),axis=0))
[xmin, ymin] = np.int32(pts_concat.min(axis=0).ravel() - 0.5)
[xmax, ymax] = np.int32(pts_concat.max(axis=0).ravel() + 0.5)
t = [-xmin, -ymin]
Ht = np.array([[1, 0, t[0]], [0, 1, t[1]], [0, 0, 1]]) # translate
```

```
print('Step2:Done')
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

max,xmin,ymax,ymin,t,h,w,Ht):

```
warp_imgs_left = []
```

```
for j,H in enumerate(H_left):
    if j==0:
        H_trans = Ht@H
    else:
        H_trans = H_trans@H
    result = cv2.warpPerspective(images_left[j+1], H_trans, (xmax-xmin, ymax-ymin))

    if j==0:
```

```

result[t[1]:h+t[1], t[0]:w+t[0]] = images_left[0]

warp_imgs_left.append(result)

print('Step31:Done')

return warp_imgs_left

def final_steps_right(images_left,images_right,H_left,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):
    warp_imgs_right = []

    for j,H in enumerate(H_right):
        if j==0:
            H_trans = Ht@H
        else:
            H_trans = H_trans@H
        result = cv2.warpPerspective(images_right[j+1], H_trans, (xmax-xmin, ymax-ymin))

        warp_imgs_right.append(result)

    print('Step32:Done')

    return warp_imgs_right

def final_steps_union(warp_imgs_left,warp_imgs_right):
    #Union

    warp_images_all = warp_imgs_left + warp_imgs_right

    warp_img_init = warp_images_all[0]

```

```
#warp_final_all=[]
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

(warp_img_init[:, :, 1] == 0) &

```

warp_img_init[black_pixels] = warp_images_all[j+1][black_pixels]

#warp_final = np.maximum(warp_img_init,warp_images_all[j+1])
#warp_img_init = warp_final
#warp_final_all.append(warp_final)

print('Step4:Done')

return warp_img_init

```

```

def final_steps_left_union(images_left,H_left,xmax,xmin,ymax,ymin,t,h,w,Ht):

    for j,H in enumerate(H_left):
        if j==0:
            H_trans = Ht@H
        else:
            H_trans = H_trans@H
        input_img = images_left[j+1]
        result = np.zeros((ymax-ymin,xmax-xmin,3),dtype='uint8')

        cv2.warpPerspective(src = np.uint8(input_img), M = H_trans, dsize = (xmax-xmin, ymax-ym
warp_img_init_curr = result

        if j==0:
            result[t[1]:h+t[1], t[0]:w+t[0]] = images_left[0]
            warp_img_init_prev = result
            continue

        black_pixels = np.where((warp_img_init_prev[:, :, 0] == 0) & (warp_img_init_prev[:, :, 1] == 0) & (warp_img_init_prev[:, :, 2] == 0))
        warp_img_init_prev[black_pixels] = warp_img_init_curr[black_pixels]

        print('Step31:Done')

    return warp_img_init_prev

def final_steps_right_union(warp_img_prev,images_right,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):

    for j,H in enumerate(H_right):
        if j==0:
            H_trans = Ht@H
        else:

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

```

        result = np.zeros((ymax-ymin,xmax-xmin,3),dtype='uint8')
        warp_img_init_curr = result

        black_pixels = np.where((warp_img_prev[:, :, 0] == 0) & (warp_img_prev[:, :, 1] == 0) &
warp_img_prev[black_pixels] = warp_img_init_curr[black_pixels]

        print('Step32:Done')

    return warp_img_prev

```

Step1:Done

Step2:Done

```
warp_imgs_left = final_steps_left_union(images_left_bgr_no_enhance,H_left_brisk,xmax,xmin,yma
```

```
warp_imgs_all_brisk = final_steps_right_union(warp_imgs_left, images_right_bgr_no_enhance,H_r
```

Step32:Done


```
fig,ax=plt.subplots()  
fig.set_size_inches(20,20)  
ax.imshow(cv2.cvtColor(warp_imgs_all_brisk , cv2.COLOR_BGR2RGB))  
ax.set_title('61-Images Mosaic-BRISK')
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

```
Text(0.5, 1.0, '61-Images Mosaic-BRISK')
```



```
mser = cv2.MSER_create()
sift = cv2.xfeatures2d.SIFT_create()

keypoints_all_left_mser = []
descriptors_all_left_mser = []
points_all_left_mser = []
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
for imgs in tqdm(images_left_bgr_no_enhance):
    kpt = mser.detect(imgs, None)
    kpt, descrip = sift.compute(imgs, kpt)
    keypoints_all_left_mser.append(kpt)
    descriptors_all_left_mser.append(descrip)
    points_all_left_mser.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))

for imgs in tqdm(images_right_bgr_no_enhance):
    kpt = mser.detect(imgs, None)
    kpt, descrip = sift.compute(imgs, kpt)
    keypoints_all_right_mser.append(kpt)
```

```
descriptors_all_right_mser.append(descrip)
points_all_right_mser.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))
```

100%|██████████| 61/61 [05:42<00:00, 5.62s/it]
100%|██████████| 61/61 [06:09<00:00, 6.05s/it]

```
#num_kps_sift = []
#num_kps_brisk = []
#num_kps_agast = []
#num_kps_kaze = []
#num_kps_akaze = []
#num_kps_orb = []
num_kps_mser = []
#num_kps_daisy = []
#num_kps_surfshift = []
#num_kps_fast = []
#num_kps_freak = []
#num_kps_gftt = []
#num_kps_star = []

#for j in tqdm(keypoints_all_left_sift + keypoints_all_right_sift):
#    num_kps_sift.append(len(j))

#for j in tqdm(keypoints_all_left_brisk + keypoints_all_right_brisk):
#    num_kps_brisk.append(len(j))

#for j in tqdm(keypoints_all_left_agast + keypoints_all_right_agast):
#    num_kps_agast.append(len(j))

#for j in tqdm(keypoints_all_left_kaze + keypoints_all_right_kaze):
#    num_kps_kaze.append(len(j))

#for j in tqdm(keypoints_all_left_akaze + keypoints_all_right_akaze):
#    num_kps_akaze.append(len(j))
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
#for j in tqdm(keypoints_all_left_daisy + keypoints_all_right_daisy):
#    num_kps_daisy.append(len(j))

#for j in tqdm(keypoints_all_left_surfshift + keypoints_all_right_surfshift):
#    num_kps_surfshift.append(len(j))

#for j in tqdm(keypoints_all_left_fast + keypoints_all_right_fast):
#    num_kps_fast.append(len(j))

#for j in tqdm(keypoints_all_left_freak + keypoints_all_right_freak):
#    num_kps_freak.append(len(j))
```

```
#num_kps_treak.append(len(j))

#for j in tqdm(keypoints_all_left_gfft + keypoints_all_right_gfft):
#num_kps_gfft.append(len(j))

#for j in tqdm(keypoints_all_left_star + keypoints_all_right_star):
#num_kps_star.append(len(j))

100%|██████████| 122/122 [00:00<00:00, 176267.68it/s]
```

```
def compute_homography_fast(matched_pts1, matched_pts2, thresh=4):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
                                    cv2.RANSAC, ransacReprojThreshold =thresh)

    inliers = inliers.flatten()
    return H, inliers
```

```
def compute_homography_fast_other(matched_pts1, matched_pts2):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
                                    0)

    inliers = inliers.flatten()
    return H, inliers
```

```
def get_Hmatrix(imgs, keypts, pts, descripts, ratio=0.8, thresh=4, disp=False):
```

```
FLANN_INDEX_KDTREE = 2
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
lff1 = np.float32(descripts[0])
lff = np.float32(descripts[1])
```

```
matches_lf1_lf = flann.knnMatch(lff1, lff, k=2)
```

```
print("\nNumber of matches", len(matches_lf1_lf))
```

```
matches_4 = []
ratio = ratio
# loop over the raw matches
```

```

for m in matches_lf1_lf:
    # ensure the distance is within a certain ratio of each
    # other (i.e. Lowe's ratio test)
    if len(m) == 2 and m[0].distance < m[1].distance * ratio:
        #matches_1.append((m[0].trainIdx, m[0].queryIdx))
        matches_4.append(m[0])

print("Number of matches After Lowe's Ratio",len(matches_4))

matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
...
# Estimate homography 1
#Compute H1
# Estimate homography 1
#Compute H1
imm1_pts=np.empty((len(matches_4),2))
imm2_pts=np.empty((len(matches_4),2))
for i in range(0,len(matches_4)):
    m = matches_4[i]
    (a_x, a_y) = keypts[0][m.queryIdx].pt
    (b_x, b_y) = keypts[1][m.trainIdx].pt
    imm1_pts[i]=(a_x, a_y)
    imm2_pts[i]=(b_x, b_y)
H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
Hn, best_inliers=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1000, RANSACthresh=6)
...

```

Hn,inliers = compute_homography_fast(imm1_pts,imm2_pts,thresh)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches",len(inlier_matchset))

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

# loop over the raw matches
for m in matches_lf1_lf:
    # ensure the distance is within a certain ratio of each
    # other (i.e. Lowe's ratio test)
    if len(m) == 2 and m[0].distance < m[1].distance * ratio:
        #matches_1.append((m[0].trainIdx, m[0].queryIdx))
        matches_4.append(m[0])
print("Number of matches After Lowe's Ratio New",len(matches_4))

```

```

matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
matches_idx = nn.array([m.trainIdx for m in matches_4])

```

```

matches_idx = np.array([idx for idx in matches_idx])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
Hn,inliers = compute_homography_fast_other(imm1_pts,imm2_pts)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches New",len(inlier_matchset))
print("\n")
"""

#H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
#Hn=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1500, RANSACthresh=6)

#global inlier_matchset

if disp==True:
    dispimg1=cv2.drawMatches(imgs[0], keypts[0], imgs[1], keypts[1], inlier_matchset, None,f1
    displayplot(dispimg1,'Robust Matching between Reference Image and Right Image ')

return Hn/Hn[2,2], len(matches_lf1_lf), len(inlier_matchset)

```

```

from functools import partial
from tqdm import tqdm
tqdm = partial(tqdm, position=0, leave=True)

```

```
print(left_files_path)
```

```
['/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0064.JPG', '/content/drive/MyDrive/
```

```
print(right_files_path)
```

```
['/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0063.JPG', '/content/drive/MyDrive/
```

File left_mser - 1

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
for j in tqdm(range(len(images_left))):
    if j==len(images_left)-1:
        break
```

```
H_a,matches,gd_matches = get_Hmatrix(images_left_bgr[j:j+2][::-1],keypoints_all_left_mser[j]
H_left_mser.append(H_a)
#num_matches_sift.append(matches)
#num_good_matches_sift.append(gd_matches)
```

```
for j in tqdm(range(len(images_right))):
    if j==len(images_right)-1:
```

```
break
```

```
H_a,matches,gd_matches = get_Hmatrix(images_right_bgr[j:j+2][::-1],keypoints_all_right_mser
H_right_mser.append(H_a)
#num_matches.append(matches)
#num_good_matches.append(gd_matches)
```

```
30%|██████| 18/61 [00:06<00:17, 2.45it/s]
```

```
Number of matches 3047
```

```
Number of matches After Lowe's Ratio 1136
```

```
Number of Robust matches 248
```

```
31%|██████| 19/61 [00:06<00:17, 2.37it/s]
```

```
Number of matches 3292
```

```
Number of matches After Lowe's Ratio 843
```

```
Number of Robust matches 193
```

```
33%|██████| 20/61 [00:07<00:17, 2.36it/s]
```

```
Number of matches 2865
```

```
Number of matches After Lowe's Ratio 738
```

```
Number of Robust matches 201
```

```
34%|██████| 21/61 [00:07<00:16, 2.40it/s]
```

```
Number of matches 3522
```

```
Number of matches After Lowe's Ratio 429
```

```
Number of Robust matches 50
```

```
36%|██████| 22/61 [00:08<00:17, 2.21it/s]
```

```
Number of matches 3409
```

```
Number of matches After Lowe's Ratio 963
```

```
Number of Robust matches 210
```

```
38%|██████| 23/61 [00:08<00:18, 2.11it/s]
```

```
Number of matches 3648
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
Number of matches After Lowe's Ratio 737
```

```
Number of Robust matches 154
```

```
41%|██████| 25/61 [00:09<00:17, 2.06it/s]
```

```
Number of matches 3162
```

```
Number of matches After Lowe's Ratio 912
```

```
Number of Robust matches 204
```

```
43%|██████| 26/61 [00:09<00:16, 2.17it/s]
```

```
Number of matches 2667
```

```
Number of matches After Lowe's Ratio 984
Number of Robust matches 271
```

```
44%|███████| 27/61 [00:10<00:15, 2.26it/s]
Number of matches 3045
Number of matches After Lowe's Ratio 708
Number of Robust matches 165
```

```
def warpnImages(images_left, images_right,H_left,H_right):
#img1-centre,img2-left,img3-right

h, w = images_left[0].shape[:2]

pts_left = []
pts_right = []

pts_centre = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)

for j in range(len(H_left)):
    pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
    pts_left.append(pts)

for j in range(len(H_right)):
    pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
    pts_right.append(pts)

pts_left_transformed=[]
pts_right_transformed=[]

for j,pts in enumerate(pts_left):
    if j==0:
        H_trans = H_left[j]
    else:
        H_trans = H_trans@H_left[j]
    pts_ = cv2.perspectiveTransform(pts, H_trans)
    pts_left_transformed.append(pts_)

for j,pts in enumerate(pts_right):
    if j==0:
        H_trans = H_right[j]
    else:
        H_trans = H_trans@H_right[j]
    pts_ = cv2.perspectiveTransform(pts, H_trans)
    pts_right_transformed.append(pts_)

print('Step1:Done')
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

#pts = np.concatenate((pts1, pts2_), axis=0)

pts_concat = np.concatenate((pts_centre,np.concatenate(np.array(pts_left_transformed),axis=0)),axis=0)

[xmin, ymin] = np.int32(pts_concat.min(axis=0).ravel() - 0.5)
[xmax, ymax] = np.int32(pts_concat.max(axis=0).ravel() + 0.5)
t = [-xmin, -ymin]
Ht = np.array([[1, 0, t[0]], [0, 1, t[1]], [0, 0, 1]]) # translate

print('Step2:Done')

return xmax,xmin,ymax,ymin,t,h,w,Ht

def final_steps_left(images_left,images_right,H_left,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):

warp_imgs_left = []

for j,H in enumerate(H_left):
    if j==0:
        H_trans = Ht@H
    else:
        H_trans = H_trans@H
    result = cv2.warpPerspective(images_left[j+1], H_trans, (xmax-xmin, ymax-ymin))

    if j==0:
        result[t[1]:h+t[1], t[0]:w+t[0]] = images_left[0]

    warp_imgs_left.append(result)

print('Step31:Done')

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)



xmax,xmin,ymax,ymin,t,h,w,Ht):

```

for j,H in enumerate(H_right):
    if j==0:
        H_trans = Ht@H
    else:
        H_trans = H_trans@H
    result = cv2.warpPerspective(images_right[j+1], H_trans, (xmax-xmin, ymax-ymin))

    warp_imgs_right.append(result)

print('Step32:Done')

```

```
return warp_imgs_right
```

```
def final_steps_union(warp_imgs_left,warp_imgs_right):
```

```
#Union
```

```
warp_images_all = warp_imgs_left + warp_imgs_right
```

```
warp_img_init = warp_images_all[0]
```

```
#warp_final_all=[]
```

```
for j,warp_img in enumerate(warp_images_all):
```

```
    if j==len(warp_images_all)-1:
```

```
        break
```

```
    black_pixels = np.where((warp_img_init[:, :, 0] == 0) & (warp_img_init[:, :, 1] == 0) &
```

```
warp_img_init[black_pixels] = warp_images_all[j+1][black_pixels]
```

```
#warp_final = np.maximum(warp_img_init,warp_images_all[j+1])
```

```
#warp_img_init = warp_final
```

```
#warp_final_all.append(warp_final)
```

```
print('Step4:Done')
```

```
return warp_img_init
```

```
def final_steps_left_union(images_left,H_left,xmax,xmin,ymax,ymin,t,h,w,Ht):
```

```
for j,H in enumerate(H_left):
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

```
result = np.zeros((ymax-ymin,xmax-xmin,3),dtype= uint8 )
```

```
cv2.warpPerspective(src = np.uint8(input_img), M = H_trans, dsize = (xmax-xmin, ymax-ymin))
warp_img_init_curr = result
```

```
if j==0:
```

```
    result[t[1]:h+t[1], t[0]:w+t[0]] = images_left[0]
```

```
    warp_img_init_prev = result
```

```
    continue
```

```
    black_pixels = np.where((warp_img_init_prev[:, :, 0] == 0) & (warp_img_init_prev[:, :, 1] == 0))
```

```
warp_img_init_prev[black_pixels] = warp_img_init_curr[black_pixels]

print('Step31:Done')

return warp_img_init_prev

def final_steps_right_union(warp_img_prev,images_right,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):

    for j,H in enumerate(H_right):
        if j==0:
            H_trans = Ht@H
        else:
            H_trans = H_trans@H
        input_img = images_right[j+1]
        result = np.zeros((ymax-ymin,xmax-xmin,3),dtype='uint8')

        cv2.warpPerspective(src = np.uint8(input_img), M = H_trans, dsize = (xmax-xmin, ymax-ym
        warp_img_init_curr = result

        black_pixels = np.where((warp_img_prev[:, :, 0] == 0) & (warp_img_prev[:, :, 1] == 0) &
        warp_img_prev[black_pixels] = warp_img_init_curr[black_pixels]

    print('Step32:Done')

    return warp_img_prev

xmax,xmin,ymax,ymin,t,h,w,Ht = warpnImages(images_left_bgr_no_enhance, images_right_bgr_no_en
```

Step1:Done

Step2:Done

```
warp_imgs_left = final_steps_left_union(images_left_bgr_no_enhance,H_left_mser,xmax,xmin,ymax
```


Your session crashed after using all available
RAM. If you are interested in access to high-
RAM runtimes, you may want to check out
[Colab Pro](#).

[View runtime logs](#)

Step32:Done

```
fig,ax=plt.subplots()
fig.set_size_inches(20,20)
ax.imshow(cv2.cvtColor(warp_imgs_all_mser , cv2.COLOR_BGR2RGB))
ax.set_title('120-Images Mosaic-MSER')
```


Text(0.5, 1.0, '120-Images Mosaic-MSER')



Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)





```

agast = cv2.AgastFeatureDetector_create()
sift = cv2.xfeatures2d.SIFT_create()

keypoints_all_left_agast = []
descriptors_all_left_agast = []
points_all_left_agast=[]

keypoints_all_right_agast = []
descriptors_all_right_agast = []
points_all_right_agast=[]

for imgs in tqdm(images_left_bgr_no_enhance):
    kpt = agast.detect(imgs,None)
    kpt,descrip = sift.compute(imgs, kpt)
    keypoints_all_left_agast.append(kpt)
    descriptors_all_left_agast.append(descrip)
    points_all_left_agast.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))

for imgs in tqdm(images_right_bgr_no_enhance):
    kpt = agast.detect(imgs,None)
    kpt,descrip = sift.compute(imgs, kpt)
    keypoints_all_right_agast.append(kpt)
    descriptors_all_right_agast.append(descrip)
    points_all_right_agast.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

```

num_kps_agast = []
#num_kps_kaze = []
#num_kps_akaze = []
#num_kps_orb = []
#num_kps_mser = []
#num_kps_daisy = []
#num_kps_surfshift = []
#num_kps_fast = []
#num_kps_freak = []
#num_kps_gftt = []
#num_kps_star = []

```

```
#for j in tqdm(keypoints_all_left_sift + keypoints_all_right_sift):
#  num_kps_sift.append(len(j))

#for j in tqdm(keypoints_all_left_brisk + keypoints_all_right_brisk):
#num_kps_brisk.append(len(j))

for j in tqdm(keypoints_all_left_agast + keypoints_all_right_agast):
  num_kps_agast.append(len(j))

#for j in tqdm(keypoints_all_left_kaze + keypoints_all_right_kaze):
#  num_kps_kaze.append(len(j))

#for j in tqdm(keypoints_all_left_akaze + keypoints_all_right_akaze):
#num_kps_akaze.append(len(j))

#for j in tqdm(keypoints_all_left_orb + keypoints_all_right_orb):
#num_kps_orb.append(len(j))

#for j in tqdm(keypoints_all_left_mser + keypoints_all_right_mser):
#  num_kps_mser.append(len(j))

#for j in tqdm(keypoints_all_left_daisy + keypoints_all_right_daisy):
#  num_kps_daisy.append(len(j))

#for j in tqdm(keypoints_all_left_surfshift + keypoints_all_right_surfshift):
#  num_kps_surfshift.append(len(j))

#for j in tqdm(keypoints_all_left_fast + keypoints_all_right_fast):
#  num_kps_fast.append(len(j))

#for j in tqdm(keypoints_all_left_freak + keypoints_all_right_freak):
#  num_kps_freak.append(len(j))

#for j in tqdm(keypoints_all_left_gftt + keypoints_all_right_gftt):
#  num_kps_gftt.append(len(j))
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
def compute_homography_fast(matched_pts1, matched_pts2, thresh=4):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
                                    cv2.RANSAC, ransacReprojThreshold =thresh)
    inliers = inliers.flatten()
```

```
    return H, inliers
```

```
def compute_homography_fast_other(matched_pts1, matched_pts2):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
                                    0)

    inliers = inliers.flatten()
    return H, inliers

def get_Hmatrix(imgs, keypoints, pts, descriptors, ratio=0.8, thresh=4, disp=False):
    FLANN_INDEX_KDTREE = 2
    index_params = dict(algorithm=FLANN_INDEX_KDTREE, trees=5)
    search_params = dict(checks=50)
    flann = cv2.FlannBasedMatcher(index_params, search_params)
    #flann = cv2.BFMatcher()

    lff1 = np.float32(descriptors[0])
    lff = np.float32(descriptors[1])

    matches_lf1_lf = flann.knnMatch(lff1, lff, k=2)

    print("\nNumber of matches", len(matches_lf1_lf))

    matches_4 = []
    ratio = ratio
    # loop over the raw matches
    for m in matches_lf1_lf:
        # ensure the distance is within a certain ratio of each
        # other (i.e. Lowe's ratio test)
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypoints[0][idx].pt for idx in matches_idx])
matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypoints[1][idx].pt for idx in matches_idx])
...
# Estimate homography 1
#Compute H1
# Estimate homography 1
#Compute H1
imm1_pts=np.empty((len(matches_4),2))
imm2_pts=np.empty((len(matches_4),2))
```

```

        +imm1_pts=mp.complex(matches_4),[])
for i in range(0,len(matches_4)):
    m = matches_4[i]
    (a_x, a_y) = keypts[0][m.queryIdx].pt
    (b_x, b_y) = keypts[1][m.trainIdx].pt
    imm1_pts[i]=(a_x, a_y)
    imm2_pts[i]=(b_x, b_y)
H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
Hn, best_inliers=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1000, RANSACthresh=6)
...

```



```

Hn,inliers = compute_homography_fast(imm1_pts,imm2_pts,thresh)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches",len(inlier_matchset))
print("\n")
...
if len(inlier_matchset)<50:
    matches_4 = []
    ratio = 0.67
    # loop over the raw matches
    for m in matches_lf1_lf:
        # ensure the distance is within a certain ratio of each
        # other (i.e. Lowe's ratio test)
        if len(m) == 2 and m[0].distance < m[1].distance * ratio:
            #matches_1.append((m[0].trainIdx, m[0].queryIdx))
            matches_4.append(m[0])
print("Number of matches After Lowe's Ratio New",len(matches_4))

matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
Hn,inliers = compute_homography_fast_other(imm1_pts,imm2_pts)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

```

#Hn=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1500, RANSACthresh=6)

#global inlier_matchset

if disp==True:
    dispimg1=cv2.drawMatches(imgs[0], keypts[0], imgs[1], keypts[1], inlier_matchset, None,f1
    displayplot(dispimg1,'Robust Matching between Reference Image and Right Image ')

return Hn/Hn[2,2], len(matches_lf1_lf), len(inlier_matchset)

```

```
from functions import partial
from tqdm import tqdm
tqdm = partial(tqdm, position=0, leave=True)

print(left_files_path)
['/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0064.JPG', '/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0065.JPG']

print(right_files_path)
['/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0063.JPG', '/content/drive/MyDrive/RGB-img/img/IX-11-01917_0004_0064.JPG']

H_left_agast = []
H_right_agast = []

num_matches_agast = []
num_good_matches_agast = []

for j in tqdm(range(len(images_left))):
    if j==len(images_left)-1:
        break

    H_a,matches,gd_matches = get_Hmatrix(images_left_bgr[j:j+2][::-1],keypoints_all_left_agast[
    H_left_agast.append(H_a)
    #num_matches_sift.append(matches)
    #num_good_matches_sift.append(gd_matches)

for j in tqdm(range(len(images_right))):
    if j==len(images_right)-1:
        break

    H_a,matches,gd_matches = get_Hmatrix(images_right_bgr[j:j+2][::-1],keypoints_all_right_agas
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
8%|██████████| 5/61 [01:59<23:13, 24.89s/it]
Number of matches 114291
Number of matches After Lowe's Ratio 8696
Number of Robust matches 5809
```

```
10%|██████████| 6/61 [02:50<29:56, 32.67s/it]
Number of matches 116170
Number of matches After Lowe's Ratio 19060
Number of Robust matches 11241
```

11% | | 7/61 [03:41<34:17, 38.11s/it]
 Number of matches 119668
 Number of matches After Lowe's Ratio 18854
 Number of Robust matches 14252

Number of matches 117998
 Number of matches After Lowe's Ratio 23134
 13% | | 8/61 [04:32<37:00, 41.89s/it]Number of Robust matches 19272

Number of matches 132866
 Number of matches After Lowe's Ratio 33376
 15% | | 9/61 [05:26<39:34, 45.66s/it]Number of Robust matches 21703

16% | | 10/61 [06:19<40:38, 47.81s/it]
 Number of matches 140126
 Number of matches After Lowe's Ratio 9338
 Number of Robust matches 6298

Number of matches 141469
 Number of matches After Lowe's Ratio 15211
 18% | | 11/61 [07:09<40:16, 48.33s/it]Number of Robust matches 10405

20% | | 12/61 [07:57<39:35, 48.48s/it]
 Number of matches 145304
 Number of matches After Lowe's Ratio 18131
 Number of Robust matches 10139

21% | | 13/61 [08:44<38:20, 47.94s/it]
 Number of matches 140550
 Number of matches After Lowe's Ratio 12022

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
def warpnImages(images_left, images_right,H_left,H_right):
    #img1-centre,img2-left,img3-right

    h, w = images_left[0].shape[:2]

    pts_left = []
    pts_right = []

    pts_centre = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
```

```

for j in range(len(H_left)):
    pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
    pts_left.append(pts)

for j in range(len(H_right)):
    pts = np.float32([[0, 0], [0, h], [w, h], [w, 0]]).reshape(-1, 1, 2)
    pts_right.append(pts)

pts_left_transformed=[]
pts_right_transformed=[]

for j,pts in enumerate(pts_left):
    if j==0:
        H_trans = H_left[j]
    else:
        H_trans = H_trans@H_left[j]
    pts_ = cv2.perspectiveTransform(pts, H_trans)
    pts_left_transformed.append(pts_)

for j,pts in enumerate(pts_right):
    if j==0:
        H_trans = H_right[j]
    else:
        H_trans = H_trans@H_right[j]
    pts_ = cv2.perspectiveTransform(pts, H_trans)
    pts_right_transformed.append(pts_)

print('Step1:Done')

```

```
#pts = np.concatenate((pts1, pts2_), axis=0)
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

X array(pts_left_transformed),axis=0
[View runtime logs](#) .5)
.5)

```
Ht = np.array([[1, 0, t[0]], [0, 1, t[1]], [0, 0, 1]]) # translate
```

```
print('Step2:Done')
```

```
return xmax,xmin,ymax,ymin,t,h,w,Ht
```

```
def final_steps_left(images_left,images_right,H_left,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):
    warp_imgs_left = []
```

```

for j,H in enumerate(H_left):
    if j==0:
        H_trans = Ht@H
    else:
        H_trans = H_trans@H
    result = cv2.warpPerspective(images_left[j+1], H_trans, (xmax-xmin, ymax-ymin))

    if j==0:
        result[t[1]:h+t[1], t[0]:w+t[0]] = images_left[0]

    warp_imgs_left.append(result)

print('Step31:Done')

return warp_imgs_left

def final_steps_right(images_left,images_right,H_left,H_right,xmax,xmin,ymax,ymin,t,h,w,Ht):
    warp_imgs_right = []

    for j,H in enumerate(H_right):
        if j==0:
            H_trans = Ht@H
        else:
            H_trans = H_trans@H
        result = cv2.warpPerspective(images_right[j+1], H_trans, (xmax-xmin, ymax-ymin))

        warp_imgs_right.append(result)

    print('Step32:Done')

    return warp_imgs_right

def final_steps_union(warp_imgs_left,warp_imgs_right):

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

#warp_final_all=[]

for j,warp_img in enumerate(warp_images_all):
    if j==len(warp_images_all)-1:
        break
    black_pixels = np.where((warp_img_init[:, :, 0] == 0) & (warp_img_init[:, :, 1] == 0) &
                           warp_img_init[:, :, 2] == 0)
    warp_img_init[black_pixels] = warp_images_all[j+1][black_pixels]

```

```

#warp_final = np.maximum(warp_img_init,warp_images_all[j+1])
#warp_img_init = warp_final
#warp_final_all.append(warp_final)

print('Step4:Done')

return warp_img_init

def final_steps_left_union(images_left,H_left,xmax,xmin,ymax,ymin,t,h,w,Ht):

for j,H in enumerate(H_left):
    if j==0:
        H_trans = Ht@H
    else:
        H_trans = H_trans@H
    input_img = images_left[j+1]
    result = np.zeros((ymax-ymin,xmax-xmin,3),dtype='uint8')

    cv2.warpPerspective(src = np.uint8(input_img), M = H_trans, dsize = (xmax-xmin, ymax-ym
    warp_img_init_curr = result

    if j==0:
        result[t[1]:h+t[1], t[0]:w+t[0]] = images_left[0]
        warp_img_init_prev = result
        continue

    black_pixels = np.where((warp_img_init_prev[:, :, 0] == 0) & (warp_img_init_prev[:, :, 1,
    warp_img_init_prev[black_pixels] = warp_img_init_curr[black_pixels]

print('Step31:Done')

Your session crashed after using all available
RAM. If you are interested in access to high-
RAM runtimes, you may want to check out
Colab Pro.X
```

[View runtime logs](#)

```

, xmax, xmin, ymax, ymin, t, h, w, Ht):

for j,H in enumerate(H_right):
    if j==0:
        H_trans = Ht@H
    else:
        H_trans = H_trans@H
    input_img = images_right[j+1]
    result = np.zeros((ymax-ymin,xmax-xmin,3),dtype='uint8')

    cv2.warpPerspective(src = np.uint8(input_img), M = H_trans, dsize = (xmax-xmin, ymax-ym
    warp_img_init_curr = result

```

6/25/2021

120_image_stitching_with_mser+sift_agast+sift.ipynb - Colaboratory

```
black_pixels = np.where((warp_img_prev[:, :, 0] == 0) & (warp_img_prev[:, :, 1] == 0) &
warp_img_prev[black_pixels] = warp_img_init_curr[black_pixels]
print('Step32:Done')

return warp_img_prev
```

```
xmax,xmin,ymax,ymin,t,h,w,Ht = warpnImages(images_left_bgr_no_enhance, images_right_bgr_no_en
```

```
Step1:Done
Step2:Done
```

```
warp_imgs_left = final_steps_left_union(images_left_bgr_no_enhance,H_left_agast,xmax,xmin,ymax
```

```
warp_imgs_all_agast = final_steps_right_union(warp_imgs_left, images_right_bgr_no_enhance,H_r
```

```
fig,ax=plt.subplots()
fig.set_size_inches(20,20)
ax.imshow(cv2.cvtColor(warp_imgs_all_agast , cv2.COLOR_BGR2RGB))
ax.set_title('120-Images Mosaic-AGAST')
```

```
fast = cv2.FastFeatureDetector_create()
sift = cv2.xfeatures2d.SIFT_create()
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

X

[View runtime logs](#)

```
descriptors_all_right_fast = []
points_all_right_fast=[]

for imgs in tqdm(images_left_bgr_no_enhance):
    kpt = fast.detect(imgs,None)
    kpt,descrip = sift.compute(imgs, kpt)
    keypoints_all_left_fast.append(kpt)
    descriptors_all_left_fast.append(descrip)
    points_all_left_fast.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))


for imgs in tqdm(images_right_bgr_no_enhance):
```

```

kpt = fast.detect(imgs, None)
kpt, descrip = sift.compute(imgs, kpt)
keypoints_all_right_fast.append(kpt)
descriptors_all_right_fast.append(descrip)
points_all_right_fast.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))


#num_kps_sift = []
#num_kps_brisk = []
#num_kps_agast = []
#num_kps_kaze = []
#num_kps_akaze = []
#num_kps_orb = []
#num_kps_mser = []
#num_kps_daisy = []
#num_kps_surfshift = []
num_kps_fast = []
#num_kps_freak = []
#num_kps_gftt = []
#num_kps_star = []


#for j in tqdm(keypoints_all_left_sift + keypoints_all_right_sift):
#    num_kps_sift.append(len(j))

#for j in tqdm(keypoints_all_left_brisk + keypoints_all_right_brisk):
#    num_kps_brisk.append(len(j))

#for j in tqdm(keypoints_all_left_agast + keypoints_all_right_agast):
#    num_kps_agast.append(len(j))

#for j in tqdm(keypoints_all_left_kaze + keypoints_all_right_kaze):
#    num_kps_kaze.append(len(j))

#for j in tqdm(keypoints_all_left_akaze + keypoints_all_right_akaze):
#    num_kps_akaze.append(len(j))

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

#for j in tqdm(keypoints_all_left_daisy + keypoints_all_right_daisy):
#    num_kps_daisy.append(len(j))

#for j in tqdm(keypoints_all_left_surfshift + keypoints_all_right_surfshift):
#    num_kps_surfshift.append(len(j))

for j in tqdm(keypoints_all_left_fast + keypoints_all_right_fast):
    num_kps_fast.append(len(j))

#for j in tqdm(keypoints_all_left_freak + keypoints_all_right_freak):

```

```
#num_kps_freak.append(len(j))

#for j in tqdm(keypoints_all_left_gftt + keypoints_all_right_gftt):
#    num_kps_gftt.append(len(j))

#for j in tqdm(keypoints_all_left_star + keypoints_all_right_star):
#    num_kps_star.append(len(j))

def compute_homography_fast(matched_pts1, matched_pts2, thresh=4):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
                                    cv2.RANSAC, ransacReprojThreshold =thresh)
    inliers = inliers.flatten()
    return H, inliers

def compute_homography_fast_other(matched_pts1, matched_pts2):
    #matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
    #matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

    # Estimate the homography between the matches using RANSAC
    H, inliers = cv2.findHomography(matched_pts1,
                                    matched_pts2,
                                    0)
    inliers = inliers.flatten()
    return H, inliers

def get_Hmatrix(imgs, keypoints, pts, descriptors, ratio=0.8, thresh=4, disp=False):
    FLANN_INDEX_KDTREE = 2
    index_params = dict(algorithm=FLANN_INDEX_KDTREE, trees=5)
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```
lff1 = np.float32(descriptors[1])

matches_lf1_lf = flann.knnMatch(lff1, lff, k=2)

print("\nNumber of matches", len(matches_lf1_lf))

matches_4 = []
ratio = ratio
# loop over the raw matches
for m in matches_lf1_lf:
    # ensure the distance is within a certain ratio of each
```

```

# other (i.e. Lowe's ratio test)
if len(m) == 2 and m[0].distance < m[1].distance * ratio:
    #matches_1.append((m[0].trainIdx, m[0].queryIdx))
    matches_4.append(m[0])

print("Number of matches After Lowe's Ratio",len(matches_4))

matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
...
# Estimate homography 1
#Compute H1
# Estimate homography 1
#Compute H1
imm1_pts=np.empty((len(matches_4),2))
imm2_pts=np.empty((len(matches_4),2))
for i in range(0,len(matches_4)):
    m = matches_4[i]
    (a_x, a_y) = keypts[0][m.queryIdx].pt
    (b_x, b_y) = keypts[1][m.trainIdx].pt
    imm1_pts[i]=(a_x, a_y)
    imm2_pts[i]=(b_x, b_y)
H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
Hn, best_inliers=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1000, RANSACthresh=6)
...

```

```

Hn,inliers = compute_homography_fast(imm1_pts,imm2_pts,thresh)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches",len(inlier_matchset))
print("\n")
...

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

# ensure the distance is within a certain ratio of each
# other (i.e. Lowe's ratio test)
if len(m) == 2 and m[0].distance < m[1].distance * ratio:
    #matches_1.append((m[0].trainIdx, m[0].queryIdx))
    matches_4.append(m[0])
print("Number of matches After Lowe's Ratio New",len(matches_4))

matches_idx = np.array([m.queryIdx for m in matches_4])
imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
...
```

```

Hn,inliers = compute_homography_fast_other(imm1_pts,imm2_pts)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches New",len(inlier_matchset))
print("\n")
```
#H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
#Hn=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1500, RANSACthresh=6)

#global inlier_matchset

if disp==True:
 dispimg1=cv2.drawMatches(imgs[0], keypts[0], imgs[1], keypts[1], inlier_matchset, None,f1
 displayplot(dispimg1,'Robust Matching between Reference Image and Right Image ')

return Hn/Hn[2,2], len(matches_lf1_lf), len(inlier_matchset)

from functools import partial
from tqdm import tqdm
tqdm = partial(tqdm, position=0, leave=True)

print(left_files_path)

print(right_files_path)

H_left_fast = []
H_right_fast = []

num_matches_fast = []
num_good_matches_fast = []

for j in tqdm(range(len(images_left))):
 if j==len(images_left)-1:
 Your session crashed after using all available
 RAM. If you are interested in access to high-
 RAM runtimes, you may want to check out
 Colab Pro.
#num_good_matches_sift.append(gd_matches)

for j in tqdm(range(len(images_right))):
 if j==len(images_right)-1:
 break

H_a,matches,gd_matches = get_Hmatrix(images_right_bgr[j:j+2][::-1],keypoints_all_right_fast
H_right_fast.append(H_a)
#num_matches.append(matches)
#num_good_matches.append(gd_matches)

```

[View runtime logs](#)

```

gftt = cv2.GFTTDetector_create()
sift = cv2.xfeatures2d.SIFT_create()

keypoints_all_left_gftt = []
descriptors_all_left_gftt = []
points_all_left_gftt=[]

keypoints_all_right_gftt = []
descriptors_all_right_gftt = []
points_all_right_gftt=[]

for imgs in tqdm(images_left_bgr_no_enhance):
 kpt = gftt.detect(imgs,None)
 kpt,descrip = sift.compute(imgs, kpt)
 keypoints_all_left_gftt.append(kpt)
 descriptors_all_left_gftt.append(descrip)
 points_all_left_gftt.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))

for imgs in tqdm(images_right_bgr_no_enhance):
 kpt = gftt.detect(imgs,None)
 kpt,descrip = sift.compute(imgs, kpt)
 keypoints_all_right_gftt.append(kpt)
 descriptors_all_right_gftt.append(descrip)
 points_all_right_gftt.append(np.asarray([[p.pt[0], p.pt[1]] for p in kpt]))

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

```

#num_kps_kaze = []
#num_kps_akaze = []
#num_kps_orb = []
#num_kps_mser = []
#num_kps_daisy = []
#num_kps_surfshift = []
#num_kps_fast = []
#num_kps_freak = []
num_kps_gftt = []
#num_kps_star = []

#for i in tqdm(keypoints_all_left_sift + keypoints_all_right_sift):

```

[https://colab.research.google.com/drive/1gbVWZfOgoprq5\\_tS30w8FkX-bJhkL7jh#scrollTo=gdQc2erUATK8&printMode=true](https://colab.research.google.com/drive/1gbVWZfOgoprq5_tS30w8FkX-bJhkL7jh#scrollTo=gdQc2erUATK8&printMode=true)

```

num_kps_sift.append(len(j))

#for j in tqdm(keypoints_all_left_brisk + keypoints_all_right_brisk):
num_kps_brisk.append(len(j))

#for j in tqdm(keypoints_all_left_agast + keypoints_all_right_agast):
num_kps_agast.append(len(j))

#for j in tqdm(keypoints_all_left_kaze + keypoints_all_right_kaze):
num_kps_kaze.append(len(j))

#for j in tqdm(keypoints_all_left_akaze + keypoints_all_right_akaze):
num_kps_akaze.append(len(j))

#for j in tqdm(keypoints_all_left_orb + keypoints_all_right_orb):
num_kps_orb.append(len(j))

#for j in tqdm(keypoints_all_left_mser + keypoints_all_right_mser):
num_kps_mser.append(len(j))

#for j in tqdm(keypoints_all_left_daisy + keypoints_all_right_daisy):
num_kps_daisy.append(len(j))

#for j in tqdm(keypoints_all_left_surf sift + keypoints_all_right_surf sift):
num_kps_surf sift.append(len(j))

#for j in tqdm(keypoints_all_left_fast + keypoints_all_right_fast):
num_kps_fast.append(len(j))

#for j in tqdm(keypoints_all_left_freak + keypoints_all_right_freak):
num_kps_freak.append(len(j))

for j in tqdm(keypoints_all_left_gftt + keypoints_all_right_gftt):
 num_kps_gftt.append(len(j))

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)

```

#matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
#matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

Estimate the homography between the matches using RANSAC
H, inliers = cv2.findHomography(matched_pts1,
 matched_pts2,
 cv2.RANSAC, ransacReprojThreshold = thresh)

inliers = inliers.flatten()
return H, inliers

```

```
def compute homography fast other(matched pts1, matched pts2):
```

```

#matched_pts1 = cv2.KeyPoint_convert(matched_kp1)
#matched_pts2 = cv2.KeyPoint_convert(matched_kp2)

Estimate the homography between the matches using RANSAC
H, inliers = cv2.findHomography(matched_pts1,
 matched_pts2,
 0)

inliers = inliers.flatten()
return H, inliers

def get_Hmatrix(imgs, keypoints, pts, descriptors, ratio=0.8, thresh=4, disp=False):
 FLANN_INDEX_KDTREE = 2
 index_params = dict(algorithm=FLANN_INDEX_KDTREE, trees=5)
 search_params = dict(checks=50)
 flann = cv2.FlannBasedMatcher(index_params, search_params)
 #flann = cv2.BFMatcher()

 lff1 = np.float32(descriptors[0])
 lff = np.float32(descriptors[1])

 matches_lf1_lf = flann.knnMatch(lff1, lff, k=2)

 print("\nNumber of matches", len(matches_lf1_lf))

 matches_4 = []
 ratio = ratio
 # loop over the raw matches
 for m in matches_lf1_lf:
 # ensure the distance is within a certain ratio of each
 # other (i.e. Lowe's ratio test)
 if len(m) == 2 and m[0].distance < m[1].distance * ratio:
 #matches_1.append((m[0].trainIdx, m[0].queryIdx))
 matches_4.append(m[0])

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).

[View runtime logs](#)



)

```

matches_idx = np.array([m.trainIdx for m in matches_4])
imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
...

Estimate homography 1
#Compute H1
Estimate homography 1
#Compute H1
imm1_pts=np.empty((len(matches_4),2))
imm2_pts=np.empty((len(matches_4),2))
for i in range(0,len(matches_4)):
 m = matches_4[i]
 (a_x, a_y) = keypts[0][m.trainIdx].pt

```

```

(b_x, b_y) = keypts[1][m.trainIdx].pt
imm1_pts[i]=(a_x, a_y)
imm2_pts[i]=(b_x, b_y)
H=compute_Homography(imm1_pts,imm2_pts)
#Robustly estimate Homography 1 using RANSAC
Hn, best_inliers=RANSAC_alg(keypts[0] ,keypts[1], matches_4, nRANSAC=1000, RANSACthresh=6)
'''

Hn,inliers = compute_homography_fast(imm1_pts,imm2_pts,thresh)
inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
print("Number of Robust matches",len(inlier_matchset))
print("\n")
'''

if len(inlier_matchset)<50:
 matches_4 = []
 ratio = 0.67
 # loop over the raw matches
 for m in matches_lf1_lf:
 # ensure the distance is within a certain ratio of each
 # other (i.e. Lowe's ratio test)
 if len(m) == 2 and m[0].distance < m[1].distance * ratio:
 #matches_1.append((m[0].trainIdx, m[0].queryIdx))
 matches_4.append(m[0])
 print("Number of matches After Lowe's Ratio New",len(matches_4))

 matches_idx = np.array([m.queryIdx for m in matches_4])
 imm1_pts = np.array([keypts[0][idx].pt for idx in matches_idx])
 matches_idx = np.array([m.trainIdx for m in matches_4])
 imm2_pts = np.array([keypts[1][idx].pt for idx in matches_idx])
 Hn,inliers = compute_homography_fast_other(imm1_pts,imm2_pts)
 inlier_matchset = np.array(matches_4)[inliers.astype(bool)].tolist()
 print("Number of Robust matches New",len(inlier_matchset))
 print("\n")
'''

```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)

, RANSACthresh=6)

```

if disp==True:
 dispimg1=cv2.drawMatches(imgs[0], keypts[0], imgs[1], keypts[1], inlier_matchset, None,f1
 displayplot(dispimg1,'Robust Matching between Reference Image and Right Image ')

return Hn/Hn[2,2], len(matches_lf1_lf), len(inlier_matchset)

from functools import partial
from tqdm import tqdm
tqdm = partial(tqdm, position=0, leave=True)

```

```
print(left_files_path)

print(right_files_path)

H_left_gfft = []
H_right_gfft = []

num_matches_gfft = []
num_good_matches_gfft = []

for j in tqdm(range(len(images_left))):
 if j==len(images_left)-1:
 break

 H_a,matches,gd_matches = get_Hmatrix(images_left_bgr[j:j+2][::-1],keypoints_all_left_gfft[j]
 H_left_gfft.append(H_a)
 #num_matches_sift.append(matches)
 #num_good_matches_sift.append(gd_matches)

for j in tqdm(range(len(images_right))):
 if j==len(images_right)-1:
 break

 H_a,matches,gd_matches = get_Hmatrix(images_right_bgr[j:j+2][::-1],keypoints_all_right_gfft
 H_right_gfft.append(H_a)
 #num_matches.append(matches)
 #num_good_matches.append(gd_matches)
```

Your session crashed after using all available RAM. If you are interested in access to high-RAM runtimes, you may want to check out [Colab Pro](#).



[View runtime logs](#)