Scalability-Aware Benchmarking of Graph Anomaly Detection on Financial and Cyber Networks: Evaluated Population, Alert Budgets, and the Exact Limits of Decoupled GNNs

Seong-Su Park*[1] and Ki-Hyung Kim†[2]

[1]Department of Computer Engineering, Ajou University, Suwon 16499, Republic of Korea; parky@ajou.ac.kr
[2]Department of Cyber Security, Ajou University, Suwon 16499, Republic of Korea; kkim86@ajou.ac.kr

October 24, 2026

Abstract

Graph anomaly detection (GAD) is increasingly adopted for financial fraud mitigation and cyber intrusion defense. However, real-world deployment faces severe obstacles: out-of-memory (OOM) failures on massive graphs are often obscured by selective reporting, severe class imbalance invalidates plain ROC-AUC rankings, and unsupervised reconstruction objectives can paradoxically assign higher anomaly scores to licit hub entities than to simple fraudulent chains. To establish a rigorous, application-oriented benchmark, we evaluate seven functioning primary detectors (DOMINANT, AnomalyDAE, CoLA, GADNR, OCGNN, DLG-Base, and DLG-Aug) across 13 primary graph benchmarks (five native financial, eight synthetic injected) and one external enterprise cybersecurity network (LANL-RedTeam) over five random seeds (455 total runs). We enforce a strict support-aware contract: 84 of 91 primary model–dataset pairs are successfully completed, while unsupported cells are reported transparently rather than silently imputed.

Our empirical results reveal critical domain-dependent behaviors. While Decoupled Local-to-Global augmentation (DLG-Aug) improves average precision (AP) over the DLG-Base reference on the Elliptic transaction network by $+0.0350$ (0.1037 vs. 0.0687), it suffers an AP degradation of -0.0656 on the large Reddit-Syn graph (0.3388 vs. 0.4044) and exhibits negative delta on LANL-RedTeam. On blockchain token-transfer networks, at least one established comparator exceeds DLG-Aug in mean AP on each of the three blockchain datasets (Ethereum: OCGNN 0.4996 vs. Aug 0.4359; BSC: AnomalyDAE 0.3609 vs. Aug 0.3411; Polygon: AnomalyDAE 0.1878 vs. Aug 0.0731). Furthermore, we audit the below-random ROC-AUC values (< 0.50) observed on Elliptic across reconstruction baselines, confirming score and label alignment while leaving topological hub bias as an informed hypothesis rather than an uncontroverted proof. Finally, we provide closed-form exact Gram decoders that eliminate dense $O(N^2)$ memory allocation and present a practical decision matrix connecting alert budgets (top-1% and top-5%) to operational detector selection.

Keywords: graph anomaly detection; graph neural networks; financial fraud detection; alert budget; exact sparse reconstruction; reproducible benchmarking; local-to-global learning

1 Introduction

Graph anomaly detection (GAD) has emerged as a cornerstone of modern machine learning for financial fraud investigation, blockchain anti-money laundering (AML), and enterprise cy-

*ORCID: https://orcid.org/0009-0008-4056-3875
†Corresponding author: kkim86@ajou.ac.kr; Tel.: +82-31-219-2433; ORCID: https://orcid.org/0000-0002-2321-4475

bersecurity monitoring [1–3]. By modeling transactions, contracts, and authentication events as interconnected graphs $G = (V, E, X)$, graph neural networks (GNNs) can capture subtle topological irregularities and feature discrepancies that evade tabular screening.

However, moving GAD from idealized academic benchmarks to operational deployment reveals fundamental challenges that conventional evaluation protocols frequently obscure:

1. **Failure-Blind Reporting and Hardware Infeasibility:** Standard leaderboards often omit unsupported cells when models suffer out-of-memory (OOM) crashes or runtime timeouts on web-scale or multi-million-node graphs, or they quietly replace the full-graph objective with localized neighborhood sampling without verifying whether score semantics are preserved.

2. **Imbalance Disconnect and Below-Random Inversion:** In real-world financial fraud, anomaly prevalence is frequently below 2% or 0.5%. In these extreme regimes, high area under the ROC curve (ROC-AUC) can be misleading. More critically, unsupervised reconstruction models (e.g., autoencoders reconstructing node attributes and adjacency) often assign their highest reconstruction errors to high-degree, structurally complex licit hubs (such as cryptocurrency exchanges or institutional accounts) rather than simple illicit chains, leading to empirical ROC-AUC scores falling well below the 0.50 random baseline. We examine this phenomenon under frozen scoring conventions.

3. **Alert-Budget Constraints:** Security operations centers (SOCs) and fraud investigation teams cannot inspect thousands of suspicious accounts; they operate under strict investigative triage budgets (e.g., auditing the top-1% or top-5% flagged alerts). Ranking metrics alone do not tell practitioners whether a detector provides actionable precision at the head of the flagged list.

4. **Conditional Utility of Architecture Augmentation:** Pretraining local graph representations and fusing them with global message passing (e.g., Decoupled Local-to-Global architectures, DLG [4]) has demonstrated strong performance in specific cryptocurrency domains, but its comparative utility across diverse topologies remains unverified under frozen, reproducible protocols.

To address these gaps, this study presents a rigorous, support-aware benchmark for graph anomaly detection. We freeze seven representative detector configurations across 13 primary graph datasets and one external cybersecurity dataset, executing five random seeds per combination. Rather than claiming universal superiority for any single model, our benchmark contributes:

1. **A Support-Aware Evaluation Protocol:** We explicitly distinguish between successful execution ('SUPPORTED_EXACT') and hardware exhaustion (OOM), evaluating exactly 84 of 91 primary pairs (420 successful primary runs plus 35 external LANL runs) without heuristic score imputation.

2. **Audited Predictive Quality vs. Evaluation Prevalence and Alert Budgets:** We pair Average Precision (AP) with explicit evaluation prevalence references and evaluate triage precision and recall at fixed 1% and 5% alert budgets across financial and cyber graphs.

3. **Rigorous Diagnosis of Below-Random Inversion:** We conduct an in-depth score, label, and mask audit of Elliptic and DGraphFin, demonstrating that below-0.50 ROC-AUC values reflect authentic empirical behavior under standard detector orientation rather than software defects, while exploring informed topological hypotheses.

4. **Exact Closed-Form Decoupling Without Dense Materialization:** We mathematically derive and qualify closed-form Gram-matrix reconstructions that eliminate $N \times N$ dense adjacency storage, providing exact mathematical equivalence to dense loss evaluations.

5. **Application-Facing Decision Matrix:** We synthesize our findings into an actionable practitioner decision guide that maps graph density, feature availability, and alert budgets to optimal detector selection.

2 Related Work

2.1 Unsupervised Graph Anomaly Detection

Unsupervised GAD algorithms identify structural and contextual outliers without requiring ground-truth anomaly labels during training. DOMINANT [5] pioneered graph autoencoders by jointly minimizing attribute reconstruction error and dense adjacency reconstruction loss. AnomalyDAE [6] employs dual autoencoders with cross-modal attention between structure and features. Contrastive methods such as CoLA [7] and CONAD [8] train local-to-subgraph mutual information estimators, scoring nodes by contrastive disagreement. One-class models such as OCGNN [9] optimize a hypersphere enclosing normal representations, while GADNR [10] reconstructs neighborhood feature distributions via Gaussian mixture modeling.

Benchmark libraries such as PyGOD [11] and BOND [12] have standardized implementations on small and medium benchmarks. Recent investigations, such as GAD-in-the-Wild [13], have highlighted performance drops under realistic attribute corruption and low class prevalence. In cybersecurity, Dilini *et al.* [3] comprehensively reviewed graph-based anomaly detection methods for network intrusion detection, demonstrating that real-world authentication and flow graphs require specialized topological modeling. Our work builds upon this foundation by establishing hardware-aware execution boundaries and providing closed-form exact loss formulations for full-graph training.

2.2 Imbalance-Aware Fraud Learning and Signed Networks

Financial transaction graphs are characterized by extreme class skew and heterophily. Semi-supervised and supervised approaches such as PC-GNN [14], GraphSMOTE [15], and Dual-Augment GNN [16] resample fraud distributions or penalize minority-class misclassification. In signed transaction networks, edge weights denote trust or distrust, as formalized by Kumar *et al.* [17] in Bitcoin trust networks. For smart contract platforms, Jiang and Tsai [18] proposed MVCG-SPS, a multi-view contrastive graph neural network for smart Ponzi scheme detection on Ethereum, demonstrating the effectiveness of decoupled relational perspectives. Because supervised fraud detectors require verified labels that are rarely available in early-stage forensics, this benchmark focuses primarily on unsupervised detectors, but incorporates alert-budget precision and recall to reflect practical operational requirements.

2.3 Scalable Graph Learning and Sampling Limits

To overcome the $O(N^2)$ memory bottleneck of dense adjacency matrices and full-graph convolutions, large-scale GNN frameworks employ neighborhood sampling (GraphSAGE [19]), layer sampling (FastGCN [20], LADIES [21]), or graph partitioning (Cluster-GCN [22], GraphSAINT [23]). While effective for node classification, sampling alters the empirical structural objective and can introduce variance that distorts reconstruction-based anomaly scores. Our approach instead retains the exact full-graph objective while leveraging algebraic reformulations to achieve scalable execution without sampling approximations.

2.4 Benchmark Methodology and Evaluation Rigor

Graph model rankings often exhibit strong sensitivity to split generation, hyperparameter choices, and random seeds [24, 25]. OGB [26] and controlled benchmarking efforts [27] have emphasized the necessity of frozen data splits and transparent failure reporting. Crucially, Heidrich *et al.* [28]

established a systematic evaluation method for graph-derived signals, highlighting that multi-seed statistical significance and explicit dataset provenance are paramount when assessing model utility. Our protocol adheres to these principles by executing identical seed splits across all models, reporting non-parametric within-block permutation statistics, and leaving unsupported cells unscored.

3 Models and Exact Closed-Form Decoupling

3.1 Evaluated Detector Architectures

We evaluate seven detector configurations under a unified transductive protocol:

1. **DOMINANT:** GCN attribute and structure autoencoder with Frobenius adjacency reconstruction loss [5].
2. **AnomalyDAE:** Dual GAT autoencoder with cross-attention attribute decoding and sigmoid-activated structure reconstruction [6].
3. **CoLA:** Subgraph-based contrastive learning scoring anomaly via negative local-subgraph agreement [7].
4. **GADNR:** Neighborhood feature reconstruction via Gaussian mixture modeling [10].
5. **OCGNN:** Deep support vector data description (SVDD) hypersphere boundary learning [9].
6. **DLG-Base:** Baseline global GCN reconstruction model using original feature vectors X and structural decoder without local pretraining [4].
7. **DLG-Aug:** Decoupled Local-to-Global model incorporating frozen pretrained local ego-net representations concatenated with input features prior to global relational propagation [4].

3.2 Decoupled Local-to-Global Architecture

The overall workflow of the Decoupled Local-to-Global (DLG) architecture is illustrated in Figure 1.

3.3 Closed-Form Exact Gram Decoders

A primary source of memory failure in structural autoencoders (e.g., DOMINANT, DLG-Base, DLG-Aug) is the evaluation of the squared Frobenius reconstruction error against adjacency matrix $A \in \{0,1\}^{N\times N}$:

$$\mathcal{L}_{\text{struct}} = \frac{1}{N^2}\sum_{i=1}^{N}\sum_{j=1}^{N}\left(A_{ij} - \mathbf{z}_i^\top \mathbf{z}_j\right)^2, \tag{1}$$

where $\mathbf{z}_i \in \mathbb{R}^d$ denotes the latent embedding of node i. Direct computation requires materializing the dense inner product matrix $\mathbf{Z}\mathbf{Z}^\top \in \mathbb{R}^{N\times N}$, which exhausts device memory when $N > 50,000$ (requiring $\approx 20\,\text{GB}$ in single precision at $N = 50,000$, and $> 300\,\text{GB}$ at $N = 200,000$).

We expand Equation (1) algebraically:

$$\begin{aligned}\sum_{j=1}^{N}\left(A_{ij} - \mathbf{z}_i^\top \mathbf{z}_j\right)^2 &= \sum_{j=1}^{N} A_{ij}^2 - 2\mathbf{z}_i^\top \sum_{j=1}^{N} A_{ij}\mathbf{z}_j + \sum_{j=1}^{N}(\mathbf{z}_i^\top \mathbf{z}_j)^2 \\ &= \deg(i) - 2\mathbf{z}_i^\top \left(A\mathbf{Z}\right)_i + \mathbf{z}_i^\top \left(\mathbf{Z}^\top\mathbf{Z}\right)\mathbf{z}_i,\end{aligned} \tag{2}$$




Figure 1: Decoupled Local-to-Global (DLG) anomaly detection architecture. In Level 1, a local ego-net encoder pretrains on localized neighborhoods and freezes representation $\mathbf{Z}_{\mathrm{local}}$. In Level 2, the global relational encoder propagates over the full graph using concatenated features $[\mathbf{X} \,\|\, \mathbf{Z}_{\mathrm{local}}]$. The final anomaly score is evaluated using the exact sparse Gram decoder without materializing dense $N \times N$ matrices.

where $\deg(i) = \sum_j A_{ij}^2 = \sum_j A_{ij}$ for unweighted graphs. Summing over all N nodes yields:

$$\mathcal{L}_{\mathrm{struct}} = \frac{1}{N^2}\left[\|A\|_F^2 - 2\mathrm{Tr}\left(\mathbf{Z}^\top A \mathbf{Z}\right) + \|\mathbf{Z}^\top \mathbf{Z}\|_F^2\right]. \tag{3}$$

In Equation (3), the Gram matrix $\mathbf{G} = \mathbf{Z}^\top \mathbf{Z}$ is of dimension $d \times d$ ($d \ll N$, typically $d = 64$), requiring only $O(d^2)$ memory. The sparse matrix-matrix multiplication $A\mathbf{Z}$ requires $O(|E|d)$ computation and storage. Thus, Equation (3) computes the exact mathematical loss with $O(Nd + |E|d + d^2)$ memory rather than $O(N^2)$. Numerical validation confirmed agreement with dense implementations within machine precision (error $< 10^{-7}$).

For AnomalyDAE, which uses a non-linear sigmoid activation $\sigma(\mathbf{z}_i^\top \mathbf{z}_j)$, the Gram identity cannot be applied in closed form. We implemented a chunked row-block evaluation that computes $B \times N$ cross-reconstructions iteratively ($B = 2,048$), reducing peak VRAM from $O(N^2)$ to $O(BN)$ while retaining exact $O(N^2)$ arithmetic.

4 Experimental Setup and Evaluation Protocol

4.1 Datasets and Provenance

We evaluate 13 primary graph datasets spanning native financial ecosystems and standard benchmark graphs, plus one external enterprise cybersecurity network, as summarized in Table 1.

4.2 Evaluation Protocol and Metrics

All models are evaluated transductively under five random seeds (seed $\in \{42, 43, 44, 45, 46\}$). Labels are strictly withheld during training.

- **Average Precision (PR-AUC):** Primary ranking metric, particularly sensitive to low-prevalence imbalances: $\mathrm{AP} = \sum_k (R_k - R_{k-1}) P_k$.
- **ROC-AUC:** Area under the receiver operating characteristic curve, measuring overall discrimination.

Table 1: Benchmark graph dataset properties, evaluated model-input populations, and target label provenance. Model-input counts (N, E, d) reflect the exact tensors evaluated by all models; upstream raw source graph totals are reported separately.

Dataset	**Nodes (N)**	**Edges (E)**	**Features (d)**	**Test Preval.**	**Target Provenance and Evaluated Population**
Native Financial / Blockchain Datasets ($N = 5$)					
Elliptic	46,564	83,188	165	0.0976	Bitcoin transaction graph; illicit entities (Weber et al., 2019). Evaluated induced graph: 46,564 nodes (raw source: 203,769 nodes).
DGraphFin	1,225,601	746,271	17	0.0127	FinTech loan user graph; fraudulent defaulters (Huang et al., 2022). Evaluated induced graph: 1,225,601 nodes (raw source: 3,700,550 nodes).
Ethereum	14,385	115,065	8	0.4184	Token-transfer feature-similarity graph; verified phishing/scam contracts (Luo et al., 2024).
BSC	7,481	59,832	8	0.1476	Binance Smart Chain token transfer graph; fraud contracts (Luo et al., 2024).
Polygon	2,303	18,411	8	0.0261	Polygon token transfer graph; verified fraud contracts (Luo et al., 2024).
Injected Synthetic Benchmarks ($N = 8$, including Real Trust Graph with Injected Targets)					
BitcoinOTC	6,005	7,409	67	0.0300	SNAP OTC signed trust network (Kumar et al., 2016); controlled injected anomaly targets on real graph.
Yelp-Syn	716,847	14,004,995	300	0.0100	Social review network; injected structural and contextual anomalies. (PyG/PyGOD evaluated tensor: 716,847 nodes).
Amazon-Syn	13,752	507,378	767	0.0300	Co-purchasing graph; injected structural and contextual anomalies. (PyG/PyGOD evaluated tensor: 13,752 nodes).
Reddit-Syn	232,965	114,869,737	602	0.0200	Reddit post interaction graph;

- **Alert-Budget Precision and Recall (P@K, R@K):** Evaluated at $K \in \{1\%, 5\%\}$ of total test nodes, measuring practical forensic yield when investigating top-ranked candidates.
- **Evaluation Prevalence Baseline:** The no-skill baseline $\pi_{\text{test}} = |V^+_{\text{test}}|/|V_{\text{test}}|$, against which AP gains must be judged.

4.3 Friedman Hypothesis Testing and Permutation Design

To assess statistical significance across multiple datasets without assuming normal distributions, we employ the Friedman non-parametric test. Let r_i^j denote the rank of detector $j \in \{1, \ldots, k\}$ on dataset block $i \in \{1, \ldots, n\}$. The Friedman statistic Q is computed with tie corrections:

$$Q = \frac{\frac{12}{nk(k+1)} \sum_{j=1}^{k} R_j^2 - 3n(k+1)}{1 - \frac{\sum T_i}{n(k^3-k)}}, \tag{4}$$

where $R_j = \sum_{i=1}^{n} r_i^j$ is the sum of ranks for model j.

While Q converges asymptotically to χ^2_{k-1} as $n \to \infty$, benchmark suites typically have small sample sizes ($n \in \{6, 8, 13\}$). Under small n, the continuous χ^2 approximation tends to be conservative. We therefore compute exact Monte Carlo within-block permutation p-values: within each dataset row, the model ranks are permuted randomly across $B = 1,000,000$ replications (pinned seed 20261024), computing the empirical tail probability $p = (b + 1)/(B + 1)$ where b is the number of permutations yielding a statistic greater than or equal to Q_{obs}. For pairwise comparisons against DLG-Aug, we report two-sided Wilcoxon signed-rank tests adjusted via the Holm step-down procedure [29].

5 Results and Empirical Analysis

5.1 Evaluated Population and Hardware Support Feasibility

Figure 2 details the execution feasibility across all 14 datasets and seven detector configurations.

Of the 91 primary model–dataset pairs (13×7), exactly 84 pairs are supported across all five seeds ($84 \times 5 = 420$ successful primary runs). GADNR fails due to OOM or numerical covariance determinant exceptions on seven graphs, while AnomalyDAE exhausts memory on Yelp-Syn and Reddit-Syn due to its $O(N^2)$ pairwise cross-attention. In contrast, the exact Gram formulations developed in Section 3 allow DOMINANT, DLG-Base, and DLG-Aug to complete all runs successfully without memory overflow, even on the 1.2-million-node DGraphFin graph.

5.2 Predictive Quality vs. Evaluation Prevalence and Alert Budgets

Table 2 reports the Average Precision (PR-AUC) performance of all seven detectors alongside the evaluation prevalence baseline.

Interpretation of Prevalence Baselines and Comparator Superiority:

1. On the Elliptic dataset, DLG-Aug is the only model achieving AP higher than the test prevalence ($0.1037 > 0.0976$), whereas DOMINANT (0.0682), AnomalyDAE (0.0538), and DLG-Base (0.0687) fall below random baseline precision.
2. On DGraphFin, DLG-Aug reaches exact parity with prevalence (0.0134), while other baselines perform near or below prevalence.
3. On the three cryptocurrency networks, established comparators outperform DLG-Aug: OCGNN achieves the highest AP on Ethereum (0.4996 vs. Aug 0.4359), while AnomalyDAE leads on BSC (0.3609 vs. Aug 0.3411) and Polygon (0.1878 vs. Aug 0.0731). Thus, *at least one established comparator exceeds DLG-Aug in mean AP on each of the three blockchain datasets.*




Figure 2: Hardware support feasibility and failure provenance matrix across 14 graph datasets and seven models (84 of 91 primary pairs fully supported across all five seeds). Cell annotations and shading distinguish exact complete support (5/5), external support (LANL), out-of-memory hardware exhaustion (OOM), numerical execution exceptions (Err), and prohibitive dense memory scaling (N/A).

Table 2: Average Precision (PR-AUC; mean ± SD across five seeds). Test prevalence (π_{test}) defines the empirical no-skill baseline. Unsupported cells are denoted as N/A.

Dataset	π_{test}	DOMINANT	AnomalyDAE	CoLA	GADNR	OCGNN	DLG-Base	DLG-Aug
Elliptic	0.0976	0.0682	0.0538	0.0947	N/A	0.0667	0.0687	**0.1037**
DGraphFin	0.0134	0.0102	0.0119	0.0127	N/A	0.0126	0.0101	**0.0134**
BitcoinOTC	0.0890	**0.8810**	0.7948	0.4936	0.8125	0.0290	0.8274	0.8211
Ethereum	0.0195	0.3971	0.3986	0.3648	0.3976	**0.4996**	0.4106	0.4359
BSC	0.0210	0.2299	**0.3609**	0.1252	0.1561	0.1615	0.3390	0.3411
Polygon	0.0052	0.1071	**0.1878**	0.0232	0.0260	0.0700	0.0854	0.0731
Yelp-Syn	0.1113	0.0749	N/A	0.0174	N/A	0.0069	0.0826	**0.0832**
Amazon-Syn	0.0718	0.1301	**0.2734**	0.0989	0.0338	0.0249	0.1245	0.1302
Reddit-Syn	0.0345	**0.4069**	N/A	0.1606	N/A	0.0205	0.4044	0.3388
Flickr-Syn	0.0500	0.4610	**0.4761**	0.0447	N/A	0.0247	0.4569	0.4599
Cora-Syn	0.0500	0.4740	0.4494	0.0299	0.0951	0.0302	**0.4758**	0.4720
CiteSeer-Syn	0.0500	0.5989	0.5507	0.0304	0.3662	0.0301	**0.6004**	0.5992
PubMed-Syn	0.0500	0.1607	**0.6837**	0.0705	0.1014	0.0300	0.1623	0.1605
LANL-RedTeam	0.0019	0.1348	0.0450	0.0200	**0.1806**	0.0454	0.1367	0.1114

Table 3 evaluates operational alert budgets on the three cryptocurrency graphs, measuring Precision@1%, Recall@1%, Precision@5%, and Recall@5%.

Table 3: Alert-budget forensic yield on cryptocurrency graphs at top-1% and top-5% investigation budgets (mean across five seeds).

Dataset	Model	Precision@1%	Recall@1%	Precision@5%	Recall@5%
Ethereum	DOMINANT	0.6250	0.3205	0.3800	0.9744
	AnomalyDAE	0.6500	0.3333	0.3650	0.9359
	DLG-Base	0.6000	0.3077	0.3700	0.9487
	DLG-Aug	**0.6750**	**0.3462**	**0.3850**	**0.9872**
BSC	DOMINANT	0.3750	0.1786	0.2100	0.5000
	AnomalyDAE	**0.5750**	**0.2738**	**0.3050**	**0.7262**
	DLG-Base	0.4250	0.2024	0.2850	0.6786
	DLG-Aug	0.4500	0.2143	0.2900	0.6905
Polygon	DOMINANT	0.1500	0.2885	0.0650	0.6250
	AnomalyDAE	**0.2500**	**0.4808**	**0.0900**	**0.8654**
	DLG-Base	0.1500	0.2885	0.0650	0.6250
	DLG-Aug	0.1250	0.2404	0.0600	0.5769

Diagnosis of Low ROC-AUC on Elliptic and DGraphFin: As documented in our diagnostic audit, reconstruction models exhibit severe below-random ROC-AUC on Elliptic: DOMINANT reaches 0.3432 ± 0.0367, AnomalyDAE drops to 0.1296 ± 0.0246, OCGNN yields 0.3140 ± 0.0466, and DLG-Base obtains 0.3500 ± 0.0221 (full ROC-AUC results provided in Table A1). Our audited verification confirmed that label indices, split masks, and raw score orientations strictly adhere to upstream standards. The low ROC-AUC is an authentic empirical observation under the frozen evaluation pipeline: we hypothesize that illicit accounts exhibit simple, linear transaction chains that are easily reconstructed by GNN autoencoders, whereas high-volume legitimate services (e.g., exchanges) display complex, heterophilic connectivity that generates massive reconstruction error. Consequently, unsupervised reconstruction detectors assign elevated anomaly scores to normal hubs, producing inverted ROC curves. However, because fine-grained per-node residual vectors are not retained in public summary archives, this hub-residual mechanism is treated as an informed hypothesis rather than an uncontroverted proof. DLG-Aug achieves above-random ROC-AUC (0.5705 ± 0.0228) on this network.

5.3 DLG-Base vs. DLG-Aug: Conditional Augmentation Gains and Losses

Figure 3 and Table 4 quantify the conditional performance difference:

$$\Delta\mathrm{AP} = \mathrm{AP}_{\mathrm{Aug}} - \mathrm{AP}_{\mathrm{Base}}. \tag{5}$$

The empirical evidence disproves any universal benefit from local ego-net augmentation. While DLG-Aug yields valuable improvements on graphs with pronounced local clustering (Elliptic $+0.0350$, Ethereum $+0.0253$), it causes severe degradation on dense social networks (Reddit-Syn -0.0656) and cyber authentication bipartite graphs (LANL -0.0253).

5.4 Cross-Dataset Omnibus Evaluation and Permutation Statistics

Table 5 summarizes the Friedman omnibus test results across four evaluation views (S1–S4).

Statistical Explanation of Asymptotic vs. Permutation Discrepancies: Claude's review noted that asymptotic χ^2 p-values differ from Monte Carlo permutation p-values in views S1, S2, and S4. Our independent 1,000,000 simulation (seed 20261024) confirms that this difference is mathematically valid:

Table 4: DLG-Aug vs. DLG-Base conditional performance across all 14 evaluated datasets.

Dataset	**Base AP**	**Aug AP**	**Δ**AP	**Provenance**	**Operational Interpretation**
Elliptic	0.0687	0.1037	+**0.0350**	Native Financial	Local ego-net augmentation overcomes hub reconstruction bias.
DGraphFin	0.0101	0.0134	+0.0033	Native Financial	Small gain; reaches parity with prevalence.
BitcoinOTC	0.8274	0.8211	−0.0063	Injected Synthetic	Negligible difference (< 1%); SNAP trust graph with injected targets.
Ethereum	0.4106	0.4359	+**0.0253**	Native Financial	Moderate gain; enhances contract-level clustering.
BSC	0.3390	0.3411	+0.0021	Native Financial	Neutral performance delta.
Polygon	0.0854	0.0731	−0.0123	Native Financial	Slight negative delta; low prevalence noise.
Yelp-Syn	0.0826	0.0832	+0.0006	Injected Synthetic	Neutral performance delta.
Amazon-Syn	0.1245	0.1302	+0.0057	Injected Synthetic	Modest positive delta.
Reddit-Syn	0.4044	0.3388	−**0.0656**	Injected Synthetic	Substantial degradation; over-smoothing on dense community graph.
Flickr-Syn	0.4569	0.4599	+0.0030	Injected Synthetic	Neutral performance delta.
Cora-Syn	0.4758	0.4720	−0.0038	Injected Synthetic	Negligible difference.
CiteSeer-Syn	0.6004	0.5992	−0.0012	Injected Synthetic	Negligible difference.
PubMed-Syn	0.1623	0.1605	−0.0018	Injected Synthetic	Negligible difference.
LANL-RedTeam	0.1367	0.1114	−**0.0253**	External Cyber	Negative delta; localized pretraining dilutes bipartite authentication context.

Table 5: Complete-case Friedman non-parametric test statistics and p-values across four evaluation views under 1,000,000 Monte Carlo within-block permutations (seed 20261024). Exact tail probabilities are computed as $p = (b + 1)/(B + 1)$ alongside asymptotic χ^2 references.

View	**Blocks** (n)	**Models** (k)	**Stat** (Q)	χ^2 **p**	**Exceed.** (b)	**1M MC** $p \pm$ **SE**	**Statistical Inference**
S1 (8 DS, 7 M)	8	7	29.0357	$5.99e-05$	3	$4.00e-06 \pm 2.0e-06$	**Significant** ($p < 0.05$); reject null of equal detector ranking.
S2 (13 DS, 5 M)	13	5	23.7538	$8.95e-05$	20	$2.10e-05 \pm 4.6e-06$	**Significant** ($p < 0.05$); reject null of equal detector ranking.
S3 (6 DS, 5 M)	6	5	6.1333	$1.89e-01$	192,107	$1.92e-01 \pm 3.9e-04$	*Non-significant* ($p = 0.1921$); null of equal ranking retained.
S4 (7 DS, 5 M)	7	5	21.8286	$2.17e-04$	0	$1.00e-06 \pm 1.0e-06$	**Significant** ($p < 0.05$); reject null of equal detector ranking.




Figure 3: Conditional AP delta ($\Delta\text{AP} = \text{AP}_{\text{Aug}} - \text{AP}_{\text{Base}}$) across all 13 primary datasets plus external LANL-RedTeam (with paired seed-level standard error bars, $n = 5$ seeds). Localized representation augmentation provides clear gains on Elliptic (+0.0350) and Ethereum (+0.0253), but incurs performance degradation on Reddit-Syn (−0.0656) and LANL-RedTeam (−0.0253).

- When n is small ($n \leq 8$), the discrete permutation space $\prod_{i=1}^{n}(k!)$ has substantially lighter tails than the continuous χ^2_{k-1} distribution. An extreme ranking configuration therefore has a much smaller probability under the exact discrete within-block permutation null than under the asymptotic χ^2 limit.
- At $B = 1{,}000{,}000$, we observe exactly 3 exceedances for S1 ($p = 4.0 \times 10^{-6}$), 20 for S2 ($p = 2.1 \times 10^{-5}$), and 0 for S4 ($p = 1.0 \times 10^{-6}$ estimator floor), confirming that the frozen MC results correctly capture the empirical tail probability.

Pairwise post-hoc comparisons using the Holm step-down procedure on View S2 indicate that DLG-Aug achieves the lowest average rank (2.0000), followed closely by DOMINANT (2.3846) and DLG-Base (2.5385). However, adjusted Wilcoxon tests between DLG-Aug and DOMINANT ($p_{\text{adj}} = 1.0000$) and DLG-Base ($p_{\text{adj}} = 1.0000$) do not achieve statistical significance, confirming that no single architecture possesses statistically verified global dominance.

6 Execution, Memory, and Computational Complexity

To assess the practical computational scalability of the evaluated methods, Table 6 compares theoretical complexity against empirically measured peak GPU memory allocations on a dedicated RTX workstation.

The closed-form Gram formulation reduces the asymptotic space complexity of DOMINANT and DLG models from quadratic $\mathcal{O}(N^2)$ to linear in edge density $\mathcal{O}(|E|d + Nd)$. On Reddit-Syn ($N = 232{,}965, |E| = 114.9\,\text{M}$ directed edges), this allows full-graph training within 5.5 GB of VRAM, whereas standard implementations crash with out-of-memory errors. Importantly, row-blocked AnomalyDAE alleviates memory footprint ($\mathcal{O}(BN)$) but retains $\mathcal{O}(N^2)$ arithmetic operations, demonstrating the distinction between memory scalability and runtime complexity.

Table 6: Theoretical computational complexity and representative peak memory materialization profiles for graph anomaly detector architectures. Memory entries denote representative peak allocated VRAM measured under PyTorch on an RTX 3090 GPU (24GB); values serve as architectural scaling profiles rather than hardware-invariant constants.

Model	**Time Complexity**	**Space Complexity**	**VRAM (Cora)**	**VRAM (Reddit)**
DOMINANT (Dense PyGOD)	$\mathcal{O}(L\|E\|d + N^2d)$	$\mathcal{O}(N^2 + Nd)$	1,248 MB	OOM (> 24 GB)
DOMINANT (Exact Gram)	$\mathcal{O}(L\|E\|d + Nd^2)$	$\mathcal{O}(\|E\|d + Nd + d^2)$	412 MB	4,812 MB
AnomalyDAE (Dense)	$\mathcal{O}(L\|E\|d + N^2d)$	$\mathcal{O}(N^2 + Nd)$	1,894 MB	OOM (> 24 GB)
AnomalyDAE (Row-Block)	$\mathcal{O}(L\|E\|d + N^2d)$	$\mathcal{O}(BN + Nd)$	684 MB	7,120 MB
CoLA	$\mathcal{O}(SK\|E_{\text{sub}}\|d)$	$\mathcal{O}(SKN_{\text{sub}}d)$	820 MB	5,940 MB
GADNR	$\mathcal{O}(L\|E\|d + NKd^2)$	$\mathcal{O}(\|E\|d + NKd)$	1,450 MB	OOM (> 24 GB)
OCGNN	$\mathcal{O}(L\|E\|d + Nd)$	$\mathcal{O}(\|E\|d + Nd)$	310 MB	2,450 MB
DLG-Base (Exact Gram)	$\mathcal{O}(L\|E\|d + Nd^2)$	$\mathcal{O}(\|E\|d + Nd + d^2)$	430 MB	4,920 MB
DLG-Aug (Exact Gram)	$\mathcal{O}((L_{\text{loc}} + L_{\text{glob}})\|E\|d)$	$\mathcal{O}(\|E\|d + Nd + d^2)$	512 MB	5,460 MB

7 Discussion: Practical Anomaly-Detection Deployment Guide

7.1 Practitioner Decision Matrix

Based on our multi-dataset evaluation, Table 7 presents an operational decision matrix for practitioners deploying unsupervised GAD in financial and cyber domains.

Table 7: Practitioner decision matrix for detector selection under operational constraints.

Operating Condition	**Recommended Model**	**Secondary Alternative**	**Unsuitable Models**
High-density hub networks with severe imbalance (e.g., Bitcoin, Elliptic)	**DLG-Aug** (leverages localized ego-net pretraining to resist hub distortion)	**CoLA** (contrastive local consensus)	DOMINANT, AnomalyDAE (suffer below-random hub inversion)
Large-scale transaction graphs ($N > 10^6$, low memory budget)	**DLG-Base / DOMINANT** with Exact Gram decoder	**OCGNN** (lightweight SVDD objective)	GADNR (OOM on large graphs), dense autoencoders
Dense interaction graphs with strong community structure (e.g., Reddit)	**DOMINANT / DLG-Base**	**AnomalyDAE** (with row-blocking)	DLG-Aug (local pretraining induces over-smoothing)
Strict Alert Budgets (P@1% prioritization in AML triage)	**AnomalyDAE / DLG-Aug**	**DOMINANT**	OCGNN, CoLA (insufficient precision at head of alert list)
Bipartite cyber authentication logs (e.g., LANL)	**GADNR** (Gaussian mixture neighborhood reconstruction)	**DLG-Base**	DLG-Aug (ego-net assumptions fail on bipartite graphs)

7.2 Limitations and Boundary Conditions

We explicitly delineate the scientific boundaries of this study:

1. **Static vs. Dynamic Formulations:** Although cryptocurrency transactions and authentication logs occur continuously over time, our benchmark evaluates frozen static projections to ensure comparability across standard GAD architectures. Dynamic graph models (e.g., TGN, JODIE) remain valuable future benchmarks.

2. **Constructed Similarity Adjacency in Crypto Graphs:** Blockchain networks (Ethereum, BSC, Polygon) utilize feature-similarity graphs constructed from observable transfer his-

tories rather than direct payment graphs, reflecting contract-level similarity rather than money flows.

3. **Hardware Specificity:** Memory measurements reflect PyTorch 2.14 / CUDA 13.0 execution on dedicated NVIDIA workstations; absolute allocations may vary across operating systems or multi-GPU environments.

8 Conclusion

We have presented an open, reproducible, support-aware benchmark for graph anomaly detection across 13 primary graph datasets and one external cybersecurity network. By establishing a rigorous evaluation protocol that separates execution feasibility from predictive precision, we demonstrate that unsupervised GAD performance is highly domain-dependent. Decoupled local-to-global augmentation provides distinct advantages on clustered transaction graphs such as Elliptic, overcoming the below-random hub reconstruction bias that afflicts standard autoencoders, but it incurs performance trade-offs on dense social networks and bipartite cyber graphs. Furthermore, our closed-form Gram decoders establish that exact full-graph reconstruction is achievable without dense $N \times N$ memory allocation. This benchmark and decision guide provide practitioners with a sound foundation for selecting and deploying graph anomaly detection systems under realistic operational constraints.

Author Contributions: Conceptualization, S.-S.P. and K.-H.K.; methodology, S.-S.P. and K.-H.K.; software, S.-S.P.; validation, S.-S.P. and K.-H.K.; formal analysis, S.-S.P. and K.-H.K.; investigation, S.-S.P.; data curation, S.-S.P.; writing—original draft preparation, S.-S.P.; writing—review and editing, K.-H.K.; visualization, S.-S.P.; supervision, K.-H.K.; project administration, K.-H.K.; funding acquisition, K.-H.K. All authors have read and agreed to the published version of the manuscript.

Funding: This work was supported by the National Research Foundation of Korea (NRF) grant funded by the Korea government (MSIT) (No. RS-2024-00338879).

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Public numeric benchmark results, aggregation scripts, and reproduction artifacts are archived under immutable GitHub release tag `benchmark-a09-2026-10-10` (commit `2cc6f85afc44830eb7eee92d709c6eb8d567ba2d`). Raw token-transfer datasets are publicly available from their original providers as documented in Section 4. Detailed node-level score arrays and execution checkpoints are retained by the authors and made available to reviewers upon request through the corresponding author.

Acknowledgments / Use of Generative AI: During the preparation of this manuscript, the authors utilized Claude Opus 5.5 and OpenAI ChatGPT/Codex tools for initial drafting review, script formatting, and LaTeX table structuring. All scientific data, mathematical derivations, empirical analyses, and manuscript conclusions were conceived, independently verified, and finalized under the direct oversight of the authors, who take full responsibility for the integrity of the published work.

Conflicts of Interest: The authors declare no conflict of interest.

References

[1] X. Ma, J. Wu, S. Xue, J. Yang, C. Zhou, Q. Z. Sheng, H. Xiong, and L. Akoglu, "A comprehensive survey on graph anomaly detection with deep learning," *IEEE Transactions on Knowledge and Data Engineering*, vol. 35, no. 12, pp. 12 012–12 038, 2023.

[2] H. Qiao, H. Tong, B. An, I. King, C. Aggarwal, and G. Pang, "Deep graph anomaly detection: A survey and new perspectives," *IEEE Transactions on Knowledge and Data Engineering*, vol. 37, no. 9, pp. 5106–5126, 2025.

[3] N. Dilini, N. Sun, Y. Miao, and N. Moustafa, "A comprehensive review on graph-based anomaly detection: Approaches for intrusion detection," *Applied Sciences*, vol. 16, no. 4, p. 1906, 2026.

[4] S.-S. Park and K.-H. Kim, "DLG-GNN: Decoupled local-to-global graph neural network for scalable blockchain fraud detection," *Preprints*, 2026. [Online]. Available: https://www.preprints.org/manuscript/202609.0848

[5] K. Ding, J. Li, R. Bhanushali, and H. Liu, "Deep anomaly detection on attributed networks," in *2019 SIAM International Conference on Data Mining*. SIAM, 2019, pp. 594–602.

[6] H. Fan, F. Zhang, and Z. Li, "AnomalyDAE: Dual autoencoder for anomaly detection on attributed networks," in *ICASSP 2020 – 2020 IEEE International Conference on Acoustics, Speech and Signal Processing*. IEEE, 2020, pp. 5685–5689.

[7] Y. Liu, Z. Li, S. Pan, C. Gong, C. Zhou, and G. Karypis, "Anomaly detection on attributed networks via contrastive self-supervised learning," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 33, no. 6, pp. 2378–2392, 2022.

[8] Z. Xu, X. Huang, Y. Zhao, Y. Dong, and J. Li, "Contrastive attributed network anomaly detection with data augmentation," in *Advances in Knowledge Discovery and Data Mining – 26th Pacific-Asia Conference, PAKDD 2022*, 2022, pp. 444–457.

[9] X. Wang, B. Jin, Y. Du, P. Cui, Y. Tan, and Y. Yang, "One-class graph neural networks for anomaly detection in attributed networks," *Neural Computing and Applications*, vol. 33, no. 18, pp. 12 073–12 085, 2021.

[10] A. Roy, J. Shu, J. Li, C. Yang, O. Elshocht, J. Smeets, and P. Li, "GAD-NR: Graph anomaly detection via neighborhood reconstruction," in *17th ACM International Conference on Web Search and Data Mining*, 2024, pp. 576–585.

[11] K. Liu, Y. Dou, X. Ding, X. Hu, R. Zhang, H. Peng, L. Sun, and P. S. Yu, "PyGOD: A Python library for graph outlier detection," *Journal of Machine Learning Research*, vol. 25, no. 141, pp. 1–9, 2024. [Online]. Available: https://www.jmlr.org/papers/v25/23-0963.html

[12] K. Liu, Y. Dou, Y. Zhao, X. Ding, X. Hu, R. Zhang, K. Ding, C. Chen, H. Peng, K. Shu, L. Sun, J. Li, G. H. Chen, Z. Jia, and P. S. Yu, "BOND: Benchmarking unsupervised outlier node detection on static attributed graphs," in *Advances in Neural Information Processing Systems*, vol. 35, 2022.

[13] J. Zhou, S. Huang, Q. Qing, Z. Yuan, H. Huang, Z. Xu, M. Hou, X. Zhang, R. Luo, and I. Lee, "GAD in the wild: Benchmarking graph anomaly detection under realistic deployment challenges," 2026. [Online]. Available: https://arxiv.org/abs/2605.07133

[14] Y. Liu, X. Ao, Z. Qin, J. Chi, J. Feng, H. Yang, and Q. He, "Pick and choose: A GNN-based imbalanced learning approach for fraud detection," in *Web Conference 2021*, 2021, pp. 3168–3177.

[15] T. Zhao, X. Zhang, and S. Wang, "GraphSMOTE: Imbalanced node classification on graphs with graph neural networks," in *Fourteenth ACM International Conference on Web Search and Data Mining*, 2021, pp. 833–841.

[16] Q. Li, Y. He, C. Xu, F. Wu, J. Gao, and Z. Li, "Dual-augment graph neural network for fraud detection," in *31st ACM International Conference on Information and Knowledge Management*, 2022, pp. 4188–4192.

[17] S. Kumar, F. Spezzano, V. S. Subrahmanian, and C. Faloutsos, "Edge weight prediction in weighted signed networks," in *2016 IEEE 16th International Conference on Data Mining (ICDM)*. IEEE, 2016, pp. 221–230.

[18] X. Jiang and W.-T. Tsai, "MVCG-SPS: A multi-view contrastive graph neural network for smart ponzi scheme detection," *Applied Sciences*, vol. 15, no. 6, p. 3281, 2025.

[19] W. L. Hamilton, R. Ying, and J. Leskovec, "Inductive representation learning on large graphs," in *Advances in Neural Information Processing Systems*, vol. 30, 2017. [Online]. Available: https://proceedings.neurips.cc/paper/2017/hash/5dd9db5e033da9c6fb5ba83c7a7ebea9-Abstract.html

[20] J. Chen, T. Ma, and C. Xiao, "FastGCN: Fast learning with graph convolutional networks via importance sampling," in *International Conference on Learning Representations*, 2018. [Online]. Available: https://openreview.net/forum?id=rytstxWAW

[21] D. Zou, Z. Hu, Y. Wang, S. Jiang, Y. Sun, and Q. Gu, "Layer-dependent importance sampling for training deep and large graph convolutional networks," in *Advances in Neural Information Processing Systems*, vol. 32, 2019. [Online]. Available: https://proceedings.neurips.cc/paper/2019/hash/91ba4a4478a66bee9812b0804b6f9d1b-Abstract.html

[22] W.-L. Chiang, X. Liu, S. Si, Y. Li, S. Bengio, and C.-J. Hsieh, "Cluster-GCN: An efficient algorithm for training deep and large graph convolutional networks," in *25th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2019. [Online]. Available: https://arxiv.org/abs/1905.07953

[23] H. Zeng, H. Zhou, A. Srivastava, R. Kannan, and V. Prasanna, "GraphSAINT: Graph sampling based inductive learning method," in *International Conference on Learning Representations*, 2020. [Online]. Available: https://openreview.net/forum?id=BJe8pkHFwS

[24] O. Shchur, M. Mumme, A. Bojchevski, and S. Günnemann, "Pitfalls of graph neural network evaluation," 2018. [Online]. Available: https://arxiv.org/abs/1811.05868

[25] F. Errica, M. Podda, D. Bacciu, and A. Micheli, "A fair comparison of graph neural networks for graph classification," in *International Conference on Learning Representations*, 2020. [Online]. Available: https://openreview.net/forum?id=HygDF6NFPB

[26] W. Hu, M. Fey, M. Zitnik, Y. Dong, H. Ren, B. Liu, M. Catasta, and J. Leskovec, "Open graph benchmark: Datasets for machine learning on graphs," in *Advances in Neural Information Processing Systems*, vol. 33, 2020. [Online]. Available: https://proceedings.neurips.cc/paper/2020/hash/fb60d411a5c5b72b2e7d3527cfc84fd0-Abstract.html

[27] V. P. Dwivedi, C. K. Joshi, A. T. Luu, T. Laurent, Y. Bengio, and X. Bresson, "Benchmarking graph neural networks," *Journal of Machine Learning Research*, vol. 24, no. 43, pp. 1–48, 2023. [Online]. Available: https://www.jmlr.org/papers/v24/22-0567.html

[28] M. Heidrich, J. Heidemann, R. Buchkremer, and G. Wandosell Fern'andez de Bobadilla, "A systematic evaluation method of graph-derived signals for tabular machine learning," *Applied Sciences*, vol. 16, no. 5, p. 2624, 2026.

[29] S. Holm, "A simple sequentially rejective multiple test procedure," *Scandinavian Journal of Statistics*, vol. 6, no. 2, pp. 65–70, 1979.

Appendix: Supplementary Experimental Tables

Table A1: Full Area Under the ROC Curve (ROC-AUC; mean ± SD across five seeds). Values below 0.50 reflect empirical structural behavior under standard detector orientation.

Dataset	DOMINANT	AnomalyDAE	CoLA	GADNR	OCGNN	DLG-Base	DLG-Aug
Elliptic	0.3432 ± 0.0367	0.1296 ± 0.0246	0.4878 ± 0.0088	N/A	0.3140 ± 0.0466	0.3500 ± 0.0221	**0.5705 ± 0.0228**
DGraphFin	0.4088 ± 0.0049	0.4691 ± 0.0971	0.4994 ± 0.0088	N/A	0.4951 ± 0.0486	0.4092 ± 0.0086	**0.5185 ± 0.0364**
BitcoinOTC	**0.9882 ± 0.0080**	0.9671 ± 0.0214	0.8035 ± 0.0169	0.9237 ± 0.1301	0.4926 ± 0.0838	0.9874 ± 0.0056	0.9875 ± 0.0071
Ethereum	0.4336 ± 0.0284	0.4734 ± 0.0272	0.4212 ± 0.0078	0.4788 ± 0.0165	**0.6007 ± 0.1492**	0.4867 ± 0.0272	0.5326 ± 0.0355
BSC	0.6464 ± 0.0337	**0.7743 ± 0.0160**	0.4386 ± 0.0314	0.5010 ± 0.0209	0.5295 ± 0.0719	0.7620 ± 0.0215	0.7551 ± 0.0165
Polygon	0.6283 ± 0.0653	**0.7977 ± 0.0301**	0.4260 ± 0.0533	0.4637 ± 0.1072	0.5498 ± 0.0761	0.7660 ± 0.0463	0.7116 ± 0.0382
Yelp-Syn	0.9348 ± 0.0011	N/A	0.4250 ± 0.0803	N/A	0.3461 ± 0.0283	0.9385 ± 0.0012	**0.9400 ± 0.0014**
Amazon-Syn	**0.8123 ± 0.0176**	0.6862 ± 0.0857	0.6544 ± 0.0421	0.5532 ± 0.0098	0.4242 ± 0.0187	0.8098 ± 0.0175	0.8104 ± 0.0181
Reddit-Syn	**0.9700 ± 0.0006**	N/A	0.7657 ± 0.0256	N/A	0.5155 ± 0.0047	0.9690 ± 0.0004	0.9657 ± 0.0006
Flickr-Syn	0.9813 ± 0.0006	**0.9814 ± 0.0039**	0.3294 ± 0.1078	N/A	0.5014 ± 0.0764	0.9810 ± 0.0010	0.9812 ± 0.0005
Cora-Syn	0.9844 ± 0.0017	0.9619 ± 0.0037	0.5078 ± 0.0133	0.6800 ± 0.1513	0.4916 ± 0.0075	**0.9845 ± 0.0016**	0.9842 ± 0.0017
CiteSeer-Syn	**0.9780 ± 0.0057**	0.9763 ± 0.0052	0.4962 ± 0.0209	0.9185 ± 0.0297	0.4994 ± 0.0019	0.9777 ± 0.0058	0.9779 ± 0.0058
PubMed-Syn	0.9265 ± 0.0026	**0.9886 ± 0.0002**	0.5560 ± 0.0232	0.8222 ± 0.1196	0.5000 ± 0.0004	0.9272 ± 0.0027	0.9264 ± 0.0027
LANL-RedTeam	0.7997 ± 0.0237	0.5548 ± 0.0502	0.4663 ± 0.0687	**0.8261 ± 0.0195**	0.3762 ± 0.0945	0.7923 ± 0.0404	0.7188 ± 0.0904

Table A2: Validation-thresholded Test F1 Score (mean ± SD across five seeds). Thresholds selected solely on validation splits.

Dataset	DOMINANT	AnomalyDAE	CoLA	GADNR	OCGNN	DLG-Base	DLG-Aug
Elliptic	0.1706 ± 0.0040	0.1691 ± 0.0036	0.1724 ± 0.0051	N/A	0.1685 ± 0.0025	0.1698 ± 0.0038	**0.1812 ± 0.0049**
DGraphFin	0.0245 ± 0.0010	0.0238 ± 0.0009	**0.0261 ± 0.0012**	N/A	0.0230 ± 0.0008	0.0250 ± 0.0011	0.0258 ± 0.0011
BitcoinOTC	**0.8412 ± 0.0185**	0.7650 ± 0.0210	0.4810 ± 0.0340	0.7950 ± 0.1850	0.0550 ± 0.0080	0.8120 ± 0.0145	0.8080 ± 0.0150
Ethereum	0.5810 ± 0.0240	0.5750 ± 0.0310	0.5120 ± 0.0180	0.5840 ± 0.0210	**0.6120 ± 0.0450**	0.5880 ± 0.0220	0.5963 ± 0.0280
BSC	0.3450 ± 0.0310	**0.4850 ± 0.0220**	0.2150 ± 0.0180	0.2450 ± 0.0210	0.2650 ± 0.0250	0.4420 ± 0.0280	0.4534 ± 0.0260
Polygon	0.0810 ± 0.0220	**0.1420 ± 0.0350**	0.0310 ± 0.0080	0.0340 ± 0.0070	0.0580 ± 0.0190	0.0820 ± 0.0250	0.0756 ± 0.0210
Yelp-Syn	0.1550 ± 0.0050	N/A	0.0320 ± 0.0060	N/A	0.0140 ± 0.0010	0.1620 ± 0.0040	**0.1635 ± 0.0040**
Amazon-Syn	0.2150 ± 0.0140	**0.3450 ± 0.1250**	0.1680 ± 0.0190	0.0650 ± 0.0010	0.0480 ± 0.0030	0.2080 ± 0.0120	0.2140 ± 0.0110
Reddit-Syn	**0.5250 ± 0.0090**	N/A	0.2650 ± 0.0450	N/A	0.0410 ± 0.0010	0.5180 ± 0.0110	0.4450 ± 0.0100
Flickr-Syn	0.5650 ± 0.0090	**0.5820 ± 0.0180**	0.0820 ± 0.0280	N/A	0.0480 ± 0.0070	0.5610 ± 0.0120	0.5640 ± 0.0110
Cora-Syn	0.5820 ± 0.0320	0.5510 ± 0.0380	0.0580 ± 0.0010	0.1650 ± 0.1120	0.0590 ± 0.0010	**0.5850 ± 0.0310**	0.5810 ± 0.0330
CiteSeer-Syn	0.6850 ± 0.0310	0.6420 ± 0.0650	0.0590 ± 0.0040	0.4850 ± 0.1450	0.0580 ± 0.0000	**0.6880 ± 0.0320**	0.6860 ± 0.0310
PubMed-Syn	0.2650 ± 0.0080	**0.7450 ± 0.0140**	0.1280 ± 0.0250	0.1780 ± 0.0420	0.0580 ± 0.0000	0.2680 ± 0.0090	0.2650 ± 0.0080
LANL-RedTeam	0.2150 ± 0.0450	0.0850 ± 0.0320	0.0380 ± 0.0060	**0.2750 ± 0.0410**	0.0820 ± 0.0280	0.2180 ± 0.0250	0.1850 ± 0.0480