

Incident report analysis

Summary	Our organisation recently experienced a DoS attack which compromised the internal network for 2 hours until it was resolved. During the attack the team reported that network services suddenly stopped responding due to a flood of ICMP packets. Normal internal traffic could no longer access any network services. In response, we blocked incoming ICMP packets and took offline all non-critical network services and restored critical network services. The attack appears to be an ICMP flood attack carried out by a malicious actor who targeted the network though an unconfigured firewall.
Identify	We identified that the malicious actor targeted network services using an ICMP flood attack. After conducting an internal audit we discovered an unconfigured firewall which allowed the attacker to overload the network and bring critical services to a stand still.
Protect	In response the team implemented a new firewall rule to limit the rate of ICMP packet requests and added source IP verification to check for spoofed IP addresses on incoming ICMP packets. Additionally we will apply network monitoring software to detect abnormal traffic patterns and an intrusion prevention system (IPS.
Detect	To detect any future ICMP flood attacks the team will implement a new firewall rule, network monitoring software and intrusion detection system (IDS) to monitor all incoming traffic for spoofed IP addresses.
Respond	The team will respond to future ICMP flood attacks by blocking incoming ICMP packets, stopping all non-critical services and restoring critical network services. We will implement stronger security measures and invest in an intrusion detection system (IDS) to monitor logs for suspicious activity and

	report incidents to the relevant authorities.
Recover	The team will recover the network services back to normal operations by stopping all non-critical services and recovering all critical network services. We will apply the new firewall to limit the rate of incoming ICMP packets. Use network monitoring software and an intrusion detection system (IDS) to filter out suspicious ICMP traffic behavior. Once the attack has stopped we can then restore all services back to normal operation.

Reflections/Notes: