Sheet 6: Training a RNN to learn sinusoidal oscillations

CC BY-NC-SA 4.0 Attribution-NonCommercial-ShareAlike 4.0 International (https://creativecommons.org/licenses/by-nc-sa/4.0/) Thomas Ingo Trappenberg, last modified on Wed Jan 29 09:49:39 2025 using Emacs 29.4 (Org mode 9.6.15)

The aim of this note book is to build, refine, and test a RNN and show where there was hard to write.

```
import torch
import torch.nn as nn
import torch.optim as optim
import numpy as np
import matplotlib.pyplot as plt
```

```
# Set device (use GPU if available)
device = torch.device('cuda' if torch.cuda.is_available() else 'cpu')
print(f"Using device: {device}")
```

```
Using device: cpu
```

RNN using nn.RNNCell

We start with the simplest option, i.e. a RNN cell. Then we add the training loop and a few plots to see how we are doing. Finally we add a few more plots to see what is going on in the hidden layer.

```
# Define the RNN model using RNNCell
class SimpleRNN(nn.Module):
    def __init__(self, input_size, hidden_size, output_size):
        super(SimpleRNN, self).__init__()
        self.hidden_size = hidden_size
        self.rnn_cell = nn.RNNCell(input_size, hidden_size)
        self.fc = nn.Linear(hidden_size, output_size)

    def forward(self, x, h):
        h = self.rnn_cell(x, h)
        out = self.fc(h)
        return out, h

    def init_hidden(self, batch_size):
        return torch.zeros(batch_size, self.hidden_size).to(device)
```

```
# Hyperparameters
input_size = 1
hidden_size = 32
output_size = 1
learning_rate = 0.01
num_epochs = 1000
seq_length = 100
```

```
# Create the model, loss function, and optimizer
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=learning_rate)
```

```
# Generate sine wave data
def generate_data(seq_length):
    x = np.linspace(0, 4*np.pi, seq_length + 1)
    y = np.sin(x)
    return y[:-1], y[1:]

# Prepare training data
y_train, y_target = generate_data(seq_length)
y_train = torch.tensor(y_train, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
y_target = torch.tensor(y_target, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
```

```
# Training loop
for epoch in range(num_epochs):
    h = model.init_hidden(1)
    optimizer.zero_grad()
    loss = 0
    for t in range(seq_length):
        y_pred, h = model(y_train[:, t, :], h)
        loss += criterion(y_pred, y_target[:, t, :])
    loss.backward()
    optimizer.step()

    if (epoch+1) % 100 == 0:
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item()/seq_length:.4f}')
```

```
Epoch [100/1000], Loss: 0.0004
Epoch [200/1000], Loss: 0.0001
Epoch [300/1000], Loss: 0.0000
Epoch [400/1000], Loss: 0.0000
Epoch [500/1000], Loss: 0.0000
Epoch [600/1000], Loss: 0.0000
Epoch [700/1000], Loss: 0.0000
Epoch [800/1000], Loss: 0.0000
Epoch [900/1000], Loss: 0.0000
Epoch [1000/1000], Loss: 0.0000
```

```
# Plot the results
model.eval()
with torch.no_grad():
    h = model.init_hidden(1)
    predictions = []
    for t in range(seq_length):
        y_pred, h = model(y_train[:, t, :], h)
        predictions.append(y_pred.cpu().numpy())

plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions, label='Predicted')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```


RNN using nn.RNN

```
# Define the RNN model using RNN
class SimpleRNN(nn.Module):
    def __init__(self, input_size, hidden_size, output_size):
        super(SimpleRNN, self).__init__()
        self.hidden_size = hidden_size
        self.rnn = nn.RNN(input_size, hidden_size, batch_first=True)
        self.fc = nn.Linear(hidden_size, output_size)

    def forward(self, x, h):
        out, h = self.rnn(x, h)
        out = self.fc(out)
        return out, h

    def init_hidden(self, batch_size):
        return torch.zeros(1, batch_size, self.hidden_size).to(device)
```

```
# Hyperparameters
input_size = 1
hidden_size = 32
output_size = 1
learning_rate = 0.01
num_epochs = 1000
seq_length = 100
```

```
# Create the model, loss function, and optimizer
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=learning_rate)
```

```
# Generate sine wave data
def generate_data(seq_length):
    x = np.linspace(0, 4*np.pi, seq_length + 1)
    y = np.sin(x)
    return y[:-1], y[1:]

# Prepare training data
y_train, y_target = generate_data(seq_length)
y_train = torch.tensor(y_train, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
y_target = torch.tensor(y_target, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
```

```
# Training loop
for epoch in range(num_epochs):
    h = model.init_hidden(1)
    optimizer.zero_grad()
    y_pred, h = model(y_train, h)
    loss = criterion(y_pred, y_target)
    loss.backward()
    optimizer.step()

    if (epoch+1) % 100 == 0:
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item():.4f}')
```

```
Epoch [100/1000], Loss: 0.0004
Epoch [200/1000], Loss: 0.0001
Epoch [300/1000], Loss: 0.0000
Epoch [400/1000], Loss: 0.0000
Epoch [500/1000], Loss: 0.0000
Epoch [600/1000], Loss: 0.0000
Epoch [700/1000], Loss: 0.0000
Epoch [800/1000], Loss: 0.0000
Epoch [900/1000], Loss: 0.0000
Epoch [1000/1000], Loss: 0.0000
```

```
# Plot the results
model.eval()
with torch.no_grad():
    h = model.init_hidden(1)
    predictions, h = model(y_train, h)

plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```


RNN using nn.RNN and plotting

```
# Define the RNN model using RNN
class SimpleRNN(nn.Module):
    def __init__(self, input_size, hidden_size, output_size):
        super(SimpleRNN, self).__init__()
        self.hidden_size = hidden_size
        self.rnn = nn.RNN(input_size, hidden_size, batch_first=True)
        self.fc = nn.Linear(hidden_size, output_size)

    def forward(self, x, h):
        out, h = self.rnn(x, h)
        out = self.fc(out)
        return out, h

    def init_hidden(self, batch_size):
        return torch.zeros(1, batch_size, self.hidden_size).to(device)
```

```
# Hyperparameters
input_size = 1
hidden_size = 32
output_size = 1
learning_rate = 0.01
num_epochs = 1000
seq_length = 100
```

```
# Create the model, loss function, and optimizer
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=learning_rate)
```

```
# Generate sine wave data
def generate_data(seq_length):
    x = np.linspace(0, 4*np.pi, seq_length + 1)
    y = np.sin(x)
    return y[:-1], y[1:]

# Prepare training data
y_train, y_target = generate_data(seq_length)
y_train = torch.tensor(y_train, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
y_target = torch.tensor(y_target, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
```

```
# Training loop
for epoch in range(num_epochs):
    h = model.init_hidden(1)
    optimizer.zero_grad()
    y_pred, h = model(y_train, h)
    loss = criterion(y_pred, y_target)
    loss.backward()
    optimizer.step()

    if (epoch+1) % 100 == 0:
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item():.4f}')
```

```
Epoch [100/1000], Loss: 0.0004
Epoch [200/1000], Loss: 0.0001
Epoch [300/1000], Loss: 0.0000
Epoch [400/1000], Loss: 0.0000
Epoch [500/1000], Loss: 0.0000
Epoch [600/1000], Loss: 0.0000
Epoch [700/1000], Loss: 0.0000
Epoch [800/1000], Loss: 0.0000
Epoch [900/1000], Loss: 0.0000
Epoch [1000/1000], Loss: 0.0000
```

```
# Plot the results
model.eval()
with torch.no_grad():
    h = model.init_hidden(1)
    predictions, h = model(y_train, h)

plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```



```
# Plot the hidden states
plt.figure(figsize=(10, 5))
plt.plot(h.cpu().numpy().squeeze())
plt.title('Hidden States')
plt.show()
```



```
# Plot the weights
plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_ih_l0.cpu().detach().numpy())
plt.title('Input-to-Hidden Weights')
plt.show()

plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_hh_l0.cpu().detach().numpy())
plt.title('Hidden-to-Hidden Weights')
plt.show()
```


RNN using nn.RNN and plotting

```
# Define the RNN model using RNN
class SimpleRNN(nn.Module):
    def __init__(self, input_size, hidden_size, output_size):
        super(SimpleRNN, self).__init__()
        self.hidden_size = hidden_size
        self.rnn = nn.RNN(input_size, hidden_size, batch_first=True)
        self.fc = nn.Linear(hidden_size, output_size)

    def forward(self, x, h):
        out, h = self.rnn(x, h)
        out = self.fc(out)
        return out, h

    def init_hidden(self, batch_size):
        return torch.zeros(1, batch_size, self.hidden_size).to(device)
```

```
# Hyperparameters
input_size = 1
hidden_size = 32
output_size = 1
learning_rate = 0.01
num_epochs = 1000
seq_length = 100
```

```
# Create the model, loss function, and optimizer
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=learning_rate)
```

```
# Generate sine wave data
def generate_data(seq_length):
    x = np.linspace(0, 4*np.pi, seq_length + 1)
    y = np.sin(x)
    return y[:-1], y[1:]

# Prepare training data
y_train, y_target = generate_data(seq_length)
y_train = torch.tensor(y_train, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
y_target = torch.tensor(y_target, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
```

```
# Training loop
for epoch in range(num_epochs):
    h = model.init_hidden(1)
    optimizer.zero_grad()
    y_pred, h = model(y_train, h)
    loss = criterion(y_pred, y_target)
    loss.backward()
    optimizer.step()

    if (epoch+1) % 100 == 0:
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item():.4f}')
```

```
Epoch [100/1000], Loss: 0.0004
Epoch [200/1000], Loss: 0.0001
Epoch [300/1000], Loss: 0.0000
Epoch [400/1000], Loss: 0.0000
Epoch [500/1000], Loss: 0.0000
Epoch [600/1000], Loss: 0.0000
Epoch [700/1000], Loss: 0.0000
Epoch [800/1000], Loss: 0.0000
Epoch [900/1000], Loss: 0.0000
Epoch [1000/1000], Loss: 0.0000
```

```
# Plot the results
model.eval()
with torch.no_grad():
    h = model.init_hidden(1)
    predictions, h = model(y_train, h)

plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```



```
# Plot the hidden states
plt.figure(figsize=(10, 5))
plt.plot(h.cpu().numpy().squeeze())
plt.title('Hidden States')
plt.show()
```



```
# Plot the weights
plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_ih_l0.cpu().detach().numpy())
plt.title('Input-to-Hidden Weights')
plt.show()

plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_hh_l0.cpu().detach().numpy())
plt.title('Hidden-to-Hidden Weights')
plt.show()
```


RNN using nn.RNN and plotting and saving

```
# Define the RNN model using RNN
class SimpleRNN(nn.Module):
    def __init__(self, input_size, hidden_size, output_size):
        super(SimpleRNN, self).__init__()
        self.hidden_size = hidden_size
        self.rnn = nn.RNN(input_size, hidden_size, batch_first=True)
        self.fc = nn.Linear(hidden_size, output_size)

    def forward(self, x, h):
        out, h = self.rnn(x, h)
        out = self.fc(out)
        return out, h

    def init_hidden(self, batch_size):
        return torch.zeros(1, batch_size, self.hidden_size).to(device)
```

```
# Hyperparameters
input_size = 1
hidden_size = 32
output_size = 1
learning_rate = 0.01
num_epochs = 1000
seq_length = 100
```

```
# Create the model, loss function, and optimizer
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=learning_rate)
```

```
# Generate sine wave data
def generate_data(seq_length):
    x = np.linspace(0, 4*np.pi, seq_length + 1)
    y = np.sin(x)
    return y[:-1], y[1:]

# Prepare training data
y_train, y_target = generate_data(seq_length)
y_train = torch.tensor(y_train, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
y_target = torch.tensor(y_target, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
```

```
# Training loop
for epoch in range(num_epochs):
    h = model.init_hidden(1)
    optimizer.zero_grad()
    y_pred, h = model(y_train, h)
    loss = criterion(y_pred, y_target)
    loss.backward()
    optimizer.step()

    if (epoch+1) % 100 == 0:
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item():.4f}')
```

```
Epoch [100/1000], Loss: 0.0004
Epoch [200/1000], Loss: 0.0001
Epoch [300/1000], Loss: 0.0000
Epoch [400/1000], Loss: 0.0000
Epoch [500/1000], Loss: 0.0000
Epoch [600/1000], Loss: 0.0000
Epoch [700/1000], Loss: 0.0000
Epoch [800/1000], Loss: 0.0000
Epoch [900/1000], Loss: 0.0000
Epoch [1000/1000], Loss: 0.0000
```

```
# Plot the results
model.eval()
with torch.no_grad():
    h = model.init_hidden(1)
    predictions, h = model(y_train, h)

plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```



```
# Plot the hidden states
plt.figure(figsize=(10, 5))
plt.plot(h.cpu().numpy().squeeze())
plt.title('Hidden States')
plt.show()
```



```
# Plot the weights
plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_ih_l0.cpu().detach().numpy())
plt.title('Input-to-Hidden Weights')
plt.show()

plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_hh_l0.cpu().detach().numpy())
plt.title('Hidden-to-Hidden Weights')
plt.show()
```



```
# Save the model
torch.save(model.state_dict(), 'simple_rnn_model.pth')
print("Model saved to simple_rnn_model.pth")
```

```
Model saved to simple_rnn_model.pth
```

RNN using nn.RNN and plotting and loading

```
# Define the RNN model using RNN
class SimpleRNN(nn.Module):
    def __init__(self, input_size, hidden_size, output_size):
        super(SimpleRNN, self).__init__()
        self.hidden_size = hidden_size
        self.rnn = nn.RNN(input_size, hidden_size, batch_first=True)
        self.fc = nn.Linear(hidden_size, output_size)

    def forward(self, x, h):
        out, h = self.rnn(x, h)
        out = self.fc(out)
        return out, h

    def init_hidden(self, batch_size):
        return torch.zeros(1, batch_size, self.hidden_size).to(device)
```

```
# Hyperparameters
input_size = 1
hidden_size = 32
output_size = 1
learning_rate = 0.01
num_epochs = 1000
seq_length = 100
```

```
# Create the model, loss function, and optimizer
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=learning_rate)
```

```
# Generate sine wave data
def generate_data(seq_length):
    x = np.linspace(0, 4*np.pi, seq_length + 1)
    y = np.sin(x)
    return y[:-1], y[1:]

# Prepare training data
y_train, y_target = generate_data(seq_length)
y_train = torch.tensor(y_train, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
y_target = torch.tensor(y_target, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
```

```
# Training loop
for epoch in range(num_epochs):
    h = model.init_hidden(1)
    optimizer.zero_grad()
    y_pred, h = model(y_train, h)
    loss = criterion(y_pred, y_target)
    loss.backward()
    optimizer.step()

    if (epoch+1) % 100 == 0:
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item():.4f}')
```

```
Epoch [100/1000], Loss: 0.0004
Epoch [200/1000], Loss: 0.0001
Epoch [300/1000], Loss: 0.0000
Epoch [400/1000], Loss: 0.0000
Epoch [500/1000], Loss: 0.0000
Epoch [600/1000], Loss: 0.0000
Epoch [700/1000], Loss: 0.0000
Epoch [800/1000], Loss: 0.0000
Epoch [900/1000], Loss: 0.0000
Epoch [1000/1000], Loss: 0.0000
```

```
# Plot the results
model.eval()
with torch.no_grad():
    h = model.init_hidden(1)
    predictions, h = model(y_train, h)

plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```



```
# Plot the hidden states
plt.figure(figsize=(10, 5))
plt.plot(h.cpu().numpy().squeeze())
plt.title('Hidden States')
plt.show()
```



```
# Plot the weights
plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_ih_l0.cpu().detach().numpy())
plt.title('Input-to-Hidden Weights')
plt.show()

plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_hh_l0.cpu().detach().numpy())
plt.title('Hidden-to-Hidden Weights')
plt.show()
```



```
# Save the model
torch.save(model.state_dict(), 'simple_rnn_model.pth')
print("Model saved to simple_rnn_model.pth")
```

```
Model saved to simple_rnn_model.pth
```

```
# Load the model
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
model.load_state_dict(torch.load('simple_rnn_model.pth'))
model.eval()
print("Model loaded from simple_rnn_model.pth")
```

```
Model loaded from simple_rnn_model.pth
```

RNN using nn.RNN and plotting and loading and predicting

```
# Define the RNN model using RNN
class SimpleRNN(nn.Module):
    def __init__(self, input_size, hidden_size, output_size):
        super(SimpleRNN, self).__init__()
        self.hidden_size = hidden_size
        self.rnn = nn.RNN(input_size, hidden_size, batch_first=True)
        self.fc = nn.Linear(hidden_size, output_size)

    def forward(self, x, h):
        out, h = self.rnn(x, h)
        out = self.fc(out)
        return out, h

    def init_hidden(self, batch_size):
        return torch.zeros(1, batch_size, self.hidden_size).to(device)
```

```
# Hyperparameters
input_size = 1
hidden_size = 32
output_size = 1
learning_rate = 0.01
num_epochs = 1000
seq_length = 100
```

```
# Create the model, loss function, and optimizer
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=learning_rate)
```

```
# Generate sine wave data
def generate_data(seq_length):
    x = np.linspace(0, 4*np.pi, seq_length + 1)
    y = np.sin(x)
    return y[:-1], y[1:]

# Prepare training data
y_train, y_target = generate_data(seq_length)
y_train = torch.tensor(y_train, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
y_target = torch.tensor(y_target, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
```

```
# Training loop
for epoch in range(num_epochs):
    h = model.init_hidden(1)
    optimizer.zero_grad()
    y_pred, h = model(y_train, h)
    loss = criterion(y_pred, y_target)
    loss.backward()
    optimizer.step()

    if (epoch+1) % 100 == 0:
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item():.4f}')
```

```
Epoch [100/1000], Loss: 0.0004
Epoch [200/1000], Loss: 0.0001
Epoch [300/1000], Loss: 0.0000
Epoch [400/1000], Loss: 0.0000
Epoch [500/1000], Loss: 0.0000
Epoch [600/1000], Loss: 0.0000
Epoch [700/1000], Loss: 0.0000
Epoch [800/1000], Loss: 0.0000
Epoch [900/1000], Loss: 0.0000
Epoch [1000/1000], Loss: 0.0000
```

```
# Plot the results
model.eval()
with torch.no_grad():
    h = model.init_hidden(1)
    predictions, h = model(y_train, h)

plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```



```
# Plot the hidden states
plt.figure(figsize=(10, 5))
plt.plot(h.cpu().numpy().squeeze())
plt.title('Hidden States')
plt.show()
```



```
# Plot the weights
plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_ih_l0.cpu().detach().numpy())
plt.title('Input-to-Hidden Weights')
plt.show()

plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_hh_l0.cpu().detach().numpy())
plt.title('Hidden-to-Hidden Weights')
plt.show()
```



```
# Save the model
torch.save(model.state_dict(), 'simple_rnn_model.pth')
print("Model saved to simple_rnn_model.pth")
```

```
Model saved to simple_rnn_model.pth
```

```
# Load the model
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
model.load_state_dict(torch.load('simple_rnn_model.pth'))
model.eval()
print("Model loaded from simple_rnn_model.pth")
```

```
Model loaded from simple_rnn_model.pth
```

```
# Predict the next 100 steps
future_steps = 100
future_predictions = []
with torch.no_grad():
    h = model.init_hidden(1)
    y_pred, h = model(y_train, h)
    last_pred = y_pred[:, -1, :]
    for _ in range(future_steps):
        y_pred, h = model(last_pred, h)
        future_predictions.append(y_pred.cpu().numpy())
        last_pred = y_pred
```

```
# Plot the predictions
plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.plot(range(seq_length, seq_length + future_steps), future_predictions, label='Future Predictions')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```


RNN using nn.RNN and plotting and loading and predicting and animating

```
# Define the RNN model using RNN
class SimpleRNN(nn.Module):
    def __init__(self, input_size, hidden_size, output_size):
        super(SimpleRNN, self).__init__()
        self.hidden_size = hidden_size
        self.rnn = nn.RNN(input_size, hidden_size, batch_first=True)
        self.fc = nn.Linear(hidden_size, output_size)

    def forward(self, x, h):
        out, h = self.rnn(x, h)
        out = self.fc(out)
        return out, h

    def init_hidden(self, batch_size):
        return torch.zeros(1, batch_size, self.hidden_size).to(device)
```

```
# Hyperparameters
input_size = 1
hidden_size = 32
output_size = 1
learning_rate = 0.01
num_epochs = 1000
seq_length = 100
```

```
# Create the model, loss function, and optimizer
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=learning_rate)
```

```
# Generate sine wave data
def generate_data(seq_length):
    x = np.linspace(0, 4*np.pi, seq_length + 1)
    y = np.sin(x)
    return y[:-1], y[1:]

# Prepare training data
y_train, y_target = generate_data(seq_length)
y_train = torch.tensor(y_train, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
y_target = torch.tensor(y_target, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
```

```
# Training loop
for epoch in range(num_epochs):
    h = model.init_hidden(1)
    optimizer.zero_grad()
    y_pred, h = model(y_train, h)
    loss = criterion(y_pred, y_target)
    loss.backward()
    optimizer.step()

    if (epoch+1) % 100 == 0:
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item():.4f}')
```

```
Epoch [100/1000], Loss: 0.0004
Epoch [200/1000], Loss: 0.0001
Epoch [300/1000], Loss: 0.0000
Epoch [400/1000], Loss: 0.0000
Epoch [500/1000], Loss: 0.0000
Epoch [600/1000], Loss: 0.0000
Epoch [700/1000], Loss: 0.0000
Epoch [800/1000], Loss: 0.0000
Epoch [900/1000], Loss: 0.0000
Epoch [1000/1000], Loss: 0.0000
```

```
# Plot the results
model.eval()
with torch.no_grad():
    h = model.init_hidden(1)
    predictions, h = model(y_train, h)

plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```



```
# Plot the hidden states
plt.figure(figsize=(10, 5))
plt.plot(h.cpu().numpy().squeeze())
plt.title('Hidden States')
plt.show()
```



```
# Plot the weights
plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_ih_l0.cpu().detach().numpy())
plt.title('Input-to-Hidden Weights')
plt.show()

plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_hh_l0.cpu().detach().numpy())
plt.title('Hidden-to-Hidden Weights')
plt.show()
```



```
# Save the model
torch.save(model.state_dict(), 'simple_rnn_model.pth')
print("Model saved to simple_rnn_model.pth")
```

```
Model saved to simple_rnn_model.pth
```

```
# Load the model
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
model.load_state_dict(torch.load('simple_rnn_model.pth'))
model.eval()
print("Model loaded from simple_rnn_model.pth")
```

```
Model loaded from simple_rnn_model.pth
```

```
# Predict the next 100 steps
future_steps = 100
future_predictions = []
with torch.no_grad():
    h = model.init_hidden(1)
    y_pred, h = model(y_train, h)
    last_pred = y_pred[:, -1, :]
    for _ in range(future_steps):
        y_pred, h = model(last_pred, h)
        future_predictions.append(y_pred.cpu().numpy())
        last_pred = y_pred
```

```
# Plot the predictions
plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.plot(range(seq_length, seq_length + future_steps), future_predictions, label='Future Predictions')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```



```
# Animate the predictions
fig, ax = plt.subplots(figsize=(10, 5))
line1, = ax.plot([], [], label='True')
line2, = ax.plot([], [], label='Predicted')
line3, = ax.plot([], [], label='Future Predictions')
ax.legend()
ax.set_title('Sine Wave Prediction')

def init():
    line1.set_data([], [])
    line2.set_data([], [])
    line3.set_data([], [])
    return line1, line2, line3

def update(frame):
    line1.set_data(range(seq_length), y_target.cpu().numpy().squeeze())
    line2.set_data(range(seq_length), predictions.cpu().numpy().squeeze())
    line3.set_data(range(seq_length, seq_length + frame), future_predictions[:frame])
    return line1, line2, line3

ani = FuncAnimation(fig, update, frames=future_steps, init_func=init, blit=True)
plt.show()
```


RNN using nn.RNN and plotting and loading and predicting and animating and saving

```
# Define the RNN model using RNN
class SimpleRNN(nn.Module):
    def __init__(self, input_size, hidden_size, output_size):
        super(SimpleRNN, self).__init__()
        self.hidden_size = hidden_size
        self.rnn = nn.RNN(input_size, hidden_size, batch_first=True)
        self.fc = nn.Linear(hidden_size, output_size)

    def forward(self, x, h):
        out, h = self.rnn(x, h)
        out = self.fc(out)
        return out, h

    def init_hidden(self, batch_size):
        return torch.zeros(1, batch_size, self.hidden_size).to(device)
```

```
# Hyperparameters
input_size = 1
hidden_size = 32
output_size = 1
learning_rate = 0.01
num_epochs = 1000
seq_length = 100
```

```
# Create the model, loss function, and optimizer
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
criterion = nn.MSELoss()
optimizer = optim.Adam(model.parameters(), lr=learning_rate)
```

```
# Generate sine wave data
def generate_data(seq_length):
    x = np.linspace(0, 4*np.pi, seq_length + 1)
    y = np.sin(x)
    return y[:-1], y[1:]

# Prepare training data
y_train, y_target = generate_data(seq_length)
y_train = torch.tensor(y_train, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
y_target = torch.tensor(y_target, dtype=torch.float32).unsqueeze(0).unsqueeze(2).to(device)
```

```
# Training loop
for epoch in range(num_epochs):
    h = model.init_hidden(1)
    optimizer.zero_grad()
    y_pred, h = model(y_train, h)
    loss = criterion(y_pred, y_target)
    loss.backward()
    optimizer.step()

    if (epoch+1) % 100 == 0:
        print(f'Epoch [{epoch+1}/{num_epochs}], Loss: {loss.item():.4f}')
```

```
Epoch [100/1000], Loss: 0.0004
Epoch [200/1000], Loss: 0.0001
Epoch [300/1000], Loss: 0.0000
Epoch [400/1000], Loss: 0.0000
Epoch [500/1000], Loss: 0.0000
Epoch [600/1000], Loss: 0.0000
Epoch [700/1000], Loss: 0.0000
Epoch [800/1000], Loss: 0.0000
Epoch [900/1000], Loss: 0.0000
Epoch [1000/1000], Loss: 0.0000
```

```
# Plot the results
model.eval()
with torch.no_grad():
    h = model.init_hidden(1)
    predictions, h = model(y_train, h)

plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```



```
# Plot the hidden states
plt.figure(figsize=(10, 5))
plt.plot(h.cpu().numpy().squeeze())
plt.title('Hidden States')
plt.show()
```



```
# Plot the weights
plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_ih_l0.cpu().detach().numpy())
plt.title('Input-to-Hidden Weights')
plt.show()

plt.figure(figsize=(10, 5))
plt.plot(model.rnn.weight_hh_l0.cpu().detach().numpy())
plt.title('Hidden-to-Hidden Weights')
plt.show()
```



```
# Save the model
torch.save(model.state_dict(), 'simple_rnn_model.pth')
print("Model saved to simple_rnn_model.pth")
```

```
Model saved to simple_rnn_model.pth
```

```
# Load the model
model = SimpleRNN(input_size, hidden_size, output_size).to(device)
model.load_state_dict(torch.load('simple_rnn_model.pth'))
model.eval()
print("Model loaded from simple_rnn_model.pth")
```

```
Model loaded from simple_rnn_model.pth
```

```
# Predict the next 100 steps
future_steps = 100
future_predictions = []
with torch.no_grad():
    h = model.init_hidden(1)
    y_pred, h = model(y_train, h)
    last_pred = y_pred[:, -1, :]
    for _ in range(future_steps):
        y_pred, h = model(last_pred, h)
        future_predictions.append(y_pred.cpu().numpy())
        last_pred = y_pred
```

```
# Plot the predictions
plt.figure(figsize=(10, 5))
plt.plot(y_target.cpu().numpy().squeeze(), label='True')
plt.plot(predictions.cpu().numpy().squeeze(), label='Predicted')
plt.plot(range(seq_length, seq_length + future_steps), future_predictions, label='Future Predictions')
plt.legend()
plt.title('Sine Wave Prediction')
plt.show()
```



```
# Animate the predictions
fig, ax = plt.subplots(figsize=(10, 5))
line1, = ax.plot([], [], label='True')
line2, = ax.plot([], [], label='Predicted')
line3, = ax.plot([], [], label='Future Predictions')
ax.legend()
ax.set_title('Sine Wave Prediction')

def init():
    line1.set_data([], [])
    line2.set_data([], [])
    line3.set_data([], [])
    return line1, line2, line3

def update(frame):
    line1.set_data(range(seq_length), y_target.cpu().numpy().squeeze())
    line2.set_data(range(seq_length), predictions.cpu().numpy().squeeze())
    line3.set_data(range(seq_length, seq_length + frame), future_predictions[:frame])
    return line1, line2, line3

ani = FuncAnimation(fig, update, frames=future_steps, init_func=init, blit=True)
ani.save('sine_wave_prediction.gif', writer='pillow')
plt.show()
```


This is a big figure so we will refer to the plots, using matrix-skewed notation, as i,j = (





Smallest model with perfect reconstruction for us was hidden size 4, with hidden size 2 we got oscillation but not perfect circular in phase space meaning the amplitudes were a bit off.

Investigating possible bifurcation, from 3.4

In [38]:
```
def get_idx(row, col, ncols):
    return row * ncols + col

# Example usage:
ncols = 3
row = 2-1
col = 3-1
idx = get_idx(row, col, ncols)
print(idx)
params = hyperparam_list[idx]
print(params)

model = LatentRNN(observation_size, hidden_size)

losses250 = train(model,epochs=250,hidden_size=hidden_size,**params)

traj1 = generate_traj(model,1_3 = data.shape[0])

losses500 = train(model,epochs=500,hidden_size=hidden_size,**params)

traj2 = generate_traj(model,1_3 = data.shape[0])

losses1250 = train(model,epochs=1250,hidden_size=hidden_size,**params)

plt.plot(losses250+losses500+losses1250,label='loss curve')
plt.axvline(x=250,label='generated traj 1')
plt.axvline(x=750,label='generated traj 2')
plt.legend()
plt.grid(True)
plt.show()
```

```
5
{'learning_rate': 0.001, 'moment': 0.9, 'optimizer_function': 'SGD', 'batch_size': 5, 'batch_sequence_length': 15, 'minibatch': False}

Starting training for 250 epochs...
Optimizer: SGD, LR: 0.001, Batch size: 5, Sequence length: 15
Epoch: 0 loss 0.588704
Epoch: 10 loss 0.562075
Epoch: 20 loss 0.541678
Epoch: 30 loss 0.474538
Epoch: 40 loss 0.436134
Epoch: 50 loss 0.405241
Epoch: 60 loss 0.378851
Epoch: 70 loss 0.358918
Epoch: 80 loss 0.340719
Epoch: 90 loss 0.326134
Epoch: 100 loss 0.314138
Epoch: 110 loss 0.303727
Epoch: 120 loss 0.294881
Epoch: 130 loss 0.287181
Epoch: 140 loss 0.280962
Epoch: 150 loss 0.275141
Epoch: 160 loss 0.269209
Epoch: 170 loss 0.263698
Epoch: 180 loss 0.260170
Epoch: 190 loss 0.254861
Epoch: 200 loss 0.249772
Epoch: 210 loss 0.245670
Epoch: 220 loss 0.241821
Epoch: 230 loss 0.238023
Epoch: 240 loss 0.232166

Starting training for 500 epochs...
Optimizer: SGD, LR: 0.001, Batch size: 5, Sequence length: 15
Epoch: 0 loss 0.227987
Epoch: 10 loss 0.225347
Epoch: 20 loss 0.223999
Epoch: 30 loss 0.217007
Epoch: 40 loss 0.208946
Epoch: 50 loss 0.205166
Epoch: 60 loss 0.199424
Epoch: 70 loss 0.192258
Epoch: 80 loss 0.186681
Epoch: 90 loss 0.179464
Epoch: 100 loss 0.171693
Epoch: 110 loss 0.163718
Epoch: 120 loss 0.155583
Epoch: 130 loss 0.146322
Epoch: 140 loss 0.136408
Epoch: 150 loss 0.145990
Epoch: 160 loss 0.133694
Epoch: 170 loss 0.189257
Epoch: 180 loss 0.499616
Epoch: 190 loss 0.091504
Epoch: 200 loss 0.081213
Epoch: 210 loss 0.073334
Epoch: 220 loss 0.064858
Epoch: 230 loss 0.058961
Epoch: 240 loss 0.054973
Epoch: 250 loss 0.044493
Epoch: 260 loss 0.039088
Epoch: 270 loss 0.034335
Epoch: 280 loss 0.029977
Epoch: 290 loss 0.025753
Epoch: 300 loss 0.023082
Epoch: 310 loss 0.019941
Epoch: 320 loss 0.016694
Epoch: 330 loss 0.014822
Epoch: 340 loss 0.013235
Epoch: 350 loss 0.012009
Epoch: 360 loss 0.010931
Epoch: 370 loss 0.009704
Epoch: 380 loss 0.008558
Epoch: 390 loss 0.008009
Epoch: 400 loss 0.008131
Epoch: 410 loss 0.006282
Epoch: 420 loss 0.006978
Epoch: 430 loss 0.006774
Epoch: 440 loss 0.006929
Epoch: 450 loss 0.005551
Epoch: 460 loss 0.005551
Epoch: 470 loss 0.005559
Epoch: 480 loss 0.006951
Epoch: 490 loss 0.005441

Starting training for 1250 epochs...
Optimizer: SGD, LR: 0.001, Batch size: 5, Sequence length: 15
Epoch: 0 loss 0.004736
Epoch: 10 loss 0.005065
Epoch: 20 loss 0.004997
Epoch: 30 loss 0.004697
Epoch: 40 loss 0.005319
Epoch: 50 loss 0.007869
Epoch: 60 loss 0.006799
Epoch: 70 loss 0.007581
Epoch: 80 loss 0.004967
Epoch: 90 loss 0.004499
Epoch: 100 loss 0.004953
Epoch: 110 loss 0.005138
Epoch: 120 loss 0.005701
Epoch: 130 loss 0.005141
Epoch: 140 loss 0.005149
Epoch: 150 loss 0.005076
Epoch: 160 loss 0.004224
Epoch: 170 loss 0.004707
Epoch: 180 loss 0.004217
Epoch: 190 loss 0.004272
Epoch: 200 loss 0.004277
Epoch: 210 loss 0.005174
Epoch: 220 loss 0.004259
Epoch: 230 loss 0.004258
Epoch: 240 loss 0.004833
Epoch: 250 loss 0.003959
Epoch: 260 loss 0.004157
Epoch: 270 loss 0.004135
Epoch: 280 loss 0.004289
Epoch: 290 loss 0.004661
Epoch: 300 loss 0.004108
Epoch: 310 loss 0.006693
Epoch: 320 loss 0.004357
Epoch: 330 loss 0.004249
Epoch: 340 loss 0.004649
Epoch: 350 loss 0.004438
Epoch: 360 loss 0.004382
Epoch: 370 loss 0.004542
Epoch: 380 loss 0.003940
Epoch: 390 loss 0.005674
Epoch: 400 loss 0.005125
Epoch: 410 loss 0.004825
Epoch: 420 loss 0.004542
Epoch: 430 loss 0.004542
Epoch: 440 loss 0.005601
Epoch: 450 loss 0.004289
Epoch: 460 loss 0.004444
Epoch: 470 loss 0.004632
Epoch: 480 loss 0.004416
Epoch: 490 loss 0.003668
Epoch: 500 loss 0.004341
Epoch: 510 loss 0.004078
Epoch: 520 loss 0.004808
Epoch: 530 loss 0.004533
Epoch: 540 loss 0.005133
Epoch: 550 loss 0.004128
Epoch: 560 loss 0.004087
Epoch: 570 loss 0.003824
Epoch: 580 loss 0.005476
Epoch: 590 loss 0.004434
Epoch: 600 loss 0.003557
Epoch: 610 loss 0.004932
Epoch: 620 loss 0.005142
Epoch: 630 loss 0.004266
Epoch: 640 loss 0.004284
Epoch: 650 loss 0.004855
Epoch: 660 loss 0.003458
Epoch: 670 loss 0.004470
Epoch: 680 loss 0.004374
Epoch: 690 loss 0.003783
Epoch: 700 loss 0.003327
Epoch: 710 loss 0.003198
Epoch: 720 loss 0.004321
Epoch: 730 loss 0.004424
Epoch: 740 loss 0.003418
Epoch: 750 loss 0.003615
Epoch: 760 loss 0.004068
Epoch: 770 loss 0.005781
Epoch: 780 loss 0.004987
Epoch: 790 loss 0.003684
Epoch: 800 loss 0.004914
Epoch: 810 loss 0.003438
Epoch: 820 loss 0.004231
Epoch: 830 loss 0.003961
Epoch: 840 loss 0.003933
Epoch: 850 loss 0.003919
Epoch: 860 loss 0.003367
Epoch: 870 loss 0.003221
Epoch: 880 loss 0.004395
Epoch: 890 loss 0.003689
Epoch: 900 loss 0.003839
Epoch: 910 loss 0.004636
Epoch: 920 loss 0.003402
Epoch: 930 loss 0.003412
Epoch: 940 loss 0.003453
Epoch: 950 loss 0.003161
Epoch: 960 loss 0.003279
Epoch: 970 loss 0.003443
Epoch: 980 loss 0.003883
Epoch: 990 loss 0.003888
Epoch: 1000 loss 0.003888
Epoch: 1010 loss 0.004674
Epoch: 1020 loss 0.004243
Epoch: 1030 loss 0.005440
Epoch: 1040 loss 0.004173
Epoch: 1050 loss 0.003873
Epoch: 1060 loss 0.003860
Epoch: 1070 loss 0.003953
Epoch: 1080 loss 0.004189
Epoch: 1090 loss 0.003165
Epoch: 1100 loss 0.003116
Epoch: 1110 loss 0.003270
Epoch: 1120 loss 0.003249
Epoch: 1130 loss 0.003875
Epoch: 1140 loss 0.003835
Epoch: 1150 loss 0.003614
Epoch: 1160 loss 0.003583
Epoch: 1170 loss 0.004646
Epoch: 1180 loss 0.004157
Epoch: 1190 loss 0.003282
Epoch: 1200 loss 0.005118
Epoch: 1210 loss 0.002936
Epoch: 1220 loss 0.002799
Epoch: 1230 loss 0.003075
Epoch: 1240 loss 0.003475
```


In [39]:
```
# Plot the input data
plt.figure(figsize=(10, 4))
plt.plot(traj[:, 0],c='g',label='250 epochs', linewidth=2)
plt.plot(traj[:, 1],c='g', linewidth=2)
plt.plot(traj2[:, 0],'--',c='r',label='750 epochs', linewidth=2)
plt.plot(traj2[:, 1],'--',c='r', linewidth=2)
plt.plot(data[:, 0],c='y',label='data', linewidth=2)
plt.plot(data[:, 1],c='y', linewidth=2)
plt.xlabel('Time step')
plt.ylabel('Value')
plt.title('predictions')
plt.legend()
plt.grid(True, alpha=0.3)
plt.show()

# Plot phase space (sin vs cos)
plt.figure(figsize=(6, 6))
plt.plot(traj[:, 0], traj[:, 1], c='g', linewidth=2, alpha=0.7,label='250 epochs')
plt.plot(traj2[:, 0], traj2[:, 1], '--',c='g', linewidth=2, alpha=0.7,label='750 epochs')
plt.scatter(traj[10, 0], traj[10, 1], c='green', s=100, label='Start', zorder=5)
plt.scatter(traj[-1, 0], traj[-1, 1], c='red', s=100, label='End', zorder=5)
plt.scatter(traj2[0, 0], traj2[0, 1], c='green', s=100, label='Start', zorder=5)
plt.scatter(traj2[-1, 0], traj2[-1, 1], c='red', s=100, label='End', zorder=5)
plt.title('Phase Space Plot')
plt.legend()
plt.grid(True, alpha=0.3)
plt.axis('equal')
plt.show()
```


Before the bifurcation in the loss curve the periodic motion of the sines is not yet learned. After the sudden drop in the loss, which we suspect to be after a bifurcation, the periodic motion is learned.