

TSAI SS2025 Exercise Sheet 9 - Template Code

```
In [1]: # import os
# os.environ["OMP_NUM_THREADS"] = "4" # Limit numpy threads if needed.
import numpy as np
import matplotlib.pyplot as plt
from scipy.ndimage import gaussian_filter1d
```

1 Reservoir computing

1.1 Implement the ESN class

```
In [2]: class ESN:
def __init__(self, N, M, alpha, beta, sigma, rho):
    # observation space dimensionality
    self.N = N
    # reservoir size
    self.M = M
    self.alpha = alpha
    self.beta = beta
    self.sigma = sigma
    self.rho = rho

    # draw W_in from Gaussian distribution with mean 0 and variance sigma^2
    self.W_in = np.random.randn(self.M, self.N) * self.sigma

    # draw b from Gaussian distribution with mean 0 and variance beta^2
    self.b = np.random.randn(self.M) * self.beta

    # draw W randomly and renormalize to have spectral radius rho
    W = np.random.randn(self.M, self.M)
    self.W = W / np.max(np.abs(np.linalg.eigvals(W))) * self.rho

    # output weights (will be overwritten by training)
    self.W_out = None

def forward(self, x, r):
    """Forward pass of the ESN. Implements the state equation.

    Args:
        x (np.ndarray): Input data (1D array, N)
        r (np.ndarray): Reservoir state (1D array, M)

    Returns:
        np.ndarray: Next reservoir state (1D array, M)
    """
    # your code here
    r_t = (1 - self.alpha)*r + self.alpha*np.tanh(self.W@r + self.W_in*x + self.b)
    return r_t

def __call__(self, x, r):
    return self.forward(x, r)

def drive(self, X):
    """Drive the ESN with input X.

    Args:
        X (np.ndarray): Input data (2D array, T x N)

    Returns:
        np.ndarray: Reservoir states (2D array, T x M)
    """
    # your code here
    T = X.shape[0]
    R = np.zeros((T, self.M))
    r = np.zeros(self.M)
    for i, x in enumerate(X):
        r = self.forward(X[i], r)
        R[i] = r

    return R

def train(self, X, Y, ridge_lambda, t_trans=1000):
    """Compute the output weights using ridge regression. Store the output weights in self.W_out.

    Args:
        X (np.ndarray): Input data (2D array, T x N)
        Y (np.ndarray): Target data (2D array, T x N)
        ridge_lambda (float): Ridge regression parameter
        t_trans (int, optional): Number of transient steps to discard.

    Returns:
        float: Training error
    """
    # drive the ESN with input X
    R = self.drive(X)
    T = X.shape[0]

    # discard transient steps
    R_ = R[t_trans:, :]
    Y_ = Y[t_trans:, :]

    # compute the output weights using ridge regression -> (N x M) output weights
    I = np.eye(self.M)
    self.W_out = Y_._T @ R_ @ np.linalg.inv(R_._T@R_ + ridge_lambda*I) # your code here

    # compute the training error using fitted W_out
    L_RR = np.mean((Y_ - R_@self.W_out.T)**2) # your code here
    return L_RR

def generate(self, X, T_gen):
    """Generate data from the ESN.

    Args:
        X (np.ndarray): Input data (2D array, T x N)
        T_gen (int): Number of steps to generate

    Returns:
        np.ndarray: Generated data in the observation space (2D array, T_gen x N)
    """
    # your code here
    # Warm up reservoir
    R = self.drive(X)
    r = R[-1].copy()
    Y_gen = np.zeros((T_gen, self.N))

    # Generate
    x_prev = X[-1]
    for t in range(T_gen):
        r = self.forward(x_prev, r)
        y = self.W_out @ r

        Y_gen[t] = y
        x_prev = y

    return Y_gen
```

1.2 Train and generate data, validate the model

```
In [3]: data = np.load("lorenz_data.npy")
print(data.shape)

T_train = 10000 # use first 10000 data points for training

# split data into input (driving) and target data
X = data[:T_train, :]
Y = data[1 : T_train + 1, :]
```

```
(20000, 3)
```

```
In [4]: # hypers
N = 3
M = 500
alpha = 0.6
beta = 0.7
sigma = 0.3
rho = 0.75
ridge_lambda = 1e-2
```

```
In [10]: # initialize ESN
esn = ESN(N, M, alpha, beta, sigma, rho)

# train ESN
loss = esn.train(X, Y, ridge_lambda)
print(loss)

# generate data using trained ESN
X_drive = X[:1000, :]
X_gen = esn.generate(X_drive, data.shape[0])
```

0.0009566285821387541

```
In [15]: # plot trajectories of respective models (plot 3d, use subplots)
x, y, z = X_gen[:, 0], X_gen[:, 1], X_gen[:, 2]
x Og, y Og, z Og = data[:, 0], data[:, 1], data[:, 2]

# Plot
fig = plt.figure(figsize=(14, 6))



# Plot ground truth
ax1 = fig.add_subplot(1, 2, 2, projection='3d')
ax1.plot(x Og, y Og, z Og, lw=0.5, color='green')
ax1.set_title('Ground truth trajectory')
ax1.set_xlabel('X')
ax1.set_ylabel('Y')
ax1.set_zlabel('Z')

# Plot generated trajectory
ax2 = fig.add_subplot(1, 2, 1, projection='3d')
ax2.plot(x, y, z, lw=0.5, color='blue')
ax2.set_title('Generated trajectory')
ax2.set_xlabel('X')
ax2.set_ylabel('Y')
ax2.set_zlabel('Z')

plt.tight_layout()
plt.show()
```

Generated trajectory

Ground truth trajectory



1.3 Line search across latent dimension

```
In [21]: # your code here
def train_model(M):
    # initialize ESN
    esn = ESN(N, M, alpha, beta, sigma, rho)

    # train ESN
    loss = esn.train(X, Y, ridge_lambda)
    print(loss)

    # generate data using trained ESN
    X_drive = X[:1000, :]
    X_gen = esn.generate(X_drive, data.shape[0])

    return X_gen

Ms = [400, 300, 200, 100, 50]
X_gens = []

for M in Ms:
    results = []

    for i in range(5):
        X_gen = train_model(M)
        results.append(X_gen)

    X_gens.append(results)

0.0009614917144100951
0.00096262526761361
0.0009663776802930286
0.0009626334904695958
0.0009607267989268809
0.000962253572846531
0.0009679933275486634
0.000967856092137784
0.0009607803403302369
0.000970779109485939
0.0009795184391076866
0.0009791196389694918
0.0009886913711226
0.0009825302417529175
0.000980061491410317
0.001024426610005586
0.0010147966516502324
0.001022087744279257
0.001008361438359472
0.0010144012100529608
0.0010783417326749687
0.0010697724859357837
0.00108396075216264
0.0010929096083955388
0.001087211389599171
```

```
In [24]: # Plot
fig = plt.figure(figsize=(15, 15))
for i, (M_val, traj_group) in enumerate(zip(Ms, X_gens)):
    for j, traj in enumerate(traj_group):
        ax = fig.add_subplot(5, 5, i * 5 + j + 1, projection='3d')
        x, y, z = traj[:, 0], traj[:, 1], traj[:, 2]
        ax.plot(x, y, z, lw=0.5)
        ax.set_xticks([])
        ax.set_yticks([])
        ax.set_zticks([])
        ax.set_title(f'M={M_val}, Traj {j+1}', fontsize=8)

plt.tight_layout(rect=[0, 0, 1, 0.97])
plt.show()
```






M=400, Traj 1

M=400, Traj 2

M=400, Traj 3

M=400, Traj 4

M=400, Traj 5







M=300, Traj 1

M=300, Traj 2

M=300, Traj 3

M=300, Traj 4

M=300, Traj 5








M=200, Traj 1

M=200, Traj 2

M=200, Traj 3

M=200, Traj 4

M=200, Traj 5








M=100, Traj 1

M=100, Traj 2

M=100, Traj 3

M=100, Traj 4

M=100, Traj 5








M=50, Traj 1

M=50, Traj 2

M=50, Traj 3

M=50, Traj 4

M=50, Traj 5



For lower M values the results deteriorate significantly. Also there seems to be a higher variability in the results for different models. Whereas with M=500 all results look good, for lower Ms there are some results that look good and other that dont.

In []: