

```
In [167... import numpy as np
import matplotlib.pyplot as plt
```

Task 1.

1.1.

```
In [168... # Import data from csv
A = np.genfromtxt("data/A.csv", delimiter=",")
B = np.genfromtxt("data/B.csv", delimiter=",")
C = np.genfromtxt("data/C.csv", delimiter=",")
Gamma = np.genfromtxt("data/Gamma.csv", delimiter=",")
L0 = np.genfromtxt("data/L0.csv", delimiter=",")
mu0 = np.genfromtxt("data/mu0.csv", delimiter=",")
Sigma = np.genfromtxt("data/Sigma.csv", delimiter=",")
u = np.genfromtxt("data/u.csv", delimiter=",")
x = np.genfromtxt("data/x.csv", delimiter=",")
z = np.genfromtxt("data/z.csv", delimiter=",")
z0 = np.genfromtxt("data/z0.csv", delimiter=",")

x = x.T
```

```
In [169... def mu_t(A, B, C, x_t, u_t, K_t, mu_tm):

    pred = A @ mu_tm + C * u_t
    mu_t = pred + K_t @ (x_t - B @ pred)

    return mu_t

def V_t(B, L_tm, Gamma):

    V_t = (np.eye(L_tm.shape[0]) - K_t(B, L_tm, Gamma)) @ L_tm

    return V_t

def K_t(B, L_tm, Gamma):

    S = B @ L_tm @ B.T + Gamma

    return L_tm @ B.T @ np.linalg.inv(S)

def L_tm(A, V_tm, Sigma):

    return A @ V_tm @ A.T + Sigma
```

```
In [170... T = 100
n = A.shape[0]
m = B.shape[0]

mu = np.zeros((T+1, n))
L = np.zeros((T+1, n, n))
V = np.zeros((T+1, n, n))
K = np.zeros((T+1, n, m))

mu[0] = mu0
L[0] = L0


for t in range(1, T+1):

    # Calculate Gain and mu
    K[t] = K_t(B, L[t-1], Gamma)
    V[t] = V_t(B, L[t-1], Gamma)
    mu[t] = mu_t(A, B, C, x[t-1], u[t-1], K[t], mu[t-1])

    # Predict covariance for next step
    if t < T:
        L[t] = L_tm(A, V[t], Sigma)
```

1.2.

```
In [171... plt.scatter(mu.T[1], mu.T[0], label='Predicted latent states')
plt.scatter(z[1], z[0], label='True latent states')
plt.xlabel('Drone velocity')
plt.ylabel('Drone height')
plt.legend()
plt.show()
```



The true latent states are recovered well. It looks like the drone is flying in a circle.

1.3.

```
In [172... print(f'A: {A}')
print(f'C: {C}')
```

A: [[1. 1.]
[0. 1.]]
C: [0.2 1.]

1.4.

```
In [173... mu_smooth = np.zeros((T+1, n))
L_n = L[:-1]
mu_smooth[-1] = mu[-1]

for t in range(T-1, -1, -1):

    J_t = V[t] @ A.T @ np.linalg.inv(L_n[t])

    pred_t1 = A @ mu[t] + C * u[t]

    mu_smooth[t] = mu[t] + J_t @ (mu_smooth[t+1] - pred_t1)
```

1.5.

```
plt.scatter(mu_smooth.T[1], mu_smooth.T[0], label='Predicted latent states')
plt.scatter(z[1], z[0], label='True latent states')
plt.xlabel('Drone velocity')
plt.ylabel('Drone height')
plt.legend()
plt.show()
```

```
In [174... filter_mu = mu[1:]
filter_smoother_mu = mu_smooth[1:]

print(f'MSE filter estimates: {((filter_mu - z.T)**2).mean()}')
print(f'MSE filter-smoother estimates: {((filter_smoother_mu - z.T)**2).mean()}')
```

MSE filter estimates: 1.9944557702444998
MSE filter-smoother estimates: 1.8940941871307801

The MSE for the Kalman filter-smoother is slightly smaller than for the Kalman filter.

3.

$$\begin{pmatrix} p_{t+1} \\ v_{t+1} \end{pmatrix} = \begin{pmatrix} 1 & 1 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} p_t \\ v_t \end{pmatrix} + \begin{pmatrix} 0,2 \\ 1,0 \end{pmatrix} u_t$$

$$\Rightarrow p_{t+1} = p_t + v_t + 0,2 \cdot u_t$$

$$v_{t+1} = v_t + u_t$$

→ This means we have a constant velocity model, except for the controls.

They shift the position by 0,2 and the velocity by 1.

So

A encodes „position = position + velocity, velocity = velocity“

C encodes „velocity gets +1 and position gets +0,2 u_t “