2.1.1. List operations

01:04

Write a Python program that implements a menu-driven interface for managing a list of integers. The program should have the following menu options:

1. Add
2. Remove
3. Display
4. Quit

The program should repeatedly prompt the user to enter a choice from the menu. Depending on the choice selected, the program should perform the following actions:

- **Add**: Prompts the user to enter an integer and add it to the integer list. If the input is not a valid integer, display "Invalid input".
- **Remove:** Prompts the user to enter an integer to remove from the list. If the integer is found in the list, remove it; otherwise, display "Element not found". If the list is empty, display "List is empty".
- **Display**: Displays the current list of integers. If the list is empty, display "List is empty".
- **Quit**: Exits the program.
- The program should handle invalid menu choices by displaying "Invalid choice".Ensure that the program continues to prompt the user until they

Explorer

listOps.py

Submit

```python
# write the code..
l = []
while True:
	print("1. Add\n2. Remove\n3. Display\n4. Quit")
	n = int(input("Enter choice: "))
	if n == 1:
		a = int(input("Integer: "))
		l.append(a)
		print(f"List after adding: {l}")
	elif n==2:
		if (len(l) !=0):
			b=int(input("Integer: "))
			if b in l:
				l.remove(b)
				print(f"List after removing: {l}")
			else:
				print("Element not found")
		else:
			print("List is empty")
```

Debugger

Terminal Test cases

2.2.1. Linear search Technique

00:23

Write a program to check whether the given element is present or not in the array of elements using linear search.

Input format:

- The first line of input contains the array of integers which are separated by space
- The last line of input contains the key element to be searched

Output format:

- If the element is found, print the index. If the element found multiple times, print the starting index
- If the element is not found, print **Not found**.

Sample Test Case:

Input:

1 2 3 4 3 5 6

3

Output:

2

CTP1709... Submit

```
l=[]
l=list(map(int,input().split()))
key=int(input())
flag=0
```

Average time	Maximum time
0.023 s	0.027 s
23.00 ms	27.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 22 ms Debug

Expected output	Actual output
1 2 3 4 3 5 6	1 2 3 4 3 5 6
3	3
2	2

Test case 2 27 ms

Terminal Test cases

2.2.2. Captain of the Team 00:18

You are provided with the heights of 11 cricket players (in centimeters). Your task is to identify the tallest player, who will be selected as the captain of the team.

Input Format:
The first line of input will contain 11 integers, each representing the height of a player (in centimeters), each separated by a space.

Output Format
The output should be the height (in centimeters) of the tallest player.

Sample Test Cases +

Explorer captainof... Submit Debugger

```
l=[]
l=list(map(int,input().split()))
max=l[0]
for i in l:
```

Average time	Maximum time
0.017 s	0.022 s
17.00 ms	22.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 22 ms Debug

Expected output	Actual output
171 169 185 156 174 191 186 190 187 172 160	171 169 185 156 174 191 186 190 187 172 160
191	191

Terminal Test cases