

VCF Parameters

/

CloudStore

Deployment

Revision History

Version	Author	Date	Notes
0.1	Samuel LEPETRE	24/09/2026	New
0.2	Samuel LEPETRE	25/09/2026	Remove parameters inherit from CloudStore
0.3	Samuel LEPETRE	25/09/2026	Doc review with MDC

Table des matières

Revision History.....	2
Management Domain (ControlPlane).....	4
Hosts.....	4
Network.....	5
DNS.....	8
Authentication & OpenStack.....	9
Passwords & Secrets.....	10
Miscellaneous.....	11
Workload Domain (DataPlane).....	12
General.....	12
Network.....	13

CloudStore — VCF Parameters

Customer input form — fill in a value for every parameter marked with a “Value:” field.

Check Configuration for VCF — Required parameters

Parameters are grouped per plan. Within a plan, the parameters the customer has to fill come first; the parameters supplied by the CloudStore or inherited from the ControlPlane are not listed.

1. Management Domain (ControlPlane)

Hosts

node_uuids

JSON formatted list, provided as a string, of the baremetal node uuids of the vcf_mgmt pool. A minimum of 4 nodes is required for the management domain. Example: "91acc6a3-b8ae-4c15-918b-917b3902d1df", "1533e7bc-8122-499c-b5e7-55298b318305"

Note: This value is provided by the CloudStore from the node selection made by the user, it is not filled by hand.

→ **Provided by the CloudStore / keep default — no customer input required.**

bootstrap_node_uuids

JSON formatted list, provided as a string, of the bootstrap pool node uuids. Only the first one is used, the list must contain at least one uuid. Example: "f6df4020-3e39-4635-a82e-c52765d04504"

Note: This value is provided by the CloudStore from the node selection made by the user, it is not filled by hand.

→ **Provided by the CloudStore / keep default — no customer input required.**

Network

vcf_mgmt_network_name

VCF Network, it should be an already created neutron network with 9000 MTU

Example: vcf_network

Value: **VCF-MGT** (beeb7852-2ae5-47eb-bc87-eea508c8d49c)

vcf_mgmt_subnet_name

Management subnet name for VCF, should be an existing /22 subnet, with a DHCP server activated with an allocation pool on the /23 part of the range (eg: if the range is 10.105.60.0/22, the allocation pool should be from 10.105.62.1 to 10.105.63.250)

Example: mgmt

Value: **VCF_MGT-subnet** (172.18.2.0/22 : start=172.18.2.2, end=172.18.2.254)

vcf_mgmt_network_vlan_id

VCF Network VLAN ID, it should match the VLAN set on the vcf_mgmt_network

Example: 2040

Value: **801**

vcf_mgmt_dhcp_ip

IP of the DHCP on the VCF management subnet. This is used as a gateway during esxi install to get the ks.cfg as user-data

Example: 10.105.40.1

Value: **172.18.3.2**

customer_network_name

Customer Network name, the network on which the CloudStore is deployed, the bootstrap machine will have an IP address on it

Example: customerapi-network

Value: **CLOUDSTORE**

customer_network_dhcp_ip

IP of the DHCP on the CloudStore network. This is used as a gateway during esxi install to get the ks.cfg as user-data

Value:

external_network_id

User network id, the dedicated external network carrying the NSX north-south (Tier-0) uplinks and the customer workload traffic.

It is bound to the second port group (grp2) of each VCF host instead of a trunk, and carried by the user-vds distributed vswitch. The TOR uses a Q-in-Q tunnel, so every VLAN tagged from that dvs is encapsulated and no per-VLAN neutron network is needed.

The network must exist before the deployment.

Value: **1f380d53-4d31-43e9-8051-69081f7232ba**

vmotion_network_id

vMotion network id, a network used for vMotion connectivity inside its own vlan

Value: **ec8a53ec-726f-4dfb-b106-53495c7a0dd9**

vmotion_subnet_id

vMotion subnet id, a subnet with a /24

Value:

vmotion_subnet_range

The /24 range defined on the vMotion subnet

Example: 10.105.44.0/24

Value: **172.18.5.0/24**

vmotion_vlan_id

The VLAN that will be used to isolate the vMotion traffic, it should match the VLAN set on the vmotion_network

Example: 2044

Value: **803**

vsan_network_id

vSAN network id, a network used for vSAN connectivity inside its own vlan

Value: **1eb70c30-2096-48d6-b087-a588cf1fda47**

vsan_subnet_id

vSAN subnet id, a subnet with a /24

Value:

vsan_subnet_range

The /24 range defined on the vSAN subnet

Example: 10.105.45.0/24

Value: **172.18.6.0/24**

vsan_vlan_id

The VLAN that will be used to isolate the vSAN traffic, it should match the VLAN set on the vsan_network

Example: 2045

Value: **804**

overlay_network_id

overlay network id, a network used for overlay connectivity inside its own vlan

Value: **a0de5d63-6219-4985-9213-d90fc10dd9b3**

overlay_subnet_id

overlay subnet id, a subnet with a /24

Value:

overlay_subnet_range

The /24 range defined on the overlay subnet

Example: 10.105.46.0/24

Value: 172.18.4.0/24

overlay_vlan_id

The VLAN that will be used to isolate the overlay traffic, it should match the VLAN set on the overlay_network

Example: 2046

Value: 802

DNS

dns_zone

The CloudStore DNS Zone

Example: staging.cloudstore.ovh

Value: **cs01.mdc.ma**

dns_server

CloudStore DNS Server address reachable from the vcf mgt network.

Either it's the reachable address of the cloudstore DNS, or a nameserver with a delegation configured properly for:

- the cloudstore dns_zone
- the reverse zone corresponding to the range of the vcf management subnet

Value: **172.27.0.1 & 172.27.0.2**

bootstrap_dns_server

CloudStore DNS Server address reachable from the cloudstore network, should be the same as dns_server and bears the same constraints

Value: **172.27.0.1**

Authentication & OpenStack

image_name

ESXi Glance image name, see this page for creation instructions.

Example: esxi-9.0.1-user-data

Value: **esxi-9.0.2-user-data**

flavor_name

Flavor name, created for vcf by the commands:

```
Without secure boot: openstack flavor create vcf-flavor --ram 128 --disk 500 --  
swap 0 --vcpus 24 --private --property architecture='bare_metal' --  
property resources:CUSTOM_DISCOVERED='1' --property resources:DISK_GB='0'  
--property resources:MEMORY_MB='0' --property resources:VCPU='0' --  
property trait:CUSTOM_VCF='required'
```

Value: **vcf-flavor**

vcf_deployer_url

URL to download vcf_deployer from, this url should be reachable from the esxi bootstrap node.

Example: http://reachable.endpoint/vcf_deployer-all_in_one-9.0.1-24957456-v0.1.0.ova

Value: **http://172.27.2.1/vcf_deployer-all_in_one-9.0.1-24957456-v0.1.0.ova**

vcf_deployer_ip

IP of the vcf deployer VM, it should be an IP in the CloudStore subnet, so it's reachable from the CloudStore.

This IP should be in the CIDR of the cloudstore customer subnet, but outside of the DHCP allocation-pool.

Value: **172.27.2.1**

Passwords & Secrets

All four are generated by the plan when left empty.

vcf_master_password

VCF Master password

This password must contain only letters, numbers and at least 1 special character from the following @!#\$%?^ and no other.

Value: **MdcMa2026!**

esxi_root_password

Default esxi root password

Value: **MdcMa2026!**

appliance_password

VCF deployer vm password

Value: **MdcMa2026!**

appliance_xapikey

VCF deployer vm xapi password

Value: **MdcMa2026!**

Miscellaneous

ntp_server

NTP Server for VCF

Example: 10.3.2.11

Value: **172.28.123.123**

vcf_subdomain

Subdomain for VCF, it will be combined with the dns_zone Example: vcf

Value: **vcf**

esxi_setup_script

Script to setup the esxi.

This is required if deploying on hardware not validated by Broadcom. Example if unvalidated hardware:

```
echo '{\n  \"vsan.health.hcl.override.esxrelease\": \"ESXi 8.0\", \n  \"vsan.health.hcl.hiderealcontrollers\": true, \n  \"vsan.health.hcl.attachrealstoragepooleligible disks\": true, \n  \"vsan.health.hcl.fake.controllers\": [{\n    \"deviceName\": \"mockedNvmeCertified\", \n    \"driverName\": \"nvme_pcie\", \n    \"driverVersion\": \"1.2.4.1-vmw.702.1.0.44910359\", \n    \"deviceDisplayName\": \"Mocked Certified Nvme Device\", \n    \"vendorId\": 5197, \n    \"deviceId\": 43044, \n    \"subVendorId\": 4136, \n    \"subDeviceId\": 8481, \n    \"pciAddress\": \"99:99:99:99\", \n    \"Firmware Version\": \"2.3.0\", \n    \"Firmware Build\": \"1.0\", \n    \"productId\": \"MO001600KWJSN\", \n    \"diskCapacity\": 1600, \n    \"usedByVsan\": true, \n    \"controllerType\": \"NVMe\" \n  }]\n}'> \n/usr/lib/vmware/vsan/perfsvc/stress.json\n\n/etc/init.d/vsanmgmt restart\n\ntrue
```

Example otherwise:

true

Value:

keycloak_clusterissuer

ClusterIssuer to use for Keycloak

Example: customer-issuer

Value: **customer-issuer**

2. Workload Domain (DataPlane)

Parameters from the dataplane are mostly inherited from the controlplane.

The ones presented below are the ones that need to be explicitly filled by the customer.

General

workload_domain_num

Rank of the created workload-domain, should be between 1 and 23

Example: 1

Value: 1

node_uuids

JSON formatted list, provided as a string, of the baremetal node uuids of this workload domain. A minimum of 3 nodes is required per workload domain.

Note: This value is provided by the CloudStore from the node selection made by the user, it is not filled by hand.

→ *Provided by the CloudStore / keep default — no customer input required.*

Network

`vcf_external_network_id`

User network id for this workload domain, the dedicated external network carrying the NSX north-south (Tier-0) uplinks and the customer workload traffic.

It is bound to the second port group (grp2) of each host instead of a trunk, and carried by the WLD-cluster-vdsXX distributed vswitch through a Q-in-Q tunnel on the TOR.

The network must exist before the deployment. It can be dedicated to this workload domain or shared with other workload domains and other OpenStack projects. Its port groups are the customer's responsibility.

Value: `1f380d53-4d31-43e9-8051-69081f7232ba`

`vcf_vmotion_network_id`

vMotion network id, a network used for vMotion connectivity inside its own vlan

Value: `f30c3c07-820b-4242-b9d4-20444bf407bb`

`vcf_vmotion_subnet_id`

vMotion subnet id, a subnet with a /24

Value:

`vmotion_subnet_range`

The /24 range defined on the vMotion subnet

Example: 10.105.47.0/24

Value: `172.18.8.0/24`

`vmotion_vlan_id`

The VLAN that will be used to isolate the vMotion traffic, it should match the VLAN set on the `vmotion_network`

Example: 2047

Value: `806`

`vcf_vsan_network_id`

vSAN network id, a network used for vSAN connectivity inside its own vlan

Value: `6b6622c4-86bc-4047-9757-9a06f91caef6`

`vcf_vsan_subnet_id`

vSAN subnet id, a subnet with a /24

Value:

`vsan_subnet_range`

The /24 range defined on the vSAN subnet

Example: 10.105.48.0/24

Value: `172.18.6.0/24`

`vsan_vlan_id`

The VLAN that will be used to isolate the vSAN traffic, it should match the VLAN set on the `vsan_network`

Value: `807`

vcf_overlay_network_id

overlay network id, a network used for overlay connectivity inside its own vlan

Value: 6b6622c4-86bc-4047-9757-9a06f91caef6

vcf_overlay_subnet_id

overlay subnet id, a subnet with a /24

Value:

overlay_subnet_range

The /24 range defined on the overlay subnet

Example: 10.105.49.0/24

Value: 172.18.7.0/24

overlay_vlan_id

The VLAN that will be used to isolate the overlay traffic, it should match the VLAN set on the overlay_network Example: 2049

Value: 805