

<i>ident, x, y, y_p, y_f, -, abbrev, r</i>	subscripts: p for pointers, f for functions
<i>n, i, j</i>	index variables
<i>impl_const</i>	implementation-defined constant
<i>member</i>	C struct/union member name
	Ott-hack, ignore (annotations)
<i>nat</i>	OCaml arbitrary-width natural number
<i>mem_ptr</i>	abstract pointer value
<i>mem_val</i>	abstract memory value
	Ott-hack, ignore (locations)
<i>mem_iv_c</i>	OCaml type for memory constraints on integer values
<i>UB_name</i>	undefined behaviour
<i>string</i>	OCaml string
	Ott-hack, ignore (OCaml type variable TY)
	Ott-hack, ignore (OCaml Symbol.prefix)
<i>mem_order, _</i>	OCaml type for memory order
<i>linux_mem_order</i>	OCaml type for Linux memory order
	Ott-hack, ignore (OCaml type variable bt)

$Stypes_t, \tau$	$::=$	C type
	τ^*	pointer to type τ
tag	$::=$	OCaml type for struct/union tag
	$ident$	
$\beta, -$	$::=$	base types
	unit	unit
	bool	boolean
	integer	integer
	real	rational numbers?
	loc	location
	array β	array
	list β	list
	$\overline{\beta_i}^i$	tuple
	struct tag	struct
	set β	set
	opt (β)	option
	$\beta \rightarrow \beta'$	parameter types
	β_τ M	of a C type
$binop$	$::=$	binary operators
	+	addition
	-	subtraction
	*	multiplication
	/	division
	rem_t	modulus
	rem_f	remainder
	^	exponentiation
	=	equality, defined both for integer and C types

		!=	inequality, similiarly defined
		>	greater than, similarly defined
		<	less than, similarly defined
		>=	greater than or equal to, similarly defined
		<=	less than or equal to, similarly defined
		/\	conjuction
		\/	disjunction
<i>binop_{arith}</i>	::=		arithmetic binary operators
		+	
		-	
		*	
		/	
		rem_t	
		rem_f	
		^	
<i>binop_{rel}</i>	::=		relational binary operators
		=	
		!=	
		>	
		<	
		>=	
		<=	
<i>binop_{bool}</i>	::=		boolean binary operators
		/\	
		\/	
<i>mem_int</i>	::=		memory integer value

	1	M
	0	M
<i>object_value</i>	$::=$ <i>mem_int</i> <i>mem_ptr</i> $\text{array}(\overline{\text{loaded_value}_i}^i)$ $(\text{struct } \textit{ident})\{\overline{\text{member}_i:\tau_i = \text{mem_val}_i}^i\}$ $(\text{union } \textit{ident})\{\text{.member} = \text{mem_val}\}$	C object values (inhabitants of object types), which can be read/stored integer value pointer value C array value C struct value C union value
<i>loaded_value</i>	$::=$ <i>specified object_value</i>	potentially unspecified C object values specified loaded value
<i>value</i>	$::=$ <i>object_value</i> <i>loaded_value</i> Unit True False $\beta[\overline{\text{value}_i}^i]$ $(\overline{\text{value}_i}^i)$	Core values C object value loaded C object value unit boolean true boolean false list tuple
<i>bool_value</i>	$::=$ True False	Core booleans boolean true boolean false
<i>ctor_val</i>	$::=$ Nil β Cons Tuple	data constructors empty list list cons tuple

		Array	C array
		Specified	non-unspecified loaded value
<i>ctor_expr</i>	::=		data constructors
		Ivmax	max integer value
		Ivmin	min integer value
		Ivsizeof	sizeof value
		Ivalignof	alignof value
		IvCOMPL	bitwise complement
		IvAND	bitwise AND
		IvOR	bitwise OR
		IvXOR	bitwise XOR
		Fvfromint	cast integer to floating value
		Ivfromfloat	cast floating to integer value
<i>name</i>	::=		
		<i>ident</i>	Core identifier
		<i>impl_const</i>	implementation-defined constant
<i>pval</i>	::=		pure values
		<i>ident</i>	Core identifier
		<i>impl_const</i>	implementation-defined constant
		<i>value</i>	Core values
		$\text{constrained}(\overline{mem_iv_c_i}, \overline{pval_i}^i)$	constrained value
		$\text{error}(string, pval)$	impl-defined static error
		$\text{ctor_val}(\overline{pval_i}^i)$	data constructor application
		$(\text{struct } ident)\{\overline{member_i = pval_i}^i\}$	C struct expression
		$(\text{union } ident)\{member = pval\}$	C union expression
<i>tpval</i>	::=		top-level pure values

		<code>undef <i>UB_name</i></code>		undefined behaviour
		<code>done <i>pval</i></code>		pure done
<i>ident_opt_β</i>	::=			type annotated optional identifier
		<code>_:β</code>	binders = {}	
		<code>ident:β</code>	binders = <i>ident</i>	
<i>pattern</i>	::=			
		<code>ident_opt_β</code>	binders = binders(<i>ident_opt_β</i>)	
		<code>ctor_val($\overline{pattern_i}^i$)</code>	binders = binders($\overline{pattern_i}^i$)	
<i>z</i>	::=			OCaml arbitrary-width integer
		<code><i>i</i></code>	M	literal integer
		<code>mem_int</code>	M	
		<code>size_of(τ)</code>	M	size of a C type
		<code>offset_of_{tag}(<i>member</i>)</code>	M	offset of a struct member
		<code>ptr_size</code>	M	size of a pointer
		<code>max_int_τ</code>	M	maximum value of int of type τ
		<code>min_int_τ</code>	M	minimum value of int of type τ
\mathbb{Q} , <i>q</i> , -	::=			OCaml type for rational numbers
		$\frac{int_1}{int_2}$		
<i>lit</i>	::=			
		<code>ident</code>		
		<code>unit</code>		
		<code>bool</code>		
		<code><i>z</i></code>		
		\mathbb{Q}		

<i>ident_or_pattern</i>	$::=$ $ \text{ ident}$ $ \text{ pattern}$	$\text{binders} = \text{ident}$ $\text{binders} = \text{binders}(\text{pattern})$
<i>bool_op</i>	$::=$ $ \neg \text{ term}$ $ \text{ term}_1 = \text{term}_2$ $ \text{ term}_1 \rightarrow \text{term}_2$ $ \bigwedge (\overline{\text{term}_i}^i)$ $ \bigvee (\overline{\text{term}_i}^i)$ $ \text{ term}_1 \text{ binop}_{\text{bool}} \text{ term}_2$ $ \text{ if } \text{ term}_1 \text{ then } \text{ term}_2 \text{ else } \text{ term}_3$	 M
<i>arith_op</i>	$::=$ $ \text{ term}_1 + \text{term}_2$ $ \text{ term}_1 - \text{term}_2$ $ \text{ term}_1 \times \text{term}_2$ $ \text{ term}_1 / \text{term}_2$ $ \text{ term}_1 \text{ rem_t } \text{term}_2$ $ \text{ term}_1 \text{ rem_f } \text{term}_2$ $ \text{ term}_1 \wedge \text{ term}_2$ $ \text{ term}_1 \text{ binop}_{\text{arith}} \text{ term}_2$	 M
<i>cmp_op</i>	$::=$ $ \text{ term}_1 < \text{term}_2$ $ \text{ term}_1 \leq \text{term}_2$ $ \text{ term}_1 \text{ binop}_{\text{rel}} \text{ term}_2$	 less than less than or equal M
<i>list_op</i>	$::=$ $ \text{ nil}$	

		$term_1 :: term_2$
		$\mathbf{tl} \ term$
		$term^{(int)}$
$tuple_op$	$::=$	
		$(\overline{term_i}^i)$
		$term^{(int)}$
$pointer_op$	$::=$	
		mem_ptr
		$term_1 +_{\text{ptr}} term_2$
		$\mathbf{cast_int_to_ptr} \ term$
		$\mathbf{cast_ptr_to_int} \ term$
$array_op$	$::=$	
		$[\overline{term_i}^i]$
		$term_1[term_2]$
$param_op$	$::=$	
		$ident:\beta. \ term$
		$term(term_1, \dots, term_n)$
$struct_op$	$::=$	
		$term.member$
ct_pred	$::=$	
		$\mathbf{representable}(\tau, term)$
		$\mathbf{aligned}(\tau, term)$
		$\mathbf{alignedI}(term_1, term_2)$

$term, _$	$::=$		
		lit	
		$arith_op$	
		$bool_op$	
		cmp_op	
		$tuple_op$	
		$struct_op$	
		$pointer_op$	
		$list_op$	
		$array_op$	
		ct_pred	
		$param_op$	
		$(term)$	S parentheses
		$\sigma(term)$	M simul-sub σ in $term$
		$pval$	M
$pexpr$	$::=$		pure expressions
		$pval$	pure values
		$ctor_expr(\overline{pval}_i^i)$	data constructor application
		$array_shift(pval_1, \tau, pval_2)$	pointer array shift
		$member_shift(pval, ident, member)$	pointer struct/union member shift
		$not(pval)$	boolean not
		$pval_1 \ binop \ pval_2$	binary operations
		$memberof(ident, member, pval)$	C struct/union member access
		$name(\overline{pval}_i^i)$	pure function call
		$assert_undef(pval, UB_name)$	
		$bool_to_integer(pval)$	
		$conv_int(\tau, pval)$	
		$wrapI(\tau, pval)$	

$tpexpr$	$::=$ $ \quad tpval$ $ \quad \text{case } pval \text{ of } \overline{tpexpr_case_branch_i}^i \text{ end}$ $ \quad \text{let } ident_or_pattern = pexpr \text{ in } tpexpr$ $ \quad \text{let } ident_or_pattern:(y_1:\beta_1. term_1) = tpexpr_1 \text{ in } tpexpr_2$ $ \quad \text{if } pval \text{ then } tpexpr_1 \text{ else } tpexpr_2$ $ \quad \sigma(tpexpr)$	 $\text{bind binders}(ident_or_pattern) \text{ in } tpexpr$ $\text{bind binders}(ident_or_pattern) \text{ in } tpexpr_2$ $\text{bind } y_1 \text{ in } term_1$ M	top-level pure expressions top-level pure values pattern matching pure let pure let pure if simul-sub σ in $tpexpr$
$tpexpr_case_branch$	$::=$ $ \quad pattern \Rightarrow tpexpr$	$\text{bind binders}(pattern) \text{ in } tpexpr$	pure top-level case expression top-level case expression br
m_kill_kind	$::=$ $ \quad \text{dynamic}$ $ \quad \text{static } \tau$		
$bool, _$	$::=$ $ \quad \text{true}$ $ \quad \text{false}$		OCaml booleans
$int, _$	$::=$ $ \quad i$		OCaml fixed-width integer literal integer
res_term	$::=$ $ \quad \text{emp}$ $ \quad points_to$ $ \quad ident$ $ \quad \langle res_term_1, res_term_2 \rangle$ $ \quad \text{pack}(pval, res_term)$ $ \quad \sigma(res_term)$	 M	resource terms empty heap single-cell heap variable seperating-conjunction pair packing for existentials substitution for resource te

<i>mem_action</i>	$::=$ <ul style="list-style-type: none"> <code>create</code> (<i>pval</i>, τ) <code>create_readonly</code> (<i>pval</i>₁, τ, <i>pval</i>₂) <code>alloc</code> (<i>pval</i>₁, <i>pval</i>₂) <code>kill</code> (<i>m_kill_kind</i>, <i>pval</i>, <i>pt</i>) <code>store</code> (<i>bool</i>, τ, <i>pval</i>₁, <i>pval</i>₂, <i>mem_order</i>, <i>pt</i>) <code>load</code> (τ, <i>pval</i>, <i>mem_order</i>, <i>pt</i>) <code>rmw</code> (τ, <i>pval</i>₁, <i>pval</i>₂, <i>pval</i>₃, <i>mem_order</i>₁, <i>mem_order</i>₂) <code>fence</code> (<i>mem_order</i>) <code>cmp_exch_strong</code> (τ, <i>pval</i>₁, <i>pval</i>₂, <i>pval</i>₃, <i>mem_order</i>₁, <i>mem_order</i>₂) <code>cmp_exch_weak</code> (τ, <i>pval</i>₁, <i>pval</i>₂, <i>pval</i>₃, <i>mem_order</i>₁, <i>mem_order</i>₂) <code>linux_fence</code> (<i>linux_mem_order</i>) <code>linux_load</code> (τ, <i>pval</i>, <i>linux_mem_order</i>) <code>linux_store</code> (τ, <i>pval</i>₁, <i>pval</i>₂, <i>linux_mem_order</i>) <code>linux_rmw</code> (τ, <i>pval</i>₁, <i>pval</i>₂, <i>linux_mem_order</i>) 	<p>memory actions</p> <p>true means store is locking</p>
<i>polarity</i>	$::=$ <ul style="list-style-type: none"> <code>neg</code> 	<p>polarities for memory actions</p> <p>(pos) sequenced by <code>let weak</code> and <code>let strong</code></p> <p>only sequenced by <code>let strong</code></p>
<i>pol_mem_action</i>	$::=$ <ul style="list-style-type: none"> <i>polarity mem_action</i> 	<p>memory actions with polarity</p>
<i>mem_op</i>	$::=$ <ul style="list-style-type: none"> <i>pval</i>₁ <i>binop_{rel}</i> <i>pval</i>₂ <i>pval</i>₁ $-_{\tau}$ <i>pval</i>₂ <code>intFromPtr</code> (τ_1, τ_2, <i>pval</i>) <code>ptrFromInt</code> (τ_1, τ_2, <i>pval</i>) <code>ptrValidForDeref</code> (τ, <i>pval</i>, <i>pt</i>) <code>ptrWellAligned</code> (τ, <i>pval</i>) 	<p>operations involving the memory state</p> <p>pointer relational binary operations</p> <p>pointer subtraction</p> <p>cast of pointer value to integer value</p> <p>cast of integer value to pointer value</p> <p>dereferencing validity predicate</p>

		<code>ptrArrayShift</code> ($pval_1, \tau, pval_2$)		
		<code>memcpy</code> ($pval_1, pval_2, pval_3$)		
		<code>memcmp</code> ($pval_1, pval_2, pval_3$)		
		<code>realloc</code> ($pval_1, pval_2, pval_3$)		
		<code>va_start</code> ($pval_1, pval_2$)		
		<code>va_copy</code> ($pval$)		
		<code>va_arg</code> ($pval, \tau$)		
		<code>va_end</code> ($pval$)		
$spine_elem$	$::=$			spine element
		$pval$		pure or logical value
		res_term		resource value
		$\sigma(spine_elem)$	M	substitution for spine elements / return values
$spine$	$::=$			spine
		$\overline{spine_elem_i}^i$		
$tval$	$::=$			(effectful) top-level values
		<code>done</code> $spine$		end of top-level expression
		<code>undef</code> UB_name		undefined behaviour
$res_pattern$	$::=$			resource terms
		<code>emp</code>	binders = {}	empty heap
		pt	binders = {}	single-cell heap
		$ident$	binders = $ident$	variable
		$\langle res_pattern_1, res_pattern_2 \rangle$	binders = $binders(res_pattern_1) \cup binders(res_pattern_2)$	seperating-conjunction pair
		<code>pack</code> ($ident, res_pattern$)	binders = $ident \cup binders(res_pattern)$	packing for existentials
$ret_pattern$	$::=$			return pattern
		<code>comp</code> $ident_or_pattern$	binders = $binders(ident_or_pattern)$	computational variable

		$\text{log } ident$	$\text{binders} = ident$	logical variable
		$\text{res } res_pattern$	$\text{binders} = \text{binders}(res_pattern)$	resource variable
$init,$	$::=$			initialisation status
		\checkmark		initialised
		\times		uninitialised
$points_to, pt$	$::=$			points-to separation logic predicate
		$term_1 \xrightarrow{init}_{\tau} term_2$		
res	$::=$			resources
		emp		empty heap
		$points_to$		points-top heap pred.
		$res_1 * res_2$		seperating conjunction
		$\exists ident:\beta. res$		existential
		$term \wedge res$		logical conjunction
		$\sigma(res)$	M	simul-sub σ in res
$ret, -$	$::=$			return types
		$\Sigma ident:\beta. ret$		return a computational value
		$\exists ident:\beta. ret$		return a logical value
		$res \otimes ret$		return a resource value
		$term \wedge ret$		return a predicate (post-condition)
		I		end return list
		$\sigma(ret)$	M	simul-sub σ in ret
seq_expr	$::=$			sequential (effectful) expressions
		$\text{ccall } (\tau, ident, spine)$		C function call
		$\text{pcall } (name, spine)$		procedure call

seq_texpr	$::=$ $ \quad tval$ $ \quad \mathbf{run} \, ident \, \overline{pval}_i^i$ $ \quad \mathbf{let} \, ident_or_pattern = pexpr \, \mathbf{in} \, texpr$ $ \quad \mathbf{let} \, ident_or_pattern:(y_1:\beta_1. term_1) = tpexpr \, \mathbf{in} \, texpr$ $ \quad \mathbf{let} \, \overline{ret_pattern}_i^i = seq_expr \, \mathbf{in} \, texpr$ $ \quad \mathbf{let} \, \overline{ret_pattern}_i^i:ret = texpr_1 \, \mathbf{in} \, texpr_2$ $ \quad \mathbf{case} \, pval \, \mathbf{of} \, \, texpr_case_branch_i^i \, \mathbf{end}$ $ \quad \mathbf{if} \, pval \, \mathbf{then} \, texpr_1 \, \mathbf{else} \, texpr_2$ $ \quad \mathbf{bound} \, [int](is_texpr)$	 $\mathbf{bind} \, binders(ident_or_pattern) \, \mathbf{in} \, texpr$ $\mathbf{bind} \, binders(ident_or_pattern) \, \mathbf{in} \, texpr$ $\mathbf{bind} \, y_1 \, \mathbf{in} \, term_1$ $\mathbf{bind} \, binders(\overline{ret_pattern}_i^i) \, \mathbf{in} \, texpr$ $\mathbf{bind} \, binders(\overline{ret_pattern}_i^i) \, \mathbf{in} \, texpr_2$	sequential top-level (effectful) expressions (effectful) top-level values run from label pure let pure let bind return patterns annotated bind return patterns pattern matching conditional limit scope of indet seq behaviour
$texpr_case_branch$	$::=$ $ \quad pattern \Rightarrow texpr$	$\mathbf{bind} \, binders(pattern) \, \mathbf{in} \, texpr$	top-level case expression branch top-level case expression branch
is_expr	$::=$ $ \quad tval$ $ \quad \mathbf{memop} \, (mem_op)$ $ \quad pol_mem_action$		indet seq (effectful) expressions (effectful) top-level values pointer op involving memory memory action
is_texpr	$::=$ $ \quad \mathbf{let} \, \mathbf{weak} \, \overline{ret_pattern}_i^i = is_expr \, \mathbf{in} \, texpr$ $ \quad \mathbf{let} \, \mathbf{strong} \, \overline{ret_pattern}_i^i = is_expr \, \mathbf{in} \, texpr$	$\mathbf{bind} \, binders(\overline{ret_pattern}_i^i) \, \mathbf{in} \, texpr$ $\mathbf{bind} \, binders(\overline{ret_pattern}_i^i) \, \mathbf{in} \, texpr$	indet seq top-level (effectful) expressions weak sequencing strong sequencing
$texpr$	$::=$ $ \quad seq_texpr$ $ \quad is_texpr$ $ \quad \sigma(texpr)$	 M	top-level (effectful) expressions sequential (effectful) expressions indet seq (effectful) expressions simul-sub σ in $texpr$
arg	$::=$		argument/function types

	$\Pi ident:\beta. arg$ $\forall ident:\beta. arg$ $res \multimap arg$ $term \supset arg$ ret $\sigma(arg)$	M	simul-sub σ in arg
$pure_arg$	$::=$ $\Pi ident:\beta. pure_arg$ $term \supset pure_arg$ $pure_ret$		pure argument/function types
$pure_ret$	$::=$ $\Sigma ident:\beta. pure_ret$ $term \wedge pure_ret$ \mathbf{I}		pure return types
\mathcal{C}	$::=$ \cdot $\mathcal{C}, ident:\beta$ $\overline{\mathcal{C}}_i^i$		computational var env
\mathcal{L}	$::=$ \cdot $\overline{\mathcal{L}}_i^i$ $\mathcal{L}, ident:\beta$		logical var env
Φ	$::=$ \cdot $\Phi, term$		constraints env

		$\overline{\Phi}_i^i$	
\mathcal{R}	::=		resources env
		.	
		\mathcal{R}, res	
		$\mathcal{R}, ident:res$	
		$\overline{\mathcal{R}}_i^i$	
σ, ψ	::=		substitutions
		.	
		$spine_elem/ident, \sigma$	
		$term/ident, \sigma$	
		$\overline{\sigma}_i^i$	
		$\sigma(\psi)$	M apply σ to all elements in ψ
$typing$::=		
		smt $(\Phi \Rightarrow term)$	
		$ident:\beta \in \mathcal{C}$	
		$ident:\beta \in \mathcal{L}$	
		struct $tag \ \& \ \overline{member_i:\tau_i}^i \in \mathbf{Globals}$	
		$\overline{\mathcal{C}_i; \mathcal{L}_i; \Phi_i \vdash mem_val_i \Rightarrow mem \beta_i}^i$	dependent on memory object model
$opsem$::=		
		$\forall i < j. \mathbf{not} (pattern_i = pval \rightsquigarrow \sigma_i)$	
		fresh (mem_ptr)	
		$term$	
		$pval:\beta$	
$formula$::=		
		$judgement$	

	$ \begin{array}{ l} typing \\ opsem \\ term \equiv term' \\ name: pure_arg \equiv \overline{x_i}^i \mapsto tpepr \in \mathbf{Globals} \\ name: arg \equiv \overline{x_i}^i \mapsto texpr \in \mathbf{Globals} \end{array} $	
$heap, h$	$ \begin{array}{ l} ::= \\ \cdot \\ h + \{points_to\} \end{array} $	heaps
$object_value_jtype$	$ \begin{array}{ l} ::= \\ \mathcal{C}; \mathcal{L}; \Phi \vdash object_value \Rightarrow \mathbf{obj} \beta \end{array} $	
$pval_jtype$	$ \begin{array}{ l} ::= \\ \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta \end{array} $	
res_jtype	$ \begin{array}{ l} ::= \\ \Phi \vdash res \equiv res' \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash res_term \Leftarrow res \end{array} $	
$spine_jtype$	$ \begin{array}{ l} ::= \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret \end{array} $	
$pexpr_jtype$	$ \begin{array}{ l} ::= \\ \mathcal{C}; \mathcal{L}; \Phi \vdash pexpr \Rightarrow ident: \beta. term \end{array} $	
$comp_pattern_jtype$	$ \begin{array}{ l} ::= \\ pattern: \beta \rightsquigarrow \mathcal{C} \mathbf{with} term \\ ident_or_pattern: \beta \rightsquigarrow \mathcal{C} \mathbf{with} term \end{array} $	

$res_pattern_jtype$	$::=$	$ \quad res_pattern:res \rightsquigarrow \mathcal{L}; \Phi; \mathcal{R}$
$ret_pattern_jtype$	$::=$	$ \quad \overline{ret_pattern_i}^i : ret \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}$
$tpval_jtype$	$::=$	$ \quad \mathcal{C}; \mathcal{L}; \Phi \vdash tpval \Leftarrow ident:\beta. term$
$tpexpr_jtype$	$::=$	$ \quad \mathcal{C}; \mathcal{L}; \Phi \vdash tpexpr \Leftarrow ident:\beta. term$
$action_jtype$	$::=$	$ \quad \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash mem_action \Rightarrow ret$
$memop_jtype$	$::=$	$ \quad \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash mem_op \Rightarrow ret$
$tval_jtype$	$::=$	$ \quad \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash tval \Leftarrow ret$
seq_expr_jtype	$::=$	$ \quad \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash seq_expr \Rightarrow ret$
is_expr_jtype	$::=$	$ \quad \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash is_expr \Rightarrow ret$
$texpr_jtype$	$::=$	$ \quad \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash seq_texpr \Leftarrow ret$ $ \quad \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash is_texpr \Leftarrow ret$

		$\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \text{texpr} \Leftarrow \text{ret}$
subs_jtype	$::=$	<ul style="list-style-type: none"> $\text{pattern} = \text{pval} \rightsquigarrow \sigma$ $\text{ident_or_pattern} = \text{pval} \rightsquigarrow \sigma$ $\text{res_pattern} = \text{res_term} \rightsquigarrow \sigma$ $\frac{\text{ret_pattern}_i = \text{spine_elem}_i}{\overline{x_i = \text{spine_elem}_i}^i} \rightsquigarrow \sigma$ $\overline{x_i = \text{spine_elem}_i}^i :: \text{arg} \gg \sigma; \text{ret}$
pure_opsem_jtype	$::=$	<ul style="list-style-type: none"> $\langle \text{pexpr} \rangle \longrightarrow \langle \text{pexpr}' \rangle$ $\langle \text{pexpr} \rangle \longrightarrow \langle \text{texpr}:(y:\beta. \text{term}) \rangle$ $\langle \text{texpr} \rangle \longrightarrow \langle \text{texpr}' \rangle$
opsem_jtype	$::=$	<ul style="list-style-type: none"> $\langle h; \text{seq_expr} \rangle \longrightarrow \langle h'; \text{texpr}:\text{ret} \rangle$ $\langle h; \text{seq_texpr} \rangle \longrightarrow \langle h'; \text{texpr} \rangle$ $\langle h; \text{mem_op} \rangle \longrightarrow \langle h'; \text{tval} \rangle$ $\langle h; \text{mem_action} \rangle \longrightarrow \langle h'; \text{tval} \rangle$ $\langle h; \text{is_expr} \rangle \longrightarrow \langle h'; \text{is_expr}' \rangle$ $\langle h; \text{is_texpr} \rangle \longrightarrow \langle h'; \text{texpr} \rangle$ $\langle h; \text{texpr} \rangle \longrightarrow \langle h'; \text{texpr}' \rangle$
lemma_jtype	$::=$	<ul style="list-style-type: none"> $\overline{x_i}^i :: \text{arg} \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \mid \text{ret}$ $\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'$ $\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (\sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}')$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{object_value} \Rightarrow \text{obj } \beta}$$

$$\frac{}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{mem_int} \Rightarrow \text{obj integer}} \quad \text{Ty_Pval_Obj_Int}$$

$$\frac{}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{mem_ptr} \Rightarrow \text{obj loc}} \quad \text{TY_PVAL_OBJ_PTR}$$

$$\frac{\overline{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{loaded_value}_i \Rightarrow \beta^i}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{array}(\text{loaded_value}_i^i) \Rightarrow \text{obj array } \beta} \quad \text{TY_PVAL_OBJ_ARR}$$

$$\frac{\frac{\text{struct tag} \ \& \ \overline{\text{member}_i: \tau_i^i} \in \text{Globals}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{mem_val}_i \Rightarrow \text{mem } \beta_{\tau_i}^i}}{\mathcal{C}; \mathcal{L}; \Phi \vdash (\text{struct tag})\{. \text{member}_i: \tau_i = \text{mem_val}_i^i\} \Rightarrow \text{obj struct tag}} \quad \text{TY_PVAL_OBJ_STRUCT}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{pval} \Rightarrow \beta}$$

$$\frac{x: \beta \in \mathcal{C}}{\mathcal{C}; \mathcal{L}; \Phi \vdash x \Rightarrow \beta} \quad \text{TY_PVAL_VAR_COMP}$$

$$\frac{x: \beta \in \mathcal{L}}{\mathcal{C}; \mathcal{L}; \Phi \vdash x \Rightarrow \beta} \quad \text{TY_PVAL_VAR_LOG}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{object_value} \Rightarrow \text{obj } \beta}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{object_value} \Rightarrow \beta} \quad \text{TY_PVAL_OBJ}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{object_value} \Rightarrow \text{obj } \beta}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{specified object_value} \Rightarrow \beta} \quad \text{TY_PVAL_LOADED}$$

$$\frac{}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{Unit} \Rightarrow \text{unit}} \quad \text{TY_PVAL_UNIT}$$

$$\frac{}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{True} \Rightarrow \text{bool}} \quad \text{TY_PVAL_TRUE}$$

$$\frac{}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{False} \Rightarrow \text{bool}} \quad \text{TY_PVAL_FALSE}$$

$$\frac{\overline{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{value}_i \Rightarrow \beta^i}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \beta[\overline{\text{value}_i^i}] \Rightarrow \text{list } \beta} \quad \text{TY_PVAL_LIST}$$

$$\frac{\overline{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{value}_i \Rightarrow \beta_i^i}}{\mathcal{C}; \mathcal{L}; \Phi \vdash (\overline{\text{value}_i^i}) \Rightarrow \beta_i^i} \quad \text{TY_PVAL_TUPLE}$$

$$\frac{\text{smt}(\Phi \Rightarrow \text{false})}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{error}(\text{string}, \text{pval}) \Rightarrow \beta} \quad \text{TY_PVAL_ERROR}$$

$$\frac{}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{Nil } \beta() \Rightarrow \text{list } \beta} \quad \text{TY_PVAL_CTOR_NIL}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi \vdash \text{pval}_1 \Rightarrow \beta \\ \mathcal{C}; \mathcal{L}; \Phi \vdash \text{pval}_2 \Rightarrow \text{list } \beta \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{Cons}(\text{pval}_1, \text{pval}_2) \Rightarrow \text{list } \beta} \quad \text{TY_PVAL_CTOR_CONS}$$

$$\frac{\overline{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{pval}_i \Rightarrow \beta_i^i}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{Tuple}(\overline{\text{pval}_i^i}) \Rightarrow \beta_i^i} \quad \text{TY_PVAL_CTOR_TUPLE}$$

$$\frac{\overline{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{pval}_i \Rightarrow \beta^i}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{Array}(\overline{\text{pval}_i^i}) \Rightarrow \text{array } \beta} \quad \text{TY_PVAL_CTOR_ARRAY}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{pval} \Rightarrow \beta}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{Specified}(\text{pval}) \Rightarrow \beta} \quad \text{TY_PVAL_CTOR_SPECIFIED}$$

$$\frac{\frac{\text{struct tag} \ \& \ \overline{\text{member}_i:\tau_i}^i \in \text{Globals}}{\mathcal{C};\mathcal{L};\Phi \vdash \text{pval}_i \Rightarrow \beta_{\tau_i}^i}}{\mathcal{C};\mathcal{L};\Phi \vdash (\text{struct tag})\{.\text{member}_i = \text{pval}_i\} \Rightarrow \text{struct tag}} \quad \text{TY_PVAL_STRUCT}$$

$$\boxed{\Phi \vdash \text{res} \equiv \text{res}'}$$

$$\frac{}{\Phi \vdash \text{emp} \equiv \text{emp}} \quad \text{TY_RES_EQ_EMP}$$

$$\frac{\text{smt}(\Phi \Rightarrow (\text{term}_1 = \text{term}'_1) \wedge (\text{term}_2 = \text{term}'_2))}{\Phi \vdash \text{term}_1 \xrightarrow{\text{init}}_{\tau} \text{term}_2 \equiv \text{term}'_1 \xrightarrow{\text{init}}_{\tau} \text{term}'_2} \quad \text{TY_RES_EQ_POINTSTO}$$

$$\frac{\begin{array}{c} \Phi \vdash \text{res}_1 \equiv \text{res}'_1 \\ \Phi \vdash \text{res}_2 \equiv \text{res}'_2 \end{array}}{\Phi \vdash \text{res}_1 * \text{res}_2 \equiv \text{res}'_1 * \text{res}'_2} \quad \text{TY_RES_EQ_SEP_CONJ}$$

$$\frac{\Phi \vdash \text{res} \equiv \text{res}'}{\Phi \vdash \exists \text{ident}:\beta. \text{res} \equiv \exists \text{ident}:\beta. \text{res}'} \quad \text{TY_RES_EQ_EXISTS}$$

$$\frac{\begin{array}{c} \text{smt}(\Phi \Rightarrow (\text{term} \rightarrow \text{term}') \wedge (\text{term}' \rightarrow \text{term})) \\ \Phi \vdash \text{res} \equiv \text{res}' \end{array}}{\Phi \vdash \text{term} \wedge \text{res} \equiv \text{term}' \wedge \text{res}'} \quad \text{TY_RES_EQ_TERM}$$

$$\boxed{\mathcal{C};\mathcal{L};\Phi;\mathcal{R} \vdash \text{res_term} \Leftarrow \text{res}}$$

$$\frac{}{\mathcal{C};\mathcal{L};\Phi;\cdot \vdash \text{emp} \Leftarrow \text{emp}} \quad \text{TY_RES_EMP}$$

$$\frac{\begin{array}{c} \Phi \vdash points_to \equiv points_to' \\ \Phi \vdash points_to' \equiv points_to'' \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \cdot, points_to \vdash points_to' \Leftarrow points_to''} \text{TY_RES_POINTSTO}$$

$$\frac{\Phi \vdash res \equiv res'}{\mathcal{C}; \mathcal{L}; \Phi; \cdot, r:res \vdash r \Leftarrow res'} \text{TY_RES_VAR}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_1 \vdash res_term_1 \Leftarrow res_1 \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_2 \vdash res_term_2 \Leftarrow res_2 \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_1, \mathcal{R}_2 \vdash \langle res_term_1, res_term_2 \rangle \Leftarrow res_1 * res_2} \text{TY_RES_SEPCONJ}$$

$$\frac{\begin{array}{c} \text{smt}(\Phi \Rightarrow term) \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash res_term \Leftarrow res \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash res_term \Leftarrow term \wedge res} \text{TY_RES_CONJ}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash res_term \Leftarrow pval/y, \cdot(res) \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \text{pack}(pval, res_term) \Leftarrow \exists y:\beta. res} \text{TY_RES_PACK}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret}$$

$$\frac{}{\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash ::ret \gg \cdot; ret} \text{TY_SPINE_EMPTY}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash x = pval, \overline{x_i = spine_elem_i}^i :: \Pi x:\beta. arg \gg pval/x, \sigma; ret} \text{TY_SPINE_COMP}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash x = pval, \overline{x_i = spine_elem_i}^i :: \forall x:\beta. arg \gg pval/x, \sigma; ret} \text{TY_SPINE_LOG}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_1 \vdash res_term \Leftarrow res \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_2 \vdash \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_1, \mathcal{R}_2 \vdash x = res_term, \overline{x_i = spine_elem_i}^i :: res \multimap arg \gg res_term/x, \sigma; ret} \text{TY_SPINE_RES}$$

$$\frac{\begin{array}{c} \text{smt}(\Phi \Rightarrow term) \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \overline{x_i = spine_elem_i}^i :: term \supset arg \gg \sigma; ret} \text{TY_SPINE_PHI}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi \vdash pexpr \Rightarrow ident:\beta. term}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta}{\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow y:\beta. y = pval} \text{TY_PE_VAL}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \Rightarrow \text{loc} \\ \mathcal{C}; \mathcal{L}; \Phi \vdash pval_2 \Rightarrow \text{integer} \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{array_shift}(pval_1, \tau, pval_2) \Rightarrow y:\text{loc}. y = pval_1 +_{\text{ptr}} (pval_2 \times \text{size_of}(\tau))} \text{TY_PE_ARRAY_SHIFT}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \text{loc} \\ \text{struct } tag \ \& \ \overline{member_i:\tau_i}^i \in \text{Globals} \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{member_shift}(pval, tag, member_j) \Rightarrow y:\text{loc}. y = pval +_{\text{ptr}} \text{offset_of}_{tag}(member_j)} \text{TY_PE_MEMBER_SHIFT}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \text{bool}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{not}(pval) \Rightarrow y:\text{bool}. y = \neg pval} \text{TY_PE_NOT}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \Rightarrow \text{integer} \\ \mathcal{C}; \mathcal{L}; \Phi \vdash pval_2 \Rightarrow \text{integer} \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \text{ binop}_{arith} pval_2 \Rightarrow y:\text{integer}. y = (pval_1 \text{ binop}_{arith} pval_2)} \quad \text{TY_PE_ARITH_BINOP}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \Rightarrow \text{integer} \\ \mathcal{C}; \mathcal{L}; \Phi \vdash pval_2 \Rightarrow \text{integer} \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \text{ binop}_{rel} pval_2 \Rightarrow y:\text{bool}. y = (pval_1 \text{ binop}_{rel} pval_2)} \quad \text{TY_PE_REL_BINOP}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \Rightarrow \text{bool} \\ \mathcal{C}; \mathcal{L}; \Phi \vdash pval_2 \Rightarrow \text{bool} \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \text{ binop}_{bool} pval_2 \Rightarrow y:\text{bool}. y = (pval_1 \text{ binop}_{bool} pval_2)} \quad \text{TY_PE_BOOL_BINOP}$$

$$\frac{\begin{array}{c} \text{name:pure_arg} \equiv \overline{x_i}^i \mapsto tpe\text{expr} \in \text{Globals} \\ \mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \overline{x_i}^i = \overline{pval_i}^i :: \text{pure_arg} \gg \sigma; \Sigma y:\beta. \text{term} \wedge \mathbf{I} \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{name}(\overline{pval_i}^i) \Rightarrow y:\beta. \sigma(\text{term})} \quad \text{TY_PE_CALL}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \text{bool} \\ \text{smt}(\Phi \Rightarrow pval) \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{assert_undef}(pval, \text{UB_name}) \Rightarrow y:\text{unit}. y = \text{unit}} \quad \text{TY_PE_ASSERT_UNDEF}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \text{bool}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{bool_to_integer}(pval) \Rightarrow y:\text{integer}. y = \text{if } pval \text{ then } 1 \text{ else } 0} \quad \text{TY_PE_BOOL_TO_INTEGER}$$

$$\frac{\begin{array}{c} \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \text{integer} \\ \text{abbrev}_1 \equiv \max_int_\tau - \min_int_\tau + 1 \\ \text{abbrev}_2 \equiv pval \text{ rem } f \text{ abbrev}_1 \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \text{wrapI}(\tau, pval) \Rightarrow y:\beta. y = \text{if } \text{abbrev}_2 \leq \max_int_\tau \text{ then } \text{abbrev}_2 \text{ else } \text{abbrev}_2 - \text{abbrev}_1} \quad \text{TY_PE_WRAP I}$$

$\boxed{\text{pattern}:\beta \rightsquigarrow \mathcal{C} \text{ with } \text{term}}$

$$\frac{}{_:\beta:\beta \rightsquigarrow \cdot \mathbf{with} _} \quad \text{TY_PAT_COMP_NO_SYM_ANNOT}$$

$$\frac{}{x:\beta:\beta \rightsquigarrow \cdot, x:\beta \mathbf{with} x} \quad \text{TY_PAT_COMP_SYM_ANNOT}$$

$$\frac{}{\mathbf{Nil} \beta():\mathbf{list} \beta \rightsquigarrow \cdot \mathbf{with nil}} \quad \text{TY_PAT_COMP_NIL}$$

$$\frac{\begin{array}{l} pattern_1:\beta \rightsquigarrow \mathcal{C}_1 \mathbf{with} term_1 \\ pattern_2:\mathbf{list} \beta \rightsquigarrow \mathcal{C}_2 \mathbf{with} term_2 \end{array}}{\mathbf{Cons}(pattern_1, pattern_2):\mathbf{list} \beta \rightsquigarrow \mathcal{C}_1, \mathcal{C}_2 \mathbf{with} term_1 :: term_2} \quad \text{TY_PAT_COMP_CONS}$$

$$\frac{\frac{}{pattern_i:\beta_i \rightsquigarrow \mathcal{C}_i \mathbf{with} term_i^i}}{\mathbf{Tuple}(\overline{pattern_i^i}):\overline{\beta_i^i} \rightsquigarrow \overline{\mathcal{C}_i^i} \mathbf{with} (\overline{term_i^i})} \quad \text{TY_PAT_COMP_TUPLE}$$

$$\frac{\frac{}{pattern_i:\beta \rightsquigarrow \mathcal{C}_i \mathbf{with} term_i^i}}{\mathbf{Array}(\overline{pattern_i^i}):\mathbf{array} \beta \rightsquigarrow \overline{\mathcal{C}_i^i} \mathbf{with} [\overline{term_i^i}]} \quad \text{TY_PAT_COMP_ARRAY}$$

$$\frac{pattern:\beta \rightsquigarrow \mathcal{C} \mathbf{with} term}{\mathbf{Specified}(pattern):\beta \rightsquigarrow \mathcal{C} \mathbf{with} term} \quad \text{TY_PAT_COMP_SPECIFIED}$$

$$\boxed{ident_or_pattern:\beta \rightsquigarrow \mathcal{C} \mathbf{with} term}$$

$$\frac{}{x:\beta \rightsquigarrow \cdot, x:\beta \mathbf{with} x} \quad \text{TY_PAT_SYM_OR_PATTERN_SYM}$$

$$\frac{pattern:\beta \rightsquigarrow \mathcal{C} \mathbf{with} term}{pattern:\beta \rightsquigarrow \mathcal{C} \mathbf{with} term} \quad \text{TY_PAT_SYM_OR_PATTERN_PATTERN}$$

$$\boxed{res_pattern:res \rightsquigarrow \mathcal{L}; \Phi; \mathcal{R}}$$

$$\frac{}{emp:emp \rightsquigarrow \cdot; \cdot; \cdot} \quad \text{TY_PAT_RES_EMPTY}$$

$$\frac{}{points_to:points_to \rightsquigarrow \cdot; \cdot; \cdot, points_to} \quad \text{TY_PAT_RES_POINTSTO}$$

$$\frac{}{r:res \rightsquigarrow \cdot; \cdot; \cdot, r:res} \quad \text{TY_PAT_RES_VAR}$$

$$\frac{\begin{array}{l} res_pattern_1:res_1 \rightsquigarrow \mathcal{L}_1; \Phi_1; \mathcal{R}_1 \\ res_pattern_2:res_2 \rightsquigarrow \mathcal{L}_2; \Phi_2; \mathcal{R}_2 \end{array}}{\langle res_pattern_1, res_pattern_2 \rangle:res_1 * res_2 \rightsquigarrow \mathcal{L}_1, \mathcal{L}_2; \Phi_1, \Phi_2; \mathcal{R}_1, \mathcal{R}_2} \quad \text{TY_PAT_RES_SEPCONJ}$$

$$\frac{res_pattern:res \rightsquigarrow \mathcal{L}; \Phi; \mathcal{R}}{res_pattern:term \wedge res \rightsquigarrow \mathcal{L}; \Phi, term; \mathcal{R}} \quad \text{TY_PAT_RES_CONJ}$$

$$\frac{res_pattern:x/y, \cdot(res) \rightsquigarrow \mathcal{L}; \Phi; \mathcal{R}}{\text{pack}(x, res_pattern):\exists y:\beta. res \rightsquigarrow \mathcal{L}, x:\beta; \Phi; \mathcal{R}} \quad \text{TY_PAT_RES_PACK}$$

$$\boxed{\overline{ret_pattern_i}^i:ret \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}}$$

$$\frac{}{:I \rightsquigarrow \cdot; \cdot; \cdot; \cdot} \quad \text{TY_PAT_RET_EMPTY}$$

$$\frac{\begin{array}{l} ident_or_pattern:\beta \rightsquigarrow \mathcal{C}_1 \text{ with } term_1 \\ \overline{ret_pattern_i}^i:term_1/y, \cdot(ret) \rightsquigarrow \mathcal{C}_2; \mathcal{L}_2; \Phi_2; \mathcal{R}_2 \end{array}}{\text{comp } ident_or_pattern, \overline{ret_pattern_i}^i:\Sigma y:\beta. ret \rightsquigarrow \mathcal{C}_1, \mathcal{C}_2; \mathcal{L}_2; \Phi_2; \mathcal{R}_2} \quad \text{TY_PAT_RET_COMP}$$

$$\frac{\overline{ret_pattern_i}^i : ret \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}}{\log y, \overline{ret_pattern_i}^i : \exists y:\beta. ret \rightsquigarrow \mathcal{C}; \mathcal{L}; y:\beta; \Phi; \mathcal{R}} \quad \text{TY_PAT_RET_LOG}$$

$$\frac{\frac{res_pattern:res \rightsquigarrow \mathcal{L}_1; \Phi_1; \mathcal{R}_1}{\overline{ret_pattern_i}^i : ret \rightsquigarrow \mathcal{C}_2; \mathcal{L}_2; \Phi_2; \mathcal{R}_2}}{\mathbf{res} res_pattern, \overline{ret_pattern_i}^i : res \otimes ret \rightsquigarrow \mathcal{C}_2; \mathcal{L}_1, \mathcal{L}_2; \Phi_1, \Phi_2; \mathcal{R}_1, \mathcal{R}_2} \quad \text{TY_PAT_RET_RES}$$

$$\frac{\overline{ret_pattern_i}^i : ret \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}}{\overline{ret_pattern_i}^i : term \wedge ret \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi, term; \mathcal{R}} \quad \text{TY_PAT_RET_PHI}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi \vdash tpval \Leftarrow ident:\beta. term}$$

$$\frac{\mathbf{smt}(\Phi \Rightarrow \mathbf{false})}{\mathcal{C}; \mathcal{L}; \Phi \vdash \mathbf{undef} \ UB_name \Leftarrow y:\beta. term} \quad \text{TY_TPVAL_UNDEF}$$

$$\frac{\frac{\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta}{\mathbf{smt}(\Phi \Rightarrow pval/y, \cdot(term))}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \mathbf{done} pval \Leftarrow y:\beta. term} \quad \text{TY_TPVAL_DONE}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi \vdash tpexpr \Leftarrow ident:\beta. term}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \mathbf{bool} \\ \mathcal{C}; \mathcal{L}; \Phi, pval = \mathbf{true} \vdash tpexpr_1 \Leftarrow y:\beta. term \\ \mathcal{C}; \mathcal{L}; \Phi, pval = \mathbf{false} \vdash tpexpr_2 \Leftarrow y:\beta. term \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \mathbf{if} pval \mathbf{then} tpexpr_1 \mathbf{else} tpexpr_2 \Leftarrow y:\beta. term} \quad \text{TY_TPE_IF}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi \vdash pexpr \Rightarrow y_1:\beta_1. term_1 \\ ident_or_pattern:\beta_1 \rightsquigarrow \mathcal{C}_1 \mathbf{with} term \\ \mathcal{C}, \mathcal{C}_1; \mathcal{L}; \Phi, term/y_1, \cdot(term_1) \vdash tpexpr \Leftarrow y_2:\beta_2. term_2 \end{array}}{\mathcal{C}; \mathcal{L}; \Phi \vdash \mathbf{let} ident_or_pattern = pexpr \mathbf{in} tpexpr \Leftarrow y_2:\beta_2. term_2} \quad \text{TY_TPE_LET}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash tpepr_1 \Leftarrow y_1:\beta_1. term_1 \\
ident_or_pattern:\beta_1 \rightsquigarrow \mathcal{C}_1 \text{ with } term \\
\mathcal{C}, \mathcal{C}_1; \mathcal{L}; \Phi, term/y_1, \cdot (term_1) \vdash tpepr \Leftarrow y_2:\beta_2. term_2 \\
\hline
\mathcal{C}; \mathcal{L}; \Phi \vdash \text{let } ident_or_pattern:(y_1:\beta_1. term_1) = tpepr_1 \text{ in } tpepr_2 \Leftarrow y_2:\beta_2. term_2
\end{array}
\quad \text{TY_TPE_LET}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta_1 \\
\overline{pattern_i:\beta_1 \rightsquigarrow \mathcal{C}_i \text{ with } term_i}^i \\
\mathcal{C}, \mathcal{C}_i; \mathcal{L}; \Phi, term_i = pval \vdash tpepr_i \Leftarrow y_2:\beta_2. term_2^i \\
\hline
\mathcal{C}; \mathcal{L}; \Phi \vdash \text{case } pval \text{ of } \overline{pattern_i \Rightarrow tpepr_i}^i \text{ end} \Leftarrow y_2:\beta_2. term_2
\end{array}
\quad \text{TY_TPE_CASE}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash mem_action \Rightarrow ret}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \text{integer} \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \text{create}(pval, \tau) \Rightarrow \Sigma y_p:\text{loc. representable}(\tau*, y_p) \wedge \text{alignedI}(pval, y_p) \wedge \exists y:\beta_\tau. y_p \overset{\times}{\mapsto}_\tau y \otimes \mathbf{I}
\end{array}
\quad \text{TY_ACTION_CREATE}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_0 \Rightarrow \text{loc} \\
\text{smt}(\Phi \Rightarrow pval_0 = pval_1) \\
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash pval_1 \overset{\checkmark}{\mapsto}_\tau pval_2 \Leftarrow pval_1 \overset{\checkmark}{\mapsto}_\tau pval_2 \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \text{load}(\tau, pval_0, -, pval_1 \overset{\checkmark}{\mapsto}_\tau pval_2) \Rightarrow \Sigma y:\beta_\tau. y = pval_2 \wedge pval_1 \overset{\checkmark}{\mapsto}_\tau pval_2 \otimes \mathbf{I}
\end{array}
\quad \text{TY_ACTION_LOAD}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_0 \Rightarrow \text{loc} \\
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \Rightarrow \beta_\tau \\
\text{smt}(\Phi \Rightarrow \text{representable}(\tau, pval_1)) \\
\text{smt}(\Phi \Rightarrow pval_2 = pval_0) \\
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash pval_2 \mapsto_\tau - \Leftarrow pval_2 \mapsto_\tau - \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \text{store}(-, \tau, pval_0, pval_1, -, pval_2 \mapsto_\tau -) \Rightarrow \Sigma -: \text{unit}. pval_2 \overset{\checkmark}{\mapsto}_\tau pval_1 \otimes \mathbf{I}
\end{array}
\quad \text{TY_ACTION_STORE}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_0 \Rightarrow \text{loc} \\
\text{smt}(\Phi \Rightarrow pval_0 = pval_1) \\
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash pval_1 \mapsto_{\tau} - \Leftarrow pval_1 \mapsto_{\tau} - \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \text{kill}(\text{static } \tau, pval_0, pval_1 \mapsto_{\tau} -) \Rightarrow \Sigma _:\text{unit}. \mathbf{I}
\end{array}
\quad \text{TY_ACTION_KILL_STATIC}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \text{mem_op} \Rightarrow \text{ret}}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \Rightarrow \text{loc} \\
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_2 \Rightarrow \text{loc} \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash pval_1 \text{ binop}_{rel} pval_2 \Rightarrow \Sigma y:\text{bool}. y = (pval_1 \text{ binop}_{rel} pval_2) \wedge \mathbf{I}
\end{array}
\quad \text{TY_MEMOP_REL_BINOP}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \text{loc} \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \text{intFromPtr}(\tau_1, \tau_2, pval) \Rightarrow \Sigma y:\text{integer}. y = \text{cast_ptr_to_int } pval \wedge \mathbf{I}
\end{array}
\quad \text{TY_MEMOP_INTFROMPTR}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \text{integer} \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \text{ptrFromInt}(\tau_1, \tau_2, pval) \Rightarrow \Sigma y:\text{loc}. y = \text{cast_int_to_ptr } pval \wedge \mathbf{I}
\end{array}
\quad \text{TY_MEMOP_PTRFROMINT}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_0 \Rightarrow \text{loc} \\
\text{smt}(\Phi \Rightarrow pval_1 = pval_0) \\
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash pval_1 \check{\mapsto}_{\tau} - \Leftarrow pval_1 \check{\mapsto}_{\tau} - \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \text{ptrValidForDeref}(\tau, pval_0, pval_1 \check{\mapsto}_{\tau} -) \Rightarrow \Sigma y:\text{bool}. y = \text{aligned}(\tau, pval_1) \wedge pval_1 \check{\mapsto}_{\tau} - \otimes \mathbf{I}
\end{array}
\quad \text{TY_MEMOP_PTRVALIDFORDEREF}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \Rightarrow \text{loc} \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \text{ptrWellAligned}(\tau, pval) \Rightarrow \Sigma y:\text{bool}. y = \text{aligned}(\tau, pval) \wedge \mathbf{I}
\end{array}
\quad \text{TY_MEMOP_PTRWELLALIGNED}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_1 \Rightarrow \text{loc} \\
\mathcal{C}; \mathcal{L}; \Phi \vdash pval_2 \Rightarrow \text{integer} \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \text{ptrArrayShift}(pval_1, \tau, pval_2) \Rightarrow \Sigma y:\text{loc}. y = pval_1 +_{\text{ptr}} (pval_2 \times \text{size_of}(\tau)) \wedge \mathbf{I}
\end{array}
\quad \text{TY_MEMOP_PTRARRAYSHIFT}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash tval \Leftarrow ret}$$

$$\frac{}{\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \mathbf{done} \Leftarrow \mathbf{I}} \text{TY_TVAL_I}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{done} \overline{spine_elem_i}^i \Leftarrow pval/y, \cdot (ret) \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{done} pval, \overline{spine_elem_i}^i \Leftarrow \Sigma y:\beta. ret} \text{TY_TVAL_COMP}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{done} \overline{spine_elem_i}^i \Leftarrow pval/y, \cdot (ret) \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{done} pval, \overline{spine_elem_i}^i \Leftarrow \exists y:\beta. ret} \text{TY_TVAL_LOG}$$

$$\frac{\begin{array}{l} \text{smt}(\Phi \Rightarrow term) \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{done} spine \Leftarrow ret \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{done} spine \Leftarrow term \wedge ret} \text{TY_TVAL_PHI}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_1 \vdash res_term \Leftarrow res \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_2 \vdash \mathbf{done} \overline{spine_elem_i}^i \Leftarrow ret \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_1, \mathcal{R}_2 \vdash \mathbf{done} res_term, \overline{spine_elem_i}^i \Leftarrow res \otimes ret} \text{TY_TVAL_RES}$$

$$\frac{\text{smt}(\Phi \Rightarrow \mathbf{false})}{\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \mathbf{undef} UB_name \Leftarrow ret} \text{TY_TVAL_UNDEF}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash seq_expr \Rightarrow ret}$$

$$\frac{\begin{array}{l} ident:arg \equiv \overline{x_i}^i \mapsto texpr \in \mathbf{Globals} \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{ccall}(\tau, ident, \overline{spine_elem_i}^i) \Rightarrow \sigma(ret)} \text{TY_SEQ_E_CCALL}$$

$$\begin{array}{c}
name:arg \equiv \overline{x_i}^i \mapsto texpr \in \mathbf{Globals} \\
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{pcall}(name, \overline{spine_elem_i}^i) \Rightarrow \sigma(ret)
\end{array} \quad \text{TY_SEQ_E_PROC}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash is_expr \Rightarrow ret}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash mem_op \Rightarrow ret \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{memop}(mem_op) \Rightarrow ret
\end{array} \quad \text{TY_IS_E_MEMOP}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash mem_action \Rightarrow ret \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash mem_action \Rightarrow ret
\end{array} \quad \text{TY_IS_E_ACTION}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash mem_action \Rightarrow ret \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{neg} mem_action \Rightarrow ret
\end{array} \quad \text{TY_IS_E_NEG_ACTION}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash seq_texpr \Leftarrow ret}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash tval \Leftarrow ret \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash tval \Leftarrow ret
\end{array} \quad \text{TY_SEQ_TE_TVAL}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pexpr \Rightarrow y:\beta. term \\
ident_or_pattern:\beta \rightsquigarrow \mathcal{C}_1 \mathbf{with} term_1 \\
\mathcal{C}, \mathcal{C}_1; \mathcal{L}; \Phi, term_1/y, \cdot(term); \mathcal{R} \vdash texpr \Leftarrow ret \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{let} ident_or_pattern = pexpr \mathbf{in} texpr \Leftarrow ret
\end{array} \quad \text{TY_SEQ_TE_LETP}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash texpr \Leftarrow y:\beta. term \\
ident_or_pattern:\beta \rightsquigarrow \mathcal{C}_1 \mathbf{with} term_1 \\
\mathcal{C}, \mathcal{C}_1; \mathcal{L}; \Phi, term_1/y, \cdot(term); \mathcal{R} \vdash texpr \Leftarrow ret \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{let} ident_or_pattern:(y:\beta. term) = texpr \mathbf{in} texpr \Leftarrow ret
\end{array} \quad \text{TY_SEQ_TE_LETPT}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}' \vdash seq_expr \Rightarrow ret_1 \\
\overline{ret_pattern_i}^i : ret_1 \rightsquigarrow \mathcal{C}_1; \mathcal{L}_1; \Phi_1; \mathcal{R}_1 \\
\mathcal{C}, \mathcal{C}_1; \mathcal{L}, \mathcal{L}_1; \Phi, \Phi_1; \mathcal{R}, \mathcal{R}_1 \vdash texpr \Leftarrow ret_2 \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}', \mathcal{R} \vdash \mathbf{let} \overline{ret_pattern_i}^i = seq_expr \mathbf{in} texpr \Leftarrow ret_2
\end{array}
\quad \text{TY_SEQ_TE_LET}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}' \vdash texpr_1 \Leftarrow ret_1 \\
\overline{ret_pattern_i}^i : ret_1 \rightsquigarrow \mathcal{C}_1; \mathcal{L}_1; \Phi_1; \mathcal{R}_1 \\
\mathcal{C}, \mathcal{C}_1; \mathcal{L}, \mathcal{L}_1; \Phi, \Phi_1; \mathcal{R}, \mathcal{R}_1 \vdash texpr_2 \Leftarrow ret_2 \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}', \mathcal{R} \vdash \mathbf{let} \overline{ret_pattern_i}^i : ret_1 = texpr_1 \mathbf{in} texpr_2 \Leftarrow ret_2
\end{array}
\quad \text{TY_SEQ_TE_LET}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta_1 \\
\overline{pattern_i}^i : \beta_1 \rightsquigarrow \mathcal{C}_i \mathbf{with} term_i \\
\mathcal{C}, \mathcal{C}_i; \mathcal{L}; \Phi, term_i = pval; \mathcal{R} \vdash texpr_i \Leftarrow ret^i \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{case} pval \mathbf{of} \mid \overline{pattern_i}^i \Rightarrow texpr_i \mathbf{end} \Leftarrow ret
\end{array}
\quad \text{TY_SEQ_TE_CASE}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \mathbf{bool} \\
\mathcal{C}; \mathcal{L}; \Phi, pval = \mathbf{true}; \mathcal{R} \vdash texpr_1 \Leftarrow ret \\
\mathcal{C}; \mathcal{L}; \Phi, pval = \mathbf{false}; \mathcal{R} \vdash texpr_2 \Leftarrow ret \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{if} pval \mathbf{then} texpr_1 \mathbf{else} texpr_2 \Leftarrow ret
\end{array}
\quad \text{TY_SEQ_TE_IF}$$

$$\begin{array}{c}
ident:arg \equiv \overline{x_i}^i \mapsto texpr \in \mathbf{Globals} \\
\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \overline{x_i}^i = pval_i^i :: arg \gg \sigma; \mathbf{false} \wedge \mathbf{I} \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash \mathbf{run} ident \overline{pval_i}^i \Leftarrow \mathbf{false} \wedge \mathbf{I}
\end{array}
\quad \text{TY_SEQ_TE_RUN}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash is_texpr \Leftarrow ret \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash \mathbf{bound} [int](is_texpr) \Leftarrow ret
\end{array}
\quad \text{TY_SEQ_TE_BOUND}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash is_texpr \Leftarrow ret}$$

$$\begin{array}{c}
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}' \vdash is_expr \Rightarrow ret_1 \\
\overline{ret_pattern_i}^i : ret_1 \rightsquigarrow \mathcal{C}_1; \mathcal{L}_1; \Phi_1; \mathcal{R}_1 \\
\mathcal{C}, \mathcal{C}_1; \mathcal{L}, \mathcal{L}_1; \Phi, \Phi_1; \mathcal{R}, \mathcal{R}_1 \vdash texpr \Leftarrow ret_2 \\
\hline
\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}', \mathcal{R} \vdash \text{let strong } \overline{ret_pattern_i}^i = is_expr \text{ in } texpr \Leftarrow ret_2
\end{array}
\quad \text{TY_IS_TE_LETS}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash texpr \Leftarrow ret}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash is_texpr \Leftarrow ret}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash is_texpr \Leftarrow ret} \quad \text{TY_TE_IS}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash seq_texpr \Leftarrow ret}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash seq_texpr \Leftarrow ret} \quad \text{TY_TE_SEQ}$$

$$\boxed{pattern = pval \rightsquigarrow \sigma}$$

$$\frac{}{\therefore _ = pval \rightsquigarrow \cdot} \quad \text{SUBS_DECONS_VALUE_NO_SYM_ANNOT}$$

$$\frac{}{x : _ = pval \rightsquigarrow pval/x, \cdot} \quad \text{SUBS_DECONS_VALUE_SYM_ANNOT}$$

$$\frac{\begin{array}{c} pattern_1 = pval_1 \rightsquigarrow \sigma_1 \\ pattern_2 = pval_2 \rightsquigarrow \sigma_2 \end{array}}{\text{Cons}(pattern_1, pattern_2) = \text{Cons}(pval_1, pval_2) \rightsquigarrow \sigma_1, \sigma_2} \quad \text{SUBS_DECONS_VALUE_CONS}$$

$$\frac{\overline{pattern_i = pval_i \rightsquigarrow \sigma_i}^i}{\text{Tuple}(\overline{pattern_i}^i) = \text{Tuple}(\overline{pval_i}^i) \rightsquigarrow \overline{\sigma_i}^i} \quad \text{SUBS_DECONS_VALUE_TUPLE}$$

$$\frac{\overline{pattern_i = pval_i \rightsquigarrow \sigma_i^i}}{\text{Array}(\overline{pattern_i^i}) = \text{Array}(\overline{pval_i^i}) \rightsquigarrow \overline{\sigma_i^i}} \quad \text{SUBS_DECONS_VALUE_ARRAY}$$

$$\frac{pattern = pval \rightsquigarrow \sigma}{\text{Specified}(pattern) = pval \rightsquigarrow \sigma} \quad \text{SUBS_DECONS_VALUE_SPECIFIED}$$

$$\boxed{ident_or_pattern = pval \rightsquigarrow \sigma}$$

$$\frac{}{x = pval \rightsquigarrow pval/x, \cdot} \quad \text{SUBS_DECONS_VALUE'_SYM}$$

$$\frac{pattern = pval \rightsquigarrow \sigma}{pattern = pval \rightsquigarrow \sigma} \quad \text{SUBS_DECONS_VALUE'_PATTERN}$$

$$\boxed{res_pattern = res_term \rightsquigarrow \sigma}$$

$$\frac{}{\mathbf{emp} = \mathbf{emp} \rightsquigarrow \cdot} \quad \text{SUBS_DECONS_RES_EMP}$$

$$\frac{}{pt = pt \rightsquigarrow \cdot} \quad \text{SUBS_DECONS_RES_POINTS_TO}$$

$$\frac{}{ident = res_term \rightsquigarrow res_term/ident, \cdot} \quad \text{SUBS_DECONS_RES_VAR}$$

$$\frac{\begin{array}{l} res_pattern_1 = res_term_1 \rightsquigarrow \sigma_1 \\ res_pattern_2 = res_term_2 \rightsquigarrow \sigma_2 \end{array}}{\langle res_pattern_1, res_pattern_2 \rangle = \langle res_term_1, res_term_2 \rangle \rightsquigarrow \sigma_1, \sigma_2} \quad \text{SUBS_DECONS_RES_PAIR}$$

$$\frac{res_pattern = res_term \rightsquigarrow \sigma}{\mathbf{pack}(ident, res_pattern) = \mathbf{pack}(pval, res_term) \rightsquigarrow pval/ident, \sigma} \quad \text{SUBS_DECONS_RES_PACK}$$

$$\boxed{\overline{ret_pattern_i = spine_elem_i}^i \rightsquigarrow \sigma}$$

$$\frac{}{\rightsquigarrow \cdot} \quad \text{SUBS_DECONS_RET_EMPTY}$$

$$\frac{\frac{ident_or_pattern = pval \rightsquigarrow \sigma}{\overline{ret_pattern_i = spine_elem_i}^i \rightsquigarrow \psi}}{\text{comp } ident_or_pattern = pval, \overline{ret_pattern_i = spine_elem_i}^i \rightsquigarrow \sigma, \psi} \quad \text{SUBS_DECONS_RET_COMP}$$

$$\frac{\overline{ret_pattern_i = spine_elem_i}^i \rightsquigarrow \psi}{\text{log } ident = pval, \overline{ret_pattern_i = spine_elem_i}^i \rightsquigarrow pval/ident, \psi} \quad \text{SUBS_DECONS_RET_LOG}$$

$$\frac{\frac{res_pattern = res_term \rightsquigarrow \sigma}{\overline{ret_pattern_i = spine_elem_i}^i \rightsquigarrow \psi}}{\text{res } res_pattern = res_term, \overline{ret_pattern_i = spine_elem_i}^i \rightsquigarrow \sigma, \psi} \quad \text{SUBS_DECONS_RET_RES}$$

$$\boxed{x_i = spine_elem_i^i :: arg \gg \sigma; ret}$$

$$\frac{}{::ret \gg \cdot; ret} \quad \text{SUBS_DECONS_ARG_EMPTY}$$

$$\frac{\overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret}{x = pval, \overline{x_i = spine_elem_i}^i :: \Pi x:\beta. arg \gg pval/x, \sigma; ret} \quad \text{SUBS_DECONS_ARG_COMP}$$

$$\frac{\overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret}{x = pval, \overline{x_i = spine_elem_i}^i :: \forall x:\beta. arg \gg pval/x, \sigma; ret} \quad \text{SUBS_DECONS_ARG_LOG}$$

$$\frac{\overline{x_i = spine_elem_i^i :: arg \gg \sigma; ret}}{x = res_term, \overline{x_i = spine_elem_i^i :: res \multimap arg \gg res_term/x, \sigma; ret}} \quad \text{SUBS_DECONS_ARG_RES}$$

$$\frac{\overline{x_i = spine_elem_i^i :: arg \gg \sigma; ret}}{\overline{x_i = spine_elem_i^i :: term \supset arg \gg \sigma; ret}} \quad \text{SUBS_DECONS_ARG_PHI}$$

$$\boxed{\langle pexpr \rangle \longrightarrow \langle pexpr' \rangle}$$

$$\frac{mem_ptr' \equiv mem_ptr +_{\text{ptr}} mem_int \times \text{size_of}(\tau)}{\langle \text{array_shift}(mem_ptr, \tau, mem_int) \rangle \longrightarrow \langle mem_ptr' \rangle} \quad \text{OP_PE_PE_ARRAYSHIFT}$$

$$\frac{mem_ptr' \equiv mem_ptr +_{\text{ptr}} \text{offset_of}_{tag}(member)}{\langle \text{member_shift}(mem_ptr, tag, member) \rangle \longrightarrow \langle mem_ptr' \rangle} \quad \text{OP_PE_PE_MEMBERSHIFT}$$

$$\frac{}{\langle \text{not}(\text{True}) \rangle \longrightarrow \langle \text{False} \rangle} \quad \text{OP_PE_PE_NOT_TRUE}$$

$$\frac{}{\langle \text{not}(\text{False}) \rangle \longrightarrow \langle \text{True} \rangle} \quad \text{OP_PE_PE_NOT_FALSE}$$

$$\frac{mem_int \equiv mem_int_1 \text{ binop}_{arith} mem_int_2}{\langle mem_int_1 \text{ binop}_{arith} mem_int_2 \rangle \longrightarrow \langle mem_int \rangle} \quad \text{OP_PE_PE_ARITH_BINOP}$$

$$\frac{bool_value \equiv mem_int_1 \text{ binop}_{rel} mem_int_2}{\langle mem_int_1 \text{ binop}_{rel} mem_int_2 \rangle \longrightarrow \langle bool_value \rangle} \quad \text{OP_PE_PE_REL_BINOP}$$

$$\frac{bool_value \equiv bool_value_1 \text{ binop}_{bool} bool_value_2}{\langle bool_value_1 \text{ binop}_{bool} bool_value_2 \rangle \longrightarrow \langle bool_value \rangle} \quad \text{OP_PE_PE_BOOL_BINOP}$$

$$\frac{}{\langle \text{assert_undef}(\text{True}, UB_name) \rangle \longrightarrow \langle \text{Unit} \rangle} \quad \text{OP_PE_PE_ASSERT_UNDEF}$$

$$\frac{}{\langle \text{bool_to_integer}(\text{True}) \rangle \longrightarrow \langle 1 \rangle} \quad \text{OP_PE_PE_BOOL_TO_INTEGER_TRUE}$$

$$\frac{}{\langle \text{bool_to_integer}(\text{False}) \rangle \longrightarrow \langle 0 \rangle} \quad \text{OP_PE_PE_BOOL_TO_INTEGER_FALSE}$$

$$\frac{\begin{array}{l} abbrev_1 \equiv \text{max_int}_\tau - \text{min_int}_\tau + 1 \\ abbrev_2 \equiv pval \text{ rem_f } abbrev_1 \\ mem_int' \equiv \text{if } abbrev_2 \leq \text{max_int}_\tau \text{ then } abbrev_2 \text{ else } abbrev_2 - abbrev_1 \end{array}}{\langle \text{wrapI}(\tau, mem_int) \rangle \longrightarrow \langle mem_int' \rangle} \quad \text{OP_PE_PE_WRAP_I}$$

$$\boxed{\langle pexpr \rangle \longrightarrow \langle tpepr:(y:\beta. term) \rangle}$$

$$\frac{\begin{array}{l} name: pure_arg \equiv \overline{x_i}^i \mapsto tpepr \in \text{Globals} \\ \overline{x_i = pval_i}^i :: pure_arg \gg \sigma; \Sigma y:\beta. term \wedge I \end{array}}{\langle name(\overline{pval_i}^i) \rangle \longrightarrow \langle \sigma(tpepr):(y:\beta. \sigma(term)) \rangle} \quad \text{OP_PE_TPE_CALL}$$

$$\boxed{\langle tpepr \rangle \longrightarrow \langle tpepr' \rangle}$$

$$\frac{\begin{array}{l} pattern_j = pval \rightsquigarrow \sigma_j \\ \forall i < j. \text{not } (pattern_i = pval \rightsquigarrow \sigma_i) \end{array}}{\langle \text{case } pval \text{ of } \overline{pattern_i \Rightarrow tpepr_i}^i \text{ end} \rangle \longrightarrow \langle \sigma_j(tpepr_j) \rangle} \quad \text{OP_TPE_TPE_CASE}$$

$$\frac{ident_or_pattern = pval \rightsquigarrow \sigma}{\langle \text{let } ident_or_pattern = pval \text{ in } tpepr \rangle \longrightarrow \langle \sigma(tpepr) \rangle} \quad \text{OP_TPE_TPE_LET_SUB}$$

$$\frac{\langle pexpr \rangle \longrightarrow \langle pexpr' \rangle}{\langle \text{let } ident_or_pattern = pexpr \text{ in } tpepr \rangle \longrightarrow \langle \text{let } ident_or_pattern = pexpr' \text{ in } tpepr \rangle} \quad \text{OP_TPE_TPE_LET_LET}$$

$$\frac{\langle pexpr \rangle \longrightarrow \langle texpr_1:(y:\beta. term) \rangle}{\langle \text{let } ident_or_pattern = pexpr \text{ in } texpr_2 \rangle \longrightarrow \langle \text{let } ident_or_pattern:(y:\beta. term) = texpr_1 \text{ in } texpr_2 \rangle} \quad \text{OP_TPE_TPE_LET_LET}$$

$$\frac{ident_or_pattern = pval \rightsquigarrow \sigma}{\langle \text{let } ident_or_pattern:(y:\beta. term) = \text{done } pval \text{ in } texpr \rangle \longrightarrow \langle \sigma(texpr) \rangle} \quad \text{OP_TPE_TPE_LET_SUB}$$

$$\frac{\langle texpr_1 \rangle \longrightarrow \langle texpr'_1 \rangle}{\langle \text{let } ident_or_pattern:(y:\beta. term) = texpr_1 \text{ in } texpr_2 \rangle \longrightarrow \langle \text{let } ident_or_pattern:(y:\beta. term) = texpr'_1 \text{ in } texpr_2 \rangle} \quad \text{OP_TPE_TPE_LET_LET}$$

$$\frac{}{\langle \text{if True then } texpr_1 \text{ else } texpr_2 \rangle \longrightarrow \langle texpr_1 \rangle} \quad \text{OP_TPE_TPE_IF_TRUE}$$

$$\frac{}{\langle \text{if False then } texpr_1 \text{ else } texpr_2 \rangle \longrightarrow \langle texpr_2 \rangle} \quad \text{OP_TPE_TPE_IF_FALSE}$$

$$\boxed{\langle h; seq_expr \rangle \longrightarrow \langle h'; texpr:ret \rangle}$$

$$\frac{\begin{array}{l} ident:arg \equiv \overline{x_i}^i \mapsto texpr \in \text{Globals} \\ \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret \end{array}}{\langle h; ccall(\tau, ident, \overline{spine_elem_i}^i) \rangle \longrightarrow \langle h; \sigma(texpr):\sigma(ret) \rangle} \quad \text{OP_SE_TE_CCALL}$$

$$\frac{\begin{array}{l} name:arg \equiv \overline{x_i}^i \mapsto texpr \in \text{Globals} \\ \overline{x_i = spine_elem_i}^i :: arg \gg \sigma; ret \end{array}}{\langle h; pcall(name, \overline{spine_elem_i}^i) \rangle \longrightarrow \langle h; \sigma(texpr):\sigma(ret) \rangle} \quad \text{OP_SE_TE_PCALL}$$

$$\boxed{\langle h; seq_texpr \rangle \longrightarrow \langle h'; texpr \rangle}$$

$$\frac{\begin{array}{l} ident:arg \equiv \overline{x_i}^i \mapsto texpr \in \text{Globals} \\ \overline{x_i = pval_i}^i :: arg \gg \sigma; \text{false} \wedge \text{I} \end{array}}{\langle h; \text{run } ident \overline{pval_i}^i \rangle \longrightarrow \langle h; \sigma(texpr) \rangle} \quad \text{OP_STE_TE_RUN}$$

$$\frac{\begin{array}{c} pattern_j = pval \rightsquigarrow \sigma_j \\ \forall i < j. \text{not } (pattern_i = pval \rightsquigarrow \sigma_i) \end{array}}{\langle h; \text{case } pval \text{ of } \mid pattern_i \Rightarrow texpr_i^i \text{ end} \rangle \longrightarrow \langle h; \sigma_j(texpr_j) \rangle} \quad \text{OP_STE_TE_CASE}$$

$$\frac{ident_or_pattern = pval \rightsquigarrow \sigma}{\langle h; \text{let } ident_or_pattern = pval \text{ in } texpr \rangle \longrightarrow \langle h; \sigma(texpr) \rangle} \quad \text{OP_STE_TE_LETP_SUB}$$

$$\frac{\langle pexpr \rangle \longrightarrow \langle pexpr' \rangle}{\langle h; \text{let } ident_or_pattern = pexpr \text{ in } texpr \rangle \longrightarrow \langle h; \text{let } ident_or_pattern = pexpr' \text{ in } texpr \rangle} \quad \text{OP_STE_TE_LETP_LETP}$$

$$\frac{\langle pexpr \rangle \longrightarrow \langle texpr:(y:\beta. term) \rangle}{\langle h; \text{let } ident_or_pattern = pexpr \text{ in } texpr \rangle \longrightarrow \langle h; \text{let } ident_or_pattern:(y:\beta. term) = texpr \text{ in } texpr \rangle} \quad \text{OP_STE_TE_LETP_LETP}$$

$$\frac{ident_or_pattern = pval \rightsquigarrow \sigma}{\langle h; \text{let } ident_or_pattern:(y:\beta. term) = \text{done } pval \text{ in } texpr \rangle \longrightarrow \langle h; \sigma(texpr) \rangle} \quad \text{OP_STE_TE_LETP_SUB}$$

$$\frac{\langle texpr \rangle \longrightarrow \langle texpr' \rangle}{\langle h; \text{let } ident_or_pattern:(y:\beta. term) = texpr \text{ in } texpr \rangle \longrightarrow \langle h; \text{let } ident_or_pattern:(y:\beta. term) = texpr' \text{ in } texpr \rangle} \quad \text{OP_STE_TE_LETP_LETP}$$

$$\frac{\overline{ret_pattern_i = spine_elem_i^i} \rightsquigarrow \sigma}{\langle h; \text{let } \overline{ret_pattern_i^i} : ret = \text{done } \overline{spine_elem_i^i} \text{ in } texpr \rangle \longrightarrow \langle h; \sigma(texpr) \rangle} \quad \text{OP_STE_TE_LETT_SUB}$$

$$\frac{\langle h; seq_expr \rangle \longrightarrow \langle h; texpr_1 : ret \rangle}{\langle h; \text{let } \overline{ret_pattern_i^i} = seq_expr \text{ in } texpr_2 \rangle \longrightarrow \langle h; \text{let } \overline{ret_pattern_i^i} : ret = texpr_1 \text{ in } texpr_2 \rangle} \quad \text{OP_STE_TE_LETT_LETT}$$

$$\frac{\langle h; texpr_1 \rangle \longrightarrow \langle h'; texpr'_1 \rangle}{\langle h; \text{let } \overline{ret_pattern_i^i} : ret = texpr_1 \text{ in } texpr_2 \rangle \longrightarrow \langle h'; \text{let } \overline{ret_pattern_i^i} : ret = texpr'_1 \text{ in } texpr_2 \rangle} \quad \text{OP_STE_TE_LETT_LETT}$$

$$\frac{}{\langle h; \text{if True then } texpr_1 \text{ else } texpr_2 \rangle \longrightarrow \langle h; texpr_1 \rangle} \quad \text{OP_STE_TE_IF_TRUE}$$

$$\frac{}{\langle h; \text{if False then } texpr_1 \text{ else } texpr_2 \rangle \longrightarrow \langle h; texpr_2 \rangle} \quad \text{OP_STE_TE_IF_FALSE}$$

$$\frac{}{\langle h; \text{bound } [int] (is_texpr) \rangle \longrightarrow \langle h; is_texpr \rangle} \quad \text{OP_STE_TE_BOUND}$$

$$\boxed{\langle h; mem_op \rangle \longrightarrow \langle h'; tval \rangle}$$

$$\frac{bool_value \equiv mem_int_1 \text{ binop}_{rel} mem_int_2}{\langle h; mem_int_1 \text{ binop}_{rel} mem_int_2 \rangle \longrightarrow \langle h; \text{done } bool_value \rangle} \quad \text{OP_MEMOP_TVAL_REL_BINOP}$$

$$\frac{mem_int \equiv \text{cast_ptr_to_int } mem_ptr}{\langle h; \text{intFromPtr } (\tau_1, \tau_2, mem_ptr) \rangle \longrightarrow \langle h; \text{done } mem_int \rangle} \quad \text{OP_MEMOP_TVAL_INTFROMPTR}$$

$$\frac{mem_ptr \equiv \text{cast_ptr_to_int } mem_int}{\langle h; \text{ptrFromInt } (\tau_1, \tau_2, mem_int) \rangle \longrightarrow \langle h; \text{done } mem_ptr \rangle} \quad \text{OP_MEMOP_TVAL_PTRFROMINT}$$

$$\frac{bool_value \equiv \text{aligned } (\tau, mem_ptr)}{\langle h + \{mem_ptr \overset{\checkmark}{\mapsto}_{\tau} -\}; \text{ptrValidForDeref } (\tau, mem_ptr, mem_ptr \overset{\checkmark}{\mapsto}_{\tau} -) \rangle \longrightarrow \langle h + \{mem_ptr \overset{\checkmark}{\mapsto}_{\tau} -\}; \text{done } bool_value, mem_ptr \overset{\checkmark}{\mapsto}_{\tau} - \rangle} \quad \text{OP_MEMOP_TVAL_PTRVALID}$$

$$\frac{bool_value \equiv \text{aligned } (\tau, mem_ptr)}{\langle h; \text{ptrWellAligned } (\tau, mem_ptr) \rangle \longrightarrow \langle h; \text{done } bool_value \rangle} \quad \text{OP_MEMOP_TVAL_PTRWELLALIGNED}$$

$$\frac{mem_ptr' \equiv mem_ptr +_{\text{ptr}} (mem_int \times \text{size_of}(\tau))}{\langle h; \text{ptrArrayShift } (mem_ptr, \tau, mem_int) \rangle \longrightarrow \langle h; \text{done } mem_ptr' \rangle} \quad \text{OP_MEMOP_TVAL_PTRARRAYSHIFT}$$

$$\boxed{\langle h; mem_action \rangle \longrightarrow \langle h'; tval \rangle}$$

$$\frac{\begin{array}{l} \text{fresh}(mem_ptr) \\ \text{representable}(\tau*, mem_ptr) \\ \text{alignedI}(mem_int, mem_ptr) \\ pval:\beta_\tau \end{array}}{\langle h; \text{create}(mem_int, \tau) \rangle \longrightarrow \langle h + \{mem_ptr \overset{\times}{\mapsto}_\tau pval\}; \text{done } mem_ptr, pval, mem_ptr \overset{\times}{\mapsto}_\tau pval \rangle} \quad \text{OP_ACTION_TVAL_CREATE}$$

$$\frac{}{\langle h + \{mem_ptr \overset{\check}{\mapsto}_\tau pval\}; \text{load}(\tau, mem_ptr, -, mem_ptr \overset{\check}{\mapsto}_\tau pval) \rangle \longrightarrow \langle h + \{mem_ptr \overset{\check}{\mapsto}_\tau pval\}; \text{done } pval, mem_ptr \overset{\check}{\mapsto}_\tau pval \rangle} \quad \text{OP_ACTION_TVAL_LOAD}$$

$$\frac{}{\langle h + \{mem_ptr \overset{\check}{\mapsto}_\tau -\}; \text{store}(-, \tau, mem_ptr, pval, -, mem_ptr \overset{\check}{\mapsto}_\tau -) \rangle \longrightarrow \langle h + \{mem_ptr \overset{\check}{\mapsto}_\tau pval\}; \text{done Unit}, mem_ptr \overset{\check}{\mapsto}_\tau pval \rangle} \quad \text{OP_ACTION_TVAL_STORE}$$

$$\frac{}{\langle h + \{mem_ptr \mapsto_\tau -\}; \text{kill}(\text{static } \tau, mem_ptr, mem_ptr \mapsto_\tau -) \rangle \longrightarrow \langle h; \text{done Unit} \rangle} \quad \text{OP_ACTION_TVAL_KILL_STATIC}$$

$$\boxed{\langle h; is_expr \rangle \longrightarrow \langle h'; is_expr' \rangle}$$

$$\frac{\langle h; mem_op \rangle \longrightarrow \langle h; tval \rangle}{\langle h; \text{memop}(mem_op) \rangle \longrightarrow \langle h; tval \rangle} \quad \text{OP_ISE_ISE_MEMOP}$$

$$\frac{\langle h; mem_action \rangle \longrightarrow \langle h'; tval \rangle}{\langle h; mem_action \rangle \longrightarrow \langle h'; tval \rangle} \quad \text{OP_ISE_ISE_ACTION}$$

$$\frac{\langle h; mem_action \rangle \longrightarrow \langle h'; tval \rangle}{\langle h; \text{neg } mem_action \rangle \longrightarrow \langle h'; tval \rangle} \quad \text{OP_ISE_ISE_NEG_ACTION}$$

$$\boxed{\langle h; is_texpr \rangle \longrightarrow \langle h'; texpr \rangle}$$

$$\frac{\overline{ret_pattern_i = spine_elem_i}^i \rightsquigarrow \sigma}{\langle h; \text{let strong } \overline{ret_pattern_i}^i = \text{done } \overline{spine_elem_i}^i \text{ in } texpr \rangle \longrightarrow \langle h; \sigma(texpr) \rangle} \quad \text{OP_ISTE_ISTE_LETS_SUB}$$

$$\frac{\langle h; is_expr \rangle \longrightarrow \langle h'; is_expr' \rangle}{\langle h; \text{let strong } \overline{ret_pattern_i}^i = is_expr \text{ in } texpr \rangle \longrightarrow \langle h'; \text{let strong } \overline{ret_pattern_i}^i = is_expr' \text{ in } texpr \rangle} \quad \text{OP_ISTE_ISTE_LETS_LETS}$$

$$\boxed{\langle h; texpr \rangle \longrightarrow \langle h'; texpr' \rangle}$$

$$\frac{\langle h; seq_texpr \rangle \longrightarrow \langle h; texpr \rangle}{\langle h; seq_texpr \rangle \longrightarrow \langle h; texpr \rangle} \quad \text{OP_TE_TE_SEQ}$$

$$\frac{\langle h; is_texpr \rangle \longrightarrow \langle h'; texpr \rangle}{\langle h; is_texpr \rangle \longrightarrow \langle h'; texpr \rangle} \quad \text{OP_TE_TE_IS}$$

$$\boxed{\overline{x_i}^i :: arg \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \mid ret}$$

$$\frac{}{::ret \rightsquigarrow \cdot; \cdot; \cdot; \cdot \mid ret} \quad \text{ARG_ENV_RET}$$

$$\frac{\overline{x_i}^i :: arg \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \mid ret}{x, \overline{x_i}^i :: \Pi x:\beta. arg \rightsquigarrow \mathcal{C}, x:\beta; \mathcal{L}; \Phi; \mathcal{R} \mid ret} \quad \text{ARG_ENV_COMP}$$

$$\frac{\overline{x_i}^i :: arg \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \mid ret}{x, \overline{x_i}^i :: \forall x:\beta. arg \rightsquigarrow \mathcal{C}; \mathcal{L}, x:\beta; \Phi; \mathcal{R} \mid ret} \quad \text{ARG_ENV_LOG}$$

$$\frac{\overline{x_i}^i :: arg \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \mid ret}{\overline{x_i}^i :: term \supset arg \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi, term; \mathcal{R} \mid ret} \quad \text{ARG_ENV_PHI}$$

$$\frac{\overline{x_i}^i :: \text{arg} \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \mid \text{ret}}{x, \overline{x_i}^i :: \text{res} \multimap \text{arg} \rightsquigarrow \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}, x:\text{res} \mid \text{ret}} \quad \text{ARG_ENV_RES}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'}$$

$$\frac{}{\cdot; \cdot; \cdot; \cdot \sqsubseteq \cdot; \cdot; \cdot; \cdot} \quad \text{WEAK_EMPTY}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'}{\mathcal{C}, x:\beta; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}', x:\beta; \mathcal{L}'; \Phi'; \mathcal{R}'} \quad \text{WEAK_CONS_COMP}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'}{\mathcal{C}; \mathcal{L}, x:\beta; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}', x:\beta; \Phi'; \mathcal{R}'} \quad \text{WEAK_CONS_LOG}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'}{\mathcal{C}; \mathcal{L}; \Phi, \text{term}; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi', \text{term}; \mathcal{R}'} \quad \text{WEAK_CONS_PHI}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}, \text{res} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}', \text{res}} \quad \text{WEAK_CONS_RES_ANON}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}, x:\text{res} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}', x:\text{res}} \quad \text{WEAK_CONS_RES_NAMED}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}', x:\beta; \mathcal{L}'; \Phi'; \mathcal{R}'} \quad \text{WEAK_SKIP_COMP}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}', x:\beta; \Phi'; \mathcal{R}'} \quad \text{WEAK_SKIP_LOG}$$

$$\frac{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}'}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \sqsubseteq \mathcal{C}'; \mathcal{L}'; \Phi'; \text{term}; \mathcal{R}'} \text{WEAK_SKIP_PHI}$$

$$\boxed{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (\sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}')}$$

$$\frac{}{\mathcal{C}; \mathcal{L}; \Phi; \cdot \vdash (\cdot):(\cdot; \cdot; \cdot; \cdot)} \text{TY_SUBS_EMPTY}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (\sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}') \\ \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (pval/x, \sigma):(\mathcal{C}', x:\beta; \mathcal{L}'; \Phi'; \mathcal{R}')} \text{TY_SUBS_CONS_COMP}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (\sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}') \\ \mathcal{C}; \mathcal{L}; \Phi \vdash pval \Rightarrow \beta \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (pval/x, \sigma):(\mathcal{C}'; \mathcal{L}', x:\beta; \Phi'; \mathcal{R}')} \text{TY_SUBS_CONS_LOG}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (\sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}') \\ \text{smt}(\Phi \Rightarrow \text{term}) \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (\sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \text{term}; \mathcal{R}')} \text{TY_SUBS_CONS_PHI}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (\sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}') \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_1 \vdash \text{res_term} \Leftarrow \sigma(\text{res}) \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}, \mathcal{R}_1 \vdash (\text{res_term}/x, \sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}', x:\text{res})} \text{TY_SUBS_CONS_RES_NAMED}$$

$$\frac{\begin{array}{l} \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R} \vdash (\sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}') \\ \mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}_1 \vdash \text{res_term} \Leftarrow \sigma(\text{res}) \end{array}}{\mathcal{C}; \mathcal{L}; \Phi; \mathcal{R}, \mathcal{R}_1 \vdash (\sigma):(\mathcal{C}'; \mathcal{L}'; \Phi'; \mathcal{R}', \text{res})} \text{TY_SUBS_CONS_RES_ANON}$$

Definition rules: 200 good 0 bad

Definition rule clauses: 446 good 0 bad