Package 'bfpwr'

November 22, 2024

Version 0.1.4

Date 2024-11-22
Author Samuel Pawel [aut, cre] (https://orcid.org/0000-0003-2779-320X)
Maintainer Samuel Pawel <samuel.pawel@uzh.ch></samuel.pawel@uzh.ch>
Title Power and Sample Size Calculations for Bayes Factor Analysis
Description Implements z-test, t-test, and normal moment prior Bayes factors based on summary statistics, along with functionality to perform corresponding power and sample size calculations as described in Pawel and Held (2024) <doi:10.48550 arxiv.2406.19940="">.</doi:10.48550>
License GPL-3
Encoding UTF-8
Imports lamW
Suggests roxygen2, tinytest, knitr
VignetteBuilder knitr
NeedsCompilation no
RoxygenNote 7.3.1
<pre>URL https://github.com/SamCH93/bfpwr</pre>
<pre>BugReports https://github.com/SamCH93/bfpwr/issues</pre>
Contents
bf01 2 binbf01 3 nbf01 4 nnmbf01 6 ntbf01 9 pbf01 10 plot.power.bftest 12 pnmbf01 13 powerbf01 14

bf01

	powernmbf01							
	powertbf01							
	print.power.bftest	 	 	 	 	 	 	 19
	ptbf01							
	tbf01	 	 	 	 	 	 	 22
Index								25

bf01 z-test Bayes factor

Description

This function computes the Bayes factor that quantifies the evidence that the data (in the form of an asymptotically normally distributed parameter estimate with standard error) provide for a point null hypothesis with a normal prior assigned to the parameter under the alternative. The standard error is assumed to be known.

Usage

```
bf01(estimate, se, null = 0, pm, psd, log = FALSE)
```

Arguments

estimate	Parameter estimate
se	Standard error of the parameter estimate
null	Parameter value under the point null hypothesis. Defaults to 0
pm	Mean of the normal prior assigned to the parameter under the alternative
psd	Standard deviation of the normal prior assigned to the parameter under the alternative. Set to 0 to obtain a point prior at the prior mean
log	Logical indicating whether the natural logarithm of the Bayes factor should be returned. Defaults to FALSE

Value

Bayes factor in favor of the null hypothesis over the alternative (BF > 1 indicates evidence for the null hypothesis, whereas BF < 1 indicates evidence for the alternative)

Author(s)

Samuel Pawel

```
bf01(estimate = 0.2, se = 0.05, null = 0, pm = 0, psd = 2)
```

binbf01 3

binbf01	Binomial Bayes factor

Description

This function computes the Bayes factor for testing a binomial proportion p based on x observed successes out of n trials. Two types of tests are possible:

- Test of a point null hypothesis: The Bayes factor quantifies the evidence for H_0 : $p=p_0$ against H_1 : $p \neq p_0$. A beta prior is assigned to the proportion p under the alternative hypothesis H_1 .
- Test of a directional null hypothesis: The Bayes factor quantifies the evidence for H_0 : $p \le p_0$ against H_1 : $p > p_0$. A beta prior that is truncated to the range $[0, p_0]$ under the null H_0 and to $(p_0, 1]$ under the alternative H_1 is assigned to the proportion p under the corresponding hypothesis.

Usage

```
binbf01(
    x,
    n,
    p0 = 0.5,
    type = c("point", "direction"),
    a = 1,
    b = 1,
    log = FALSE
)
```

Arguments

X	Number of successes
^	Trumoer of successes
n	Number of trials
p0	Tested binomial proportion. Defaults to 0.5
type	Type of test. Can be "point" or "directional". Defaults to "point"
а	Number of successes parameter of the beta prior distribution. Defaults to 1
b	Number of failures parameter of the beta prior distribution. Defaults to 1
log	Logical indicating whether the natural logarithm of the Bayes factor should be returned. Defaults to FALSE

Value

Bayes factor in favor of the null hypothesis over the alternative (BF > 1 indicates evidence for the null hypothesis, whereas BF < 1 indicates evidence for the alternative)

4 nbf01

Author(s)

Samuel Pawel

Examples

```
## example on Mendelian inheritance from ?stats::binom.test binbf01(x = 682, n = 925, p0 = 3/4, a = 1, b = 1, type = "point") ## 18.6 => strong evidence for the hypothesized p = 3/4 compared to other p ## with directional hypothesis binbf01(x = 682, n = 925, p0 = 3/4, a = 1, b = 1, type = "direction") ## 1.5 => only anecdotal evidence that p <= p0 compared to p > p0
```

nbf01

Sample size determination for z-test Bayes factor

Description

This function computes the required sample size to obtain a Bayes factor (bf01) more extreme than a threshold k with a specified target power.

Usage

```
nbf01(
    k,
    power,
    usd,
    null = 0,
    pm,
    psd,
    dpm = pm,
    dpsd = psd,
    nrange = c(1, 10^5),
    lower.tail = TRUE,
    integer = TRUE,
    analytical = TRUE,
    ...
)
```

Arguments

k	Bayes factor threshold
power	Target power
usd	Unit standard deviation, the standard error of the parameter estimate based on $n=1$, see details
null	Parameter value under the point null hypothesis. Defaults to 0

nbf01 5

pm	Mean of the normal prior assigned to the parameter under the alternative in the analysis
psd	Standard deviation of the normal prior assigned to the parameter under the alternative in the analysis. Set to \emptyset to obtain a point prior at the prior mean
dpm	Mean of the normal design prior assigned to the parameter. Defaults to the same value as the analysis prior pm
dpsd	Standard deviation of the normal design prior assigned to the parameter. Defaults to the same value as the analysis prior psd
nrange	Sample size search range over which numerical search is performed. Defaults to $c(1, 10^5)$
lower.tail	Logical indicating whether $Pr(BF \le k)$ (TRUE) or $Pr(BF > k)$ (FALSE) should be computed. Defaults to TRUE
integer	Logical indicating whether only integer valued sample sizes should be returned. If TRUE the required sample size is rounded to the next larger integer. Defaults to TRUE
analytical	Logical indicating whether analytical (if available) or numerical method should be used. Defaults to TRUE
	Other arguments passed to stats::uniroot

Details

It is assumed that the standard error of the future parameter estimate is of the form $se = usd/\sqrt{n}$. For example, for normally distributed data with known standard deviation sd and two equally sized groups of size n, the standard error of an estimated standardized mean difference is $se = sd\sqrt{2/n}$, so the corresponding unit standard deviation is $usd = sd\sqrt{2}$. See the vignette for more information.

Value

The required sample size to achieve the specified power

Note

A warning message will be displayed in case that the specified target power is not achievable under the specified analysis and design priors.

Author(s)

Samuel Pawel

See Also

pbf01, powerbf01, bf01

6 nmbf01

Examples

nmbf01

Normal moment prior Bayes factor

Description

This function computes the Bayes factor that quantifies the evidence that the data (in the form of an asymptotically normally distributed parameter estimate with standard error) provide for a point null hypothesis with a normal moment prior assigned to the parameter under the alternative.

Usage

```
nmbf01(estimate, se, null = 0, psd, log = FALSE)
```

Arguments

estimate	Parameter estimate
se	Standard error of the parameter estimate
null	Parameter value under the point null hypothesis. Defaults to 0
psd	Spread of the normal moment prior assigned to the parameter under the alternative. The modes of the prior are located at $\pm\sqrt{2}\rm psd$
log	Logical indicating whether the natural logarithm of the Bayes factor should be returned. Defaults to FALSE

Details

A normal moment prior has density $f(x \mid \text{null}, \text{psd}) = N(x \mid \text{null}, \text{psd}^2) \times (x - \text{null})/\text{psd}^2$ with $N(x \mid m, v)$ the normal density with mean m and variance v evaluated at x.

nnmbf01 7

Value

Bayes factor in favor of the null hypothesis over the alternative (BF > 1 indicates evidence for the null hypothesis, whereas BF < 1 indicates evidence for the alternative)

Author(s)

Samuel Pawel

References

Johnson, V. E. and Rossell, D. (2010). On the use of non-local prior densities in Bayesian hypothesis tests. Journal of the Royal Statistical Society: Series B (Statistical Methodology), 72(2):143–170. doi:10.1111/j.14679868.2009.00730.x

Pramanik, S. and Johnson, V. E. (2024). Efficient alternatives for Bayesian hypothesis tests in psychology. Psychological Methods, 29(2):243–261. doi:10.1037/met0000482

See Also

```
nmbf01, pnmbf01, nnmbf01, powernmbf01
```

Examples

```
nmbf01(estimate = 0.25, se = 0.05, null = 0, psd = 0.5/sqrt(2)) # mode at 0.5
```

nnmbf01

Sample size determination for normal moment prior Bayes factor

Description

This function computes the required sample size to obtain a normal moment prior Bayes factor (nbf01) more extreme than a threshold k with a specified target power.

```
nnmbf01(
    k,
    power,
    usd,
    null = 0,
    psd,
    dpm,
    dpsd,
    nrange = c(1, 10^5),
    lower.tail = TRUE,
    integer = TRUE,
    ...
)
```

8 nnmbf01

Arguments

k	Bayes factor threshold
power	Target power
usd	Unit standard deviation, the standard error of the parameter estimate based on $n=1,$ see details
null	Parameter value under the point null hypothesis. Defaults to 0
psd	Spread of the normal moment prior assigned to the parameter under the alternative in the analysis. The modes of the prior are located at $\pm\sqrt{2}\rm psd$
dpm	Mean of the normal design prior assigned to the parameter
dpsd	Standard deviation of the normal design prior assigned to the parameter. Set to 0 to obtain a point prior at the design prior mean
nrange	Sample size search range over which numerical search is performed. Defaults to $c(1, 10^5)$
lower.tail	Logical indicating whether $Pr(BF \le k)$ (TRUE) or $Pr(BF > k)$ (FALSE) should be computed. Defaults to TRUE
integer	Logical indicating whether only integer valued sample sizes should be returned. If TRUE the required sample size is rounded to the next larger integer. Defaults to TRUE
	Other arguments passed to stats::uniroot

Details

It is assumed that the standard error of the future parameter estimate is of the form $se = usd/\sqrt{n}$. For example, for normally distributed data with known standard deviation sd and two equally sized groups of size n, the standard error of an estimated standardized mean difference is $se = sd\sqrt{2/n}$, so the corresponding unit standard deviation is $usd = sd\sqrt{2}$. See the vignette for more information.

Value

The required sample size to achieve the specified power

Author(s)

Samuel Pawel

See Also

```
nmbf01, pnmbf01, powernmbf01
```

```
nnmbf01(k = 1/10, power = 0.9, usd = 1, null = 0, psd = 0.5/sqrt(2), dpm = 0.5, dpsd = 0)
```

ntbf01

ntbf01

Sample size calculations for t-test Bayes factor

Description

This function computes the required sample size to obtain a t-test Bayes factor (tbf01) more extreme than a threshold k with a specified target power.

Usage

```
ntbf01(
    k,
    power,
    null = 0,
    plocation = 0,
    pscale = 1/sqrt(2),
    pdf = 1,
    type = c("two.sample", "one.sample", "paired"),
    alternative = c("two.sided", "less", "greater"),
    dpm = plocation,
    dpsd = pscale,
    lower.tail = TRUE,
    integer = TRUE,
    nrange = c(2, 10^4),
    ...
)
```

Arguments

k	Bayes factor threshold
power	Target power
null	Standardized mean difference under the point null hypothesis. Defaults to 0
plocation	t prior location. Defaults to 0
pscale	t prior scale. Defaults to 1/sqrt(2)
pdf	t prior degrees of freedom. Defaults to 1 (a Cauchy prior)
type	Type of t -test. Can be "two.sample" (default), "one.sample", or "paired"
alternative	Direction of the test. Can be either "two.sided" (default), "less", or "greater" The latter two truncate the analysis prior to negative and positive effects, respectively. If set to "less" or "greater", the power is only computed based on data with effect estimates in the direction of the alternative
dpm	Mean of the normal design prior assigned to the standardized mean difference. Defaults to the analysis prior location
dpsd	Standard deviation of the normal design prior assigned to the standardized mean difference. Set to 0 to obtain a point prior at the design prior mean. Defaults to the analysis prior scale

10 pbf01

lower.tail	Logical indicating whether $Pr(BF \le k)$ (TRUE) or $Pr(BF > k)$ (FALSE) should be computed. Defaults to TRUE
integer	Logical indicating whether only integer valued sample sizes should be returned. If TRUE the required sample size is rounded to the next larger integer. Defaults to TRUE
nrange	Sample size search range over which numerical search is performed. Defaults to $c(2, 10^4)$
	Other arguments passed to stats::uniroot

Value

The required sample size to achieve the specified power

Author(s)

Samuel Pawel

See Also

```
ptbf01, powertbf01, tbf01
```

Examples

```
## example from Schönbrodt and Wagenmakers (2018, p.135)  
ntbf01(k = 1/6, power = 0.95, dpm = 0.5, dpsd = 0, alternative = "greater")  
ntbf01(k = 1/6, power = 0.95, dpm = 0.5, dpsd = 0.1, alternative = "greater")  
ntbf01(k = 6, power = 0.95, dpm = 0, dpsd = 0, alternative = "greater", lower.tail = FALSE, nrange = <math>c(2, 10000))
```

pbf01

Cumulative distribution function of the z-test Bayes factor

Description

This function computes the probability of obtaining a Bayes factor (bf01) more extreme than a threshold k with a specified sample size.

```
pbf01(k, n, usd, null = 0, pm, psd, dpm = pm, dpsd = psd, lower.tail = TRUE)
```

pbf01

Arguments

k	Bayes factor threshold
n	Sample size
usd	Unit standard deviation, the standard error of the parameter estimate based on $n=1,$ see details
null	Parameter value under the point null hypothesis. Defaults to 0
pm	Mean of the normal prior assigned to the parameter under the alternative in the analysis
psd	Standard deviation of the normal prior assigned to the parameter under the alternative in the analysis. Set to 0 to obtain a point prior at the prior mean
dpm	Mean of the normal design prior assigned to the parameter. Defaults to the same value as the analysis prior pm
dpsd	Standard deviation of the normal design prior assigned to the parameter. Defaults to the same value as the analysis prior psd
lower.tail	Logical indicating whether $Pr(BF \le k)$ (TRUE) or $Pr(BF > k)$ (FALSE) should be computed. Defaults to TRUE

Details

It is assumed that the standard error of the future parameter estimate is of the form $se = usd/\sqrt{n}$. For example, for normally distributed data with known standard deviation sd and two equally sized groups of size n, the standard error of an estimated standardized mean difference is $se = sd\sqrt{2/n}$, so the corresponding unit standard deviation is $usd = sd\sqrt{2}$. See the vignette for more information.

Value

The probability that the Bayes factor is less or greater (depending on the specified lower.tail) than the specified threshold k

Author(s)

Samuel Pawel

See Also

```
nbf01, powerbf01, bf01
```

```
## point alternative (psd = 0)
pbf01(k = 1/10, n = 200, usd = 2, null = 0, pm = 0.5, psd = 0)

## normal alternative (psd > 0)
pbf01(k = 1/10, n = 100, usd = 2, null = 0, pm = 0.5, psd = 2)

## design prior is the null hypothesis (dpm = 0, dpsd = 0)
pbf01(k = 10, n = 1000, usd = 2, null = 0, pm = 0.3, psd = 2, dpm = 0, dpsd = 0, lower.tail = FALSE)
```

12 plot.power.bftest

plot.power.bftest

Plot method for class "power.bftest"

Description

Plot method for class "power.bftest"

Usage

```
## S3 method for class 'power.bftest' plot(x, nlim = c(2, 500), ngrid = 100, plot = TRUE, nullplot = TRUE, ...)
```

Arguments

x	Object of class "power.bftest"
nlim	Range of sample sizes over which the power should be computed. Defaults to $c(2, 500)$
ngrid	Number of grid point for which power should be computed. Defaults to 100
plot	Logical indicating whether data should be plotted. If FALSE only the data used for plotting are returned.
nullplot	Logcal indicating whether a second plot with the power in favor of the null (using a Bayes factor threshold of 1/k) should be created. Defaults to TRUE
	Other arguments (for consistency with the generic)

Value

Plots power curves (if specified) and invisibly returns a list of data frames containing the data underlying the power curves

pnmbf01 13

Author(s)

Samuel Pawel

See Also

```
powerbf01, powertbf01, powernmbf01
```

Examples

```
ssd1 \leftarrow powerbf01(k = 1/6, power = 0.95, pm = 0, psd = 1/sqrt(2), dpm = 0.5, dpsd = 0) plot(ssd1, nlim = c(1, 8000)) power1 <- powerbf01(k = 1/2, n = 120, pm = 0, psd = 1/sqrt(2), dpm = 0.5, dpsd = 0) plot(power1, nlim = c(1, 1000))
```

pnmbf01

Cumulative distribution function of the normal moment prior Bayes factor

Description

This function computes the probability of obtaining a normal moment prior Bayes factor (nmbf01) more extreme than a threshold k with a specified sample size.

Usage

```
pnmbf01(k, n, usd, null = 0, psd, dpm, dpsd, lower.tail = TRUE)
```

Arguments

k	Bayes factor threshold
n	Sample size
usd	Unit standard deviation, the standard error of the parameter estimate based on $n=1,$ see details
null	Parameter value under the point null hypothesis. Defaults to 0
psd	Spread of the normal moment prior assigned to the parameter under the alternative in the analysis. The modes of the prior are located at $\pm\sqrt{2}\text{psd}$
dpm	Mean of the normal design prior assigned to the parameter
dpsd	Standard deviation of the normal design prior assigned to the parameter. Set to 0 to obtain a point prior at the design prior mean
lower.tail	Logical indicating whether $Pr(BF \le k)$ (TRUE) or $Pr(BF > k)$ (FALSE) should be computed. Defaults to TRUE

powerbf01

Details

It is assumed that the standard error of the future parameter estimate is of the form $se = usd/\sqrt{n}$. For example, for normally distributed data with known standard deviation sd and two equally sized groups of size n, the standard error of an estimated standardized mean difference is $se = sd\sqrt{2/n}$, so the corresponding unit standard deviation is $usd = sd\sqrt{2}$. See the vignette for more information.

Value

The probability that the Bayes factor is less or greater (depending on the specified lower.tail) than the specified threshold k

Author(s)

Samuel Pawel

See Also

```
nmbf01, nnmbf01, powernmbf01
```

Examples

powerbf01

Power and sample size calculations for z-test Bayes factor

Description

Compute probability that z-test Bayes factor is smaller than a specified threshold (the power), or determine sample size to obtain a target power.

```
powerbf01(
    n = NULL,
    power = NULL,
    k = 1/10,
    sd = 1,
    null = 0,
```

powerbf01 15

```
pm,
psd,
type = c("two.sample", "one.sample", "paired"),
dpm = pm,
dpsd = psd,
nrange = c(1, 10^5)
)
```

Arguments

n	Sample size (per group for two-sample tests). Has to be NULL if power is specified. Defaults to NULL
power	Target power. Has to be NULL if n is specified. Defaults to NULL
k	Bayes factor threshold. Defaults to 1/10, Jeffreys' threshold for 'strong evidence' against the null hypothesis
sd	Standard deviation of one observation (for type = "two.sample" or type = "one.sample") or of one difference within a pair of observations (type = "paired"). Is assumed to be known. Defaults to 1
null	Mean difference under the point null hypothesis. Defaults to 0
pm	Mean of the normal prior assigned to the mean difference under the alternative in the analysis
psd	Standard deviation of the normal prior assigned to the mean difference under the alternative in the analysis. Set to 0 to obtain a point prior at the prior mean
type	The type of test. One of "two.sample", "one.sample", "paired". Defaults to "two.sample"
dpm	Mean of the normal design prior assigned to the mean difference. Defaults to the same value as the analysis prior pm
dpsd	Standard deviation of the normal design prior assigned to the mean difference. Defaults to the same value as the analysis prior psd
nrange	Sample size search range over which numerical search is performed (only taken into account when n is NULL). Defaults to c(1, 10^5)

Details

This function provides a similar interface as stats::power.t.test. It also assumes that the data are continuous and that the parameter of interest is either a mean or a (standardized) mean difference. For some users, the low-level functions nbf01 (to directly compute the sample size for a fixed power) and pbf01 (to directly compute the power for a fixed sample size) may also be useful because they can be used for other data and parameter types.

Value

Object of class "power.bftest", a list of the arguments (including the computed one) augmented with method and note elements

powernmbf01

Note

A warning message will be displayed in case that the specified target power is not achievable under the specified analysis and design priors.

Author(s)

Samuel Pawel

See Also

```
plot.power.bftest, nbf01, pbf01, bf01
```

Examples

```
## determine power
powerbf01(n = 100, pm = 0, psd = 1, dpm = 0.5, dpsd = 0)
## determine sample size
powerbf01(power = 0.99, pm = 0, psd = 1, dpm = 0.5, dpsd = 0)
```

powernmbf01

Power and sample size calculations for normal moment prior Bayes factor

Description

Compute probability that normal moment prior Bayes factor is smaller than a specified threshold (the power), or determine sample size to obtain a target power.

```
powernmbf01(
    n = NULL,
    power = NULL,
    k = 1/10,
    sd = 1,
    null = 0,
    psd,
    type = c("two.sample", "one.sample", "paired"),
    dpm,
    dpsd,
    nrange = c(1, 10^5)
)
```

powernmbf01 17

Arguments

n	Sample size (per group for two-sample tests). Has to be NULL if power is specified. Defaults to NULL
power	Target power. Has to be NULL if n is specified. Defaults to NULL
k	Bayes factor threshold. Defaults to 1/10, Jeffreys' threshold for 'strong evidence' against the null hypothesis
sd	Standard deviation of one observation (for type = "two.sample" or type = "one.sample") or of one difference within a pair of observations (type = "paired"). Is assumed to be known. Defaults to 1
null	Parameter value under the point null hypothesis. Defaults to 0
psd	Spread of the normal moment prior assigned to the parameter under the alternative in the analysis. The modes of the prior are located at $\pm\sqrt{2}$ psd
type	The type of test. One of "two.sample", "one.sample", "paired". Defaults to "two.sample"
dpm	Mean of the normal design prior assigned to the parameter
dpsd	Standard deviation of the normal design prior assigned to the parameter. Set to 0 to obtain a point prior at the design prior mean
nrange	Sample size search range over which numerical search is performed (only taken into account when n is NULL). Defaults to $c(1, 10^5)$

Details

This function provides a similar interface as stats::power.t.test. It also assumes that the data are continuous and that the parameter of interest is either a mean or a (standardized) mean difference. For some users, the low-level functions nnmbf01 (to directly compute the sample size for a fixed power) and pnmbf01 (to directly compute the power for a fixed sample size) may also be useful because they can be used for other data and parameter types.

Value

Object of class "power.bftest", a list of the arguments (including the computed one) augmented with method and note elements

Author(s)

Samuel Pawel

See Also

```
plot.power.bftest, nnmbf01, pnmbf01, nmbf01
```

```
## determine power
powernmbf01(n = 100, psd = 1, dpm = 0.5, dpsd = 0)
## determine sample size
```

powertbf01

```
powernmbf01(power = 0.99, psd = 1, dpm = 0.5, dpsd = 0)
```

powertbf01

Power and sample size calculations for t-test Bayes factor

Description

Compute probability that t-test Bayes factor is smaller than a specified threshold (the power), or determine sample size to obtain a target power.

Usage

```
powertbf01(
  n = NULL,
  power = NULL,
  k = 1/10,
  null = 0,
  plocation = 0,
  pscale = 1/sqrt(2),
  pdf = 1,
  type = c("two.sample", "one.sample", "paired"),
  alternative = c("two.sided", "less", "greater"),
  dpm = plocation,
  dpsd = pscale,
    nrange = c(2, 10^4)
)
```

Arguments

n	Sample size (per group)
power	Target power. Has to be NULL if n is specified. Defaults to NULL
k	Bayes factor threshold. Defaults to 1/10, Jeffreys' threshold for 'strong evidence' against the null hypothesis
null	Standardized mean difference under the point null hypothesis. Defaults to \emptyset
plocation	t prior location. Defaults to \emptyset
pscale	t prior scale. Defaults to 1/sqrt(2)
pdf	t prior degrees of freedom. Defaults to 1 (a Cauchy prior)
type	Type of t -test. Can be "two.sample" (default), "one.sample", or "paired"
alternative	Direction of the test. Can be either "two.sided" (default), "less", or "greater". The latter two truncate the analysis prior to negative and positive effects, respectively. If set to "less" or "greater", the power is only computed based on data with effect estimates in the direction of the alternative
dpm	Mean of the normal design prior assigned to the standardized mean difference. Defaults to the analysis prior location

print.power.bftest 19

dpsd Standard deviation of the normal design prior assigned to the standardized mean

difference. Set to 0 to obtain a point prior at the design prior mean. Defaults to

the analysis prior scale

nrange Sample size search range over which numerical search is performed (only taken

into account when n is NULL). Defaults to c(2, 10⁴)

Details

This function provides a similar interface as stats::power.t.test. For some users, the low-level functions ntbf01 (to directly compute the sample size for a fixed power) and ptbf01 (to directly compute the power for a fixed sample size) may also be useful.

Value

Object of class "power.bftest", a list of the arguments (including the computed one) augmented with method and note elements

Author(s)

Samuel Pawel

See Also

```
plot.power.bftest, ptbf01, ntbf01, tbf01
```

Examples

```
## determine power
powertbf01(n = 146, k = 1/6, dpm = 0.5, dps = 0, alternative = "greater")
## determine sample size
powertbf01(power = 0.95, k = 1/6, dpm = 0.5, dps = 0, alternative = "greater")
```

print.power.bftest

Print method for class "power.bftest"

Description

Print method for class "power.bftest"

```
## S3 method for class 'power.bftest'
print(x, digits = getOption("digits"), ...)
```

20 ptbf01

Arguments

```
x Object of class "power.bftest"digits Number of digits for formatting of numbers... Other arguments (for consistency with the generic)
```

Value

Prints text summary in the console and invisibly returns the "power.bftest" object

Note

Function adapted from stats:::print.power.htest written by Peter Dalgaard

Author(s)

Samuel Pawel

See Also

powerbf01

Examples

```
powerbf01(power = 0.95, pm = 0, psd = 1, dpm = 0.5, dpsd = 0)
powerbf01(power = 0.95, pm = 0, psd = 1, dpm = 0.5, dpsd = 0, type = "one.sample")
powerbf01(power = 0.95, pm = 0, psd = 1, dpm = 0.5, dpsd = 0, type = "paired")
powerbf01(power = 0.95, pm = 1, psd = 0, dpm = 0.8, dpsd = 0, type = "paired")
```

ptbf01

Cumulative distribution function of the t-test Bayes factor

Description

This function computes the probability of obtaining a t-test Bayes factor (tbf01) more extreme than a threshold k with a specified sample size.

```
ptbf01(
    k,
    n,
    n1 = n,
    n2 = n,
    null = 0,
    plocation = 0,
    pscale = 1/sqrt(2),
```

ptbf01 21

```
pdf = 1,
  dpm = plocation,
  dpsd = pscale,
  type = c("two.sample", "one.sample", "paired"),
  alternative = c("two.sided", "less", "greater"),
  lower.tail = TRUE,
  drange = "adaptive",
  ...
)
```

Arguments

k	Bayes factor threshold
n	Sample size (per group)
n1	Sample size in group 1 (only required for two-sample t -test with unequal group sizes)
n2	Sample size in group 2 (only required for two-sample t -test with unequal group sizes)
null	Standardized mean difference under the point null hypothesis. Defaults to 0
plocation	t prior location. Defaults to 0
pscale	t prior scale. Defaults to 1/sqrt(2)
pdf	t prior degrees of freedom. Defaults to 1 (a Cauchy prior)
dpm	Mean of the normal design prior assigned to the standardized mean difference. Defaults to the analysis prior location
dpsd	Standard deviation of the normal design prior assigned to the standardized mean difference. Set to \emptyset to obtain a point prior at the design prior mean. Defaults to the analysis prior scale
type	Type of t -test. Can be "two.sample" (default), "one.sample", or "paired"
alternative	Direction of the test. Can be either "two.sided" (default), "less", or "greater" The latter two truncate the analysis prior to negative and positive effects, respectively. If set to "less" or "greater", the power is only computed based on data with effect estimates in the direction of the alternative
lower.tail	Logical indicating whether $Pr(BF \le k)$ (TRUE) or $Pr(BF > k)$ (FALSE) should be computed. Defaults to TRUE
drange	Standardized mean difference search range over which the critical values are searched for. Can be either set to a numerical range or to "adaptive" (default) which determines the range in an adaptive way from the other input parameters
•••	Other arguments passed to stats::uniroot

Value

The probability that the Bayes factor is less or greater (depending on the specified lower. tail) than the specified threshold k

22 tbf01

Author(s)

Samuel Pawel

See Also

```
tbf01, ntbf01, powertbf01
```

Examples

tbf01

t-test Bayes factor

Description

This function computes the Bayes factor that forms the basis of the informed Bayesian t-test from Gronau et al. (2020). The Bayes factor quantifies the evidence that the data provide for the null hypothesis that the standardized mean difference (SMD) is zero against the alternative that the SMD is non-zero. A location-scale t-distribution is assumed for the SMD under the alternative hypothesis. The Jeffreys-Zellner-Siow (JZS) Bayes factor (Rouder et al., 2009) is obtained as a special case by setting the location of the prior to zero and the prior degrees of freedom to one, which is the default.

The data are summarized by t-statistics and sample sizes. The following types of t-statistics are accepted:

- Two-sample *t*-test where the SMD represents the standardized mean difference between two group means (assuming equal variances in both groups)
- ullet One-sample t-test where the SMD represents the standardized mean difference to the null value
- Paired t-test where the SMD represents the standardized mean change score

tbf01 23

Usage

```
tbf01(
    t,
    n,
    n1 = n,
    n2 = n,
    plocation = 0,
    pscale = 1/sqrt(2),
    pdf = 1,
    type = c("two.sample", "one.sample", "paired"),
    alternative = c("two.sided", "less", "greater"),
    log = FALSE,
    ...
)
```

Arguments

t	t-statistic
n	Sample size (per group)
n1	Sample size in group 1 (only required for two-sample t -test with unequal group sizes)
n2	Sample size in group 2 (only required for two-sample t -test with unequal group sizes)
plocation	t prior location. Defaults to \emptyset
pscale	t prior scale. Defaults to 1/sqrt(2)
pdf	t prior degrees of freedom. Defaults to 1 (a Cauchy prior)
type	Type of t -test. Can be "two.sample" (default), "one.sample", or "paired"
alternative	Direction of the test. Can be either "two.sided" (default), "less", or "greater". The latter two truncate the analysis prior to negative and positive effects, respectively.
log	Logical indicating whether the natural logarithm of the Bayes factor should be returned. Defaults to FALSE
	Additional arguments passed to stats::integrate

Details

The Bayes factor is implemented as in equation (5) in Gronau et al. (2020), and using suitable truncation in case of one-sided alternatives. Integration is performed numerically with stats::integrate.

Value

Bayes factor in favor of the null hypothesis over the alternative (BF > 1 indicates evidence for the null hypothesis, whereas BF < 1 indicates evidence for the alternative)

Author(s)

Samuel Pawel

24 tbf01

References

Rouder, J. N., Speckman, P. L., Sun, D., Morey, R. D., Iverson, G. (2009). Bayesian *t* tests for accepting and rejecting the null hypothesis. Psychonomic Bulletin & Review, 16(2):225-237. doi:10.3758/PBR.16.2.225

Gronau, Q. F., Ly., A., Wagenmakers, E.J. (2020). Informed Bayesian t-Tests. The American Statistician, 74(2):137-143. doi:10.1080/00031305.2018.1562983

See Also

```
powertbf01, ptbf01, ntbf01
```

Index

```
bf01, 2, 4, 5, 10, 11, 16
binbf01, 3
nbf01, 4, 7, 11, 15, 16
nmbf01, 6, 7, 8, 13, 14, 17
nnmbf01, 7, 7, 14, 17
ntbf01, 9, 19, 22, 24
pbf01, 5, 10, 15, 16
plot.power.bftest, 12, 16, 17, 19
pnmbf01, 7, 8, 13, 17
powerbf01, 5, 11, 13, 14, 20
powernmbf01, 7, 8, 13, 14, 16
powertbf01, 10, 13, 18, 22, 24
print.power.bftest, 19
ptbf01, 10, 19, 20, 24
tbf01, 9, 10, 19, 20, 22, 22
```