

Documentation

Automated Document Generator - Setup Guide

Prerequisites

Before starting, ensure you have the following installed on your system:

- **Node.js** (v16 or higher) - [Download Node.js](#)
 - **Python** (v3.9 or higher) - [Download Python](#)
 - **PostgreSQL** (v13 or higher) - [Download PostgreSQL](#)
 - **Git** - [Download Git](#)
-

Step 1: Clone the Repository

bash

```
git clone <repository-url>
cd Automated-Document-Generator
```

Step 2: Frontend Setup

2.1 Navigate to Frontend Directory

bash

```
cd frontend
cd react
```

2.2 Install Dependencies

bash

```
npm install
```

2.3 Check if Configuration exists for Frontend Environment Variables

Open the `.env` file in the `frontend/react` directory:

env

```
VITE_API_BASE_URL=http://127.0.0.1:8000
```

2.4 Start Frontend Development Server

bash

```
npm run dev
```

The frontend will be available at: <http://localhost:5173>

Note: Keep this terminal window open. The frontend will auto-reload when you make changes.

Step 3: Database Setup (PostgreSQL)

3.1 Install PostgreSQL and pgAdmin

- Download and install PostgreSQL from [official website](#)
- During installation, remember the **postgres** user password you set
- pgAdmin comes bundled with PostgreSQL installation

3.2 Create Database using pgAdmin

1. Open **pgAdmin** from Start Menu
2. Enter your postgres password when prompted
3. In the left sidebar, expand **Servers** → **PostgreSQL**
4. Right-click on **Databases** → **Create** → **Database**
5. Enter database name: `olg_2026` (or any name you prefer)
6. Click **Save**

3.3 Note Database Connection Details

Right-click on the PostgreSQL server → **Properties** and note:

- **Host:** Usually `localhost` or `127.0.0.1`
 - **Port:** Usually `5432`
 - **Username:** Usually `postgres`
 - **Database Name:** `olg_2026`
-

Step 4: Backend Setup

4.1 Navigate to Backend Directory

Open a **new terminal** window:

bash

```
cd backend
```

4.2 Create Virtual Environment

Windows:

bash

```
python -m venv venv
```

macOS/Linux:

bash

```
python3 -m venv venv
```

4.3 Activate Virtual Environment

Windows:

bash

```
venv\Scripts\activate
```

macOS/Linux:

bash

```
source venv/bin/activate
```

You should see `(venv)` appear in your terminal prompt.

4.4 Install Python Dependencies

bash

```
pip install -r requirements.txt
```

4.5 Configure Backend Environment Variables

Create a `.env` file in the `backend` directory with your database details:

`env`

```
DB_HOST=localhost
DB_PORT=5432
DB_USERNAME=postgres
DB_PASSWORD=your_postgres_password
DB_NAME=olg_2026
JWT_SECRET_KEY=bwb34ewr3b4jhd87
JWT_ALGORITHM=HS256
ACCESS_TOKEN_EXPIRE_MINUTES=15
REFRESH_TOKEN_EXPIRE_DAYS=7
```

Email Configuration (Optional - For Password Reset)

```
SMTP_SERVER=smtp.gmail.com
SMTP_PORT=587
SMTP_USERNAME=your-email@gmail.com
SMTP_PASSWORD=your-app-password
FROM_EMAIL=your-email@gmail.com
FRONTEND_URL=http://localhost:5173
```

Important: Replace `your_postgres_password` with the actual password you set during PostgreSQL installation.

4.6 Fix Potential bcrypt/passlib Error

If you encounter an error like: *"password exceeds maximum bcrypt password length of 72 bytes"*, run:

`bash`

```
pip uninstall bcrypt -y
pip uninstall passlib -y

pip install bcrypt==3.2.2
pip install passlib==1.7.4
```

4.7 Start Backend Server

`bash`

```
uvicorn main:app --reload
```

The backend will be available at: <http://127.0.0.1:8000>

Note: Keep this terminal window open. The backend will auto-reload when you make changes.

4.8 Verify Tables are Created

When the backend starts, it automatically creates all required database tables:

- `users`
- `refresh_tokens`
- `offer_letters`
- `password_reset_tokens`

Step 5: Initialize Database with User Data

5.1 Open pgAdmin Query Tool

1. Open **pgAdmin**
2. Navigate to your database (`olg_2026`)
3. Click on **Tools** → **Query Tool**

5.2 Run User Insertion Queries

Copy and execute the following SQL queries:

sql

```
-- Insert initial users

INSERT INTO users (username, hashed_password, role, is_active)
VALUES
('jagadeesh',
'$2b$12$0TFNDNxIU90av06Rp/3Dt.a.Cm/f7CsA0dFrSPwHwa58VI7HbVbbe', 'user',
true),
('sandeep', '$2b$12$5rvuyN/wY0eUSzHVv4a6m0saG6r/rvET1vtai6tK7wjKVFzrsrH6W',
'user', true),
('nidhi', '$2b$12$EoHFqZJIMnAWbeJIVITA/OfawYWn8Klaw3nxTZTo1HfiwQEgB5cNS',
'user', true),
('anusha', '$2b$12$hNZ9/j9yeSoLOgvX92M0teTcxbpyo2V2MHnm.thkKPHtQZ.4Fuiau',
'user', true),
('jyothi', '$2b$12$xtrxdKxGuup8qRX9zCThRumXbDrMDEpZrjRUH/0Ks3TI1vgJM6K20',
'user', true),
('shwetha', '$2b$12$Dl5o6b/BEprjqzgU4lMc60mUTKbEt.KThtAEU4Q1TVqN6EjCHo.ha',
'user', true);
```

```

-- Add email column

ALTER TABLE users
ADD COLUMN IF NOT EXISTS email VARCHAR(200);

-- Update email addresses for existing users

UPDATE users SET email = 'jagadeeshdonthi@mirafra.com' WHERE username =
'jagadeesh';
UPDATE users SET email = 'sandeepvaineni@mirafra.com' WHERE username =
'sandeep';
UPDATE users SET email = 'nidhikumari@mirafra.com' WHERE username = 'nidhi';
UPDATE users SET email = 'anushasuri@mirafra.com' WHERE username = 'anusha';
UPDATE users SET email = 'jyothikrishnappa@mirafra.com' WHERE username =
'jyothi';
UPDATE users SET email = 'Shwetharanjanna@mirafra.com' WHERE username =
'shwetha';

-- Add unique constraint and index on email

ALTER TABLE users ADD CONSTRAINT users_email_unique UNIQUE (email);
CREATE INDEX idx_users_email ON users(email);

```

Step 6: Access the Application

6.1 Verify Both Servers are Running

Service	URL	Status
Frontend	http://localhost:5173	✓ Running
Backend	http://127.0.0.1:8000	✓ Running

6.2 Login to Application

1. Open browser and navigate to: <http://localhost:5173>
2. Enter login credentials:

Username	Password
jagadeesh	Mirafra@2026
sandeep	Mirafra@2026
nidhi	Mirafra@2026
anusha	Mirafra@2026

Username	Password
jyothi	Mirafra@2026
shwetha	Mirafra@2026

Troubleshooting

Frontend Issues

Issue	Solution
npm install fails	Delete <code>node_modules</code> and <code>package-lock.json</code> , then run <code>npm install</code> again
Port 5173 already in use	Change port: <code>npm run dev -- --port 5174</code>
Cannot connect to backend	Check if backend is running and <code>.env</code> has correct <code>VITE_API_BASE_URL</code>

Backend Issues

Issue	Solution
Virtual environment not activating	Use full path: <code>C:\path\to\project\backend\venv\Scripts\activate</code>
Module not found errors	Run <code>pip install -r requirements.txt</code> again
Database connection refused	Check PostgreSQL service is running in Services app
bcrypt/passlib error	Follow Step 4.6 to reinstall specific versions
Port 8000 already in use	Change port: <code>uvicorn main:app --reload --port 8001</code>

Database Issues

Issue	Solution
Cannot connect to PostgreSQL	Check Windows Services → PostgreSQL is running
Authentication failed	Verify username/password in <code>.env</code> matches PostgreSQL

Issue	Solution
Tables not created	Restart backend after ensuring database connection works

Project Structure

text

```
Automated-Document-Generator/
├── frontend/
│   ├── react/
│   │   ├── src/
│   │   ├── .env
│   │   ├── package.json
│   │   └── index.html
│   └── backend/
│       ├── config/
│       ├── models/
│       ├── routers/
│       ├── schemas/
│       ├── services/
│       ├── utils/
│       ├── .env
│       ├── main.py
│       └── requirements.txt
└── README.md
```

Stopping the Application

1. **Stop Frontend:** Press `Ctrl + C` in the frontend terminal
2. **Stop Backend:** Press `Ctrl + C` in the backend terminal
3. **Deactivate Virtual Environment:** Type `deactivate` and press Enter

Quick Reference Commands

Frontend Commands

bash


```
cd frontend/react  
npm install  
npm run dev
```

Backend Commands (Windows)

bash

```
cd backend  
python -m venv venv  
venv\Scripts\activate  
pip install -r requirements.txt  
uvicorn main:app --reload
```

Backend Commands (macOS/Linux)

bash

```
cd backend  
python3 -m venv venv  
source venv/bin/activate  
pip install -r requirements.txt  
uvicorn main:app --reload
```