# **VELIS EVO**





Velis Evo is the perfect blend of comfort and design. Revolutionary in electric storage water heating, the Velis Evo is shower ready in as little as 50 minutes.

- / Twin tank design providing 16% more hot water
- / Ultra slim only 27cm deep
- / "Eco Evo" function
- / Best in class ErP rating
- / Anti-legionella and ABS safety system
- / Shower ready alerts on screen
- / Fast re-heat times, shower ready in 50 minutes
- / Premium Italian design
- / Available in 45 and 80 litre models
- / Must be installed with supplied unvented kit

**ENERGY RATING** 






























TITANIUM PLUS



#### **VELIS EVO 45**

**B** = 405mm **A** = 776mm

#### **VELIS EVO 80**

**A** = 1251mm **B** = 880mm

#### LEGEND


**E** Cold water inlet G 1/2"

Hot water outlet G 1/2"

| TECHNICAL DATA                              |         | VELIS EVO   |             |
|---|---------|-------------|-------------|
| Model                                       |         | 45          | 80          |
| Installation                                |         | Vertical    | Vertical    |
| Thermostat                                  |         | Electronic  | Electronic  |
| Power                                       | kW      | 1.5/1.5     | 1.5/1.5     |
| Body Colour                                 |         | Polar White | Polar White |
| Warranty                                    | years   | 5           | 5           |
| Voltage                                     | V       | 220-240     | 220-240     |
| Max Working Temperature                     | °C      | 65          | 65          |
| Heat-Up Time (ΔT 45°C)                      | mins    | 1h          | 1h 52m      |
| Standing Losses At 65°C                     | kWh/24h | 0.96        | 1.32        |
| V40   | I       | 77          | 115         |
| IP Protection                               |         | IPX4        | IPX4        |
| ErP Class                                   |         | В           | В           |
| ErP Tapping Profile                         |         | М           | М           |
| Weight When Empty                           | kg      | 21          | 32          |
| Weight When Full                            | kg      | 66          | 112         |
| Qelec                                       | kWh     | 6,79        | 7,125       |
| Qelec, Week, Smart                          | kWh     | 25,467      | 27,141      |
| Qelec, Week                                 | kWh     | 28,758      | 32,041      |
| L wa  | dB      | 15          | 15          |
| $\eta_{\text{wh}}$                          |         | 39.1%       | 39.0%       |
| Maximum Inlet Pressure (Rated Pressure)     | bar     | 12          | 12          |
| Maximum Design Pressure                     | bar     | 6           | 6           |
| Set Operating Pressure Expansion Valve      | bar     | 6           | 6           |
| Pre-charge Pressure Of The Expansion Vessel | bar     | 3.5         | 3.5         |
| Frequency (Hz)                              |         | 50/60       | 50/60       |
| Set Opening T&P Relief Valve                | bar     | 7           | 7           |
| Capacity                                    | I       | 45          | 80          |
| Product Codes (including unvented kits)     |         | 3626305     | 3626306     |

### **TWIN TANK TECHNOLOGY**

Get up to 16% more hot water with all models in the Velis Evo range, which boasts an innovative, high quality titanium enamelled twin tank structure for added durability. Reduced **stratification** with the unique twin tank technology, providing extra hot water and a hot shower in just 50 minutes.





## **ECO EVO - SMART FUNCTION**

The innovative **ECO EVO** function memorises user habits to deliver hot water while saving up to 14% on energy bills. The product operates in compliance with top standards on energy efficiency within the electric water heating category.

**UP TO 14% ENERGY SAVINGS**