Rajalakshmi Engineering College

Name: Sam Devaraja J
Email: 240701463@rajalakshmi.edu.in
Roll no: 2116240701463
Phone: 7395954829
Branch: REC
Department: I CSE FE
Batch: 2028
Degree: B.E - CSE

NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue.Delete an element from the queue.Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

Input Format

Each line contains an integer representing the chosen option from 1 to 3.

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

Output Format

For option 1 (insertion):-

1. The program outputs: "<data> is inserted in the queue." if the data is successfully inserted.
2. "Queue is full." if the queue is already full and cannot accept more elements.

For option 2 (deletion):-

1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 10

3
5
Output: 10 is inserted in the queue.
Elements in the queue are: 10
Invalid option.

Answer

```c
#include <stdio.h>
#include <stdlib.h>

#define max 5

int queue[max];
int front = -1, rear = -1;

// You are using GCC
int isFull(){
    return rear==max-1;
}
int isempty(){
    return front==-1;
}
int insertq(int *data)
{
    //Type your code here
    if(isFull()){
        return 0;
    }
    else{
        queue[++rear]=*data;
        if(isempty()){
            front=0;
        }
    }
    return 1;
}

int delq()
{
    //Type your code here
    if(isempty()){
        printf("Queue is empty.\n");
```

```c
        return 0;
    } else{
        printf("Deleted number is: %d\n",queue[front]);
        if(front==rear){
            front=rear=-1;
        }else{
            front+=1;
        }
    }
    return 1;
}

void display()
{
//Type your code here
    if(isempty()){
        printf("Queue is empty.\n");
    }else{
        printf("Elements in the queue are: ");
        for(int i=front;i<=rear;i++){
            printf("%d ",queue[i]);
        }
        printf("\n");
    }
}
int main()
{
    int data, reply, option;
    while (1)
    {
        if (scanf("%d", &option) != 1)
            break;
        switch (option)
        {
            case 1:
                if (scanf("%d", &data) != 1)
                    break;
                reply = insertq(&data);
                if (reply == 0)
                    printf("Queue is full.\n");
                else
                    printf("%d is inserted in the queue.\n", data);
```

```c
            break;
        case 2:
            delq();  //    Called without arguments
            break;
        case 3:
            display();
            break;
        default:
            printf("Invalid option.\n");
            break;
        }
    }
    return 0;
}
```

Status : Correct   ***Marks : 10/10***