

```

Driver.cpp
//C++ Lexical Analyzer
//Sam Dressler
//CSCI 465
//9/26/2020
//This program takes in an input file and generates a list of lexeme-spelling pairs.
//The program takes the loads the file, generate symbols, and then classifies them into
// their appropriate lexemes.
//The output is generated into "output_lex.txt"
#include "lexical_analyzer.h"
#include "intermediate_code_generator.h"
#include "driver.h"
//Main Function to drive the modules.
int main(int argc, char * argv []){
    //Check to see if the user input a file
    if(argc != 2){
        cout << "Error: Enter the name of the pascal file to parse" << endl;
        exit(0);
    }
    //get the file name from user
    ifstream file(argv[1]);
    //Verify the file is opened.
    //If the file can not be opened, tell the user.
    if(!file.is_open()){
        cout << "Error file: "<<" "<<argv[1]<<" "<<" could not be opened"<<endl;
        exit(0);
    }
    //read from the file all of the characters and return to main
    char * file_as_chars = load_file(file);
    //Print raw input file
    cout << "-----" << endl;
    cout << "      Contents of: "<<" "<<argv[1]<<" "<<endl;
    cout << "-----" << endl;
    cout << file_as_chars << endl;
    cout << "-----" << endl;
    vector<symbol> lex_symbol_table = vector<symbol>();
    vector<icg_symbol> icg_symbol_table = vector<icg_symbol>();
    vector<string> symbols = vector<string>();
    symbols = generate_symbols(file_as_chars);
    //for(vector<string>::iterator it = symbols.begin(); it < symbols.end(); ++it){
    //    string temp = *it;
    //    cout << "SYM : " << temp << endl;
    //}
    lex_symbol_table = classify_symbols(symbols, lex_symbol_table);
    FILE * output_lex = NULL;
    output_lex = fopen("output_lex.txt", "w");

```

```

        for(vector<symbol>::iterator it = lex_symbol_table.begin(); it != lex_symbol_table.end(); +
+it)
        {
            symbol temp = *it;
            icg_symbol s;
            s.token_type = temp.token_type;
            s.value = temp.value;
            icg_symbol_table.push_back(s);
            const char * token_t = temp.token_type.c_str();
            const char * token = temp.value.c_str();
            //cout << left << setw(12) << temp.token_type << " --> " << temp.value << endl;
            fprintf(output_lex,"%s %s\n",token_t, token);

        }
        cout << "-----" << endl;
        cout << "          Output file for lex created" << endl;
        cout << "-----" << endl;
        /*
           beginning of code for version 2
        */
        cout << "-----" << endl;
        cout << "          Beginning Intermediate Code Generation " << endl;
        cout << "-----" << endl;

        generate_three_address_code(icg_symbol_table);
        cout << "-----" << endl;
        cout << "Output file for intermediate code generation created" << endl;
        cout << "-----" << endl;
        cout << "          Symbol table: " << endl;
        cout << "-----" << endl;
        print_sym_table();

        fclose(output_lex);

        return 0;
    }

```

Driver.h

```

#include <iostream>
#include <fstream>
#include <string>
#include <string.h>

```

```
#include <stdio.h>
#include <vector>
#include <regex>
#include <iomanip>
```

```
using namespace std;
```