

Product Name: HYDRORENE AW 4

Type of Polymer:	Low free monomer solventless hydro-dispersible aliphatic hardener based on HDI.	
Range of use:	HYDRORENE AW 4 is recommended as a hardener for two component water-based polyurethane systems.	
Specifications:	HYDRORENE AW 4 % of NCO % of free monomer Viscosity (23°C mPa*s)	20.0 – 21.0 ≤ 0.1 1600 - 2400
Other data:	HYDRORENE AW 4 % NV Type of isocyanate Equivalent weight	100 HDI 205
Properties and application:	HYDRORENE AW 4 can be easily emulsified in the aqueous phase, thanks to its low viscosity, also without any further dilution. HYDRORENE AW 4, due to his high NCO %, is recommended for systems that need high chemical/physical resistance, excellent external durability and good mechanical properties. HYDRORENE AW 4 can be used to formulate hardener for 2K paints for different substrates like wood, metal, plastic.	
Storage and warranty:	In sealed drums we guarantee a storage life of 12 months, provided the product is stored under dry and cool condition. Once opened the packaging, the product should be used in short time, because it is sensitive to moisture that can cause his curing of inside the drum.	

The technical information provided in this sheet or given in oral or written form is general information designed to assist customers in determining the suitability of our Products for their applications. Our Products are intended for sale to professional users. The technical and safety information contained herein are made without guarantee and are only suggestions. Our customers must test our Products to their application and intended use to determine if our Products meet their requirements. There is no implied warranty of merchantability or fitness for a particular purpose of the Products described herein. In no event shall Sun Chemical be liable for damages of any nature arising out of the use or reliance upon this information. Modifications of the product for reasons of improvement might be made without further notice.

