

# User accounts in UNIX

ComS 252 — Iowa State University

Andrew Miner

# Motivation

This lecture gives an **in depth** look at UNIX-style user accounts

- ▶ Applies to Linux and most variants of UNIX
- ▶ Mac OS is a little different
  - ▶ E.g., different set of utilities
- ▶ But why **in depth**?

# Motivation

This lecture gives an **in depth** look at UNIX-style user accounts

- ▶ Applies to Linux and most variants of UNIX
- ▶ Mac OS is a little different
  - ▶ E.g., different set of utilities
- ▶ But why **in depth**?
  1. You will need it for homework

# Motivation

This lecture gives an **in depth** look at UNIX-style user accounts

- ▶ Applies to Linux and most variants of UNIX
- ▶ Mac OS is a little different
  - ▶ E.g., different set of utilities
- ▶ But why **in depth**?
  1. You will need it for homework
  2. You should know it anyway
    - ▶ Explains some potentially confusing behaviors
    - ▶ Helps keep your system secure

# Motivation

This lecture gives an **in depth** look at UNIX-style user accounts

- ▶ Applies to Linux and most variants of UNIX
- ▶ Mac OS is a little different
  - ▶ E.g., different set of utilities
- ▶ But why **in depth**?
  1. You will need it for homework
  2. You should know it anyway
    - ▶ Explains some potentially confusing behaviors
    - ▶ Helps keep your system secure
  3. I have lied to you (as usual)
    - ▶ “Simplified things” is probably a nicer way to put it
    - ▶ Finally . . . the shocking truth

# Managing user accounts and groups

## 1. GUI-based tools

- ▶ E.g., `system-config-users`
- ▶ Are for *wimps*
- ▶ I assume you can figure these out

## 2. Command-line tools

- ▶ As the demi-Gods intended
- ▶ We will discuss these next. . .

## 3. By hand

- ▶ Effective and safe **if done correctly**

# Adding users

## useradd

- ▶ Create a new user account
- ▶ Many switches, e.g. to specify
  - ▶ Location of user's home directory
  - ▶ User's **primary** (i.e., “default”) group
  - ▶ Other groups the user belongs to
  - ▶ Default login shell
- ▶ Check your `man` pages for details

Pro tips for lazy system administrators:

- ▶ Lots of defaults may be specified in `/etc/login.defs`
- ▶ Can use a “skeleton” directory
  - ▶ User's home directory is copied from the skeleton

# Adding users

## useradd

- ▶ Create a new user account
- ▶ Many switches, e.g. to specify
  - ▶ Location of user's home directory
  - ▶ User's **primary** (i.e., "default") group
  - ▶ Other groups the user belongs to
  - ▶ Default login shell
- ▶ Check your `man` pages for details
- ▶ **Only root may do this**

Pro tips for lazy system administrators:

- ▶ Lots of defaults may be specified in `/etc/login.defs`
- ▶ Can use a "skeleton" directory
  - ▶ User's home directory is copied from the skeleton



# Changing a user's account

## usermod

- ▶ Change “anything” about a user's account
  - ▶ Even the username
- ▶ Switches for each thing to change
- ▶ Switches typically match those found in `useradd` (with some extras)
- ▶ Check your `man` pages for details

# Changing a user's account

## usermod

- ▶ Change “anything” about a user's account
  - ▶ Even the username
- ▶ Switches for each thing to change
- ▶ Switches typically match those found in `useradd` (with some extras)
- ▶ Check your `man` pages for details
- ▶ Only root may do this

# Removing users

## userdel

- ▶ Remove a user account
- r option:
  - ▶ Remove user's home directory and files
  - ▶ Other files must be tracked down "by hand"
- ▶ Check your `man` pages for details

Pro tip for lazy system administrators:

- ▶ Can specify an executable, in `/etc/login.defs`
- ▶ Will run with username as argument, whenever `userdel` is run
- ▶ Shell scripts are commonly used here
  - ▶ E.g., one that removes **all** files owned by that user  
(`find` can do this)

# Removing users

## userdel

- ▶ Remove a user account
- r option:
  - ▶ Remove user's home directory and files
  - ▶ Other files must be tracked down "by hand"
- ▶ Check your `man` pages for details
- ▶ **Only root may do this**

Pro tip for lazy system administrators:

- ▶ Can specify an executable, in `/etc/login.defs`
- ▶ Will run with username as argument, whenever `userdel` is run
- ▶ Shell scripts are commonly used here
  - ▶ E.g., one that removes **all** files owned by that user (find can do this)

# Groups

- ▶ There are **group** equivalents of the previous 3 utilities
- ▶ **groupadd**: create a new group
- ▶ **groupmod**: modify an existing group
- ▶ **groupdel**: remove an existing group
  - ▶ You cannot remove a user's primary group
- ▶ These tend to have only a few switches
- ▶ Check your `man` pages for details

# Groups

- ▶ There are **group** equivalents of the previous 3 utilities
- ▶ **groupadd**: create a new group
- ▶ **groupmod**: modify an existing group
- ▶ **groupdel**: remove an existing group
  - ▶ You cannot remove a user's primary group
- ▶ These tend to have only a few switches
- ▶ Check your `man` pages for details
- ▶ **Only root may run these**

# Changing your account — yourself

What can ordinary users do?

# Changing your account — yourself

What can ordinary users do?

`chsh`

- ▶ Change your login shell
- ▶ Typically: must select one listed in `/etc/shells`



# Changing your account — yourself

What can ordinary users do?

## chsh

- ▶ Change your login shell
- ▶ Typically: must select one listed in `/etc/shells`

## passwd

- ▶ Change your password
- ▶ You will be prompted for your current password
- ▶ You type a new password
  - ▶ Twice
- ▶ These days: checks the strength of the password

# Running passwd as root

## passwd

- ▶ Change the root password
- ▶ Works the same as for ordinary users
  - ▶ Prompt for current password
  - ▶ Type the new password, twice

# Running passwd as root

## passwd

- ▶ Change the root password
- ▶ Works the same as for ordinary users
  - ▶ Prompt for current password
  - ▶ Type the new password, twice

## passwd user

- ▶ Change the password for user
- ▶ **DOES NOT** prompt for current password
- ▶ Type the new password, twice

# Forgotten passwords

Normal user (in this case, “luser”)

1. Find a system administrator
2. She/he will run `passwd username` for you

# Forgotten passwords

Normal user (in this case, “luser”)

1. Find a system administrator
2. She/he will run `passwd username` for you

root

# Forgotten passwords

## Normal user (in this case, “luser”)

1. Find a system administrator
2. She/he will run `passwd username` for you

## root

1. Boot in **single-user mode** (runlevel 1)  
OR using “`rescue.target`” on systemd
2. Run `passwd`
3. Reboot

# Forgotten passwords

Normal user (in this case, “luser”)

1. Find a system administrator
2. She/he will run `passwd username` for you

root

1. Boot in **single-user mode** (runlevel 1)  
OR using “`rescue.target`” on systemd
2. Run `passwd`
3. Reboot

How can I boot in single-user mode without root access?

# Forgotten passwords

## Normal user (in this case, “luser”)

1. Find a system administrator
2. She/he will run `passwd username` for you

## root

1. Boot in **single-user mode** (runlevel 1)  
OR using “`rescue.target`” on systemd
2. Run `passwd`
3. Reboot

How can I boot in single-user mode without root access?

- ▶ Can be done with GrUB at boot time, OR
- ▶ Boot from install DVD/CD in **rescue mode**



# Current group

- ▶ When a user creates a new file, what group does it have?

## Current group

- ▶ When a user creates a new file, what group does it have?
  - ▶ Whatever the “current group” is set to
    - ▶ Default upon login: the user’s **primary group**

## Current group

- ▶ When a user creates a new file, what group does it have?
  - ▶ Whatever the “current group” is set to
    - ▶ Default upon login: the user’s **primary group**
- ▶ Can the current group be changed?

# Current group

- ▶ When a user creates a new file, what group does it have?
  - ▶ Whatever the “current group” is set to
    - ▶ Default upon login: the user’s **primary group**
- ▶ Can the current group be changed? **Of course**

## `newgrp [groupname]`

- ▶ Change your current group to the one specified
  - ▶ If none specified — change to the primary group
- ▶ Will start a subshell
  - ▶ Exit this to get back the the previous group
  - ▶ Same idea as `su`
- ▶ What groups can I change to?

# Current group

- ▶ When a user creates a new file, what group does it have?
  - ▶ Whatever the “current group” is set to
    - ▶ Default upon login: the user’s **primary group**
- ▶ Can the current group be changed? **Of course**

## `newgrp [groupname]`

- ▶ Change your current group to the one specified
  - ▶ If none specified — change to the primary group
- ▶ Will start a subshell
  - ▶ Exit this to get back the the previous group
  - ▶ Same idea as `su`
- ▶ What groups can I change to?
  - ▶ Whatever groups I belong to, right?

# Current group

- ▶ When a user creates a new file, what group does it have?
  - ▶ Whatever the “current group” is set to
    - ▶ Default upon login: the user’s **primary group**
- ▶ Can the current group be changed? **Of course**

## `newgrp [groupname]`

- ▶ Change your current group to the one specified
  - ▶ If none specified — change to the primary group
- ▶ Will start a subshell
  - ▶ Exit this to get back the the previous group
  - ▶ Same idea as `su`
- ▶ What groups can I change to?
  - ▶ Whatever groups I belong to, right?
  - ▶ Normally, **yes**, but there is more ...

# Group administration

## gpaswd

- ▶ Administer groups
- ▶ Lots of switches — check your man pages
- ▶ When run as root:
  - ▶ Can add and remove users
  - ▶ Can assign **group administrators**

# Group administration

## gpaswd

- ▶ Administer groups
- ▶ Lots of switches — check your man pages
- ▶ When run as root:
  - ▶ Can add and remove users
  - ▶ Can assign **group administrators**
  - ▶ Can set or remove a **group password**
- ▶ When run as a group administrator:
  - ▶ Can change the group password
  - ▶ Can add and remove users (**I think ...**)
- ▶ Fun fact:
  - ▶ A group administrator does not need to belong to the group



# Group passwords?

## newgrp: the full story

When you try to change groups:

- ▶ If you are a member of the group
  - ▶ You do **not** need to type the group password
- ▶ If you are not a member of the group
  - ▶ If there is a group password
    - ▶ You are prompted for the group password
  - ▶ If there is not a group password: denied

# Group passwords?

## newgrp: the full story

When you try to change groups:

- ▶ If you are a member of the group
  - ▶ You do **not** need to type the group password
- ▶ If you are not a member of the group
  - ▶ If there is a group password
    - ▶ You are prompted for the group password
  - ▶ If there is not a group password: denied

I have seen conflicting documentation on this

# Does anyone use group passwords on a production system?

- ▶ Probably not
  - ▶ If so I would like to know about it

# Does anyone use group passwords on a production system?

- ▶ Probably not
  - ▶ If so I would like to know about it
- ▶ Why not?

# Does anyone use group passwords on a production system?

- ▶ Probably not
  - ▶ If so I would like to know about it
- ▶ Why not?
- ▶ Shared passwords are much less secure
  - ▶ Difficult to enforce “don’t share with everyone”
  - ▶ *Three can keep a secret, if two of them are dead*
    - Benjamin Franklin

# Does anyone use group passwords on a production system?

- ▶ Probably not
  - ▶ If so I would like to know about it
- ▶ Why not?
- ▶ Shared passwords are much less secure
  - ▶ Difficult to enforce “don’t share with everyone”
  - ▶ *Three can keep a secret, if two of them are dead*  
— Benjamin Franklin
- ▶ Logistics
  - ▶ Think about changing a group password

# Does anyone use group passwords on a production system?

- ▶ Probably not
  - ▶ If so I would like to know about it
- ▶ Why not?
- ▶ Shared passwords are much less secure
  - ▶ Difficult to enforce “don’t share with everyone”
  - ▶ *Three can keep a secret, if two of them are dead*
    - Benjamin Franklin
- ▶ Logistics
  - ▶ Think about changing a group password
- ▶ Adding or removing users has the same effect
  - ▶ Give me any scenario that uses group passwords
  - ▶ I will be able to either:
    1. Convince you that this violates security policy; or
    2. Find a way to use `gpaswd` to fix it, without a group password

# What is a user ID?



# What is a user ID?

## User Identifier

- ▶ **Kernel-level** mechanism to identify users
- ▶ Is an **unsigned integer**
  - ▶ Range is at least 0 to 32,767

# What is a user ID?

## User Identifier

- ▶ **Kernel-level** mechanism to identify users
- ▶ Is an **unsigned integer**
  - ▶ Range is at least 0 to 32,767
- ▶ Superuser (root) **always** has user ID 0
  - ▶ Note: root is the **username**
- ▶ Low values are set aside for system use
  - ▶ E.g., 1 through 499 (RHEL) or 999 (Debian)

# What is a user ID?

## User Identifier

- ▶ Kernel-level mechanism to identify users
- ▶ Is an **unsigned integer**
  - ▶ Range is at least 0 to 32,767
- ▶ Superuser (root) **always** has user ID 0
  - ▶ Note: root is the **username**
- ▶ Low values are set aside for system use
  - ▶ E.g., 1 through 499 (RHEL) or 999 (Debian)

## Group Identifier

- ▶ Kernel-level mechanism to identify groups
- ▶ Also an unsigned integer

# How to find my user ID?

## id

- ▶ Usage: `id [option]... [username]`
- ▶ Print user identity for specified user (default: current user)
- ▶ Also prints the current group (or primary group)
- ▶ Check your `man` pages for options

```
prompt$ █
```

# How to find my user ID?

## id

- ▶ Usage: `id [option]... [username]`
- ▶ Print user identity for specified user (default: current user)
- ▶ Also prints the current group (or primary group)
- ▶ Check your `man` pages for options

```
prompt$ id
```

# How to find my user ID?

## id

- ▶ Usage: `id [option]... [username]`
- ▶ Print user identity for specified user (default: current user)
- ▶ Also prints the current group (or primary group)
- ▶ Check your `man` pages for options

```
prompt$ id
uid=1235(alice) gid=152(staff) groups=152(staff),424(hackers)
prompt$ █
```

# How to find my user ID?

## id

- ▶ Usage: `id [option]... [username]`
- ▶ Print user identity for specified user (default: current user)
- ▶ Also prints the current group (or primary group)
- ▶ Check your man pages for options

```
prompt$ id
uid=1235(alice) gid=152(staff) groups=152(staff),424(hackers)
prompt$ newgrp hackers
```

# How to find my user ID?

## id

- ▶ Usage: `id [option]... [username]`
- ▶ Print user identity for specified user (default: current user)
- ▶ Also prints the current group (or primary group)
- ▶ Check your man pages for options

```
prompt$ id
uid=1235(alice) gid=152(staff) groups=152(staff),424(hackers)
prompt$ newgrp hackers
prompt$ █
```



# How to find my user ID?

## id

- ▶ Usage: `id [option]... [username]`
- ▶ Print user identity for specified user (default: current user)
- ▶ Also prints the current group (or primary group)
- ▶ Check your man pages for options

```
prompt$ id
uid=1235(alice) gid=152(staff) groups=152(staff),424(hackers)
prompt$ newgrp hackers
prompt$ id
```

# How to find my user ID?

## id

- ▶ Usage: `id [option]... [username]`
- ▶ Print user identity for specified user (default: current user)
- ▶ Also prints the current group (or primary group)
- ▶ Check your man pages for options

```
prompt$ id
uid=1235(alice) gid=152(staff) groups=152(staff),424(hackers)
prompt$ newgrp hackers
prompt$ id
uid=1235(alice) gid=424(hackers) groups=152(staff),424(hackers)
prompt$ █
```

# How to find my user ID?

## id

- ▶ Usage: `id [option]... [username]`
- ▶ Print user identity for specified user (default: current user)
- ▶ Also prints the current group (or primary group)
- ▶ Check your man pages for options

```
prompt$ id
uid=1235(alice) gid=152(staff) groups=152(staff),424(hackers)
prompt$ newgrp hackers
prompt$ id
uid=1235(alice) gid=424(hackers) groups=152(staff),424(hackers)
prompt$ id bob
```

# How to find my user ID?

## id

- ▶ Usage: `id [option]... [username]`
- ▶ Print user identity for specified user (default: current user)
- ▶ Also prints the current group (or primary group)
- ▶ Check your man pages for options

```
prompt$ id
uid=1235(alice) gid=152(staff) groups=152(staff),424(hackers)
prompt$ newgrp hackers
prompt$ id
uid=1235(alice) gid=424(hackers) groups=152(staff),424(hackers)
prompt$ id bob
uid=1239(bob) gid=152(staff) groups=152(staff),207(webadmin)
prompt$ █
```

# Why this is important

# Why this is important

- ▶ How does the `ext $n$`  filesystem store the owner and group for each file and directory?

# Why this is important

- ▶ How does the `ext $n$`  filesystem store the owner and group for each file and directory?
  - ▶ The file's owner is stored as the `userid`
  - ▶ The file's group is stored as the `groupid`

# Why this is important

- ▶ How does the `ext $n$`  filesystem store the owner and group for each file and directory?
  - ▶ The file's owner is stored as the `userid`
  - ▶ The file's group is stored as the `groupid`
- ▶ You can see this using the `-n` switch for `ls`



# Why this is important

- ▶ How does the `ext $n$`  filesystem store the owner and group for each file and directory?
  - ▶ The file's owner is stored as the `userid`
  - ▶ The file's group is stored as the `groupid`
- ▶ You can see this using the `-n` switch for `ls`
- ▶ And you need to care about this because...

# Why this is important

- ▶ How does the `ext $n$`  filesystem store the owner and group for each file and directory?
  - ▶ The file's owner is stored as the **userid**
  - ▶ The file's group is stored as the **groupid**
- ▶ You can see this using the `-n` switch for `ls`
- ▶ And you need to care about this because...
- ▶ What happens if you mount a disk on another machine?

# Why this is important

- ▶ How does the `ext $n$`  filesystem store the owner and group for each file and directory?
  - ▶ The file's owner is stored as the **userid**
  - ▶ The file's group is stored as the **groupid**
- ▶ You can see this using the `-n` switch for `ls`
- ▶ And you need to care about this because...
- ▶ What happens if you mount a disk on another machine?
  - ▶ The file owners and groups **may change**
  - ▶ Happens if the `userids` and `groupids` do not “match” on the two machines

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ █
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ █
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy  
prompt$ mkfs -t ext2 /dev/fd0
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ █
```



# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ mkdir /mnt/floppy
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ mkdir /mnt/floppy
prompt$ █
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ █
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ cp -p /tmp/* /mnt/floppy
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ cp -p /tmp/* /mnt/floppy
prompt$ █
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ cp -p /tmp/* /mnt/floppy
prompt$ ls -l /mnt/floppy
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ cp -p /tmp/* /mnt/floppy
prompt$ ls -l /mnt/floppy
-rw----- 1 alice  staff    1024 Dec 25  2010 card.txt
-rw----- 1 bob    bob      8001 Apr 22  23:41 fooB6WGlB
-rw-r--r-- 1 chuck web      3239 Jul  5  13:02 hello.html
drwx----- 2 root   root    12288 Nov  1  12:45 lost+found
prompt$ █
```



# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkfs -t ext2 /dev/fd0
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ cp -p /tmp/* /mnt/floppy
prompt$ ls -l /mnt/floppy
-rw----- 1 alice  staff    1024 Dec 25  2010 card.txt
-rw----- 1 bob    bob      8001 Apr 22 23:41 fooB6WGlB
-rw-r--r-- 1 chuck  web      3239 Jul  5 13:02 hello.html
drwx----- 2 root   root    12288 Nov  1 12:45 lost+found
prompt$ ls -ln /mnt/floppy
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ ls -l /mnt/floppy
-rw----- 1 alice  staff    1024 Dec 25  2010 card.txt
-rw----- 1 bob    bob      8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 chuck  web      3239 Jul  5 13:02 hello.html
drwx----- 2 root   root    12288 Nov  1 12:45 lost+found
prompt$ ls -ln /mnt/floppy
-rw----- 1 1001  401    1024 Dec 25  2010 card.txt
-rw----- 1 1002  513    8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 1003  425    3239 Jul 05 13:02 hello.html
drwx----- 2 0      0     12288 Nov  1 12:45 lost+found
prompt$ █
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
prompt$ ls -l /mnt/floppy
-rw----- 1 alice  staff    1024 Dec 25  2010 card.txt
-rw----- 1 bob    bob      8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 chuck  web      3239 Jul  5 13:02 hello.html
drwx----- 2 root   root    12288 Nov  1 12:45 lost+found
prompt$ ls -ln /mnt/floppy
-rw----- 1 1001  401    1024 Dec 25  2010 card.txt
-rw----- 1 1002  513    8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 1003  425    3239 Jul 05 13:02 hello.html
drwx----- 2 0      0     12288 Nov  1 12:45 lost+found
prompt$ umount /mnt/floppy
```

# Concrete example: part 1

Machine A: copy stuff to a floppy (as root)

```
-rw----- 1 alice  staff    1024 Dec 25  2010 card.txt
-rw----- 1 bob    bob      8001 Apr 22  23:41 fooB6WG1B
-rw-r--r-- 1 chuck  web      3239 Jul  5  13:02 hello.html
drwx----- 2 root   root    12288 Nov  1  12:45 lost+found
prompt$ ls -ln /mnt/floppy
-rw----- 1 1001  401    1024 Dec 25  2010 card.txt
-rw----- 1 1002  513    8001 Apr 22  23:41 fooB6WG1B
-rw-r--r-- 1 1003  425    3239 Jul 05  13:02 hello.html
drwx----- 2 0      0     12288 Nov  1  12:45 lost+found
prompt$ umount /mnt/floppy
prompt$ █
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ █
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ modprobe floppy
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ modprobe floppy
prompt$ █
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkdir /mnt/floppy
```



## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkdir /mnt/floppy
prompt$ █
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ █
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ ls -l /mnt/floppy
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ ls -l /mnt/floppy
-rw----- 1 chuck  users    1024 Dec 25  2010 card.txt
-rw----- 1 dave   513      8001 Apr 22  23:41 fooB6WG1B
-rw-r--r-- 1 frank noobs   3239 Jul  5  13:02 hello.html
drwx----- 2 root   root   12288 Nov  1  12:45 lost+found
prompt$ █
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ modprobe floppy
prompt$ mkdir /mnt/floppy
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ ls -l /mnt/floppy
-rw----- 1 chuck  users    1024 Dec 25  2010 card.txt
-rw----- 1 dave   513      8001 Apr 22  23:41 fooB6WG1B
-rw-r--r-- 1 frank noobs   3239 Jul  5  13:02 hello.html
drwx----- 2 root   root   12288 Nov  1  12:45 lost+found
prompt$ ls -ln /mnt/floppy
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ ls -l /mnt/floppy
-rw----- 1 chuck  users    1024 Dec 25  2010 card.txt
-rw----- 1 dave   513      8001 Apr 22  23:41 fooB6WG1B
-rw-r--r-- 1 frank noobs    3239 Jul  5  13:02 hello.html
drwx----- 2 root   root    12288 Nov  1  12:45 lost+found
prompt$ ls -ln /mnt/floppy
-rw----- 1 1001  401      1024 Dec 25  2010 card.txt
-rw----- 1 1002  513      8001 Apr 22  23:41 fooB6WG1B
-rw-r--r-- 1 1003  425      3239 Jul 05  13:02 hello.html
drwx----- 2 0      0      12288 Nov  1  12:45 lost+found
prompt$ █
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ mount -t ext2 /dev/fd0 /mnt/floppy
prompt$ ls -l /mnt/floppy
-rw----- 1 chuck  users    1024 Dec 25  2010 card.txt
-rw----- 1 dave   513      8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 frank noobs    3239 Jul  5 13:02 hello.html
drwx----- 2 root   root    12288 Nov  1 12:45 lost+found
prompt$ ls -ln /mnt/floppy
-rw----- 1 1001  401      1024 Dec 25  2010 card.txt
-rw----- 1 1002  513      8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 1003  425      3239 Jul 05 13:02 hello.html
drwx----- 2 0      0      12288 Nov  1 12:45 lost+found
prompt$ umount /mnt/floppy
```



## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ ls -l /mnt/floppy
-rw----- 1 chuck  users   1024 Dec 25  2010 card.txt
-rw----- 1 dave   513     8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 frank noobs   3239 Jul  5 13:02 hello.html
drwx----- 2 root   root   12288 Nov  1 12:45 lost+found
prompt$ ls -ln /mnt/floppy
-rw----- 1 1001  401     1024 Dec 25  2010 card.txt
-rw----- 1 1002  513     8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 1003  425     3239 Jul 05 13:02 hello.html
drwx----- 2 0      0     12288 Nov  1 12:45 lost+found
prompt$ umount /mnt/floppy
prompt$ █
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
prompt$ ls -l /mnt/floppy
-rw----- 1 chuck  users   1024 Dec 25  2010 card.txt
-rw----- 1 dave   513     8001 Apr 22  23:41 fooB6WG1B
-rw-r--r-- 1 frank noobs   3239 Jul  5  13:02 hello.html
drwx----- 2 root   root   12288 Nov  1  12:45 lost+found
prompt$ ls -ln /mnt/floppy
-rw----- 1 1001  401     1024 Dec 25  2010 card.txt
-rw----- 1 1002  513     8001 Apr 22  23:41 fooB6WG1B
-rw-r--r-- 1 1003  425     3239 Jul 05  13:02 hello.html
drwx----- 2 0      0     12288 Nov  1  12:45 lost+found
prompt$ umount /mnt/floppy
prompt$ id frank
```

## Concrete example: part 2

Machine B: copy stuff off the floppy (as root)

```
-rw----- 1 dave      513      8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 frank    noobs     3239 Jul  5 13:02 hello.html
drwx----- 2 root     root     12288 Nov  1 12:45 lost+found
prompt$ ls -ln /mnt/floppy
-rw----- 1 1001    401      1024 Dec 25  2010 card.txt
-rw----- 1 1002    513      8001 Apr 22 23:41 fooB6WG1B
-rw-r--r-- 1 1003    425     3239 Jul  5 13:02 hello.html
drwx----- 2 0      0      12288 Nov  1 12:45 lost+found
prompt$ umount /mnt/floppy
prompt$ id frank
uid=1003(frunk) gid=401(users) groups=401(users)
prompt$ █
```

# Changing users and groups “by hand”

- ▶ Done in the usual way:
  - ▶ Find the appropriate file(s)
  - ▶ Change the appropriate “magic text”
    - ▶ But need to do this properly
- ▶ Let’s see where the files are, and how they are formatted

# Wait a minute

- ▶ We will discuss the inner workings of UNIX passwords?

# Wait a minute

- ▶ We will discuss the inner workings of UNIX passwords?
  - ▶ Yes

# Wait a minute

- ▶ We will discuss the inner workings of UNIX passwords?
  - ▶ Yes
- ▶ But ... what about system security and stuff?

# Wait a minute

- ▶ We will discuss the inner workings of UNIX passwords?
  - ▶ Yes
- ▶ But ... what about system security and stuff?
  1. This material is common knowledge already
    - ▶ And not everyone that knows it is “nice”
  2. Relying on “security through obscurity” is generally a bad idea



# Wait a minute

- ▶ We will discuss the inner workings of UNIX passwords?
  - ▶ Yes
- ▶ But ... what about system security and stuff?
  1. This material is common knowledge already
    - ▶ And not everyone that knows it is “nice”
  2. Relying on “security through obscurity” is generally a bad idea
- ▶ But isn't **all** security done by obscuring something?

# Wait a minute

- ▶ We will discuss the inner workings of UNIX passwords?
  - ▶ Yes
- ▶ But ... what about system security and stuff?
  1. This material is common knowledge already
    - ▶ And not everyone that knows it is “nice”
  2. Relying on “security through obscurity” is generally a bad idea
- ▶ But isn't **all** security done by obscuring something?
  - ▶ “Security through obscurity” keeps the inner workings secret
  - ▶ But there are **publicly-known** algorithms that provide security
  - ▶ Compare this to an algorithm that **relies on** being secret
  - ▶ We can discuss this more when we get to “Security”

## /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”

## /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username

## /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here

## /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. UserID

## /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. UserID
  4. Primary groupID

# /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. UserID
  4. Primary groupID
  5. GECOS
    - ▶ Usually, user’s full name



## /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. UserID
  4. Primary groupID
  5. GECOS
    - ▶ Usually, user’s full name
  6. Home directory

## /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. UserID
  4. Primary groupID
  5. GECOS
    - ▶ Usually, user’s full name
  6. Home directory
  7. Default shell

# /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. UserID
  4. Primary groupID
  5. GECOS
    - ▶ Usually, user’s full name
  6. Home directory
  7. Default shell

```
prompt$ █
```

# /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. UserID
  4. Primary groupID
  5. GECOS
    - ▶ Usually, user’s full name
  6. Home directory
  7. Default shell

```
prompt$ tail -n 1 /etc/passwd
```

## /etc/passwd

- ▶ World-readable text file
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. UserID
  4. Primary groupID
  5. GECOS
    - ▶ Usually, user’s full name
  6. Home directory
  7. Default shell

```
prompt$ tail -n 1 /etc/passwd
chuck:x:502:502:Carlos R. Norris:/home/chuck:/bin/bash
prompt$ █
```

## /etc/shadow

- ▶ **NOT** world-readable
  - ▶ Permissions tend to be **000**
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”

## /etc/shadow

- ▶ **NOT** world-readable
  - ▶ Permissions tend to be **000**
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username

## /etc/shadow

- ▶ **NOT** world-readable
  - ▶ Permissions tend to be **000**
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password (“encrypted”)
    - ▶ Or “!!” to indicate no password



## /etc/shadow

- ▶ **NOT** world-readable
  - ▶ Permissions tend to be **000**
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password (“encrypted”)
    - ▶ Or “!!” to indicate no password
  3. Date of last password change
    - ▶ Format is “number of days since Jan 1, 1970”

## /etc/shadow

- ▶ **NOT** world-readable
  - ▶ Permissions tend to be **000**
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password (“encrypted”)
    - ▶ Or “!!” to indicate no password
  3. Date of last password change
    - ▶ Format is “number of days since Jan 1, 1970”
  4. How many days until a password change is allowed

## /etc/shadow

- ▶ **NOT** world-readable
  - ▶ Permissions tend to be **000**
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password (“encrypted”)
    - ▶ Or “!!” to indicate no password
  3. Date of last password change
    - ▶ Format is “number of days since Jan 1, 1970”
  4. How many days until a password change is allowed
  5. How many days until password expires

## /etc/shadow

- ▶ **NOT** world-readable
  - ▶ Permissions tend to be **000**
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password (“encrypted”)
    - ▶ Or “!!” to indicate no password
  3. Date of last password change
    - ▶ Format is “number of days since Jan 1, 1970”
  4. How many days until a password change is allowed
  5. How many days until password expires
  6. Number of days before expiration that warnings are given

## /etc/shadow

- ▶ **NOT** world-readable
  - ▶ Permissions tend to be **000**
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password (“encrypted”)
    - ▶ Or “!!” to indicate no password
  3. Date of last password change
    - ▶ Format is “number of days since Jan 1, 1970”
  4. How many days until a password change is allowed
  5. How many days until password expires
  6. Number of days before expiration that warnings are given
  7. Number of days after expiration that account is disabled

## /etc/shadow

- ▶ **NOT** world-readable
  - ▶ Permissions tend to be **000**
- ▶ One user “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Username
  2. Password (“encrypted”)
    - ▶ Or “!!” to indicate no password
  3. Date of last password change
    - ▶ Format is “number of days since Jan 1, 1970”
  4. How many days until a password change is allowed
  5. How many days until password expires
  6. Number of days before expiration that warnings are given
  7. Number of days after expiration that account is disabled
  8. Date when the account is disabled
    - ▶ Format is “number of days since Jan 1, 1970”

# How is the password encrypted?

# How is the password encrypted?

Using a **cryptographic hash function**



# How is the password encrypted?

Using a **cryptographic hash function**

- ▶ Takes a string as input
  - ▶ In this case, the password plus a “salt” string
  - ▶ “salt” is random text, and not secret
- ▶ Produces a random-looking string as output
  - ▶ “salt” is added to the output string

# How is the password encrypted?

Using a **cryptographic hash function**

- ▶ Takes a string as input
  - ▶ In this case, the password plus a “salt” string
  - ▶ “salt” is random text, and not secret
- ▶ Produces a random-looking string as output
  - ▶ “salt” is added to the output string

## Properties of an ideal cryptographic hash function

1. Easy: compute the output string, for any input string
2. **Infeasible**: find an input string for a given output string
3. **Infeasible**: change input string without changing output string
4. **Infeasible**: find two different input strings with same output

Infeasible: possible, but time required is too long to be useful

# How does password authentication work?

1. User types password
2. System pulls salt and hashed password from `/etc/shadow`
3. Typed password and salt are plugged into hash function
4. If output matches hashed password then
  - ▶ We are “sure” that the passwords match
    - ▶ But could be **extremely** low probability of no match
    - ▶ I.e., we found another input string with the same output
5. Otherwise we **know** the passwords did not match

## /etc/group

- ▶ World-readable text file
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”

## /etc/group

- ▶ World-readable text file
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name

# /etc/group

- ▶ World-readable text file
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here

## /etc/group

- ▶ World-readable text file
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. GroupID

## /etc/group

- ▶ World-readable text file
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. GroupID
  4. Comma separated list of group members (usernames)



# /etc/group

- ▶ World-readable text file
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. GroupID
  4. Comma separated list of group members (usernames)

```
prompt$ █
```

# /etc/group

- ▶ World-readable text file
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. GroupID
  4. Comma separated list of group members (usernames)

```
prompt$ tail -n 1 /etc/group
```

# /etc/group

- ▶ World-readable text file
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password
    - ▶ Ancient systems: password information was here
    - ▶ Modern systems: “x” or “\*” here
  3. GroupID
  4. Comma separated list of group members (usernames)

```
prompt$ tail -n 1 /etc/group
hackers:x:600:alice,bob
prompt$ █
```

## /etc/gshadow

- ▶ Not world-readable text file (usually has permissions 000)
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”

## /etc/gshadow

- ▶ Not world-readable text file (usually has permissions 000)
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name

## /etc/gshadow

- ▶ Not world-readable text file (usually has permissions 000)
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password (encrypted)
    - ▶ Or “!” to indicate no password

## /etc/gshadow

- ▶ Not world-readable text file (usually has permissions 000)
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password (encrypted)
    - ▶ Or “!” to indicate no password
  3. Comma separated list of group administrators (usernames)

## /etc/gshadow

- ▶ Not world-readable text file (usually has permissions 000)
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password (encrypted)
    - ▶ Or “!” to indicate no password
  3. Comma separated list of group administrators (usernames)
  4. Comma separated list of group members (usernames)



# /etc/gshadow

- ▶ Not world-readable text file (usually has permissions 000)
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password (encrypted)
    - ▶ Or “!” to indicate no password
  3. Comma separated list of group administrators (usernames)
  4. Comma separated list of group members (usernames)

```
prompt$ █
```

# /etc/gshadow

- ▶ Not world-readable text file (usually has permissions 000)
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password (encrypted)
    - ▶ Or “!” to indicate no password
  3. Comma separated list of group administrators (usernames)
  4. Comma separated list of group members (usernames)

```
prompt$ tail -n 1 /etc/gshadow
```

# /etc/gshadow

- ▶ Not world-readable text file (usually has permissions 000)
- ▶ One group “record” per line
- ▶ Each record has these fields, separated by “:”
  1. Group name
  2. Password (encrypted)
    - ▶ Or “!” to indicate no password
  3. Comma separated list of group administrators (usernames)
  4. Comma separated list of group members (usernames)

```
prompt$ tail -n 1 /etc/gshadow
hackers:!::alice,bob
prompt$ █
```

# Changing things

- ▶ Do the earlier utilities
  - ▶ useradd, passwd, gpasswd, etc., just modify the files
    - ▶ /etc/passwd, /etc/shadow,
    - ▶ /etc/group, /etc/gshadow
- as appropriate?

# Changing things

- ▶ Do the earlier utilities
    - ▶ useradd, passwd, gpasswd, etc., just modify the files
      - ▶ /etc/passwd, /etc/shadow,
      - ▶ /etc/group, /etc/gshadow
- as appropriate? **Yes.**

# Changing things

- ▶ Do the earlier utilities
  - ▶ useradd, passwd, gpasswd, etc., just modify the files
    - ▶ /etc/passwd, /etc/shadow,
    - ▶ /etc/group, /etc/gshadow
  - as appropriate? **Yes.**
- ▶ Can I edit those files myself, by hand?

# Changing things

- ▶ Do the earlier utilities
  - ▶ useradd, passwd, gpasswd, etc., just modify the files
    - ▶ /etc/passwd, /etc/shadow,
    - ▶ /etc/group, /etc/gshadow
  - as appropriate? **Yes.**
- ▶ Can I edit those files myself, by hand? **Yes.**

# Changing things

- ▶ Do the earlier utilities
  - ▶ useradd, passwd, gpasswd, etc., just modify the files
    - ▶ /etc/passwd, /etc/shadow,
    - ▶ /etc/group, /etc/gshadow
- as appropriate? **Yes.**
- ▶ Can I edit those files myself, by hand? **Yes.**
- ▶ Just using vi, emacs, nano, or whatever?



# Changing things

- ▶ Do the earlier utilities
  - ▶ useradd, passwd, gpasswd, etc., just modify the files
    - ▶ /etc/passwd, /etc/shadow,
    - ▶ /etc/group, /etc/gshadow
  - as appropriate? **Yes.**
- ▶ Can I edit those files myself, by hand? **Yes.**
- ▶ Just using vi, emacs, nano, or whatever?
  - ▶ **NO — dangerous**
    - ▶ Files are not locked, could be corrupted:
    - ▶ Someone could run a utility while you are editing
  - ▶ Safe way:
    - ▶ `vipw /etc/passwd` or `vipw -s /etc/shadow`
    - ▶ `vigr /etc/group` or `vigr -s /etc/gshadow`
    - ▶ Locks files to prevent corruption

Let's have a look at an actual `/etc/passwd` from one of the VMs:

```
prompt$ █
```

Let's have a look at an actual `/etc/passwd` from one of the VMs:

```
prompt$ cat /etc/passwd
```

Let's have a look at an actual `/etc/passwd` from one of the VMs:

```
prompt$ cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
bin:x:1:1:bin:/bin:/sbin/nologin
daemon:x:2:2:daemon:/sbin:/sbin/nologin
adm:x:3:4:adm:/var/adm:/sbin/nologin
lp:x:4:7:lp:/var/spool/lpd:/sbin/nologin
sync:x:5:0:sync:/sbin:/bin/sync
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
halt:x:7:0:halt:/sbin:/sbin/halt
mail:x:8:12:mail:/var/spool/mail:/sbin/nologin
uucp:x:10:14:uucp:/var/spool/uucp:/sbin/nologin
operator:x:11:0:operator:/root:/sbin/nologin
games:x:12:100:games:/usr/games:/sbin/nologin
gopher:x:13:30:gopher:/var/gopher:/sbin/nologin
ftp:x:14:50:FTP User:/var/ftp:/sbin/nologin
nobody:x:99:99:Nobody:/:/sbin/nologin
dbus:x:81:81:System message bus:/:/sbin/nologin
saslauth:x:499:499:"Saslauthd user":/var/empty/saslauth:/sbin/nologin
mailnull:x:47:47:/:/var/spool/mqueue:/sbin/nologin
smmmsp:x:51:51:/:/var/spool/mqueue:/sbin/nologin
sshd:x:74:74:Privilege-separated SSH:/var/empty/sshd:/sbin/nologin
user:x:500:500:~/home/user:/bin/bash
prompt$ █
```

## Why so many system accounts?

- ▶ Usually for running daemons
- ▶ Why not just run these as root?

# Why so many system accounts?

- ▶ Usually for running daemons
- ▶ Why not just run these as root?
  - ▶ General security rule: don't do it as root unless necessary

## Why so many system accounts?

- ▶ Usually for running daemons
- ▶ Why not just run these as root?
  - ▶ General security rule: don't do it as root unless necessary
- ▶ But only root processes can bind to reserved ports!

# Why so many system accounts?

- ▶ Usually for running daemons
- ▶ Why not just run these as root?
  - ▶ General security rule: don't do it as root unless necessary
- ▶ But only root processes can bind to reserved ports!
  - ▶ True.
  - ▶ But, we can:



# Why so many system accounts?

- ▶ Usually for running daemons
- ▶ Why not just run these as root?
  - ▶ General security rule: don't do it as root unless necessary
- ▶ But only root processes can bind to reserved ports!
  - ▶ True.
  - ▶ But, we can:
    1. Start out running as root

# Why so many system accounts?

- ▶ Usually for running daemons
- ▶ Why not just run these as root?
  - ▶ General security rule: don't do it as root unless necessary
- ▶ But only root processes can bind to reserved ports!
  - ▶ True.
  - ▶ But, we can:
    1. Start out running as root
    2. Get our ports set up

# Why so many system accounts?

- ▶ Usually for running daemons
- ▶ Why not just run these as root?
  - ▶ General security rule: don't do it as root unless necessary
- ▶ But only root processes can bind to reserved ports!
  - ▶ True.
  - ▶ But, we can:
    1. Start out running as root
    2. Get our ports set up
    3. Have the process EITHER:  
switch to an ordinary user, OR  
create a new process running as an ordinary user

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?
  - ▶ NO
  - ▶ That's `lp`

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?
  - ▶ NO
  - ▶ That's lp
- ▶ Some random system account that should be left alone?

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?
  - ▶ NO
  - ▶ That's lp
- ▶ Some random system account that should be left alone? NO



# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?
  - ▶ NO
  - ▶ That's `lp`
- ▶ Some random system account that should be left alone? NO
- ▶ A cracker who has broken into the system?

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?
  - ▶ NO
  - ▶ That's `lp`
- ▶ Some random system account that should be left alone? NO
- ▶ A cracker who has broken into the system?
  - ▶ YES!

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?
  - ▶ NO
  - ▶ That's lp
- ▶ Some random system account that should be left alone? NO
- ▶ A cracker who has broken into the system?
  - ▶ YES!
  - ▶ System accounts should have shell: `/sbin/nologin`

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?
  - ▶ NO
  - ▶ That's lp
- ▶ Some random system account that should be left alone? NO
- ▶ A cracker who has broken into the system?
  - ▶ YES!
  - ▶ System accounts should have shell: `/sbin/nologin`
- ▶ But “low userIDs are set aside for system use”, aren't they?

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?
  - ▶ NO
  - ▶ That's `lp`
- ▶ Some random system account that should be left alone? NO
- ▶ A cracker who has broken into the system?
  - ▶ YES!
  - ▶ System accounts should have shell: `/sbin/nologin`
- ▶ But “low userIDs are set aside for system use”, aren't they?
  - ▶ Just a convention, `root` can do anything
  - ▶ This person probably got root access and created the account

# Fun aside

What is the likely purpose of this account in `/etc/passwd`?

```
lpd:x:57:57:lpd:/var/spool/lpd:/bin/bash
```

- ▶ The system account for the printing daemon?
  - ▶ NO
  - ▶ That's `lp`
- ▶ Some random system account that should be left alone? NO
- ▶ A cracker who has broken into the system?
  - ▶ YES!
  - ▶ System accounts should have shell: `/sbin/nologin`
- ▶ But “low userIDs are set aside for system use”, aren't they?
  - ▶ Just a convention, root can do anything
  - ▶ This person probably got root access and created the account

Paranoid yet?

# And now for a very serious question

## And now for a very serious question

How is it possible for an ordinary user to change their own password?



# And now for a very serious question

How is it possible for an ordinary user to change their own password?

Consider the following statements

1. The `passwd` utility modifies file `/etc/shadow` directly
2. `/etc/shadow` typically has permissions **000**
3. Whenever a user runs a process,  
the process runs with that user's permissions
4. An ordinary user can change their own password using `passwd`

## And now for a very serious question

How is it possible for an ordinary user to change their own password?

Consider the following statements

1. The `passwd` utility modifies file `/etc/shadow` directly
2. `/etc/shadow` typically has permissions **000**
3. Whenever a user runs a process,  
the process runs with that user's permissions
4. An ordinary user can change their own password using `passwd`

These statements **cannot all be true**. Which one is incorrect?

## And now for a very serious question

How is it possible for an ordinary user to change their own password?

Consider the following statements

1. The `passwd` utility modifies file `/etc/shadow` directly
2. `/etc/shadow` typically has permissions `000`
3. Whenever a user runs a process,  
the process runs with that user's permissions
4. An ordinary user can change their own password using `passwd`

These statements **cannot all be true**. Which one is incorrect?

# The truth about processes

# The truth about processes

A process has **multiple** userIDs and groupIDs:

- ▶ **real user ID**

- ▶ User who started the process; its “owner”
- ▶ C system call: `getuid()` to obtain this

- ▶ **real group ID**

- ▶ Current group of user who started the process
- ▶ C system call: `getgid()` to obtain this

- ▶ **effective user ID**

- ▶ User ID to use for file permissions
- ▶ *Usually* the same as the real user ID
- ▶ C system call: `geteuid()` to obtain this

- ▶ **effective group ID**

- ▶ Group ID to use for file permissions
- ▶ *Usually* the same as the group user ID
- ▶ C system call: `getegid()` to obtain this

# Why alice can change her password

When alice runs passwd:

- ▶ The real user ID is alice's
- ▶ The effective user ID is root's (0)

# Why alice can change her password

When alice runs passwd:

- ▶ The real user ID is alice's
- ▶ The effective user ID is root's (0)

By what magic does this happen?

# setuid and setgid bits

- ▶ There are **two permission bits** we have not discussed
  - setuid bit** : set user ID upon execution
    - ▶ When set, the process's effective user ID is set to the **owner of the executable file**
  - setgid bit** : set group ID upon execution
    - ▶ When set, the process's effective group ID is set to the **group of the executable file**
- ▶ These can be changed with `chmod`
  - ▶ Use “s” where you would use “r”, “w”, or “x”
  - ▶ Use an extra octal digit before the usual three
    - 4 : setuid bit is on
    - 2 : setgid bit is on
    - 1 : sticky bit is on
- ▶ These can be seen in `ls -l`
  - ▶ Will have an “s” instead of “x” in the appropriate place



# setuid and setgid bits

- ▶ There are **two permission bits** we have not discussed
  - setuid bit** : set user ID upon execution
    - ▶ When set, the process's effective user ID is set to the **owner of the executable file**
  - setgid bit** : set group ID upon execution
    - ▶ When set, the process's effective group ID is set to the **group of the executable file**
- ▶ These can be changed with `chmod`
  - ▶ Use “s” where you would use “r”, “w”, or “x”
  - ▶ Use an extra octal digit before the usual three
    - 4 : setuid bit is on
    - 2 : setgid bit is on
    - 1 : sticky bit is on
- ▶ These can be seen in `ls -l`
  - ▶ Will have an “s” instead of “x” in the appropriate place

**BE VERY CAREFUL WITH THESE BITS** — we'll see why later

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: █
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob█
```

## Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password: █
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ █
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
```

## Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ █
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
```



# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ █
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ █
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ █
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ █
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
```



# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ █
```

# Fun setuid example

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: bob
Password:
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout
```

# Fun setuid example

```
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout
```

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)
```

```
krankor login: █
```

# Fun setuid example

```
Last login: Wed Oct 31 23:06:11 on tty1
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout
```

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)
```

```
krankor login: alice█
```

# Fun setuid example

```
prompt$ cd /tmp
prompt$ cp /bin/cat bobcat
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout
```

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)
```

```
krankor login: alice
Password: █
```

# Fun setuid example

```
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout
```

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)
```

```
krankor login: alice
Password:
Last login: Thu Nov 1 17:12:23 on tty1
prompt$ █
```

# Fun setuid example

```
prompt$ chmod 4711 bobcat
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout
```

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)
```

```
krankor login: alice
Password:
Last login: Thu Nov 1 17:12:23 on tty1
prompt$ cd /tmp
```

# Fun setuid example

```
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout
```

Fedora release 15 (Lovelock)

Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: alice

Password:

Last login: Thu Nov 1 17:12:23 on tty1

prompt\$ cd /tmp

prompt\$ █



# Fun setuid example

```
prompt$ echo "This is an unreadable file" > file.txt
prompt$ chmod 400 file.txt
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout
```

```
Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)
```

```
krankor login: alice
Password:
Last login: Thu Nov 1 17:12:23 on tty1
prompt$ cd /tmp
prompt$ cat file.txt
```

# Fun setuid example

```
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout

Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: alice
Password:
Last login: Thu Nov 1 17:12:23 on tty1
prompt$ cd /tmp
prompt$ cat file.txt
cat: file.txt: Permission denied
prompt$ █
```

# Fun setuid example

```
prompt$ ls -l | grep bob
-rws--x--x 1 bob bob 47292 Nov 2 13:33 bobcat
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
prompt$ logout

Fedora release 15 (Lovelock)
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)

krankor login: alice
Password:
Last login: Thu Nov 1 17:12:23 on tty1
prompt$ cd /tmp
prompt$ cat file.txt
cat: file.txt: Permission denied
prompt$ ./bobcat file.txt
```

# Fun setuid example

```
-r----- 1 bob bob    27 Nov 2 13:34 file.txt
```

```
prompt$ logout
```

```
Fedora release 15 (Lovelock)
```

```
Kernel 2.6.43.8-1.fc15.i686.PAE on a i686 (tty1)
```

```
krankor login: alice
```

```
Password:
```

```
Last login: Thu Nov 1 17:12:23 on tty1
```

```
prompt$ cd /tmp
```

```
prompt$ cat file.txt
```

```
cat: file.txt: Permission denied
```

```
prompt$ ./bobcat file.txt
```

```
This is an unreadable file
```

```
prompt$ █
```

# Running stuff as another user

Choices so far:

- ▶ `su [username]`
  - ▶ Actually starts a shell as the given user
  - ▶ Need to know the user's password, of course
- ▶ `setuid` programs
  - ▶ Executables owned by another user, with `setuid` bit set
  - ▶ Anyone with permission can run these at any time
  - ▶ Are a security concern (we will discuss **why** later)

Is there a way to let **certain** users run **certain** things as other users?

# sudo utility

- ▶ Usage: `sudo command args args ...`
- ▶ Some important switches (check your man pages):
  - u : specify “new” user (default is root)
  - g : specify “new” group  
(default is primary of new user)
- ▶ Runs the command but sets
  - ▶ Effective userid to the specified user
  - ▶ Effective groupid to the specified group
- ▶ When run as root: no password prompt
- ▶ When run as ordinary user:
  - ▶ Type **your own** password (usually)

# sudo utility

- ▶ Usage: `sudo command args args ...`
- ▶ Some important switches (check your man pages):
  - u : specify “new” user (default is root)
  - g : specify “new” group  
(default is primary of new user)
- ▶ Runs the command but sets
  - ▶ Effective userid to the specified user
  - ▶ Effective groupid to the specified group
- ▶ When run as root: no password prompt
- ▶ When run as ordinary user:
  - ▶ Type **your own** password (usually)
- ▶ Is this a huge security hole?

# sudo utility

- ▶ Usage: `sudo command args args ...`
- ▶ Some important switches (check your man pages):
  - u : specify “new” user (default is root)
  - g : specify “new” group  
(default is primary of new user)
- ▶ Runs the command but sets
  - ▶ Effective userid to the specified user
  - ▶ Effective groupid to the specified group
- ▶ When run as root: no password prompt
- ▶ When run as ordinary user:
  - ▶ Type **your own** password (usually)
- ▶ Is this a huge security hole? **Usually not...**



# sudo configuration

## /etc/sudoers

- ▶ Specifies **who** may do **what**
- ▶ Fancy configuration file
  - ▶ Can define aliases (variables)
- ▶ Should be edited with `visudo`
  - ▶ Locks the file and edits it with `vi`
- ▶ For more info: `man sudoers`

Example fragment of /etc/sudoers:

```
## This is a comment
CmndAlias POWER = /sbin/shutdown, /sbin/poweroff, /sbin/halt
## Allow anyone in group "staff" to shut down the machine
%staff  ALL = POWER
```

## Important stuff with sudo

- ▶ Can configure sudo to **log** usage
  - ▶ Successful attempts
  - ▶ Unsuccessful attempts
- ▶ Can configure sudo to **send mail** on failed attempts

# Important stuff with sudo

- ▶ Can configure sudo to **log** usage
  - ▶ Successful attempts
  - ▶ Unsuccessful attempts
- ▶ Can configure sudo to **send mail** on failed attempts
- ▶ But still need to **be careful** with sudo configuration:
  - ▶ `sudo bash` gives you a **root** shell
    - ▶ Administrator accounts can do this in Mac OS
    - ▶ sudo log entry will just show that `bash` was run
    - ▶ Commands run inside `bash` will not be logged
    - ▶ Generally, this is to be avoided

# Important stuff with sudo

- ▶ Can configure sudo to **log** usage
  - ▶ Successful attempts
  - ▶ Unsuccessful attempts
- ▶ Can configure sudo to **send mail** on failed attempts
- ▶ But still need to **be careful** with sudo configuration:
  - ▶ `sudo bash` gives you a **root** shell
    - ▶ Administrator accounts can do this in Mac OS
    - ▶ `sudo log` entry will just show that `bash` was run
    - ▶ Commands run inside `bash` will not be logged
    - ▶ Generally, this is to be avoided
  - ▶ Allowing `sudo vi` is just as bad
    - ▶ `vi` lets you invoke a shell using `“:!”`
    - ▶ Not to mention the ability to edit **any** file

`chsh` : change your login shell

`gpsswd` : group administration

`groupadd` : add a new group

`groupdel` : remove an existing group

`groupmod` : modify an existing group

`id` : show userID and groupID

`newgrp` : change the current group

`passwd` : change passwords


`sudo` : run a command as another user

`useradd` : add a new user account

`userdel` : remove an existing user account

`usermod` : modify an existing user account

An appropriate xkcd comic: <http://xkcd.com/149>



End of lecture