# Introduction to ddply Cleaning and Summarizing Data

Iowa State University

### Outline

- ► conditionals & subsets
- ▶ for loops
- ▶ avoiding for loops with ddply

### Baseball Data

- The plyr package contains the data set baseball
- seasonal batting statistics of all major league players (through 2007)

```
library(plyr)
help(baseball)
head(baseball)
```

```
id year stint team lg
                                   ab r h X2b X3b hr rbi sb cs bb so ibb hbp sh sf gidp
    ansonca01 1871
                         RC1
   forceda01 1871
                         WS3
                                32 162 45 45
                                                                             NA NA NA
                                19 89 15 24
                                                         10
                                                                         NA
   mathebo01 1871
                      1 FW1
                                                                                        NA
    startjo01 1871
                      1 NY2
                                33 161 35 58
                                                         34
                                                                         NA
102 suttoez01 1871
                         CL1
                                29 128 35 45
                                                                         NA
                                                                             NA NA NA
                                                                                        NΑ
106 whitede01 1871
                         CL.1
                                29 146 40 47
                                                                         NA
                                                                             NA NA NA
                                                                                        NA
```

#### Baseball Data

- We would like to create career summary statistics for each player
- ▶ Plan: subset on a player, and compute statistics

```
ss <- subset(baseball, id=="sosasa01")
head(ss)
         id year stint team lg g ab r h X2b X3b hr rbi sb cs bb so ibb hbp sh sf
66822 sosasa01 1989
                 1 TEX AL 25 84 8
                                   20
66823 sosasa01 1989
                             99 19
                                   27 5
                                          0 3
                                              10 7
                                                    3 11
                1 CHA AL 153 532 72 124 26
67907 sosasa01 1990
                                         10 15
                                               70 32 16 33
33 13 6 14
70599 sosasa01 1992
                1 CHN NL 67 262 41 68 7
                                          2 8
                                              25 15 7 19
71757 sosasa01 1993
                1 CHN NL 159 598 92 156 25
                                          5 33 93 36 11 38 135
```

```
mean(ss$h/ss$ab)
## [1] 0.2681506
```

#### Baseball Data

- ► We would like to create career summary statistics for each player
- Plan: subset on a player, and compute statistics

```
ss <- subset(baseball, id=="sosasa01")
head(ss)

id year stint team lg g ab r h X2b X3b hr rbi sb cs bb so ibb hbp sh sf gidp
66822 sosasa01 1989 1 TEX AL 25 84 8 20 3 0 1 3 0 2 0 20 0 0 0 4 0 3
66823 sosasa01 1989 2 CHA AL 33 99 19 27 5 0 3 10 7 3 11 27 2 2 2 1 2 3
67907 sosasa01 1990 1 CHA AL 153 532 72 124 26 10 15 70 32 16 33 150 4 6 2 6 10
69018 sosasa01 1991 1 CHA AL 116 316 39 64 10 1 10 33 13 614 98 2 2 5 1 5
70599 sosasa01 1992 1 CHN NL 67 262 41 68 7 2 8 25 15 7 19 63 1 4 4 2 4
71757 sosasa01 1993 1 CHN NL 159 598 92 156 25 5 33 93 36 11 38 135 6 4 0 1 14

mean(ss$h/ss$ab)
## [1] 0.2681506
```

We need an automatic way to calculate this

## for loops

- ► Idea: repeat the same (set of) statement(s) for each element of an index set
- ► Setup:
  - Introduce counter variable (sometimes named i)
  - Reserve space for results
- ► Generic Code:

```
result <- rep(NA, length(indexset))
for(i in indexset){
    ... some statments ...
    result[i] <- ...
}</pre>
```

- Index set: player id
- Setup:

```
# Index set
players <- unique(baseball$id)</pre>
n <- length(players)</pre>
# Place to store data
ba \leftarrow rep(NA, n)
# Loop
for(i in 1:n){
  career <- subset(baseball, id==players[i])</pre>
  ba[i] <- with(career, mean(h/ab, na.rm=T))</pre>
# Results
summary(ba)
##
      Min. 1st Qu. Median Mean 3rd Qu.
                                                  Max.
                                                           NA's
## 0.0000 0.1831 0.2459 0.2231 0.2699 0.5000
                                                              6
```

- Index set: player id
- ▶ i=0

```
# Index set
players <- unique(baseball$id)
n <- length(players)

# Place to store data
ba <- rep(NA, n)
head(ba)
## [1] NA NA NA NA NA NA</pre>
```

- Index set: player id
- ▶ i=1

```
# Index set
players <- unique(baseball$id)</pre>
n <- length(players)</pre>
# Place to store data
ba \leftarrow rep(NA, n)
# Loop
for(i in 1:1){
  career <- subset(baseball, id==players[i])</pre>
  ba[i] <- with(career, mean(h/ab, na.rm=T))</pre>
## [1] 1
head(ba)
## [1] 0.3371163
                           NΑ
                                       NΑ
                                                   NΑ
```

NA

NΑ

- Index set: player id
- ▶ i=2

```
# Index set
players <- unique(baseball$id)</pre>
n <- length(players)</pre>
# Place to store data
ba \leftarrow rep(NA, n)
# Loop
for(i in 1:2){
  career <- subset(baseball, id==players[i])</pre>
  ba[i] <- with(career, mean(h/ab, na.rm=T))</pre>
## [1] 2
head(ba)
## [1] 0.3371163 0.2489226
                                       NA
                                                   NΑ
```

NA

NΑ

#### Your Turn

► MLB rules for the greatest all-time hitters are that players have to have played at least 1000 games with at least as many at-bats in order to be considered

Extend the for loop above to collect the additional information Introduce and collect data for two new variables: games and atbats

# How did it go? What was difficult?

 household chores (declaring variables, setting values each time) distract from real work

indices are error-prone

▶ loops often result in slow code because R can compute quantities using entire vectors in an optimized way

#### Summarise

▶ A special function: summarise or summarize

```
library(dplyr)
##
## Attaching package: 'dplyr'
##
   The following objects are masked from 'package:plyr':
##
##
      arrange, count, desc, failwith, id, mutate, rename, summarise,
##
      summarize
##
   The following objects are masked from 'package:qdata':
##
##
      combine, first, last
##
   The following object is masked from 'package:stats':
##
##
      filter
##
   The following objects are masked from 'package:base':
##
##
      intersect, setdiff, setequal, union
```

## dplyr + Summarize

### A powerful combination to create summary statistics

```
careers <- summarise(group_by(baseball, id),</pre>
                ba = mean(h/ab, na.rm=T),
                games = sum(g, na.rm=T),
                homeruns = sum(hr, na.rm=T),
                atbats = sum(ab, na.rm=T))
head(careers)
## Source: local data frame [6 x 5]
##
##
           id
                     ba games homeruns atbats
  1 aaronha01 0.3010752
                                  755 12364
                       3298
## 2 abernte02 0.1824394 681
                                    0 181
  3 adairje01 0.2363071 1165
                                   57 4019
## 4 adamsba01 0.2096513
                       482
                                    3 1019
## 5 adamsbo03 0.2378073 1281
                                   37 4019
## 6 adcocjo01 0.2751690
                       1959
                                  336
                                        6606
```

#### Your Turn

- Find some summary statistics for each of the teams (variable team)
  - How many different (unique) players has the team had?
  - What was the team's first/last season?
- Challenge: Find the number of players on each team over time. Does the number change?