

# SRGroups

**Self-replicating groups of regular rooted trees.**

0.1

17 December 2020

**Sam King**

**Sarah Shotter**

**Sam King**

Email: [sam.king@newcastle.edu.au](mailto:sam.king@newcastle.edu.au)

Address: University Drive, Callaghan NSW 2308

**Sarah Shotter**

Email: [sarah.shotter@newcastle.edu.au](mailto:sarah.shotter@newcastle.edu.au)

Address: University Drive, Callaghan NSW 2308

## Abstract

To do.

## Copyright

??? is free software; you can redistribute it and/or modify it under the terms of the [GNU General Public License](#) as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

## Acknowledgements

DE210100180, FL170100032.

# Contents

<b>1</b>	<b>The package</b>	<b>4</b>
1.1	Framework . . . . .	4
1.2	Auxiliary methods . . . . .	7
<b>2</b>	<b>The library</b>	<b>9</b>
2.1	Methods . . . . .	9
	<b>Index</b>	<b>10</b>

# Chapter 1

## The package

?? is a package which does some interesting and cool things. To be continued...

### 1.1 Framework

#### 1.1.1 IsRegularRootedTreeGroup (for IsPermGroup)

▷ IsRegularRootedTreeGroup(*arg*) (filter)

**Returns:** true or false

Groups acting on regular rooted trees are stored together with their degree (RegularRootedTreeGroupDegree (??)), depth (RegularRootedTreeGroupDepth (??)) and other attributes in this category. See also RegularRootedTreeGroup (??).

Example

```
gap> G:=SymmetricGroup(3);
Sym( [ 1 .. 3 ] )
gap> IsRegularRootedTreeGroup(G);
false
gap> H:=RegularRootedTreeGroup(3,1,SymmetricGroup(3));
Sym( [ 1 .. 3 ] )
gap> IsRegularRootedTreeGroup(H);
true
```

#### 1.1.2 RegularRootedTreeGroup (for IsInt, IsInt, IsPermGroup)

▷ RegularRootedTreeGroup(*k*, *n*, *G*) (operation)

**Returns:** the regular rooted tree group *G* as an object of the category IsRegularRootedTreeGroup (??), after checking that *G* is indeed a subgroup of  $\text{Aut}(T_{k,n})$ .

The arguments of this method are a degree  $k \in \mathbb{N}_{\geq 2}$ , a depth  $n \in \mathbb{N}$  and a subgroup *G* of  $\text{Aut}(T_{k,n})$ .

Example

to do

#### 1.1.3 RegularRootedTreeGroupNC (for IsInt, IsInt, IsPermGroup)

▷ RegularRootedTreeGroupNC(*k*, *n*, *G*) (operation)

**Returns:** the regular rooted tree group *G* as an object of the category IsRegularRootedTreeGroup (??), without checking that *G* is indeed a subgroup of  $\text{Aut}(T_{k,n})$ .

The arguments of this method are a degree  $k \in \mathbb{N}_{\geq 2}$ , a depth  $n \in \mathbb{N}$  and a subgroup  $G$  of  $\text{Aut}(T_{k,n})$ .

Example

to do

### 1.1.4 RegularRootedTreeGroupDegree (for IsRegularRootedTreeGroup)

▷ `RegularRootedTreeGroupDegree( $G$ )` (attribute)

**Returns:** the degree  $k$  of the regular rooted tree that  $G$  is acting on.

The argument of this attribute is a regular rooted tree group  $G \leq \text{Aut}(T_{k,k})$  (`IsRegularRootedTreeGroup(??)`).

Example

to do

### 1.1.5 RegularRootedTreeGroupDepth (for IsRegularRootedTreeGroup)

▷ `RegularRootedTreeGroupDepth( $G$ )` (attribute)

**Returns:** the depth  $n$  of the regular rooted tree that  $G$  is acting on.

The argument of this attribute is a regular rooted tree group  $G \leq \text{Aut}(T_{k,k})$  (`IsRegularRootedTreeGroup(??)`).

Example

to do

### 1.1.6 ParentGroup (for IsRegularRootedTreeGroup)

▷ `ParentGroup( $G$ )` (attribute)

**Returns:** the regular rooted tree group that arises from  $G$  by restricting to  $T_{k,n-1}$ .

The argument of this attribute is a regular rooted tree group  $G \leq \text{Aut}(T_{k,k})$  (`IsRegularRootedTreeGroup(??)`).

Example

```
gap> G:=AutT(2,4);
<permutation group of size 32768 with 15 generators>
gap> ParentGroup(G)=AutT(2,3);
true
```

### 1.1.7 IsSelfReplicating (for IsRegularRootedTreeGroup)

▷ `IsSelfReplicating( $G$ )` (property)

**Returns:** true, if  $G$  is self-replicating, and false otherwise.

The argument of this property is a regular rooted tree group  $G \leq \text{Aut}(T_{k,k})$  (`IsRegularRootedTreeGroup(??)`).

Example

```
gap> G:=AutT(2,2);
Group([ (1,2), (3,4), (1,3)(2,4) ])
gap> subgroups:=AllSubgroups(G);
gap> Apply(subgroups,H->RegularRootedTreeGroup(2,2,H));
gap> for H in subgroups do Print(IsSelfReplicating(H),"\n"); od;
false
```

```

false
false
false
false
false
false
true
true
true

```

### 1.1.8 HasSufficientRigidAutomorphisms (for IsRegularRootedTreeGroup)

▷ `HasSufficientRigidAutomorphisms( $G$ )` (property)

**Returns:** true, if  $G$  has sufficient rigid automorphisms, and false otherwise.

The argument of this property is a regular rooted tree group  $G \leq \text{Aut}(T_{k,k})$  (`IsRegularRootedTreeGroup (??)`).

Example

```
to do
```

### 1.1.9 RepresentativeWithSufficientRigidAutomorphisms (for IsRegularRootedTreeGroup)

▷ `RepresentativeWithSufficientRigidAutomorphisms( $G$ )` (attribute)

**Returns:** a regular rooted tree group which is conjugate to  $G$  in  $\text{Aut}(T_{k,n})$  and which has sufficient rigid automorphisms, i.e. it satisfies `HasSufficientRigidAutomorphisms (??)`. This returned group is  $G$  itself, if  $G$  already has sufficient rigid automorphisms. Furthermore, the returned group has the same parent group as  $G$  if the parent group of  $G$  has sufficient rigid automorphisms.

The argument of this attribute is a regular rooted tree group  $G \leq \text{Aut}(T_{k,k})$  (`IsRegularRootedTreeGroup (??)`), which is self-replicating (`IsSelfReplicating (??)`).

Example

```
to do
```

### 1.1.10 MaximalExtension (for IsRegularRootedTreeGroup)

▷ `MaximalExtension( $G$ )` (attribute)

**Returns:** the regular rooted tree group  $M(G) \leq \text{Aut}(T_{k,n})$  which is the unique maximal self-replicating extension of  $G$  to  $T_{k,n+1}$ .

The argument of this attribute is a regular rooted tree group  $G \leq \text{Aut}(T_{k,k})$  (`IsRegularRootedTreeGroup (??)`), which is self-replicating (`IsSelfReplicating (??)`) and has sufficient rigid automorphisms (`HasSufficientRigidAutomorphisms (??)`).

Example

```
to do
```

### 1.1.11 ConjugacyClassRepsSelfReplicatingGroupsWithProjection (for IsRegularRootedTreeGroup)

▷ ConjugacyClassRepsSelfReplicatingGroupsWithProjection( $G$ ) (attribute)

**Returns:** a list  $\text{Aut}(T_{k,n+1})$ -conjugacy class representatives of regular rooted tree groups which are self-replicating, have sufficient rigid automorphisms and whose parent group is  $G$ .

The argument of this attribute is a regular rooted tree group  $G \leq \text{Aut}(T_{k,k})$  ( $\text{IsRegularRootedTreeGroup}(\text{??})$ ), which is self-replicating ( $\text{IsSelfReplicating}(\text{??})$ ) and has sufficient rigid automorphisms ( $\text{HasSufficientRigidAutomorphisms}(\text{??})$ ).

Example

to do

### 1.1.12 ConjugacyClassRepsSelfReplicatingGroupsWithConjugateProjection (for IsRegularRootedTreeGroup)

▷ ConjugacyClassRepsSelfReplicatingGroupsWithConjugateProjection( $G$ ) (attribute)

**Returns:** a list  $\text{Aut}(T_{k,n+1})$ -conjugacy class representatives of regular rooted tree groups which are self-replicating, have sufficient rigid automorphisms and whose parent group is conjugate to  $G$ .

The argument of this attribute is a regular rooted tree group  $G \leq \text{Aut}(T_{k,k})$  ( $\text{IsRegularRootedTreeGroup}(\text{??})$ ), which is self-replicating ( $\text{IsSelfReplicating}(\text{??})$ ) and has sufficient rigid automorphisms ( $\text{HasSufficientRigidAutomorphisms}(\text{??})$ ).

Example

to do

## 1.2 Auxiliary methods

This section explains the methods of this package.

### 1.2.1 RemoveConjugates

▷ RemoveConjugates( $G$ ,  $subgroups$ ) (function)

**Returns:** n/a. This method removes  $G$ -conjugates from the mutable list  $subgroups$ .

The arguments of this method are a group  $G$  and a mutable list  $subgroups$  of subgroups of  $G$ .

Example

```
gap> G:=SymmetricGroup(3);
Sym( [ 1 .. 3 ] )
gap> subgroups:=[Group((1,2)),Group((2,3))];
[ Group([ (1,2) ]), Group([ (2,3) ]) ]
gap> RemoveConjugates(G,subgroups);
gap> subgroups;
[ Group([ (1,2) ]) ]
```

### 1.2.2 AutT

▷ AutT( $k$ ,  $n$ ) (function)

**Returns:** the regular rooted tree group  $\text{Aut}(T_{k,n})$  ( $\text{IsRegularRootedTreeGroup}(\text{??})$ ) as a permutation group of the  $k^n$  leaves of  $T_{k,n}$ .

The arguments of this method are a degree  $k \in \mathbb{N}_{\geq 2}$  and a depth  $n \in \mathbb{N}$ .

## Example

```
gap> G:=AutT(2,2);
Group([ (1,2), (3,4), (1,3)(2,4) ])
gap> RegularRootedTreeGroupDegree(G);
2
gap> RegularRootedTreeGroupDepth(G);
2
```

### 1.2.3 BelowAction

▷ BelowAction( $k, n, aut, i$ )

(function)

**Returns:** the automorphism of  $\text{Aut}(T_{k,n})$  that arises from  $aut$  by restricting to the subtree below the  $i$ -th vertex at depth 1.

The arguments of this method are a degree  $k \in \mathbb{N}_{\geq 2}$ , a depth  $n \in \mathbb{N}_{\neq 0}$ , an automorphism  $aut \in \text{Aut}(T_{k,n})$  and an index  $i \in [1..k]$ .

## Example

```
gap> G:=AutT(2,2);
Group([ (1,2), (3,4), (1,3)(2,4) ])
gap> a:=Random(G);
(1,3,2,4)
gap> BelowAction(2,2,a,1);
()
gap> BelowAction(2,2,a,2);
(1,2)
```



## Chapter 2

# The library

### 2.1 Methods

#### 2.1.1 `bar` (for `IsObject`)

▷ `bar(arg)`

**Returns:** `true` or `false`  
`foo`

(filter)

# Index

AutT, [7](#)

bar

for IsObject, [9](#)

BelowAction, [8](#)

ConjugacyClassRepsSelfReplicating-  
GroupsWithConjugateProjection

for IsRegularRootedTreeGroup, [7](#)

ConjugacyClassRepsSelfReplicating-  
GroupsWithProjection

for IsRegularRootedTreeGroup, [7](#)

HasSufficientRigidAutomorphisms

for IsRegularRootedTreeGroup, [6](#)

IsRegularRootedTreeGroup

for IsPermGroup, [4](#)

IsSelfReplicating

for IsRegularRootedTreeGroup, [5](#)

MaximalExtension

for IsRegularRootedTreeGroup, [6](#)

ParentGroup

for IsRegularRootedTreeGroup, [5](#)

RegularRootedTreeGroup

for IsInt, IsInt, IsPermGroup, [4](#)

RegularRootedTreeGroupDegree

for IsRegularRootedTreeGroup, [5](#)

RegularRootedTreeGroupDepth

for IsRegularRootedTreeGroup, [5](#)

RegularRootedTreeGroupNC

for IsInt, IsInt, IsPermGroup, [4](#)

RemoveConjugates, [7](#)

RepresentativeWithSufficientRigid-  
Automorphisms

for IsRegularRootedTreeGroup, [6](#)